

HOT-MIX ASPHALT SCHEDULE

40600200 40600300 40600735 40600837 40603310 40603085 40603540 48203019 48203029

LOCATION	REMARKS (END LOCATION)	LENGTH	PROPOSED SURFACE		BIT MATERIAL PRIME COAT (2 APPLICATIONS)	AGG PRIME COAT	POLYMERIZED LEVEL BINDER (HM) N70 (10 TON/MILE)	POLYMERIZED LEVEL BINDER (MM) N70	HOT-MIX ASPHALT SURFACE COURSE MIX "C", N50	HOT-MIX ASPHALT BINDER COURSE IL-19.0, N70	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE MIX "D", N70	HOT-MIX ASPHALT SHOULDERS 5 1/2"	HOT-MIX ASPHALT SHOULDERS 8"
			Width	Sq Yd	Ton	Ton	Ton	Ton	Ton	Ton	Ton	Sq Yd	Sq Yd
US 20 BR Mainline													
Sta 265+21.5 - 265+71.5	Butt Joint	50	58.1' - 55.3'	315.0	0.18	0.47	0.09	22.1			26.5		
Sta 265+71.5 - 267+72.2		200.7	55.3' - 41.5'	1,077.6	0.62	1.62	0.38	75.4			90.5		
Sta 267+72.2 - 275+64.2	Start Widening - LT	792	42.5' - 40.2'	3,541.1	2.03	5.31	1.50	247.9			297.5		
Sta 275+64.2 - 280+25.8	Start RT Turn Lane	461.6	40.2' - 51.8'	2,483.5	1.42	3.73	0.87	173.8			208.6		
Sta 280+25.8 - 280+75.8	50' Milling Taper	50	51.8'	288.3	0.16	0.43	0.09	20.2			24.2		
Sta 280+75.8 - 283+81.8		306	51.8' & Var	2,556.5	1.46	3.83	0.58	179.0			214.7		
Sta 283+81.8 - 284+31.8	50' Milling Taper	50	52'	288.9	0.17	0.43	0.09	20.2			24.3		
Sta 284+31.8 - 287+99.6	End Right RT Turn Lane	367.8	52' - 40.9'	1,973.9	1.13	2.96	0.70	138.2			165.8		
Sta 287+99.6 - 296+21.7	End of Widening - RT	822.1	39.9'	3,638.9	2.08	5.46	1.56	254.7			305.7		
Sta 296+21.7 - 301+79.6		557.9	39.9' - 40.6'	2,466.6	1.41	3.70	1.06	172.7			207.2		
Sta 301+79.6 - 302+29.6	Butt Joint	50	40.6' - 42.2'	229.8	0.13	0.34	0.09	16.1			19.3		
US 20 BR Widening													
Sta 267+70.9 - 275+64.5	Start of Widening RT w/ 10"	793.6	1' - 10.7'	1,079.1	0.62	1.62				604.3			
Sta 275+64.5 - 280+25.8	Start of RT Turn Lane w/ 10"	461.3	10.7' - 16.1'	1,263.3	0.72	1.89				707.4			
Sta 280+25.8 - 280+75.8	50' Taper & 12.5" Binder	50	16.1' - 28'	155.9	0.09	0.23				109.1			
Sta 280+75.8 - 280+81.2	End of Widening RT & 12.5"	5.4	28'	16.8	0.01	0.03				11.8			
Sta 282+54.0 - 283+81.8	Start of Widening LT & 12.5"	127.8	1' - 12'	137.7	0.08	0.21				96.4			
Sta 283+81.8 - 284+31.8	50' Taper & 12.5" Binder	50	12'	66.7	0.04	0.10				46.7			
Sta 284+31.8 - 287+99.6	End of Widening LT w/ 10"	367.8	12' - 1'	342.0	0.20	0.51				191.5			
Sta 283+81.8 - 284+31.8	Start of Widening RT & 12.5"	50	12' - 1'	87.6	0.05	0.13				61.3			
Sta 284+31.8 - 296+21.8	End of Widening RT w/ 10"	1190	15.8' - 16'	2,114.2	1.21	3.17				1,184.0			