

# GENERAL NOTES

The final top four inches of soil in any right-of-way area disturbed by the Contractor must be capable of supporting vegetation. The soil must be from the A horizon (zero to 2' deep) of soil profiles of local soils.

All Borrow/Waste/Use sites must be approved by the Department prior to removing any material from the project or initiating any earthmoving activities, including temporary stockpiling outside the limits of construction.

The Contractor shall seed all disturbed areas within the project limits. Seeding Class 4 or 2A shall be used, except in front of properties where the grass will be mowed, then use Seeding, Class 1. Class 2A shall be used on front slopes and ditch bottoms. Class 4 shall be used behind Type A gutter, on all backslopes and areas behind the backslope, and beyond the toe of front slope on fill sections without ditches. This work will be included in the contract unit price per Pound for FURNISHING AND ERECTING STRUCTURAL STEEL.

Fertilizer shall be applied to all disturbed areas and incorporated into the seedbed prior to seeding or placement of sod at the rate specified in Sections 250 and 252 of the Standard Specifications. This work shall be included in the cost of FURNISHING AND ERECTING STRUCTURAL STEEL.

Mulch Method II shall be applied over all seeded areas. This shall be included in the cost of the FURNISHING AND ERECTING STRUCTURAL STEEL.

The Contractor shall be responsible for protecting utility property during construction operations as outlined in Article 107.31 of the Standard Specifications. A minimum of 48 hours advance notice is required for non-emergency work. The JULIE number is 800-892-0123.

No Stream Permits have been procured for this project. None are required from the Regulatory Agencies as long as there is no debris falling or being placed into the stream or the compromising of the dike (if applicable) will not be allowed. If the contractor chooses to use an alternate/modified construction method from the aforementioned, they will be responsible for obtaining the proper permits. Absolutely no construction activities will take place without the proper permits being secured.

# STANDARDS

- 701001-02 Off-Road Operations, 2L, 2W, More Than 4.5 m (15') Away
- 701006-03 Off-Road Operations, 2L, 2W, 4.5 m (15') to 600 mm (24") From Pavement Edge
- 701201-03 Lane Closure, 2L, 2W, Day Only, for Speeds > 45 MPH
- 701301-03 Lane Closure, 2L, 2W, Short Time Operations
- 701901-01 Traffic Control Devices

# INDEX OF SHEETS

1. Cover Sheet
2. Summary of Quantities
3. General Notes, Standards, Index of Sheets  
Bridge Repair Plans Structure 052-0026
4. Plan and Elevation
5. Repair Details  
Bridge Repair Plans Structure 098-0044
6. Plan and Elevation
7. Repair Details

\* FAP Route 316 (IL 26) & FAS Route 200 (IL 172)  
\*\* Lee & Whiteside

FILE NAME =	USER NAME = lmkdj	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>GENERAL NOTES, INDEX OF SHEETS STANDARDS</b>	F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
G:\BRV\CADD plans\Various Counties\64G10	2010 desk beam supports\PLANeng.dgn	DRAWN -	REVISED -			•	(102BR-1M-2 & 141BRM	**	7	3	
	PLOT SCALE = 50.0000' / IN.	CHECKED -	REVISED -			CONTRACT NO. 64G10					
	PLOT DATE = Wed Jan 20 07:26:31 2010	DATE -	REVISED -			ILLINOIS FED. AID PROJECT					
					SCALE: _____	SHEET NO. ____ OF ____ SHEETS		STA. _____ TO STA. _____			