

FLUSH PAVED MEDIAN: TWO-WAY LEFT TURN LANE WITH ONE-WAY LEFT TURN LANE AT SIGNALIZED INTERSECTION

TYPICAL PAVEMENT MARKING LEGEND


(Note: This is a District Standard Legend. Some elements may not apply to specific project.)

- 1 4(100) Solid (Yellow)
- (2) 4(100) Solid (White)
- 3 2-6(150) Crosswalk @ 6'-6" (2m)min C.-C. (White)
 2-8(200) Crosswalk @ 6'-6" (2m)min C.-C. (White) (When traffic signals are present.)
- 4 6(150) Skip-Dash (White)
- 10' 30' 10' (See Special Note 1)

(3.05m)

(See Special Note 1)

- (5) 8(200) Solid (White)
- (6) 12(300) Diagonal (White) (Item (6) is shown on Std. 780001)
- 7) 24(600) Stop Bar (White)
- (8) Letters & Arrows



9 4(100) Skip-Dash (Yellow)

(11) 4(100) Double Solid (Yellow)

(ii) 12(300) Diagonal (Yellow) (See Table A)

See Table A

SPECIAL NOTES

- Skip-Dash markings will be centered between both ends of city blocks and shall be placed in alignment transversly across the pavement.
- The following shall apply to arrows located in one-way left turn lanes:
 - A. A minimum of two (2) arrows is required.
 - B. The maximum spacing between arrows is 80′ (24 m).
 - Arrows shall be evenly spaced if three (3) or more are required.
- 3. The following shall apply to arrow pairs located in two-way left turn lanes:
 - A. A minimum of two (2) arrow pairs is required. B. The maximum spacing between arrow pairs
 - is 200' (61 m). C. Arrow pairs shall be evenly spaced if three (3)
 - or more are required.

 D. The spacing between Bi Directional Left Turn Arrows is 33' (10 m).

NOT TO SCALE

GENERAL NOTES

- Refer to State Standard 780001 for additional Pavement Markings including letters & arrows.
- See Plans for Pavement Markings adjacent to curbed islands and medians, and through lane reductions.

01-01-97	RENUM. F-8.03, NEW REVISION BOX	T.P.		10-16-06	REVISED TO 2007 SPEC.			
02-07-97	ADD BI DIRECTIONAL DIMENSION	J.A.						
10-97	CORRECT BI DIRECTIONAL DIMENSION	J.A.						
08-02	ADD CROSSWALK DMNS. WITH T.S.	M.A.						

11(280) C.-C.-

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TYPICAL PAVEMENT MARKINGS

SHT. 1 OF 2
CADD STD. 780001-D4

FED. ROAD DIST. NO. | ILLINOIS FED. AID PROJECT