

TABULATION OF HMA PAVEMENT QUANTITIES										
LOCATION	AVE. WIDTH	AVG LENGTH	AREA	POLY. BIT. MAT. PR. CT.	AGG. PRIME COAT	GEOTECH FABRIC FOR GROUND STABILIZATION	SUB-BASE GRANULAR MATERIAL, TY B	HMA BASE COURSE	HMA SC, MIX "C", N50	AGGREGATE SHOULDERS, TY B
	FEET	FEET	SQYD	TONS	TONS	SQYD	TONS	TONS	TONS	TONS
JOBSITE 1	31.6	43.7	153.6	0.4	0.20	213.0	73.0	52.0	18.0	19.0
TOTAL				0.4	0.2	213	73	52	18	19

TABULATION OF PAVEMENT MARKING QUANTITIES					
LOCATION	PAINT PVT MARKING - LINE 4"		SHORT TERM PAVEMENT MARKING		WORK ZONE PAVEMENT MARKING REMOVAL
	FOOT	FOOT	FOOT	FOOT	SQFT
JOBSITE	YELLOW	WHITE	YELLOW	WHITE	
	56.0	150.0	24.0	48.0	12.0
TOTAL	206		72		12

APPLICATION RATES	
FOR ALL HOT MIXES: 112 LBS / SQ YD / IN	
FOR AGGREGATE SHOULDERS TYPE B: 2.05 TON / CU YD	
FOR POLY BITUMINOUS MATERIAL (PRIME COAT):	FOR AGGREGATE (PRIME COAT):
- ON GRANULAR BASE: 0.5 GAL / SQ YD	- ON EXISTING PAVEMENT: 4 LBS / SQ YD
- ON EXISTING PAVEMENT: 0.05 GAL /SQ YD	- ON COLD MILLED SURFACE: 4 LBS / SQ YD
- ON COLD MILLED SURFACE : 0.1 GAL / SQ YD	- ON NEW PAVEMENT: 2 LBS / SQ YD
- ON NEW PAVEMENT: 0.03 GAL / SQ YD	

CONVERSION: (0.004 TON = GALLON) , (2000 LBS = TON)