

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
315	(102X)BR, BR-3	MCLEAN	42	13
STA.		TO STA.		
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		

# PROPOSED TYPICAL SECTION (C.H. 21)

- ① HOT-MIX ASPHALT SURFACE COURSE MIXTURE C, 38 mm (91 kg/sq m)
- ② LEVELING BINDER (MACHINE METHOD), N50, 19 mm (46 kg/sq m) & VARIABLE
- ③ HOT-MIX ASPHALT SHOULDERS, 150 mm
- ④ SUB-BASE GRANULAR MATERIAL, TYPE A, 100 mm
- ⑤ HOT-MIX ASPHALT BASE COURSE, 270 mm
- ⑥ HOT-MIX ASPHALT BASE COURSE WIDENING 270 mm
- ⑦ AGGREGATE SHOULDERS, TYPE B
- ⑧ HOT-MIX ASPHALT SHOULDER M TON, 57 mm (137 kg/sq m)
- ⑨ HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH (USE AS NEEDED TO ENSURE 38mm RESURFACING ACCORDING TO PROPOSED PROFILE.)

LOCATION 1 IS FROM STA. 40+500 TO STA. 40+675

LOCATION 2 IS FROM STA. 43+975 TO STA. 44+150

NOTE:  
SEE SHEET 24 FOR INTERSECTION WIDENING AT LOCATION 2.

WHERE INDICATED ON THE PLAN & PROFILE SHEETS DITCH SHALL BE LINED WITH AGGREGATE ACCORDING TO SECTION 283 OF THE STANDARD SPECIFICATIONS AND THE DETAIL ON THIS SHEET.

