## **GENERAL NOTES**

- ALL ELEVATIONS SHOWN IN THE PLANS ARE U. S. G. S. MEAN SEA LEVEL DATUM.
- ANY REFERENCE TO STANDARDS THROUGHOUT THE PLANS SHALL BE
  INTERPRETED TO BE THE LATEST STANDARDS OF THE DEPARTMENT AS INCLUDED
  IN THE BACK OF THE PLANS.
- THE THICKNESS OF HOT-MIX ASPHALT SHOWN ON THE PLANS IS THE NORMAL THICKNESS. DEVIATIONS FROM THE NORMAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HOT-MIX ASPHALT IS PLACED.
- 4 SEEDING WILL NOT BE PERMITTED AT ANY TIME WHEN THE GROUND IS FROZEN.
  WET OR IN AN UNTILLABLE CONDITION. AREAS TO BE SEEDED SHALL BE
  DETERMINED BY THE ENGINEER.
- 5 EXISTING PAVEMENT DAMAGED DUE TO THE CONTRACTOR'S OPERATIONS, AND NOT OTHER WISE NECESSARY TO REPLACE, SHALL BE REPLACED AT THE EXPENSE OF THE CONTRACTOR.
- THE LOCATIONS OF THOSE BURIED AND ABOVE GROUND UTILITIES SHOWN ARE APPROXIMATE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY FROM CONSTRUCTION OPERATIONS AS OUTLINE IN ARTICLE 107.26 OF THE STANDARD SPECIFICATIONS. THE J.U.L.I.E. NUMBER IS 800-892-0123. A MINIMUM OF FORTY-EIGHT HOURS ADVANCED NOTICE IS REQUIRED.
- THE EXISTING ROAD SIGNS THAT INTERFERE WITH CONSTRUCTION SHALL BE RELOCATED AS DIRECTED BY THE ENGINEER. AFTER THE CONSTRUCTION IS COMPLETED, THE CONTRACTOR WILL REPLACE THE SIGNS AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.
- ABANDONED UNDERGROUND UTILITIES THAT CONFLICT WITH CONSTRUCTION
  SHALL BE DISPOSED OUTSIDE THE LIMITS OF RIGHT-OF-WAY ACCORDING TO
  ARTICLE 202.03 OF THE STANDARDS SPECIFICATIONS AND AS DIRECTED BY THE
  ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE
  CONSIDERED INCLUDED IN THE COST OF EARTH EXCAVATION AND NO ADDITIONAL
  COMPENSATION WILL BE ALLOWED.
- 9 WHERE SECTION OR SUBSECTION MONUMENTS ARE ENCOUNTERED THE DEPARTMENT SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL PROPERTY MARKERS AND MONUMENTS UNTIL THE OWNER AND AUTHORIZED SURVEYOR OR AGENT HAS WITNESSED OR OTHERWISE REFERENCED THEIR LOCATION. IF THE ENGINEER DECIDES TO HAVE THE CONTRACTOR RESET THE MONUMENT, THIS WORK WILL BE PAID FOR IN ACCORDANCE WITH ARTICLE 109.04.
- NO PASSING ZONES SHALL BE FIELD VERIFIED BY OPERATIONS, DIST. 6, 14 DAYS PRIOR TO FINAL PAVEMENT MARKINGS. THE DISTRICT 6 SIGN SHOP CAN BE REACHED AT (217)785-0288.
- WHERE PROPOSED CONSTRUCTION ABUTS EXISTING APPURTENANCES, A SAW CUT SHALL BE MADE TO ACHIEVE A NEAT BUTT JOINT. ALL SAWED JOINTS FOR REMOVAL AND BUTT JOINTS SHALL BE CONSIDERED INCLUDED IN HOT-MIX ASPHALT SURFACE REMOVAL, 11/2".

THE FOLLOWING APPLICATION RATES WERE USED FOR QUANTITY CALCULATIONS.

HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N**  HOT-MIX ASPHALT SURFACE COURSE, MIX "-", N**  HOT-MIX ASPHALT SHOULDER  INCIDENTAL BITUMINOUS SURFACE  AGGREGATE (PRIME COAT)  BITUMINOUS MATERIAL (PRIME COAT) (ON BITUMINOUS)  BITUMINOUS MATERIAL (PRIME COAT) (ON AGGREGATE)  NITROGEN  112 lbs/sq, yd, inch  0.002 TON / SQ YD  0.00038 TON / SQ YD  0.001425 TON / SQ YD  90 LBS / ACRE
HOT-MIX ASPHALT SHOULDER  INCIDENTAL BITUMINOUS SURFACE  AGGREGATE (PRIME COAT)  BITUMINOUS MATERIAL (PRIME COAT) (ON BITUMINOUS)  BITUMINOUS MATERIAL (PRIME COAT) (ON AGGREGATE)  112 lbs/sq. yd. inch 0.002 TON / SQ yD 0.00038 TON / SQ yD
INCIDENTAL BITUMINOUS SURFACE  AGGREGATE (PRIME COAT)  BITUMINOUS MATERIAL (PRIME COAT) (ON BITUMINOUS)  BITUMINOUS MATERIAL (PRIME COAT) (ON AGGREGATE)  112 lbs/sq. yd. inch 0.002 TON / SQ YD 0.00038 TON / SQ YD
AGGREGATE (PRIME COAT)  BITUMINOUS MATERIAL (PRIME COAT) (ON BITUMINOUS)  BITUMINOUS MATERIAL (PRIME COAT) (ON AGGREGATE)  0.002 TON / SQ YD  0.00038 TON / SQ YD
BITUMINOUS MATERIAL (PRIME COAT) (ON BITUMINOUS)  BITUMINOUS MATERIAL (PRIME COAT) (ON AGGREGATE)  O.00038 TON / SQ YD  O.001425 TON / SQ YD
BITUMINOUS MATERIAL (PRIME COAT) (ON AGGREGATE) 0.001425 TON / SQ YD
NITROGEN 90 LBS / ACRE
30 ED3 7 AGIL
PHOSPHOROUS 90 LBS / ACRE
POTASSIUM 90 LBS / ACRE
MULCH 2 TON / ACRE
AGRICULTURAL GROUND LIMESTONE 2.0 TON / ACRE
TEMPORARY EROSION CONTROL SEEDING 100 LB / ACRE
RIPRAP 1.50 TON / CU YD
AGGREGATE SHOULDERS TYPE B 1.89 TON / CU YD

12 THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT.

MIXTURE USE(S):	HMA SURFACE & INCIDENTAL HMA SURFACE PG 64-22 4.0% © N DESIGN = 50				
PG					
DESIGN AIR VOIDS					
MIXTURE COMPOSITION	IL 9.5 OR 12.5				
(GRADATION MIXTURE)					
FRICTION AGGREGATE	MIX "C"				

## **COMMITMENTS**

THE RESIDENT ENGINEER SHALL CONTACT STUDIES & PLANS CONCERNING ANY MAJOR PLAN CHANGE, TO MAKE SURE NO PREVIOUS COMMITMENTS (NOT LISTED) WERE MADE AFFECTING THE DESIGN AND ALLOW AN IMPROVED DESIGN FOR FUTURE PROJECTS.

DISTRICT SIX	
EXAMINED Peb 3	20 10
OPERATIONS ENGINEER	
EXAMINED Feb 2	20 10
PROGRAM IMPLEMENTATION ENGIN	NEER
EXAMINED JANY	20 [0
PROGRAM DEVELOPMENT ENGINEE	R

FILE NAME =	USER NAME = nwajelel	DESIGNED	-		REVISED	-
c:\pw_work\PWIDOT\NWAJEISI\dms30940\D67		DRAWN	-	AAD	REVISED	-
	PLOT SCALE = 100.0000 FT / IN.	CHECKED	-	JAC	REVISED	•
	PLOT DATE = Feb-04-2010 07:59:29AM	DATE	-	6/11/2007	REVISED	-