

ENTRANCE IMPROVEMENT SCHEDULE FOR RURAL / URBAN "3R" PROJECTS																	
LOCATION	TYPE OF ENTRANCE	EX MATERIAL TYPE	WIDTH	TOTAL AREA	HMA AREA	LENGTH (FROM EDGE OF PVT/ BIT SHLD TO LIMITS OF HMA IMPROVEMENT)	PR BIT. CONC. THICKNESS	PIPE CULVERT REMOVAL	PAVEMENT REMOVAL	PREP OF BASE	AGG. BASE REPAIR	BIT (P. C.)	AGG (P. C.)	INCIDENTAL BIT. SURF.	HMA SURFACE REMOVAL - BUTT JOINT		
(LT / RT) (STA) ( + )	(FE / PE / CE / MB) - (RURAL / URBAN)	(EARTH / AGG. / HMA / P. C. C.)	FOOT	SQ. FT.	SQ. FT.	FOOT	INCH	FOOT	SQ. YD.	SQ. YD.	TON	TON	TON	TON	SQ. YD.		
LT 816+14	PE	AGG	12	300	300	17	3.5	16		33.3	1	0.01	0.05	6.5			
RT 816+89	ALLEY	O & C	12	249	249	15	3.5			27.7	1	0.01	0.04	5.4			
LT 817+02	PE	AGG	12	306	306	17	3.5	18		34.0	1	0.01	0.05	6.7			
RT 817+09	PE	HMA	20	372	372	15	3.5					0.02	0.06	8.1	41.3		
LT 817+46	PE	AGG	12	285	285	17	3.5	22		31.7	1	0.01	0.05	6.2			
LT 817+68	PE	EARTH	16	354	354	17	3.5	17		39.3	1	0.01	0.06	7.7			
LT 818+47	SW							5									
RT 818+47	SW							5									
RT 818+57	SW							5									
RT 818+74	POPLAR	O & C	25.5	543	543	18	8	36	60.3	60.3	1	0.02	0.09	27.0			
LT 818+88	PE	O & C	12	305	305	17	3.5	18		33.9	1	0.01	0.05	6.6			
LT 819+71	PE	AGG	12	311	311	17.5	3.5	20		34.6	1	0.01	0.05	6.8			
RT 820+34	PE & MB	AGG	55	943	943	13.5	3.5			104.8	1	0.04	0.15	20.5			
LT 820+48	PE	AGG	12	312	312	17.5	3.5	21		34.7	1	0.01	0.05	6.8			
LT 820+89	PE	AGG	12	315	315	18	3.5	20		35.0	1	0.01	0.05	6.9			
LT 822+03	PE	AGG	14	351	351	18	3.5			39.0	1	0.01	0.06	7.6			
LT 822+72	CE	O & C	35	718	718	17.5	8			79.8	1	0.03	0.11	35.7			
RT 823+20	PE	AGG	20	334	334	13.5	3.5			37.1	1	0.01	0.05	7.3			
TOTAL =									203	60.3	625.1	14.0	0.3	0.9	165.9	41.3	

STATION	RT/LT	WIDTH FT	AVG DEPTH FT	VOLUME CU YD
815+17	CL	47	2.75	9.7
816+14	LT	20	2.5	3.6
817+02	LT	20	2.3	3.1
817+46	LT	20	2.1	2.6
817+68	LT	24	2.1	3.2
818+74	RT	40	1.4	2.2
818+88	LT	20	2.1	2.6
819+71	LT	20	2	2.4
820+48	LT	20	2.3	3.1
820+89	LT	20	2.2	2.9
822+03	LT	22	2.5	3.7
TOTAL				39.1
USE				40.0

LOCATION	RT/LT	CURB LENGTH FT	SUBBASE GRANULAR MATERIAL TON
814+65. 814+78.58	LT	18.9	2.15
814+97. 815+15.84	LT	25.2	2.87
815+01. 815+19.38	RT	22.2	2.52
TOTAL			66.3
USE			66.3
8.0			

STATION	RT/LT	PROPOSED WIDTH FT	REMOVAL AREA SQ FT	PROPOSED AREA SQ FT	DETECTABLE WARNING SQ FT
814+70	LT	5	61.5	40.5	10
815+10	LT	5	83.5	110.8	20
815+10	RT	4	79.6	102.0	16
818+47	LT	4	68.1	69.5	8
818+47	RT	4	90.1	134.2	16
818+95	RT	4	30.9	58.7	8
TOTAL			413.7	515.7	78.0
USE			414.0	516.0	78.0

LOCATION (STA)	RT/LT	GRADING AND SHOULDERING (FEET)	
IL 10			
815+29	816+75	RT	146.0
817+29	818+40	RT	111.0
819+00	819+60	RT	60.0
POPLAR STREET			
9+00	9+60	RT	60.0
9+00	9+60	LT	60.0
TOTAL		437.0	