



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

April 5, 2021

SUBJECT FAP 749/FAS Route 659 (IL 133/Cadwell Road)
Section D7 SHLDR Repairs 2021-1
Moultrie County
Contract No. 74A35
Item No. 155, April 23, 2021 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised pages 6 the Special Provisions

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.
Bureau Chief, Design and Environment

MTS

BORROW AREAS, USE AREAS, AND/OR WASTE AREAS

In addition to the provisions contained in Article 107.22 of the Standard Specifications, the Contractor shall submit all required documents to the District electronically. All photos shall be in color.

CHANGEABLE MESSAGE SIGNS

This work shall be completed in accordance with Section 701 of the Standard Specifications, the Supplemental Specifications and the following additional requirements.

The Changeable Message Signs to be installed under this item are to be used as advanced notification of the impending work and as notification of slow-moving vehicles during construction. The Engineer will determine the messages to be displayed on the advanced notification signs. (4) Changeable Message Signs will be required for this project 14 days prior to commencement of work, one for each approach to the project on IL 133 and one for each approach to the project on Cadwell Road. Then, (2) Changeable Message Signs displaying the message "SLOW MOVING VEHICLES AHEAD" will be required to remain during construction, one on each approach to current work zone. The Engineer will determine the exact locations of the Changeable Message Signs.

HOT-MIX ASPHALT SHOULDERS, SPECIAL

In addition to the requirements of Article 406 and 1030 of the Standard Specifications, the following restrictions shall apply.

The coarse aggregate for the Hot-Mix Asphalt Shoulders, Special shall be crushed granite or crushed gravel meeting gradation requirements for CA-16. If crushed gravel is used, it must contain a minimum of 40% hard particles d(siliceous and/or igneous) by weight. The Department must approve the aggregate for the mixture. The coarse aggregate shall be blended with natural sand, FA-01/02 and/or crushed gravel sand, FA-20 to meet the requirements for an IL-9.5 mixture per article 1030.04 (a)(1). A maximum of 10% Recycled Asphalt Pavement (RAP) will be allowed in the mixture.

This work will be paid for at the contract unit price per ton for HOT-MIX ASPHALT SHOULDERS, SPECIAL.

1