



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

April 14, 2015

SUBJECT: FAU Route 1569 (73rd Street)
Section 14-00037-00-RS (Bedford Park)
Cook County
Contract No. 61B26
Item 130
April 24, 2015 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

- 1. Deleted the Special Provision HMA-Quantity Correction (BMPPR) from page 45**

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.
Acting Engineer of Design and Environment

A handwritten signature in cursive script, reading "Ted B. Walschleger, P.E." with a small "P.E." to the right.

By: Ted B. Walschleger, P.E.
Engineer of Project Management

INDEX OF SPECIAL PROVISIONS

LOCATION OF PROJECT.....1

DESCRIPTION OF PROJECT.....1

TRAFFIC CONTROL PLAN.....2

PORTLAND CEMENT CONCRETE SIDEWALK.....3

FRAMES AND LIDS TO BE ADJUSTED (SPECIAL).....3

COMBINATION CURB AND GUTTER REMOVAL AND
REPLACEMENT.....4

CONSTRUCTION STAKING.....4

MAINTENANCE OF ROADWAYS.....5

STATUS OF UTILITIES TO BE ADJUSTED.....6-7

RECLAIMED ASPHALT PAVEMENT AND RECLAIMED
ASPHALT SHINGLES (D-1).....8-18

ADJUSTMENTS AND RECONSTRUCTIONS.....19

HMA MIXTURE DESIGN REQUIREMENTS (D-1).....20-34

GROUND TIRE RUBBER MODIFIED ASPHALT BINDER.....35-36

DETECTOR REPLACEMENT AND/OR INSTALLATION ON ROAD-
WAY GRINDING, RESURFACING AND PATCHING OPERATIONS.....37-40

COARSE AGGREGATE FOR BACKFILL, TRENCH BACKFILL,
AND BEDDING (D-1).....41

PUBLIC CONVENIENCE AND SAFETY (D-1).....42

DRAINAGE & INLET PROTECTION.....43-44

~~HOT MIX ASPHALT QUANTITY CORRECTION (BMPR).....45~~

~~HOT MIX ASPHALT - QUANTITY CORRECTION (BMPP)~~

~~Effective: October 1, 2014~~

~~Revised: October 2, 2014~~

Revise the fifth paragraph of Article 406.13(b) of the Standard Specifications to read as follows:

"HMA and Stone Matrix Asphalt (SMA) mixture in excess of 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer will not be measured for payment. The "adjusted quantity to be placed" and the "adjusted pay quantity" for HMA and SMA mixtures will be calculated as follows.

Adjusted Quantity To Be Placed = C x quantity shown on the plans or the plan quantity as specified by the Engineer

where: C = English: $C = \frac{G_{mb} \times 46.8}{U}$ Metric: $C = \frac{G_{mb} \times 24.99}{U}$

and where: G_{mb} = average bulk specific gravity from approved mix design
U = unit weight of HMA shown on the plans in lb/sq yd/in.
(kg/sq m/25 mm), used to estimate plan quantity
46.8 = English constant
24.99 = metric constant

Adjusted Pay Quantity (not to exceed 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer) = B x HMA tons actually placed

where: $B = \frac{1}{C}$

If project circumstances warrant a new mix design, the above equations shall be used to calculate the adjusted plan quantity and adjusted pay quantity for each mix design using its respective average bulk specific gravity."