



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

April 14, 2015

SUBJECT: FAS 91 (Mulford Road)
Project RS-0091(104)
Section 13-00296-00-RS
Ogle County
Contract No. 85621
Item 179
April 24, 2015 Letting
Addendum (A)

NOTICE TO PROSPECTIVE BIDDERS:

Due to clarify information necessary to revise the following:

- 1. Deleted Hot Mix Asphalt – Quantity Correction (BMPR) from the Index of the Special Provisions.**
- 2. Deleted Hot Mix Asphalt – Quantity Correction (BMPR) from Page 10 of the Special Provisions.**

Prime contractors must utilize the enclosed material when preparing their bid and must include any Schedule of Prices changes in their bidding proposal.

Bidders using computer-generated bids are cautioned to reflect any and all Schedule of Prices changes, if involved, into their computer programs.

Very truly yours,

John Baranzelli, P.E.
Acting Engineer of Design and Environment

A handwritten signature in black ink, reading "Ted B. Walschleger P.E." with a stylized flourish at the end.

By: Ted B. Walschleger, P.E.
Engineer of Project Management

Section: 13-00296-00-RS
County: Ogle County
Project No.: RS-0091(104)
Job No.: C-92-038-15
Contract No.: 85621

INDEX OF SPECIAL PROVISIONS

<u>PAGE</u>	<u>DESCRIPTION</u>
1	DESCRIPTION OF WORK
1	COLD-IN-PLACE RECYCLING – 4”
1	CIR-FDR EMUSLIFIED ASPHALT
1	BITUMINOUS MATERIALS (PRIME COAT)
1	LEVELING BINDER (MACHINE METHOD), IL-9.5FG, N50
2	HOT-MIX ASPHALT SHOULDERS (SPECIAL)
2	AGGREGATE SHOULDER WEDGE (BY OTHERS)
2	HOT-MIX ASPHALT BINDER COURSE, IL 19.0, N50
3	HOT-MIX ASPHALT SURFACE COURSE, MIX C, N50
3	INCIDENTAL HOT-MIX ASPHALT SURFACING
3	SHORT TERM PAVEMENT MARKING
4	HOT-MIX ASPHALT SURFACE REMOVAL – BUTT JOINT
4	TEMPORARY RAMPS
4	TRAFFIC CONTROL & PROTECTION (SPECIAL)
7	HOT-MIX ASPHALT MIXTURE IL-9.5FG (BMPR)
10	HOT-MIX ASPHALT – QUANTITY CORRECTION (BMPR)

Revised 4/14/15

~~HOT MIX ASPHALT QUANTITY CORRECTION (BMPP)~~

~~Effective: October 1, 2014~~

~~Revised: October 2, 2014~~

~~Revise the fifth paragraph of Article 406.13(b) of the Standard Specifications to read as follows:~~

~~"HMA and Stone Matrix Asphalt (SMA) mixture in excess of 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer will not be measured for payment. The "adjusted quantity to be placed" and the "adjusted pay quantity" for HMA and SMA mixtures will be calculated as follows.~~

~~Adjusted Quantity To Be Placed = C x quantity shown on the plans or the plan quantity as specified by the Engineer~~

~~where: C = English: $C = \frac{G_{mb} \times 46.8}{U}$ Metric: $C = \frac{G_{mb} \times 24.99}{U}$~~

~~and where: G_{mb} = average bulk specific gravity from approved mix design
U = unit weight of HMA shown on the plans in lb/sq yd/in.
(kg/sq m/25 mm), used to estimate plan quantity
46.8 = English constant
24.99 = metric constant~~

~~Adjusted Pay Quantity (not to exceed 103 percent of the quantity shown on the plans or the plan quantity as specified by the Engineer) = B x HMA tons actually placed~~

~~where: $B = \frac{1}{C}$~~

~~If project circumstances warrant a new mix design, the above equations shall be used to calculate the adjusted plan quantity and adjusted pay quantity for each mix design using its respective average bulk specific gravity."~~