



SIGN PANEL							
STATION	SIGN	MUTCD CODE	DIMENSIONS	SOLAR-POWERED FLASHING BEACON ASSEMBLY (EACH)	SIGN PANEL TYPE 1 (SQ FT)	TELESCOPING STEEL SIGN SUPPORT (FEET)	ELECTRICAL POWERED BEACON (EACH)
104+55.00	24.00' RT	STOP AHEAD	3' X 3'	1	9.0	10	
104+55.00	24.00' RT	800 FEET	2' X 1.5'		3.0		
111+50.00	38.20' RT	STOP AHEAD	3' X 3'	1	9.0	10	
114+30.00	52.50' RT	STOP SIGN	2.5' X 2.5'		6.3	10	
114+62.50	21.50' RT	STOP SIGN	2.5' X 2.5'		6.3	10	1
114+65.00	53.80' LT	STOP SIGN	2.5' X 2.5'		6.3	10	
115+17.50	18.50' LT	STOP SIGN	2.5' X 2.5'		6.3	10	1
115+30.00	56.00' RT	STOP SIGN	2.5' X 2.5'		6.3	10	
115+50.00	47.00' LT	STOP SIGN	2.5' X 2.5'		6.3	10	
118+35.00	32.00' LT	STOP AHEAD	3' X 3'	1	9.0	10	
123+30.00	23.40' LT	STOP AHEAD	3' X 3'	1	9.0	10	
123+30.00	23.40' LT	800 FEET	2' X 1.5'		3.0		
TOTAL				4	79.8	100	2

*SEE SPECIAL PROVISION FOR "FLASHING BEACON ASSEMBLY (COMPLETE)"

- NOTE:
- SEE SCHEDULE OF QUANTITIES FOR LOCATION OF PROPOSED PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS.
 - FLASHING BEACONS TO BE HARD WIRED TO NEW STOP SIGNS LOCATED IN THE PROPOSED CORNER ISLANDS ADJACENT TO SPRINGFIELD ROAD. SEE SPECIAL PROVISIONS FOR CONSTRUCTION REQUIREMENTS.

