

STORM SEWER STRUCTURE SCHEDULE

STORM SEWER SCHEDULE

STRUCTURE ID	STATION	OFFSET	STRUCTURE TYPE	DIAMETER (FT)	FRAME	RIM	DOWNSTREAM INVERT AND DIRECTION	UPSTREAM INVERT AND DIRECTION	UPSTREAM INVERT AND DIRECTION	UPSTREAM INVERT AND DIRECTION
*/**	16	279+10.14	0.00' RT	MH Type A	4	T24 F&G	655.29	651.62 N	651.62 E	651.62 W
*/**	17	279+10.14	29.00' RT	Inlet Type A	2	T20 F&G	654.81	651.76 E		
*/**	18	279+10.27	29.00' LT	CB Type A	4	T20 F&G	654.81	651.76 W	651.76 NE	
	19	279+21.94	30.58' LT	Inlet Type A	2	T24 F&G	654.81	651.82 NW		
	64	276+56.38	0.00' LT	MH Type A	4	T1F CL	645.00	639.68 N	639.68 W	639.68 E
*/**	65	276+56.38	29.77' RT	CB Type C	2	T20 F&G	644.53	639.98 E		641.50 S
*/**	66	276+63.89	29.62' LT	CB Type A	4	T20 F&G	644.80	639.81 W	639.81 SE	
*	97	276+75.48	30.94' LT	Inlet Type A	2	T24 F&G	645.19	639.93 N		
*/**	100	283+16.71	30.06' RT	CB Type C	2	T20 F&G	660.05	653.47 E		
	102	283+17.34	0.00' RT	MH Type A	4	T1F CL	660.63	653.27 S	653.34 W	653.27 E
*	103	283+17.70	32.02' LT	CB Type C	2	T20 F&G	660.00	653.40 W		
	104	284+77.91	0.00' RT	MH Type A	4	T1F CL	657.04	648.66 S	648.66 N	
*/**	105	286+27.56	36.92' RT	CB Type C	2	T20 F&G	650.28	642.21 E		
	106	286+29.30	3.93' LT	MH Type A	5	T1F CL	651.30	642.04 SE	642.04 N	642.04 W
*	107	286+30.87	35.00' LT	CB Type A	4	T20 F&G	650.15	642.85 W	642.89 N	
	109	287+95.28	5.67' LT	MH Type A	4	T1F CL	645.00	635.81 NE	636.06 SW	636.06 SE
	109A	288+01.19	41.12' LT	CB Type A	4	T24 F&G	643.68	632.46 NE	632.46 SE	
	109B	288+09.69	40.56' LT	Inlet Type A	4	T24 F&G	643.35	636.15 NW		
	110	288+07.97	100.68' RT	FES 15	-	--	--	--	628.00 E	
	201	278+73.45	67.03' LT	Restrictor MH	6	T1F 2 CL	631.74	625.71 W		
	202	288+04.34	59.99' LT	Restrictor MH	6	T1F 2 CL	633.00	627.31 W	627.31 N	
	203	287+55.71	88.01' LT	FES 12	-	--	--	628.00		
	204	285+43.10	58.78' LT	MH Type A	5	T1F CL	633.00	627.70	627.70 E	627.70 N
	205	285+44.82	84.33' LT	FES 12	-	--	--	628.00		
	206	283+50.00	83.76' LT	FES 24	-	--	--	628.00		
	207	283+71.70	59.45' LT	MH Type A	4	T1F CL	633.00	627.96	627.96 E	
	208	287+56.30	67.31' LT	MH Type A	5	T1F CL	633.00	626.38 S	627.70 E	627.38 N

PIPE ID	UPSTREAM STRUCTURE ID	DOWNSTREAM STRUCTURE ID	PIPE CLASS	PIPE TYPE	DIAMETER (INCHES)	LENGTH (FEET)	SLOPE (%)	UPSTREAM INVERT	DOWNSTREAM INVERT	TRENCH BACKFILL (CY)
p16	16	15	A	Type 2	12	253	4.00	651.62	641.50	62.09
p17	17	16	A	Type 2	12	27	0.52	651.76	651.62	2.21
p18	18	17	A	Type 2	12	27	0.52	651.76	651.62	2.21
p19	19	17	A	Type 2	12	11	0.55	651.82	651.76	0.51
P65	65	64	A	Type 2	12	30	1.00	639.98	639.68	0.00
P66	66	64	A	Type 2	12	30	0.43	639.81	639.68	0.00
P97	97	66	A	Type 2	12	12	1.00	639.93	639.81	3.21
P100	100	102	A	Type 2	12	33	0.39	653.47	653.34	0.00
P102	102	104	A	Type 2	12	160	2.88	653.27	648.66	0.00
P103	103	102	A	Type 2	12	33	0.39	653.40	653.27	0.00
P104	104	106	A	Type 2	12	151	4.38	648.66	642.04	0.00
P105	105	106	A	Type 2	12	42	0.40	642.21	642.04	0.00
P106	106	109	A	Type 2	18	165	3.64	642.04	636.06	0.00
P107	107	106	A	Type 2	12	31	1.45	642.85	642.40	0.00
P109	109	109A	A	Type 2	15	58	5.74	635.81	632.46	0.00
P109A	109A	110	A	Type 2	15	48	9.32	632.46	628.00	0.00
P109B	109B	109	A	Type 2	12	39	0.23	636.15	636.06	0.00
P201	201	48	A	Type 2	12	110	0.44	625.71	625.23	101.40
P202	202	82	A	Type 2	24	134	0.87	627.31	626.15	118.02
P203	203	202	A	Type 2	12	21	1.43	628.00	627.70	0.00
P204	204	202	A	Type 2	24	200	0.16	627.70	627.38	98.66
P205	205	204	A	Type 2	12	22	1.36	628.00	627.70	0.00
P206	206	207	A	Type 2	24	28	0.14	628.00	627.96	10.33
P207	207	204	A	Type 2	24	162	0.16	627.96	627.70	72.90
P208	208	202	A	Type 2	24	47	0.17	627.38	627.31	35.51

* SHIM F&G TO MATCH 2.00% ROADWAY CROSS SLOPE
 ** OFFSET TO BACK OF FRAME