

Geo Services, Inc. SOIL BORING LOG PAGE 2 of 2
 Geotechnical, Environmental & Civil Engineering
 805 Amherst Court, Suite 204
 Naperville, Illinois 60563
 (630) 355-2838

ROUTE FAP 353 (US 30) DESCRIPTION US Route 30 @ EJ&E/CN Railroad, IDOT Job No. D-91-046-12
 SECTION 11-Y-A LOCATION SEC 20 & 29, T 35 N, R 15 E, 3rd PM
 COUNTY Cook DRILLING METHOD Hollow Stem Auger/Rotary HAMMER TYPE Diedrich Automatic

STRUCT. NO. 016-1280
 Station ---
 BORING NO. RW-29
 Station 287+40
 Offset 66.0' Left
 Ground Surface Elev. 630.2

DEPTH (ft)	BLOW COUNT (blows/6")	UCS (tsf)	MOIST (%)	Surface Water Elev.		Stream Bed Elev.		Groundwater Elevation:		DEPTH (ft)	BLOW COUNT (blows/6")	UCS (tsf)	MOIST (%)
				First Encounter	Upon Completion	First Encounter	Upon Completion	First Encounter	Upon Completion				
0				n/a		n/a		Dry to -10.0'		0			
7										7			
10										10			
12	NP	11								12	NP	22	
19										19			
26										26			
30	NP	20								30	NP	20	
38										38			
45										45			
50	NP	21								50	NP	19	
55										55			
60	NP	23								60	NP	23	

End of Boring @ -75.0'
 Hollow Stem Augers To -10.0'
 Rotary Drilling To Completion
 10.0' Of 4.0" Casing Used
 Diedrich Automatic Hammer

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) ST-Shelby Tube Sample VS-Vane Shear Test
 The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) The Unit Dry Weight (pcf) is noted in Italics above moist (%)
 NR-No Recovery

Geo Services, Inc. SOIL BORING LOG PAGE 1 of 2
 Geotechnical, Environmental & Civil Engineering
 805 Amherst Court, Suite 204
 Naperville, Illinois 60563
 (630) 355-2838

ROUTE FAP 353 (US 30) DESCRIPTION US Route 30 @ EJ&E/CN Railroad, IDOT Job No. D-91-046-12
 SECTION 11-Y-A LOCATION SEC 20 & 29, T 35 N, R 15 E, 3rd PM
 COUNTY Cook DRILLING METHOD Hollow Stem Auger/Rotary HAMMER TYPE Diedrich Automatic

STRUCT. NO. 016-1282
 Station ---
 BORING NO. RW-31
 Station 283+75
 Offset 23.0' Right
 Ground Surface Elev. 632.7

DEPTH (ft)	BLOW COUNT (blows/6")	UCS (tsf)	MOIST (%)	Surface Water Elev.		Stream Bed Elev.		Groundwater Elevation:		DEPTH (ft)	BLOW COUNT (blows/6")	UCS (tsf)	MOIST (%)
				First Encounter	Upon Completion	First Encounter	Upon Completion	First Encounter	Upon Completion				
0				n/a		n/a		Dry to -10.0'		0			
3										3			
5										5			
7	3.1B	26								7	3.1B	26	
6										6			
7										7			
5										5			
7	3.25B	26								7	3.25B	26	
1										1			
2										2			
2										2			
3										3			
4										4			
10										10			
2										2			
2										2			
2	NP	19								2	NP	19	
2										2			
3										3			
15										15			
5										5			
2										2			
3										3			
3	NP	24								3	NP	24	
2										2			
3										3			
3										3			
2										2			
3										3			
15										15			
19										19			
20										20			
4										4			
5										5			

End of Boring @ -75.0'
 Hollow Stem Augers To -10.0'
 Rotary Drilling To Completion
 10.0' Of 4.0" Casing Used
 Diedrich Automatic Hammer

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) ST-Shelby Tube Sample VS-Vane Shear Test
 The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) The Unit Dry Weight (pcf) is noted in Italics above moist (%)
 NR-No Recovery

Geo Services, Inc. SOIL BORING LOG PAGE 2 of 2
 Geotechnical, Environmental & Civil Engineering
 805 Amherst Court, Suite 204
 Naperville, Illinois 60563
 (630) 355-2838

ROUTE FAP 353 (US 30) DESCRIPTION US Route 30 @ EJ&E/CN Railroad, IDOT Job No. D-91-046-12
 SECTION 11-Y-A LOCATION SEC 20 & 29, T 35 N, R 15 E, 3rd PM
 COUNTY Cook DRILLING METHOD Hollow Stem Auger/Rotary HAMMER TYPE Diedrich Automatic

STRUCT. NO. 016-1282
 Station ---
 BORING NO. RW-31
 Station 283+75
 Offset 23.0' Right
 Ground Surface Elev. 632.7

DEPTH (ft)	BLOW COUNT (blows/6")	UCS (tsf)	MOIST (%)	Surface Water Elev.		Stream Bed Elev.		Groundwater Elevation:		DEPTH (ft)	BLOW COUNT (blows/6")	UCS (tsf)	MOIST (%)
				First Encounter	Upon Completion	First Encounter	Upon Completion	First Encounter	Upon Completion				
0				n/a		n/a		Dry to -10.0'		0			
9										9			
12										12			
17	NP	23								17	NP	23	
18										18			
25										25			
25	NP	22								25	NP	22	
25										25			
12										12			
13										13			
13	NP	21								13	NP	21	
14										14			
19										19			
22										22			
22	4.5+P	10								22	4.5+P	10	
12										12			
18										18			
15										15			
18										18			
15	NP	20								15	NP	20	
18										18			
15										15			
18										18			
15	NP	20								15	NP	20	
18										18			
15										15			
18										18			
15										15			
18										18			
15	NP	20								15	NP	20	
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15										15			
18										18			
15		</											