FRAME EXTENSION INTO PAVEMENT	INNER HOOP REINFORCEMENT DIAMETER	SEMI CIRCULAR FORM DIAMETER	OUTER HOOP REINFORCEMENT DIAMETER
UP TO 8" (200)	3′-6″ (1.1 m)	4'-0" (1.2 m)	5'-0" (1.5 m)
> 8" (200) T0 14" (360)	4'-0'' (1.2 m)	4'-6" (1.4 m)	5′-0″ (1.5 m)

DESIGNER NOTE: THIS DETAIL IS TO BE USED WHEN THE GUTTER FLAG IS LESS THAN 24"

LEGEND:

DRAWN

DATE

LOT DATE = 8/21/2013

CHECKED

DRP

VJD

08/14/2013

REVISED

REVISED

REVISED

NOTES :

- 1. THE ROUNDOUT AND ADDED REINFORCEMENT WILL NOT BE PAID SEPARATELY, BUT SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR THE PAYEMENT.
- 2. TRANSVERSE JOINTS MAY BE MOVED TO ACCOMMODATE ROUNDOUT, EDGE OF CIRCULAR JOINT SHALL BE MINIMUM 12" (300) FROM TRANSVERSE JOINT.
 RELOCATED TRANSVERSE JOINT SHALL BE CONTINUOUS FROM EDGE OF PAVEMENT
- 3. SEMI-CIRCULAR FORM SHALL BE REMOVED PRIOR TO DRILL AND GROUT OF TIE BARS.
- 4. ALL REINFORCED BARS SHALL BE EPOXY COATED.
- 5. DRILL AND GROUT IS PREFERRED, HOWEVER TIE BARS CAN BE POURED IN PLACE IF CLEARANCE IS PROVIDED TO OUTER EDGE OF FRAME. MINIMUM 2" (50) CLEARANCE.
- 6. WOOD SHIMS SHALL BE USED TO ADJUST ALL FRAMES. AFTER ADJUSTING MORTAR HAS CURED, THE WOOD SHIMS SHALL BE REMOVED AND THE VOIDS UNDER THE FRAMES FILLED WITH NON SHRINK GROUT.

SECTION

11-Y-A

353

COUNTY

ILLINOIS FED. AID PROJECT

COOK 354 294

CONTRACT NO. 60R19


- 7. HOOP REINFORCEMENT SHALL BE ONE PIECE CONSTRUCTION.
- 8. CIRCULAR FRAMES AND GRATES MAY BE SUBSTITUTED.
- 9. CURB DOWELS MUST BE PLACED LEVEL & TRUE TO ALLOW CONTRACTION MOVEMENT.

PCC PAVEMENT ROUNDOUTS AT

CURB AND GUTTER

SHEET NO. 1 OF 1 SHEETS

SCALE: N/A



STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION