## GENERAL NOTES

Reinforcement bars designated (E) shall be epoxy coated.

Layout of the slope protection system may be varied to suit ground conditions in the field as directed by the Engineer.

The embankment configuration shown shall be the minimum that must be placed and compacted prior to construction of the abutments.

Seal coat thickness design is based on the Cofferdam Design Water Elevation (CDWE). Cofferdam design details and proposed changes in seal coat thickness shall be submitted to the Engineer for approval with the cofferdam design.

Slipforming of the parapets is not allowed.

The Contractor shall retain the services of an engineering firm, prequalified in the IDOT consultant selection category of Highway Bridges-Typical for preparation of the Structural Assessment Reports. Contractor's pre-approval shall not be applicable for this project. See Special Provision.

Current Ratings on File for Existing Structure Inventory: HS 11.5 Operating: HS 19.2 Live Load Restrictions: No

Inventory and Operating Ratings and Live Load Restrictions are provided for information only. Inventory and Operating Ratings are based on HS loading and configuration. Live Load Restrictions are based on Illinois legal loads and configurations. The Ratings and Live Load Restrictions are not necessarily representative of capacities to support the Contractor's equipment.

The Contractor is advised that the existing structure contains members that are in a deteriorated condition with reduced load carrying capacity. It is the Contractor's responsibility to account for the condition of the existing structure when developing construction procedures for the complete or partial removal, or replacement of the structure. An Existing Structure Information Package is available upon request as noted in the special provisions.

### DESIGN SCOUR ELEVATION TABLE

Design Scour	W. Abut.	Pier 1	Pier 2	Pier 3	E. Abut.
Elevation (ft.)	632.3	602.75	602.75	602.75	632.2

#### WATERWAY INFORMATION

Drainage Area = 252.0 sq. mi.				Low Grade Elev. 640.70 @ Sta. 732+50						
Flood	Freq.	a	Opening	Sq. Ft.	Nat.	Head - Ft.		Headwater El.		
1 1000	Yr.	C.F.S.	Exist.	Prop.	H.W.E.	Exist.	Prop.	Exist.	vater El. Prop. 3 633.3 2 635.4 2 636.2	
	10	12823	1993	2624	631.6	2.2	1.7	633.8	633.3	
Design	50	19116	2357	3086	633.0	3.2	2.4	636.2	635.4	
Base	100	21855	2507	3279	633.6	3.6	2.6	637.2	636.2	
Overtopping										
Max. Calc.	500	28752	2836	3381	634.9	4.6	3.7	639.5	638.6	







1'-0'' min.-

Note:



#### LEGEND



Existing Riprap to be reused.

Existing riprap to be used in place except as directed by the Engineer. Cost included with Stone Dumped Riprap, Class A6. Cost of existing riprap removal required for cofferdam and pier construction included with Cofferdam Excavation.

EFK Moen, LLC	USER NAME = cdl	DESIGNED - CTW	REVISED -	STATE OF ILLINOIS	GENERAL DATA		SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
Civil Engineering Design		CHECKED - CDL	REVISED -		STRUCTURE NO 002_0207	711	116BR-1	VERMILION	84	32
331 Salem Place, Suite 225 Fairview Heights, IL, 62208	PLOT SCALE = 0:2 ':' / IN.	DRAWN - CTW	REVISED -	DEPARTMENT OF TRANSPORTATION	31N0010NL NO. 032-0207	CONTRACT NO. 70				J614
Phone 618-206-4250	PLOT DATE = 3/17/2014 DATE - 3/17/2014 REVISED -	REVISED -		SHEET NO. 2 OF 33 SHEETS	ILLINOIS FED. AID PROJECT					



# SECTION THRU INTEGRAL ABUTMENT

\*Included in the cost of Pipe Underdrains for Structures.

All drainage system components shall extend to 2'-O'' from the end of each wingwall except an outlet pipe shall extend until intersecting with the side slopes. The pipes shall drain into concrete headwalls. (See Article 601.05 of the Standard Specifications and Highway Standard 601101).