



SEQUENCE OF CONSTRUCTION

1. Remove the existing bituminous surface.
2. Remove and replace full depth patches.
3. Replace bituminous surface.

PAVEMENT PATCHING FOR BITUMINOUS SURFACED PAVEMENT

GENERAL NOTES

1. The width of the full depth patch over a trench shall be 12 (300) wider on each side of the trench.
2. For basis of payment see Special Provision "Bituminous Surface Removal over Patches".

All dimensions are in inches (millimeters) unless otherwise shown.

FILE NAME =	USER NAME = sparksgw	DESIGNED -	REVISED -
c:\pwork\pwork\sparksgw\0373645\0672890-sht-district.details.dgn		DRAWN -	REVISED -
PATCHBIT.DGN		CHECKED -	REVISED -
D6BitPatch	PLOT DATE = Feb-04-2014 01:49:46PM	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

DISTRICT 6 DETAILS FOR PAVEMENT PATCHING FOR
BITUMINOUS SURFACED PAVEMENT

SCALE: SHEET OF SHEETS STA. TO STA.

F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
8012	21(W-3, TS-1, RS-7)	SANGAMON	679	450
			CONTRACT NO. 72890	
ILLINOIS FED. AID PROJECT				