

MILLING & RESURFACING						
LOCATION	HMA SURF REMOVAL, 2 1/4"	BITUMINOUS MATERIALS (PC)	AGGREGATE (PC)	HMA SURFACE COURSE, MIX D. N70	HMA SHOULDERS	AGG WEDGE SHOULDER, TYPE B
	SO YD	TON	TON	TON	TON	TON
MM 0.000 - 0.012	176.0	0.06	0.3	22.2		2.0
MM 0.012 - 0.176	2405.3	0.75	3.6	303.1		
MM 0.176 - 0.492	4634.7	1.45	7.0	584.0		
MM 0.492 - 0.541	718.7	0.22	1.1	90.6		23.6
MM 0.541 - 0.730	2661.1	0.83	4.0	335.3		
MM 0.730 - 0.797	982.7	0.31	1.5	123.8		11.4
MM 0.797 - 0.965	2464.0	0.77	3.7	310.5		28.8
MM 0.965 - 1.874	13332.0	4.17	20.0	1679.8		155.6
MM 1.874 - 2.025	2214.7	0.69	3.3	279.1		25.8
MM 2.025 - 2.179	2258.7	0.71	3.4	284.6		26.4
MM 2.179 - 3.458	18758.7	5.87	28.1	2363.6		218.8
MM 3.458 - 3.557	1452.0	0.45	2.2	183.0		17.0
MM 3.557 - 3.590	571.1	0.18	0.9	72.0	7.3	5.6
ENTRANCE				10.1		
TOTALS	52629.7	16.46	79.1	6641.7	7.3	515.0

△

CONCRETE GUTTER											
LOCATION		GUTTER REMOVAL (SPECIAL)	CONCRETE GUTTER, TYPE A	CONCRETE GUTTER, TYPE B	CLASS SI CONCRETE	PERIMETER EROSION BARRIER	SEEDING, CLASS 2	NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	EROSION CONTROL BLANKET
		FOOT	FOOT	FOOT	CU YD	FOOT	ACRE	POUND	POUND	POUND	SO YD
LOCATION #1	RT	12		687	4.18	757	0.07	6.3	6.3	6.3	344.0
LOCATION #1	LT		391		6.04	336	0.10	9.0	9.0	9.0	144.7
LOCATION #2	RT	289		212	5.94	444	0.07	6.3	6.3	6.3	325.7
LOCATION #2	LT	335	287		6.04	485	0.03	2.7	2.7	2.7	125.3
LOCATION #3	RT	402		315	6.62	397	0.02	1.8	1.8	1.8	109.3
LOCATION #3	LT	413	365		6.04	475	0.03	2.7	2.7	2.7	130.8
TOTALS		1451	1043	1214	34.86	2894	0.32	28.8	28.8	28.8	1179.8

THERMOPLASTIC PAVEMENT MARKING - LINE 4"			
LOCATION	CENTERLINE		EDGELINE
	SOLID YELLOW	DASHED YELLOW	SOLID WHITE
	FOOT	FOOT	FOOT
MM 0.000 - 0.39	4171		4171
MM 0.395 - 0.56	887	220	1774
MM 0.563 - 0.680		160	1236
MM 0.680 - 0.90	1183	300	2365
MM 0.904 - 1.07	1795		1795
MM 1.074 - 1.179	554	140	1109
MM 1.179 - 1.277	1035		1035
MM 1.277 - 1.341	338	90	676
MM 1.341 - 1.377		50	380
MM 1.377 - 1.556	945	240	1890
MM 1.556 - 1.752		260	2070
MM 1.752 - 1.972	1162	290	2323
MM 1.972 - 2.471	5269		5269
MM 2.471 - 2.69	1188	300	2376
MM 2.696 - 2.796		130	1056
MM 2.796 - 3.00	1093	270	2186
MM 3.003 - 3.16	1700		1700
MM 3.164 - 3.30	760	190	1521
MM 3.308 - 3.37	729		729
MM 3.377 - 3.51	750	190	1500
MM 3.519 - 3.59	750		750
SUB-TOTALS	24309	2830	37911
TOTAL		65050	

RAISED REFLECTIVE PAVEMENT MARKERS		
LOCATION	NEW 2-WAY AMBER	REMOVAL
	EACH	EACH
MM 0.000 - 0.39	26	26
MM 0.395 - 0.56	11	11
MM 0.563 - 0.68	8	8
MM 0.680 - 0.90	15	15
MM 0.904 - 1.07	11	11
MM 1.074 - 1.179	7	7
MM 1.179 - 1.277	6	6
MM 1.277 - 1.341	4	4
MM 1.341 - 1.377	2	2
MM 1.377 - 1.556	12	12
MM 1.556 - 1.752	13	13
MM 1.752 - 1.972	15	15
MM 1.972 - 2.471	33	33
MM 2.471 - 2.69	15	15
MM 2.696 - 2.79	7	7
MM 2.796 - 3.00	14	14
MM 3.003 - 3.16	11	11
MM 3.164 - 3.30	10	10
MM 3.308 - 3.37	5	5
MM 3.377 - 3.51	9	9
MM 3.519 - 3.59	5	5
TOTALS	239	239

PAVEMENT PATCHING, 17"					
LOCATION	SIZE	TYPE I	TYPE II	TYPE III	TYPE IV
		SO YD	SO YD	SO YD	SO YD
MM 0.20 NB	10' X 12'		13.3		
MM 0.20 SB	10' X 12'		13.3		
MM 0.21 SB	15' X 12'			20.0	
PROJECT LIMITS		4.0			25.0
15% CONT.			4.0	3.0	
TOTALS		4.0	30.6	23	25.0

△ REV. 4-9-14