



LEGEND	
(A)	EXISTING HMA PAVEMENT
(B)	PAVED SHOULDER REMOVAL
(1)	HOT-MIX ASPHALT SURFACE COURSE, MIX C, N90, 1 1/2"
(2)	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N90, 2 1/2"
(3)	HOT-MIX ASPHALT SHOULDERS, 4"
(4)	AGGREGATE BASE COURSE, TYPE A 8"
(5)	HOT-MIX ASPHALT SHOULDERS, 15 1/4"
(6)	PIPE UNDERDRAINS, 4"
(7)	PROCESSING LIME STABILIZED SOIL MIXTURE 12"
(8)	COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24
(9)	PORTLAND CEMENT CONCRETE SIDEWALK 6 INCH
(10)	SUBBASE GRANULAR MATERIAL, TYPE C
(11)	AGGREGATE SHOULDERS, TYPE A 8"
(12)	HOT-MIX ASPHALT SURFACE COURSE, MIX D, N90, 2 1/2"
(13)	PORTLAND CEMENT CONCRETE SIDEWALK 4 INCH
(14)	CONCRETE GUTTER, TYPE A
(15)	HOT-MIX ASPHALT SHOULDERS, 8"
(16)	CONCRETE MEDIAN SURFACE, 4 INCH
(17)	PAVED DITCH, TYPE A-15
(18)	NOT USED
(19)	STEEL PLATE BEAM GUARDRAIL, TYPE A, 6 FOOT POSTS
(20)	HOT-MIX ASPHALT PAVEMENT (FULL DEPTH), 15 1/4"
(21)	SUBBASE GRANULAR MATERIAL, TYPE A 8"
(22)	HOT-MIX ASPHALT PAVEMENT (FULL DEPTH), 10 3/4"
(23)	AGGREGATE SHOULDERS, TYPE B
(24)	CONCRETE MEDIAN, TYPE SB-6.24
(25)	SUBBASE GRANULAR MATERIAL, TYPE A 12"
(26)	COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.24
(27)	CONCRETE MEDIAN, TYPE SB-6.06
(28)	HOT-MIX ASPHALT REMOVAL, 2"
(29)	HOT-MIX ASPHALT SURFACE COURSE, MIX E, N90, 2"

- 1 STA 55+22.19 TO STA 62+90.00  
STA 75+15.00 TO STA 85+45.00  
STA 97+95.00 TO STA 101+80.00  
STA 105+95.00 TO STA 115+15.00
- 2 STA 53+87.19 TO STA 55+22.19
- 3 STA 50+75.00 TO STA 53+87.19
- 4 STA 52+25.85 TO STA 62+90.00  
STA 75+15.00 TO STA 85+45.00  
STA 97+95.00 TO STA 101+80.00  
STA 105+95.00 TO STA 115+15.00
- 5 STA 50+75.00 TO STA 52+25.85

NOTES:

- INDEPENDENT SHARED USE PATH ALIGNMENT AND PROFILE NORTH FRONTAGE RD STA 69+12.88 TO STA 106+11.79.
- FOR SUPERELEVATED CURBED SECTIONS, TOP SIDE CURB AND GUTTER TO HAVE REJECT SLOPE.
- FOR SPECIAL DITCH PROFILES, SEE ROADWAY, DRAINAGE AND UTILITY PLANS.