



SYMBOLS

- Work area
- Sign on portable or permanent support
- Direction indicator barricade with steady burn monodirectional light
- Barricade or drum with flashing light
- Type III barricade with flashing lights
- Type II barricade, drum, or vertical barricade with steady burn monodirectional light
- Temporary rumble strip

- ① ReflectORIZED temporary pavement marking tape shall be placed throughout the taper and along-side the work area where the closure time is greater than fourteen days. The edge line shall be white for right lane closures and yellow for left lane closures.
- ② Type II barricade, drum, or vertical barricade with steady burn monodirectional light at 100' spacings.
- ③ The Work Zone speed limit and wrong way signs shall be spaced evenly through the closure limits.

GENERAL NOTES

Sheet 1 of 2

All dimensions are in inches (millimeters) unless otherwise shown.

A check barricade shall be placed in the middle of the closed lane and at the shoulder at 1000' (300 m) centers.

Prior to placement of the signs for TRAFFIC CONTROL AND PROTECTION, (SPECIAL) the Resident Engineer should contact the Bureau of Operations and arrange for inspection and approval of the layout.

TRAFFIC CONTROL AND PROTECTION, (SPECIAL)

FILE NAME =	USER NAME = halsteadtw	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TRAFFIC CONTROL AND PROTECTION (SPECIAL)				F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
Default	ct:\pw\work\p\dot\halsteadtw\d0373650\78401-Design.dgn	DRAWN -	REVISED -		SCALE:	SHEET	OF	SHEETS	STA.	TO STA.	869	104RS-3	SALINE	21 18
	PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -		CONTRACT NO. 78401									
	PLOT DATE = 1/28/2014	DATE -	REVISED -		ILLINOIS FED. AID PROJECT									