

STRUCTURE GEOTECHNICAL REPORT

BRIDGE REPLACEMENT FAP 331 (IL 13) OVER CRAB ORCHARD LAKE

Section 1-4(B-1)
Williamson County, Illinois
Job No. C-99-045-13
Contract No. 78373
PTB 200-038
Existing Structure No. 100-0018 (EB)/100-0066 (WB)
Proposed Structure No. 100-0106 (EB)/100-0107 (WB)

Prepared For:
IDOT District 9
2801 W. Murphysboro Rd.
Carbondale, IL 62903
T: 618-549-2171



Prepared By:
Civil Design, Inc.
Tyler Ziegler, P.E., S.E.
307 E. Washington Ave.
Effingham, IL 62401
tziegler@civildesigninc.com T: 217-340-0349



Handwritten signature of Tyler J. Ziegler 2-5-2024
Exp. 11-30-2025

February 2024

Table of Contents

1.0 Project Description and Scope.....	1
1.1 Introduction	1
1.2 Existing Structure Information	1
1.3 Proposed Structure Information.....	2
2.0 Field Exploration.....	2
2.1 Subsurface Exploration and Testing	2
2.2 Subsurface Conditions.....	2
3.0 Geotechnical Evaluations and Recommendations	4
3.1 Settlement	4
3.2 Slope Stability.....	4
3.3 Seismic Considerations	5
3.4 Scour	6
3.5 Mining Activity	6
3.6 Liquefaction	6
3.7 Lateral Load Analysis	7
4.0 Foundation Recommendations.....	9
4.1 Abutments	9
4.2 Piers.....	11
5.0 Construction Considerations	13
5.1 Construction Activities	13
5.2 Temporary Shoring	13
5.3 Foundation Construction	13
5.4 Excavation	13
6.0 Limitations	13

Appendices

- A) Location Map
- B) Type, Size, and Location Plan (TS&L)
- C) Subsurface Data Profile Plot
- D) Soil Boring and Rock Core Logs
- E) Settlement Analysis
- F) Slope Stability Analysis
- G) Seismic Site Class Determination
- H) Liquefaction Analysis
- I) Integral Abutment Feasibility Analysis
- J) Driven Pile Analysis



1.0 Project Description and Scope

1.1 Introduction

The geotechnical investigation summarized herein was performed for the proposed dual bridges at IL 13 over Crab Orchard Lake in Williamson County, Illinois. See Appendix A for Location Map. The purpose of this report is to provide geotechnical design and construction recommendations to aid in the structure planning, final design plans and specification preparation.

1.2 Existing Structure Information

SN 100-0066 - Originally built in 1939, the west bound structure is a three span continuous wide flange bridge. The 0 degree skew structure is 133'-6" from back to back abutment with approximate span lengths of 39'-7", 50'-0" and 39'-7". The abutments are pile bent abutments on H-piles driven to refusal. The pier foundations consist of a single row of precast concrete piles.

The structure was later reconstructed in 1989 including a new superstructure, abutment caps and pier caps. The original piling was incorporated into the reconstruction of the substructure caps. The current, reconstructed superstructure consists of 7 composite steel beam lines of W24x62's for spans one and three and W24x68's for span two. Beams are spaced on 6'-4" centers. The reinforced concrete deck thickness is 7 1/2" and is on a normal crown. The clear width between face to face of parapets is 40'-0" and the overall out to out width of the bridge is 43'-2". At the piers, two new H-piles were driven and incorporated into the caps.

SN 100-0066 has a sufficiency rating of 86.4 with a deck rating of 8, very good condition, superstructure rating of 5, fair condition with minor section loss, and a substructure rating of 5, fair condition with minor section loss.

SN 100-0018 - Originally built in 1964, the eastbound structure is a three span continuous wide flange bridge. The 0 degree skew structure is 132'-0" from back to back abutment with approximate span lengths of 38'-3", 50'-11" and 38'-3". The superstructure consists of 7 steel beam lines of 27WF94 on 6'-4" centers with a 7" reinforced concrete deck on normal crown. The clear width between face to face of parapets is 40'-0" and the overall out to out width of the bridge is 42'-0". The abutments are pile bent abutments on H-piles driven to refusal with the front row battered and the back row vertical. The wingwalls consist of 12" walls bearing on a single H-pile. The piers are pile bents on a single row of 7 individually encased H-piles driven to refusal.

Two rehabilitations have been complete since the original construction. In 1997, repairs included abutment joint replacement, new elastomeric bearings and new diaphragms. In 1999, repair included partial and full depth patching of the deck in the driving lanes only, extending and eliminating drains, and installation of a concrete overlay. The overlay work consisted of 1/2" scarification with a 2 1/4" microsilica concrete overlay for a total deck thickness of 8 3/4".

SN 100-0018 has a sufficiency rating of 69.2 with a deck rating of 5, fair condition with minor section loss, superstructure rating of 4, poor condition with advanced deterioration, and a substructure rating of 6, satisfactory condition with minor deterioration.



1.3 Proposed Structure Information

Proposed SN 100-0106 to replace SN 100-0018 and proposed SN 100-0107 to replace SN 100-0066. The proposed replacement structures are 3 span bridges with continuous, composite steel W27 beams with an 8" reinforced concrete deck on a 0 degree skew. Proposed back to back abutment lengths are 139'-6" with span lengths of 41'-5½" – 56'-7" – 41'-5½". SN 100-0106 consists of 12 beams with typical spacing at 5'-7" centers and 2'-7½" overhangs for an overall width of 66'-8" out to out. SN 100-0107 consists of 10 beams with typical spacing at 6'-4" centers and 3'-0½" overhangs for an overall width of 63'-1" out to out. The SN 100-0106 roadway cross sections consist of a 6'-0" shoulder, 36'-0" roadway, 10'-0" shoulder, and a 11'-0" multi use trail. The SN 100-0107 roadway cross sections consist of a 6'-0" shoulder, 48'-3" roadway, and a 6'-0" shoulder. Staged construction will be utilized to maintain traffic. For further proposed structure information, see Appendix B for Type, Size, and Location Plan (TS&L).

2.0 Field Exploration

2.1 Subsurface Exploration and Testing

The subsurface investigation consisted of four borings drilled by the Illinois Department of Transportation in June and September of 2014. Borings were taken near the west and east abutment locations at each structure. Soil boring exploration was performed by drilling methods using a hollow stem auger and split spoon. Rock coring performed with conventional rotary drilling with water. See Appendix C for Subsurface Data Profile Plot and Appendix D for Soil Boring and Rock Core Logs.

Table 2.1 - Boring Log Summary

Location	Boring No.	Station	Offset	Ground Surface Elevation	Top of Rock Elevation
SN 100-0106 (E. Abut.)	1-S	310+40	13' RT - CL EB	414.8	352.3
SN 100-0106 (W. Abut.)	2-S	308+53	14' RT - CL EB	414.9	348.4
SN 100-0107 (E. Abut.)	1-S	310+32	14' LT - CL WB	415.2	350.7
SN 100-0107 (W. Abut.)	2-S	308+65	14' LT - CL WB	415.2	350.2

In addition to the borings discussed above, the existing borings of SN 100-0018 from 1964 are included in Appendix D to provide the designer with further soils information. In particular, the recent drillings do not include borings at the piers. The existing borings indicate the top of rock elevations of 346.2 and 348.0 at the existing west and east piers, respectively.

2.2 Subsurface Conditions

The groundwater conditions at each soil boring varies. See Table 2.2 below. Temperature, seasonal variations, and recent rainfall conditions may influence the levels of groundwater table. Without extended periods of observation, the measurement of groundwater conditions may not give a true indication of typical groundwater levels. Volume of water depends on the permeability of the soils.



Table 2.2 – Groundwater Conditions Summary

Location	Boring No.	First Encounter	Upon Completion	After 24 Hours
SN 100-0106 (E. Abut.)	1-S	404.8	404.8	-----
SN 100-0106 (W. Abut.)	2-S	403.9	-----	-----
SN 100-0107 (E. Abut.)	1-S	380.2	-----	-----
SN 100-0107 (W. Abut.)	2-S	380.7	-----	-----

SN 100-0106 - Built 25 years after the adjacent westbound structure, crushed aggregate (CA-6) and rock fill embankment layers are encountered below the groundline and appear to have been used to build up the surrounding elevation to construct this bridge. The crushed aggregate extends down 8 to 9.5 feet in borings 1-S and 2-S, respectively, and has SPT (N) values ranging from 24 to 84. The rock fill extends down 24 to 26 feet in borings 1-S and 2-S, respectively. Riprap and crusher run make up the rock fill with primarily boulder sized with some gravel and sand recovered in the sample tube. Rock fill SPT (N) values range from 1 to 30.

Below the rockfill down to a depth of 34.5 feet, the boring show soft to medium, grey and mottled brown, moist silty clay with SPT (N) values ranging from WOH to 2 blows per foot, Q_u values of 0.2 to 0.7 tsf, and moisture contents ranging between 28% and 34%. From 34.5 feet to down to rock, both borings show soft to stiff, grey to mottled brown moist clays with SPT (N) values ranging from WOH to 10 blows per foot, Q_u values of 0.4 to 2.9 tsf, and moisture contents ranging between 20% and 37%.

At a depth of 62.5 feet, boring 1-S encounters a dense grey, dry sandstone layer with clay shale seams with SPT (N) of 100/5". Boring 2-S encounters a dense grey, dry sandstone with clay shale lenses at a depth of 66.5 feet with SPT (N) of 100/2".

SN 100-0107 - Both borings, 1-S and 2-S, encountered stiff brown and grey moist clay from the ground surface elevation to an approximate depth of 29.5 feet. The moist clay has SPT (N) values ranging from 3 to 8 blows per foot with Q_u values of 1.2 to 2.7 tsf and moisture contents ranging between 16% and 25%.

Beneath the top moist clay layers, boring 1-S shows a potentially liquefiable layer at depths of 29.5 to 34.5 feet. This layer consists of stiff, moist silty clay loam with average soil contents of 9% sand, 72% silt, and 19% clay. Average liquid limit is 30 and plasticity index is 10, both values being estimated based on visual ID and historical database. SPT (N) values range from 3 to 5 blows per foot with Q_u values of 1.1 to 1.7 tsf and moisture contents ranging between 21% and 25%. Boring 2-S shows soft to medium grey moist silty clay to silty clay loam within this same depth range. SPT (N) values range from WOH to 2 blows per foot with Q_u values of 0.3 to 0.6 tsf and moisture contents ranging between 25% and 29%.

From 34.5 to 39.5 feet, both borings show soft to medium grey and mottled brown moist silty clay loam with SPT (N) values ranging from 1 to 4 blows per foot, Q_u values of 0.1 to 1.0 tsf, and moisture contents ranging between 24% and 30%. From 39.5 feet down to rock, both borings show soft to stiff, grey to mottled brown moist clays with SPT (N) values ranging from WOH to 7 blows



per foot, Q_u values of 0.3 to 2.9 tsf, and moisture contents ranging between 22% and 48%.

At a depth of 64.5 feet, boring 1-S encounters a dense grey, dry sandstone layer with some clay shale with SPT (N) of 100/8". Rock core logs at 1-S show the top 5 feet of rock with an RQD of 16% and uniaxial compressive strength (UCS) of 350 tsf. The next 5 feet have an RQD of 37% and UCS of 250 tsf. Boring 2-S encounters a hard grey, dry clay shale at a depth of 64 feet with SPT (N) of 100/3".

3.0 Geotechnical Evaluations and Recommendations

3.1 Settlement

Existing Embankment - Based on the provided preliminary plan and profile, the anticipated difference between the existing and proposed elevations at the abutments is minimal. Thus, settlement of the existing embankment is not anticipated due to minimal changes in loading and existing soil conditions. By inspection, the proposed structure should result in less than 0.4 inches of settlement. Per IDOT Geotechnical Manual Section 6.9.2, driven pile capacity need not account for downdrag if total settlement of soil around the piling is less than 0.4 inches.

Regarding settlement of approach slabs, one end of the slab is supported by the pile supported abutment. The other end of the slab is supported by the existing embankment subgrades. Provided proper compaction according to IDOT Standard Specifications is performed during construction, settlement of the approach slab is not a concern.

Proposed Widening Embankment – Due to the widening of the bridges, proposed embankment outside of the limits of the existing embankment is necessary. Potential settlement due to the proposed widened embankment was investigated using the IDOT Cohesive Soil Settlement Estimate spreadsheet. This simplified procedure estimates the primary settlement anticipated. The results from the settlement analysis shows settlement of less than 0.1". See Appendix E. In addition, secondary settlement is considered negligible with no organic layers are present.

3.2 Slope Stability

Slope stability analyses of the end slopes at both abutments of each structure were performed due to the high seismic region, unique high water conditions and proposed embankment required for widening. Engineering soil properties taken from the subsurface exploration descriptions were input and slope stability was evaluated using the software program StablPro. The Bishop's method analysis was used to search for the critical circular failure surface to calculate the factor of safety for the slope.

A critical factor of safety was calculated for three modeled conditions: short term static, long term static, and seismic. Short term conditions capture full cohesive values, while long term conditions assume drained soil properties. A live load surcharge of 250 psf was considered at both abutments. For seismic analysis, a horizontal acceleration coefficient of 0.422g was calculated according to guidance in the FHWA-NHI-11-032, LFRD Seismic Analysis and Design of Transportation Geotechnical Features and Structural Foundations.

See Table 3.1 below for slope stability factors of safety at each abutment. Each abutment location achieved the minimum factor of safety of 1.5 for static conditions and 1.0 for seismic conditions. See Appendix F for soil parameters and individual output of the analyses presented in the table.



Table 3.1 - Summary of Slope Stability Calculated Factors of Safety

Structure No.	Location	Short Term Static	Long Term Static	Seismic
100-0106	East Abut.	1.50	1.95	1.03
100-0106	West Abut.	1.81	2.23	1.02
100-0107	East Abut.	1.94	1.57	1.02
100-0107	West Abut.	1.92	1.56	1.03

As validation of the results, no known issues or concerns are present or have been present at the existing embankment slopes which have been in place for over 55 plus years. In addition, the existing piles supporting the abutments and piers will remain in place and increase the nominal slope stability FOS by intersecting the circular failure planes.

3.3 Seismic Considerations

LRFD Seismic Soil Site Class Definition was determined based on the methodology described in IDOT AGMU 9.1 and the IDOT BBS 149 form for Seismic Site Class Determination. See Appendix G for determination.

Further seismic parameters were determined using the figures and tables provided in AASHTO LRFD Bridge Design Specifications, Article 3.10 for Earthquake Effects, EQ. These parameters are based on a 1000 Year Return Period with a Probability of Exceedance of 7% in 75 years. See table below for a summary of seismic parameters.

Table 3.2 - Summary of Seismic Parameters

Parameter	Value
Seismic Soil Site Class	D
Spectral Acceleration Coefficient at period of 0.2 sec., S _s	0.682g
Spectral Acceleration Coefficient at period of 1.0 sec., S ₁	0.171g
Site Factor, Short Period, F _a	1.24
Site Factor, Long Period, F _v	2.10
Design Spectral Acceleration at 0.2 sec. (SDS)	0.864g



Design Spectral Acceleration at 1.0 sec. (SD1)	0.359g
Seismic Performance Zone	SPZ 3

The Spectral Acceleration Coefficient at T=1.0 sec. (SD1) and Seismic Performance Zone were confirmed using Bridge Manual Planning Section 2.3.10.3.

Abutment foundations shall be designed for the full elastic base shear (R=1.0) and the solid wall encased pile bent piers shall be designed with an R of 2.0 for the longitudinal and transverse directions per BM 3.15.4.3.

3.4 Scour

Design scour elevations for the proposed structures were provided by Crawford, Murphy & Tilly. See table below. Stone Riprap, Class A4 is proposed to protect the bridge embankment side slopes from each abutment down to the toe of the lake bed.

Table 3.3 – Design Scour Elevation Table

Event/Limit State	Design Scour Elevations (ft.)				Item 113
	W. Abut.	Pier 1	Pier 2	E. Abut.	
Q100	Note 1	385.3	385.3	Note 1	5
Q200	Note 1	385.2	385.2	Note 1	
Design	Note 1	385.3	385.3	Note 1	
Check	Note 1	385.2	385.2	Note 1	

Note 1: Bottom of Abutment Cap Elevation

Scour loss shall be accounted for in the pier pile capacity design calculations. The design event shall be considered for the Strength Limit State and the check event shall be considered for the Extreme Event II Limit State. Though by inspection of the minimal difference between design and check scour elevations, the design event controls over the check event due to larger factored loads and smaller factored geotechnical resistance required for the Strength Limit State.

3.5 Mining Activity

Reviewing the Illinois State Geological Survey (ISGS) “Directory of Coal Mines in Illinois” for Williamson County, no mining activity is present at the bridge location. The nearest underground mine proximity region is located near Cambria, 2 miles northeast of the project location.

3.6 Liquefaction

The subsurface exploration indicated a potential liquefiable soil layer in the SN 100-0107 east abutment soil boring (1-S) between elevations 385.7 to 380.7. By inspection, no liquefiable layers are present at the other subject boring locations.



A liquefaction analysis was performed using the IDOT Liquefaction Analysis spreadsheet. The results from the liquefaction analysis show no liquefaction concern within the first 60 ft of the soil profile; thus, liquefaction was not considered for the pile capacity tables below. See Appendix H for Liquefaction Analysis.

3.7 Lateral Load Analysis

The tables below provide soil parameters to structural engineer for lateral or displacement analysis of the foundations. The values were estimated based on the descriptions given in the soil boring logs. Short term conditions are recommended for lateral load analysis. Full cohesion was assumed with a friction angle of 0 degrees for cohesive soils. No specific analyses were performed on the soil to determine the estimated parameters.

Table 3.4 –Soil Parameters for Lateral Load Analysis at SN 100-0106 Pier 1 (2-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Medium Clay to Silty Clay	385.4	125	0.7	0	300	0.007
Medium Silt Loam to Silty Clay Loam	382.9	120	0.7	0	300	0.007
Medium Clay to Silty Clay	380.4	125	0.7	0	300	0.007
Medium Silty Clay to Silty Clay Loam	377.9	120	0.8	0	300	0.007
Medium Clay	375.4	125	0.8	0	300	0.007
Stiff Clay	360.4	125	1.1	0	300	0.007
Medium Clay to Silty Clay	355.4	125	0.6	0	300	0.007
Soft Clay to Silty Clay	350.4	120	0.4	0	100	0.01
Stiff Sandy Clay	348.4	125	1.8	0	300	0.007
Sandstone	-	150	0	45	-	0.001

Table 3.5 –Soil Parameters for Lateral Load Analysis at SN 100-0106 Pier 2 (1-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Very Stiff Silty Clay Loam	387.8	125	2.5	0	500	0.005
Very Soft Silty Clay	385.3	120	0.2	0	100	0.01
Soft Clay to Silty Clay	380.3	120	0.4	0	100	0.01
Very Stiff Clay	377.8	125	2.1	0	500	0.005
Stiff Clay	370.3	125	1.5	0	300	0.007
Medium Clay	364.8	125	0.8	0	300	0.007
Stiff Clay	360.3	125	1.6	0	300	0.007
Very Stiff Clay	352.3	125	2.3	0	500	0.005
Sandstone	-	150	0	45	-	0.001



Table 3.6 –Soil Parameters for Lateral Load Analysis at SN 100-0107 Pier 1 (2-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Very Stiff Clay	388.2	125	2.5	0	500	0.005
Stiff Clay	385.7	125	1.2	0	300	0.007
Medium Silty Clay to Silty Clay Loam	383.2	125	0.6	0	300	0.007
Soft Clay	378.2	120	0.3	0	100	0.01
Medium Silty Clay Loam	375.7	125	1.0	0	500	0.005
Stiff Clay	370.7	125	2.3	0	300	0.007
Stiff Silty Clay to Clay	360.7	125	1.6	0	300	0.007
Medium Clay	351.2	125	0.6	0	300	0.007
Sandstone	-	150	0	45	-	0.001

Table 3.7 –Soil Parameters for Lateral Load Analysis at SN 100-0107 Pier 2 (1-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Stiff Clay	385.7	125	1.3	0	300	0.007
Stiff Silt Loam	383.2	125	1.7	0	300	0.007
Stiff Silty Clay to Silty Clay Loam	380.7	125	1.1	0	300	0.007
Medium to Stiff Silty Clay Loam	378.2	125	1.0	0	300	0.007
Very Soft Silty Clay Loam	375.7	120	0.1	0	100	0.01
Very Stiff Clay	370.7	125	2.9	0	500	0.005
Stiff Clay	365.2	125	1.8	0	300	0.007
Medium to Stiff Clay	360.7	125	1.0	0	300	0.007
Soft Clay	355.7	120	0.3	0	100	0.01
Medium Clay	350.7	125	0.6	0	300	0.007
Sandstone	-	150	0	45	-	0.001

4.0 Foundation Recommendations

4.1 Abutments

Preliminary superstructure loads for the proposed structure configuration discussed above were provided by Civil Design, Inc. See tables below for total factored loads at each substructure. These loads include the approach slab and abutment self-weight.

Table 4.1 – SN 100-0106 Abut. Load

Location	Total Factored Reaction (k)
W. Abut.	1,500
E. Abut.	1,500

Table 4.2 – SN 100-0107 Abut. Load

Location	Total Factored Reaction (k)
W. Abut.	1,400
E. Abut.	1,400

Integral abutments are preferred to eliminate joints in the bridge decks, decreasing maintenance costs and increasing service life. See results of preliminary Integral Abutment Feasibility Analysis in Appendix I. The designer shall verify integral abutment feasibility analysis with final configuration. In addition, see IDOT ABD Memo 19.8 for further integral abutment design guidance.

Foundation type for integral abutments shall be pile supported with a pile placed under each girder. Due to the presence of sandstone at the subject site and H-piles being most effective in point bearing applications, H-piles are recommended over metal shell piles.

The tables below summarize the nominal required bearing (R_N), factored resistance available (R_F), estimated pile length and estimated pile tip elevation for the strength limit state. R_N indicates the resistance of the pile during driving, which assists the Contractor from causing damage to the pile. R_F represents the net long term axial geotechnical resistance available to support the factored structure loads. The estimated pile lengths include a 2 foot embedment into the abutment. Analyses have been performed using the IDOT Static Method of Estimating Pile Length. See Appendix J.

The factored resistance available values shown in the tables are intended to provide the designer with a range of feasible options for the anticipated vertical loading. Piles shall be evaluated for lateral resistance in final design.

Table 4.3 – H-Pile Capacity at SN 100-0106 West Abutment (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	65	344.6
HP 12x53	418	230	65	344.6
HP 14x73	578	317	65	344.6



Table 4.4 – H-Pile Capacity at SN 100-0106 East Abutment (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	60	347.5
HP 12x53	418	230	61	346.5
HP 14x73	578	317	61	346.5

Table 4.5 – H-Pile Capacity at SN 100-0107 West Abutment (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	61	348.9
HP 12x53	418	230	61	348.9
HP 14x73	578	317	62	347.9

Table 4.6 – H-Pile Capacity at SN 100-0107 East Abutment (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	61	349.0
HP 12x53	418	230	61	349.0
HP 14x73	578	317	62	348.0

One test pile is recommended at each abutment location. Due to the presence of the rock fill riprap layer and hard sandstone, pile shoes are recommended.

4.2 Piers

Preliminary superstructure loads for the proposed structure configuration discussed above were provided by Civil Design, Inc. See tables below for total factored loads at each substructure.

Table 4.7 – SN 100-0106 Pier Load

Location	Total Factored Reaction (k)
Pier 1	2,900
Pier 2	2,900

Table 4.8 – SN 100-0107 Pier Load

Location	Total Factored Reaction (k)
Pier 1	2,700
Pier 2	2,700

A pile-supported bent matches the existing substructure foundations. In addition, driven piles are recommended at the abutments so pile driving equipment will already be mobilized. Driven piles appear to be the most efficient pier foundation type. Similar to the abutments, H-piles are recommended over metal shell piles due to the presence of sandstone.

The tables below summarize the nominal required bearing (R_N), factored resistance available (R_F), estimated pile length and estimated pile tip elevation. R_N indicates the resistance of the pile during driving, which assists the Contractor from causing damage to the pile. R_F represents the net long term axial geotechnical resistance available to support the factored structure loads. Geotechnical scour loss to the elevations shown in the design scour elevation tables herein were applied at each pier. The estimated pile lengths include a 1 foot embedment into the pier cap. Analysis has been performed using the IDOT Static Method of Estimating Pile Length. See Appendix J.

The factored resistance available values shown in the tables are intended to provide the designer with a range of feasible options for the anticipated vertical loading. Piles shall be evaluated for lateral resistance in final design.

Table 4.9 – H-Pile Capacity at SN 100-0106 Pier 1 (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	224	63	346.0
HP 12x74	589	317	64	347.0
HP 14x73	578	311	63	346.0

Table 4.10 – H-Pile Capacity at SN 100-0106 Pier 2 (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	219	59	350.0
HP 12x74	589	312	61	351.0
HP 14x73	578	304	60	349.0

Table 4.11 – H-Pile Capacity at SN 100-0107 Pier 1 (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	215	61	348.0
HP 12x74	589	308	64	345.0
HP 14x73	578	300	62	347.0

Table 4.12 – H-Pile Capacity at SN 100-0107 Pier 2 (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	218	62	347.0
HP 12x74	589	306	65	344.0
HP 14x73	578	303	63	346.0

One test pile is recommended at each pier location. Pile shoes are recommended when driving into hard sandstone.

5.0 Construction Considerations

5.1 Construction Activities

All construction activities shall be performed in accordance with the current IDOT Standard Specifications for Road and Bridge Construction and any pertinent Special Provisions or Policies.

The bridge cone embankment necessary for widening the existing roadway shall satisfy the requirements of Section 205 of the Standard Specifications.

5.2 Temporary Shoring

Temporary shoring will be required at the abutments during staged construction. From the preliminary TS&L, the distance from the proposed profile grade to the bottom of proposed abutment is approximately 8 feet, which represents the maximum soil retention anticipated. Investigating the subsurface conditions below the excavation line, the use of IDOT temporary sheet piling design charts appears feasible at the abutments for SN 100-0107. The use of a temporary soil retention system is advised at SN 100-0106 due to drivability concerns with the encountered crushed aggregate and rockfill. In addition, Type 2 Cofferdams will be required at both piers during staged construction due to more than 6 feet of water anticipated above the bottom of the pier. Seal coat is recommended at each cofferdam.

5.3 Foundation Construction

Conventional pile driving equipment and methodologies shall be assumed.

5.4 Excavation

Excavation shall be performed in accordance with IDOT Standard Specifications Section 202. Substructure construction shall occur after removal of the existing structure is complete.

A Joint Utility Locating Information for Excavators (J.U.L.I.E.) locate shall be performed prior to commencing construction activities to determine underground utilities within the project limits. On SN 100-0066, fiber optics utility runs through the existing abutment backwalls and spans the entire length of the bridge on hangers. In addition, IDOT shall be contacted to locate private utilities.

At foundation and structural fill locations, the exposed subgrade shall be proofrolled to aid in locating any unstable and unsuitable materials. Unstable and unsuitable materials shall be removed and replaced with compacted structural fill.

6.0 Limitations


The analysis and discussion provided herein are for the exclusive use of IDOT District 9. They are based upon the subsurface data obtained at boring locations within the bridge area and are specific to the project described, our understanding of the project as described herein, and geotechnical engineering practice consistent with the standard of care.



Appendix A

Location Map





Location Map

IL 13 over Crab Orchard Lake
 Williamson County, Illinois
 Existing Structure No. 100-0018 (EB)/100-0066 (WB)
 Proposed Structure No. 100-0106 (EB)/100-0107 (WB)

Appendix B

Type, Size, and Location Plan (TS&L)






Bench Mark: Sq. cut in N.W. corner W. wall of S.N. 100-0020.

Existing Structure: S.N. 100-0018 was originally constructed in 1964 under F.A. Rte. 14, Section 5-3B-3. The structure is a three span (38'-3", 50'-11", 38'-3") continuous wide flange bridge with seven beam lines on pile bent abutments. The structure is 132'-0" from bk. to bk. abutments on a zero degree skew. The clear width is 40'-0" between face to face of parapets and the overall out to out width of the bridge is 42'-0". The superstructure consists of seven beam lines of 27WF94 on 6'-4" centers. The original reinforced concrete deck thickness was 7", but was later scarified 1/2" (1999) and a 2 1/4" Microsilica concrete overlay was installed for a total thickness of +/- 8 3/4". The bridge deck is on a normal crown. The abutments are pile bent abutments on H-piles driven to refusal. The wingwalls consist of 12" walls bearing on a single H-pile. The piers are pile bents on seven individually encased piles driven to refusal.

Traffic to be maintained utilizing stage construction.

No salvage.



HIGHWAY CLASSIFICATION
F.A.P. Rte. 331 - IL Rte. 13 E.B.
Functional Class: Other Principal Arterial
ADT: 16,000 (2011); 23,560 (2037)
ADTT: 600 (2011); 885 (2037)
DHW: 2355
Design Speed: 65 m.p.h.
Posted Speed: 55 m.p.h.
One-Way Traffic
Directional Dist.: 100

LOADING HL-93
Allow 50#/sq. ft. for future wearing surface.


DESIGN SPECIFICATIONS
2020 AASHTO LRFD Bridge Design Specifications, 9th Edition.

DESIGN STRESSES

FIELD UNITS
f'c = 3,500 psi (Substructure)
f'c = 4,000 psi (Superstructure)
fy = 60,000 psi (Reinforcement)
fy = 50,000 psi (M270 Grade 50)
All new structural steel to be galvanized.


SEISMIC DATA

Seismic Performance Zone (SPZ) = 3
Design Spectral Acceleration at 1.0 sec. (SD1) = 0.359g
Design Spectral Acceleration at 0.2 sec. (SDS) = 0.864g
Soil Site Class = D



PROFILE GRADE

Along Centerline of Eastbound Lanes



LOCATION SKETCH

GENERAL PLAN AND ELEVATION
IL 13 E.B. OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SEC. 1-4(B-1)
WILLIAMSON COUNTY
STATION 309+50.00
STRUCTURE NO. 100-0106

MODEL: Default
FILE NAME: P:\5XXXX\50XX-51XX\5000 - IDOT PTB 200-038 D9 IL 13 Crab Orchard Bridges\24-Structures\CAD-MSTSL\100-0106 - R1.dgn



CIVIL DESIGN, INC.
WBE | DBE
EFFINGHAM, IL
LICENSE #184.003222

USER NAME =
DESIGNED - K. STREICHER
CHECKED - R. TIWARI
PLOT SCALE =
PLOT DATE =


DESIGNED - K. STREICHER
CHECKED - R. TIWARI
DRAWN - K. STREICHER
CHECKED - R. TIWARI

REVISED -
REVISED -
REVISED -
REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET 1 OF 2 SHEETS


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
331	1-4(B-1)	WILLIAMSON		
CONTRACT NO. 78383				
ILLINOIS FED. AID PROJECT				



CROSS SECTION
(Looking East)
* Prior to grinding



PIER SKETCH



SECTION THRU INTEGRAL ABUTMENT
(Horiz. dim. @ Rt. L's)

WATERWAY INFORMATION

Drainage Area = 1.3 Sq. mi. Low Grade Elev. 415.0 @ Sta. 311+00									
Flood	Freq. Yr.	Q C.F.S.	Opening Ft ²		Nat. H.W.E.	Head - Ft.		Headwater E	
			Exist.	Prop.		Exist.	Prop.	Exist.	Prop.
Ten-Year	10	586	1,314	1,347	407.5	0.0	0.0	407.5	407.5
Design	50	962	1,424	1,466	408.5	0.0	0.0	408.5	408.5
Base	100	1,131	1,470	1,515	408.9	0.0	0.0	408.9	408.9
Scour Check	200	1,295	1,517	1,565	409.3	0.0	0.0	409.3	409.3
Max. Calc.	500	1,570	1,602	1,653	410.0	0.0	0.0	410.0	410.0

DESIGN SCOUR ELEVATION TABLE

Event / Limit State	Design Scour Elevations (ft.)					Item 113
	W. Abut.	Pier 1	Pier 2	E. Abut.		
Q100	407.5	385.3	385.3	407.5		5
Q200	407.5	385.2	385.2	407.5		
Design	407.5	385.3	385.3	407.5		
Check	407.5	385.2	385.2	407.5		

DETAILS

IL 13 E.B. OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SEC. 1-4(B-1)
WILLIAMSON COUNTY
STATION 309+50.00
STRUCTURE NO. 100-0106

MODEL: Default
FILE NAME: P:\5XXXXX\50XX-51XX\5000 - IDOT PTB 200-038 D9 IL 13 Crab Orchard Bridges\24-Structures\CAD-MSTSL\100-0106 - R1.dgn
2/2/2024 1:26:44 PM



CIVIL DESIGN, INC.
WBE | DBE
EFFINGHAM, IL
LICENSE #184.003222

USER NAME =	DESIGNED - K. STREICHER	REVISED -
	CHECKED - R. TIWARI	REVISED -
PLOT SCALE =	DRAWN - K. STREICHER	REVISED -
PLOT DATE =	CHECKED - R. TIWARI	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET 2 OF 2 SHEETS


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
331	1-4(B-1)	WILLIAMSON		
CONTRACT NO. 78383				
ILLINOIS FED. AID PROJECT				

Bench Mark: Sq. cut in N.W. corner W. wall of S.N. 100-0020.

Existing Structure: S.N. 100-0066 was originally constructed in 1939 under F.A. Proj. 15, Section 5-B1 and 5-A1. An extensive reconstruction was built in 1989 under F.A. Route 410, Section (5B-1)DR. This reconstruction included an entirely new superstructure, abutments, and pier caps. The structure is a three span (39'-7", 50'-0", 39'-7") continuous wide flange bridge with seven beam lines on pile bent abutments. The structure is 133'-6" from bk. to bk. abutments on a zero degree skew. The clear width is 40'-0" between face to face of parapets and the overall out to out width of the bridge is 43'-2". The composite superstructure consists of seven beam lines of W24x62 for spans one and three, and W24x68 for span two, on 6'-4" centers. The reinforced concrete deck thickness is 7 1/2". The bridge deck is on a normal crown. The abutments are pile bent abutments on H-piles driven to refusal. The wingwalls are typical 12" thick dog ear wing walls. Each pier is comprised of 6 original precast concrete piles, two new H-piles encased in concrete driven to refusal, and new pier caps installed in 1989. There is a fiber optics utility that runs through the backwalls on the abutments and spans the entire length of the bridge on hangers.

Traffic to be maintained utilizing stage construction.

No salvage.



HIGHWAY CLASSIFICATION

F.A.P. Rte. 331 - IL Rte. 13 W.B.
Functional Class: Other Principal Arterial
ADT: 16,200 (2011); 23,860 (2037)
ADTT: 650 (2011); 955 (2037)
DHW: 2385
Design Speed: 65 m.p.h.
Posted Speed: 55 m.p.h.
One-Way Traffic
Directional Dist.: 100

LOADING HL-93

Allow 50#/sq. ft. for future wearing surface.

DESIGN SPECIFICATIONS

2020 AASHTO LRFD Bridge Design
Specifications, 9th Edition.

DESIGN STRESSES


FIELD UNITS

f'c = 3,500 psi (Substructure)
f'c = 4,000 psi (Superstructure)
fy = 60,000 psi (Reinforcement)
fy = 50,000 psi (M270 Grade 50)
All new structural steel to be galvanized.

SEISMIC DATA


Seismic Performance Zone (SPZ) = 3
Design Spectral Acceleration at 1.0 sec. (SD1) = 0.359g
Design Spectral Acceleration at 0.2 sec. (SDS) = 0.864g
Soil Site Class = D

SECTION A-A



PROFILE GRADE

Along Centerline Westbound Lanes



LOCATION SKETCH

GENERAL PLAN AND ELEVATION
IL 13 W.B. OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SEC. 1-4(B-2)
WILLIAMSON COUNTY
STATION 309+50.00
STRUCTURE NO. 100-0107

MODEL: Default
FILE NAME: P:\5XXXX\50XX-51XX\5000 - IDOT RTE 200-038 D9 IL 13 Crab Orchard Bridges\24-Structures\CAD-MST\SL100-0107 - R1.dgn
2/5/2024 12:30:02 PM




CIVIL DESIGN, INC.
WBE | DBE
EFFINGHAM, IL
LICENSE #184.003222

USER NAME =	DESIGNED - K. STREICHER	REVISED -
PLOT SCALE =	CHECKED - R. TIWARI	REVISED -
PLOT DATE =	DRAWN - K. STREICHER	REVISED -
	CHECKED - R. TIWARI	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET 1 OF 2 SHEETS


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
331		WILLIAMSON		
CONTRACT NO. 78373				
ILLINOIS FED. AID PROJECT				



CROSS SECTION

(Looking East)

* Prior to grinding




PIER SKETCH

WATERWAY INFORMATION

Drainage Area = 1.3 Sq. mi. Low Grade Elev. 411.65 @ Sta. 310+17									
Flood	Freq. Yr.	Q C.F.S.	Opening Ft ²		Nat. H.W.E.	Head - Ft.		Headwater El.	
			Exist.	Prop.		Exist.	Prop.	Exist.	Prop.
Ten-Year	10	586	1,314	1,316	407.5	0.0	0.0	407.5	407.5
Design	50	962	1,424	1,435	408.5	0.0	0.0	408.5	408.5
Base	100	1,131	1,470	1,483	408.9	0.0	0.0	408.9	408.9
Scour Check	200	1,295	1,517	1,532	409.3	0.0	0.0	409.3	409.3
Max. Calc.	500	1,570	1,602	1,620	410.0	0.0	0.0	410.0	410.0

DESIGN SCOUR ELEVATION TABLE

Event / Limit State	Design Scour Elevations (ft.)				
	W. Abut.	Pier 1	Pier 2	E. Abut.	Item 113
Q100	407.9	385.3	385.3	407.9	5
Q200	407.9	385.2	385.2	407.9	
Design	407.9	385.3	385.3	407.9	
Check	407.9	385.2	385.2	407.9	



SECTION THRU INTEGRAL ABUTMENT

(Horiz. dim. @ Rt. L's)

DETAILS

IL 13 W.B. OVER CRAB ORCHARD LAKE

F.A.P. RT. 331 - SEC. 1-4(B-2)

WILLIAMSON COUNTY

STATION 309+50.00

STRUCTURE NO. 100-0107

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SHEET 2 OF 2 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
331	14 (B-1)	WILLIAMSON		
CONTRACT NO. 78373				
ILLINOIS FED. AID PROJECT				

USER NAME =	DESIGNED - K. STREICHER	REVISED -
	CHECKED - R. TIWARI	REVISED -
PLOT SCALE =	DRAWN - K. STREICHER	REVISED -
PLOT DATE =	CHECKED - R. TIWARI	REVISED -

Appendix C



Subsurface Data Profile Plot



Boring 2-S
STA 308+53
OFFSET 14 FT RT CL BLE
EL 414.9 FT
6/18/2014

PR $\varnothing$ PROFILE

Boring 1-S
STA 310+40
OFFSET 13 FT RT CL EBL
EL 414.8 FT
6/23/2014



LEGEND

EL = Elevation (FT)
D = Depth Below Existing Ground Surface (FT)
N = SPT N-VALUE (AASHTO T206)
Qu = Unconfined Compressive Strength in tons per sq. ft. (tsf)
Failure Mode (B=bulge, S=shear, P=penetrometer)
W% = Moisture Content Percentage

▽ = Groundwater Level First Encountered
Soil profile is for illustrative purposes only. Actual conditions will vary.

SUBSURFACE DATA PROFILE
ILL 13 EB OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SECTION 1-4(B-1)
WILLIAMSON COUNTY
STATION 309+50.00
SN 100-0106

Boring 2-S
STA 308+65
OFFSET 14 FT LT CL WBL
EL 415.2 FT
6/19/2014

PR CL PROFILE

Boring 1-S
STA 310+32
OFFSET 14 FT LT CL WBL
EL 415.2 FT
6/17/2014

	D	N	Qu	W%
Asphalt & crushed aggregate	413.7			
Stiff, moist, brown, Clay A7-6				
	5	3	1.4 B	22
Very stiff, moist, brown and grey, Clay A7-6				
	5	5	2.3 B	25
Stiff, moist, brown, Clay to Silty Clay A7-6				
	10	3	1.6 B	16
		5	1.7 B	21
	15	5	1.3 B	21
		5	1.5 B	21
	20	5	1.5 B	20
		5	1.9 B	21
	25	6	1.9 B	19
Very stiff, moist, grey, Clay A7-6	390.2			
Stiff, moist, grey, Clay A7-6	388.2			
		8	2.5 B	19
Medium, very moist, grey, Silty Clay to Silty Clay Loam A-6	385.7			
	30	5	1.2 B	21
		2	0.6 B	29
Soft, very moist, grey mottled brown, Silty Clay A-6	380.7			
	35	WH	0.3 B	35
Stiff to medium, moist to very moist, grey mottled brown, Silty Clay Loam A-6	378.2			
		1	0.4 B	29
Very stiff, moist, grey mottled brown, Clay A7-6	375.7			
	40	2	1.0 B	26
		5	2.3 S	35
Stiff, moist, grey mottled brown, Clay A7-6	370.7			
	45	-	-	-
Stiff, moist, grey mottled brown, Clay A7-6				
		4	1.6 B	48
Stiff, moist, brown, Silty Clay to Clay A7-6	365.2			
	50	-	-	-
		2	1.6 B	42
Medium, very moist, grey, Clay A7-6	360.7			
	55	-	-	-
		WH	0.6 B	28
	60	-	-	-
		3	0.8 B	24
Hard, dry, grey weathered Clay Shale	351.2			
	65	-	-	-
Hard, dry, grey, Clay Shale	350.2			
End of Boring		100/3"		
	70	-	-	-
	75	-	-	-
	80	-	-	-
	85	-	-	-
	90	-	-	-

EL	D	N	Qu	W%
413.7				
	5	4	2.5 B	19
		7	2.3 B	18
	10	7	2.5 B	18
		8	2.5 B	20
	15	7	2.0 B	21
		8	2.7 B	18
398.2				
	20	8	1.7 S	19
		7	1.6 B	19
	25	7	1.9 B	19
		6	1.3 B	19
	30	5	1.5 B	24
385.7				
		5	1.7 S	21
383.2				
	35	3	1.1 B	25
380.7				
		4	1.0 B	24
378.2				
	40	1	0.1 B	30
375.7				
		7	2.9 B	24
370.7				
	45	-	-	-
		5	1.8 S	29
365.2				
	50	-	-	-
		3	1.0 B	43
360.7				
	55	-	-	-
		2	0.3 B	24
355.7				
	60	-	-	-
		1	0.6 B	22
350.7				
	65	-	-	-
349.7				
	70	-	-	-
344.7				
	75	-	-	-
339.7				
	80	-	-	-
	85	-	-	-
	90	-	-	-

LEGEND

EL = Elevation (FT)
D = Depth Below Existing Ground Surface (FT)
N = SPT N-VALUE (AASHTO T206)
Qu = Unconfined Compressive Strength in tons per sq. ft. (tsf)
Failure Mode (B=bulge, S=shear, P=penetrometer)
W% = Moisture Content Percentage

▽ = Groundwater Level First Encountered
Soil profile is for illustrative purposes only. Actual conditions will vary.

SUBSURFACE DATA PROFILE
ILL 13 WB OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SECTION 1-4(B-1)
WILLIAMSON COUNTY
STATION 309+50.00
SN 100-0107

Appendix D

Soil Boring and Rock Core Logs





Illinois Department of Transportation

Division of Highways District 9

SOIL BORING LOG

Page 1 of 2

Date 6/23/14

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 EB Lanes over Crab Orchard Lake	LOGGED BY	L. Estel
-------	-----------------	-------------	---------------------------------------	-----------	----------

SECTION	5-3B-3	LOCATION	1.1 mi. E of Jackson Co. (near E Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	--------	-----------------	---

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lb
---------------	------------	------------------------	---	--------------------	-----------------

STRUCT. NO.	100-0018
Station	309+50

BORING NO.	<u>1-S</u>
Station	<u>310+40</u>
Offset	<u>13.0ft Rt EB CL</u>
Ground Surface Elev.	<u>414.8</u>

DEPTH (ft)	BLOW S	UCS Qu (tsf)	MOIST (%)
---------------	-----------	--------------------	--------------

Surface Water Elev.	<u>405.5</u>	ft
Stream Bed Elev.	<u> </u>	ft
Groundwater Elev.:		
▽ First Encounter	<u>404.8</u>	ft
▽ Upon Completion	<u>404.8</u>	ft
▽ After Hrs.	<u> </u>	ft

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	--------------------------------	----------------------------------

[illegible]

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 EB Lanes over Crab Orchard Lake	LOGGED BY	L. Estel
--------------	------------------------	--------------------	--	------------------	-----------------

SECTION 5-3B-3 **LOCATION** 1.1 mi. E of Jackson Co. (near E Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM

COUNTY Williamson **DRILLING METHOD** Hollow Stem Auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lb

STRUCT. NO.	100-0018
Station	309+50

BORING NO.	<u>1-S</u>
Station	<u>310+40</u>
Offset	<u>13.0ft Rt EB CL</u>
Ground Surface Elev.	<u>414.8</u>

DEPTH (ft)	BLOWS	UCS (tsf)	MOIST (%)
---------------	-------	--------------	--------------

Surface Water Elev.	405.5	ft
Stream Bed Elev.		ft
Groundwater Elev.:		
▽ First Encounter	404.8	ft
▽ Upon Completion	404.8	ft
▽ After Hrs.		ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Stiff Grey and mottled Brown,	2	1.8	31
Moist CLAY (<i>continued</i>)	3	B	

V. Stiff Brown and mottled Grey, Moist CLAY (<i>continued</i>)	4 6	2.3 B	21
---	--------	----------	----

Medium Grey and mottled Brown, V. Moist CLAY	-45	WOH		
		1	0.8	28

V. Dense Grey, Dry SANDSTONE with CLAY SHALE seams

Stiff Brown and mottled Grey, Moist CLAY	2	1.6	23
	2	B	

(end of boring)

Bottom of hole @ 64.9 feet

Free water observed at 10.0 feet

Ground Surface Elevation
referenced to BM at NW corner of
SN 100-0018; Elev. 416.6

SPT Hammer Efficiency: 75% (To
convert "N" values to "N60",
multiply by 1.25)

V. Stiff Brown and mottled Grey, Moist CLAY	-55	1		
		3	2.9	20



Illinois Department of Transportation

Division of Highways District 9

SOIL BORING LOG

Page 1 of 2

Date 6/18/14

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 EB Lanes over Crab Orchard Lake	LOGGED BY	L. Estel
-------	-----------------	-------------	---------------------------------------	-----------	----------

SECTION	5-3B-3	LOCATION	1.1 mi. E of Jackson Co. (near W Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	--------	-----------------	---

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lb
---------------	------------	------------------------	---	--------------------	-----------------

STRUCT. NO. 100-0018
Station 309+50

BORING NO.	<u>2-S</u>
Station	<u>308+53</u>
Offset	<u>14.0ft Rt EB CL</u>
Ground Surface Elev.	<u>414.9</u>

DEPTH (ft)	BLOW S	UCS Qu (tsf)	MOIST (%)
---------------	-----------	--------------------	--------------

Surface Water Elev.	<u>405.5</u>	ft
Stream Bed Elev.	<u></u>	ft
Groundwater Elev.:		
▽ First Encounter	<u>403.9</u>	ft
▽ Upon Completion	<u></u>	ft
▼ After Hrs.	<u></u>	ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Cored HMA Pavement				Rock Fill (Rip Rap or Crusher Run)	5		
413.90					1		
Crushed Aggregate (CA-6)							
	14			Note: despite low blow counts the material encountered from 9.5 to 26.0 ft was primarily boulder sized with some gravel and sand recovered in the sample tube. (continued)	1		
	25				5		
	19				1		
	-5	28			-25	1	
		45				WOH	
		39		388.90		1	
				Medium Grey, V. Moist CLAY to SILTY CLAY			
		9				WOH	
		13				WOH	0.7
		9				1	B 32
405.40				385.40			
Rock Fill (Rip Rap or Crusher Run)	-10	8		Medium Grey and mottled Brown, V. Moist SILT LOAM to SILTY CLAY LOAM	-30	WOH	
		20				WOH	0.7
		10				1	B 29
Note: despite low blow counts the material encountered from 9.5 to 26.0 ft was primarily boulder sized with some gravel and sand recovered in the sample tube.		6		382.90		1	
		6		Medium Grey and mottled Brown, V. Moist CLAY to SILTY CLAY		1	0.7
		3				1	B 28
	-15	3		380.40	-35	1	
		4		Medium Brown and mottled Grey, V. Moist SILTY CLAY to SILTY CLAY LOAM		2	0.8
		3				2	B 26
		5		377.90		WOH	
		1		Medium Grey, V. Moist CLAY		1	0.8
		1				1	B 27
	-20	1		375.40	-40	WOH	

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 EB Lanes over Crab Orchard Lake	LOGGED BY	L. Estel
-------	-----------------	-------------	---------------------------------------	-----------	----------

SECTION	5-3B-3	LOCATION	1.1 mi. E of Jackson Co. (near W Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	--------	-----------------	---

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lb
---------------	------------	------------------------	---	--------------------	-----------------

STRUCT. NO.	100-0018
Station	309+50

BORING NO.	<u>2-S</u>
Station	<u>308+53</u>
Offset	<u>14.0ft Rt EB CL</u>
Ground Surface Elev.	<u>414.9</u>

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	------------------------------------	----------------------------------

Surface Water Elev.	405.5	ft
Stream Bed Elev.		ft
Groundwater Elev.:		
▼ First Encounter	403.9	ft
▼ Upon Completion		ft
▼ After	Hrs.	ft

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	--------------------------------	----------------------------------

Stiff Grey and mottled Brown,
Moist to V. Moist CLAY
(continued)

	1	1.1	27
	1	B	

Soft Grey, V. Moist CLAY to SILTY CLAY (continued)

	WOH	0.4	24
	WOH	B	

-45	1		
	2	1.2	27
	5	B	

Stiff Grey, Moist SANDY CLAY
with broken SANDSTONE

-65	2		
	3	1.8	19
	10	B	

-50	1		
	2	1.4	37
	2	B	

Very Dense Grey, Dry
SANDSTONE with Black CLAY
SHALES LENSES

[illegible]

2	1.4	37
2	B	

(end of boring)

Bottom of hole @ 69.7 feet

Ground Surface Elevation
referenced to benchmark at NW
corner of SN 100-0018; Elev.
416.6

SPT Hammer Efficiency: 75% (To convert "N" values to "N60", multiply by 1.25)

Note: During drilling in the rock fill from 9.5 to 26.0 feet, the augers were "kicked out" of plumb such that coring was not possible

Medium Grey, V. Moist CLAY to SILTY CLAY

-55	WOH		
	1	0.6	24
	WOH	B	

-75			

-60	WOH		
-----	-----	--	--

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

STATE OF ILLINOIS
DEPARTMENT OF PUBLIC WORKS & BUILDINGS
DIVISION OF HIGHWAYS

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
14	5-38	WILLIAMSON	18	13
FED. HIGHWAY NO. 7		ILLINOIS	FED. AID PROJECT	

SHEET NO. 8
SHEETS 8

COUNTY Williamson		Elevation	N	On 1/4	%
Boring No. 1					
Station 208-98					
Offset 10 ft. SW					
see previous sheet		4.0			
			15	1.08 LB	
366.7					
Dense moist gray mottled brown sandy gravel with clay binder		366.0	100	Blow	5
		4.5			
Hard gray fine grained sandstone with thin laminations of black sandy shale				Cored 80% Recovery	
		344.0			
Bottom of Hole 49.1 feet		40			
		40			
Washing procedure used in drilling entire hole.					
		5			
Location: Near the N.W. corner of the NW 1/4 Sec. 17, R1E, T9S, P.M.		5			

Type failure:
B - Bulge Failure
S - Shear Failure
E - Estimated Value
P - Penetrometer Value

FEB 18 1964

EXAMINED W.E. Brumm
ENGINEER IN CHARGE AND TRAFFIC STRUCTURES

PASSED E.P. Shultz
ENGINEER OF DESIGN


APPROVED O.F. Smith
CHIEF OF DESIGN

COUNTY - Williams	Elevation	N	Q _u /L.E.	w (%)	Surface Water El. Groundwater El. at Completion After * Hours	403.2 e e	Elevation	N	Q _u /L.E.	w (%)
Boring No. A Station 30296 Offset 19 ft. R.R.										
Ground Surface	391.0	0			See previous column					
Medium moist light brown mottled gray and black clay A7-6(1A-15)							-25	11	Lost Sample	
	386.5		0.8B 11		Medium moist dark gray clay A7-6(15)	386.0				
Soft very moist gray mottled black silty loam A-6(8) with rotten vegetation	385.0	-5	0.2F 31				7	1.0B	30	
Stiff moist gray mottled brown silty clay loam A-6(9)		6	1.1R 26		Medium very moist dark gray silty clay A-6(11-12) with some rotten vegetation	382.5	-10	6	0.6B	27
	381.0-10	7	1.0B 23				6	0.6B	32	
Medium moist light brown mottled black silty clay loam A-6(9-10)		9	0.8B 24		Soft very moist dark gray silty clay loam A-6(9-10) with some rotten vegetation	377.0	-35	9	0.4B	29
	377.0									
Stiff moist gray mottled brown and black clay A7-6(17+)		-15	1.2 40B 30		Medium to soft very moist dark gray silty clay A-6(12-13) with some rotten vegetation	374.5	6	0.6F	24	
		9	1.6B 34							
	372.5				Soft gray mottled brown sandy shale with silt seams	371.2	-40	19	—	—
Medium moist gray mottled brown and black clay A7-6(17+)		-20	8 0.8F 43		Soft light brown sandstone	359.0	100	Blow	1	
		6	1.0B 45							
							-43			

Card
NOT
Inventory

County	Williamson	Elevation	N	Qa / a.L.
Station	No. 4			
Boring	2005			
Offset	12 ft. N.			
See previous sheet		40		
Soft light brown sandstone	350.0			100 Blows in 6"
	349.5			
Medium hard light brown to gray sandstone with thin laminations of black sandy shale				Cored 40% Recovery
	4.5			
	44.5			
Bottom of Hole = 44.5 ft.				
*Boring taken in Lake through 12.2 feet of water.				
Washing procedure used in drilling entire hole.				
		40		

BORINGS
F.A. RTE. 14 SEC. 5-3B-3
WILLIAMSON COUNTY
STA. 309+50





**Illinois Department
of Transportation**
 Division of Highways
 District 9

SOIL BORING LOG

Page 1 of 2

Date 6/17/14

ROUTE FAP 331 (IL 13) DESCRIPTION IL 13 WB over Crab Orchard Lake LOGGED BY L. Estel

SECTION 5-B1 LOCATION 0.2 miles W of Cambria Road (near E Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM

COUNTY Williamson DRILLING METHOD Hollow Stem Auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140 lbs

STRUCT. NO. 100-0066
 Station 309+50
 BORING NO. 1-S
 Station 310+32
 Offset 14.0ft Lt CL WB
 Ground Surface Elev. 415.2 ft

DEPTH H (ft)	BLOW S (tsf)	UCS Qu (%)	MOIST T (%)	Surface Water Elev. <u>405.5</u> ft Stream Bed Elev. <u> </u> ft Groundwater Elev.: ▽ First Encounter <u>380.2</u> ft ▽ Upon Completion <u> </u> ft ▽ After <u> </u> Hrs. <u> </u> ft	DEPTH H (ft)	BLOW S (tsf)	UCS Qu (%)	MOIST T (%)
				Stiff Brown and Grey, Moist CLAY (continued)		3 4	1.6 B	19
413.70								
	1					1		
	2	2.5	19			3	1.9	19
	2	B				4	B	
-5	1				-25	1		
	3	2.3	18			2	1.3	19
	4	B				4	B	
	1					1		
	3	2.5	18			2	1.5	24
	4	B				3	B	
-10	1			385.70	-30	1		
	4	2.5	20	Stiff Grey, Moist to V. Moist SILT LOAM SAND 9%, SILT 74%, CLAY 17%, LL 28, PI 9 (estimated based on visual ID and historical database)		1	1.7	21
	4	B				4	S	
				383.20				
	1			Stiff Grey and mottled Brown, Moist to V. Moist SILTY CLAY to SILTY CLAY LOAM SAND 9%, SILT 70%, CLAY 21%, LL 31, PI 11 (estimated based on visual ID and historical database)		1	1.1	25
	3	2.0	21			2	B	
	4	B		380.70				
-15	1			Medium Grey and mottled Brown, V. Moist SILTY CLAY LOAM	-35	1		
	3	2.7	18			2	1.0	24
	5	B				2	B	
398.20				378.20				
	1			V. Soft Grey and mottled Brown, Wet SILTY CLAY LOAM		WOH		
	3	1.7	19			WOH	0.1	30
	5	S				1	B	
				375.70				
-20	1				-40	1		

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated)
 Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating
 The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 WB over Crab Orchard Lake	LOGGED BY	L. Estel
-------	-----------------	-------------	---------------------------------	-----------	----------

SECTION	5-B1	LOCATION	0.2 miles W of Cambria Road (near E Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	------	-----------------	--

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lbs
---------------	------------	------------------------	---	--------------------	------------------

STRUCT. NO. 100-0066
Station 309+50

BORING NO.	<u>1-S</u>
Station	<u>310+32</u>
Offset	<u>14.0ft Lt CL WB</u>
Ground Surface Elev.	<u>415.2</u>

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	--------------------------------	----------------------------------

Surface Water Elev.	<u>405.5</u>	ft
Stream Bed Elev.	<u> </u>	ft
Groundwater Elev.:		
▼ First Encounter	<u>380.2</u>	ft
▼ Upon Completion	<u> </u>	ft
▼ After Hrs.	<u> </u>	ft

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	------------------------------------	----------------------------------

V. Stiff Grey and mottled Brown, Moist CLAY (continued)	3	2.9	24
	4	B	

Medium Grey, V. Moist CLAY
(continued)

WOH	0.6	22
1	B	

Stiff Grey and mottled Brown, Moist CLAY	-45	1		
		2	18	29

V. Dense Grey, Dry SANDSTONE with some CLAY SHALE
--

5	100/8"		

(Borehole continued with rock coring.)

Bottom of hole @ 75.5 feet

Ground Surface Elevation
Referenced to BM at NW corner of
SN 100-0018: Elev. 416.6

Hammer Efficiency = 75% (To convert "N" values to "N60", multiply by 1.25)

Medium Grey, Moist to V. Moist CLAY	1	1.0	43
	2	B	

Soft Grey, V. Moist CLAY	55	WOH
--------------------------	----	-----

Medium Grey, V. Moist CLAY	60	WOH
----------------------------	----	-----

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



ROCK CORE 100-0066 IL 13 WB OVER CRAB ORCHARD LAKE.GPJ D6TEMPLT.GDT 4/14/21

Illinois Department of Transportation
District Nine Materials
Unconfined Compressive Strength

FAP 331 (IL 13)
Structure 100-0066 (Boring 1-S)
Williamson County



<u>Boring #</u>	<u>Specimen#</u>	<u>Depth</u>	<u>Unconfined Compression</u>
1-S	1	66' 8"	4,954 psi
1-S	2	67' 8"	4,785 psi
1-S	3	74' 6"	3,456 psi



SOIL BORING LOG

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 WB over Crab Orchard Lake	LOGGED BY	L. Estel
-------	-----------------	-------------	---------------------------------	-----------	----------

SECTION	5-B1	LOCATION	0.2 miles W of Cambria Road (near W Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	------	-----------------	--

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lbs
---------------	------------	------------------------	---	--------------------	------------------

STRUCT. NO. 100-0066
Station 309+50

BORING NO.	<u>2-S</u>
Station	<u>308+65</u>
Offset	<u>14.0ft Lt CL WB</u>
Ground Surface Elev.	<u>415.2</u>

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	------------------------------------	----------------------------------

Surface Water Elev.	_____	405.5	ft
Stream Bed Elev.	_____		ft
Groundwater Elev.: _____ ft			
▼ First Encounter	_____	380.7	ft
▼ Upon Completion	_____		ft
▼ After Hrs.			ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Cored Pavement, HMA over
Crushed AGGREGATE

413.70

Stiff Brown, Moist CLAY

1		
1	1.4	22
2	B	

410.70

V. Stiff Brown and Grey, Moist
CLAY

1		
2	2.3	25
3	B	

408.20

Stiff Brown, Moist CLAY to SILTY CLAY

1		
1	1.6	16
2	B	

-10

-10	1		
	2	1.7	21
	3	B	

1		
2	1.3	21
3	B	

-15

-15	1		
	2	1.5	21
	3	B	

1		
2	1.5	20
3	B	

-20

Stiff Brown, Moist CLAY to SILTY CLAY (continued)

390.20

V. Stiff Grey, Moist CLAY

388.20

Stiff Grey, Moist CLAY

385.70

Medium Grey, V. Moist SILTY
CLAY to SILTY CLAY LOAM

383.20

Soft Grey, V. Moist CLAY

▽ 380.70

Soft Grey and mottled Brown, V.
Moist SILTY CLAY

378.20

Medium Grey and mottled Brown,
Moist to V. Moist SILTY CLAY
LOAM

375.70

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE	FAP 331 (IL 13)	DESCRIPTION	IL 13 WB over Crab Orchard Lake	LOGGED BY	L. Estel
-------	-----------------	-------------	---------------------------------	-----------	----------

SECTION	5-B1	LOCATION	0.2 miles W of Cambria Road (near W Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	------	-----------------	--

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lbs
---------------	------------	------------------------	---	--------------------	------------------

STRUCT. NO. 100-0066
Station 309+50

BORING NO.	<u>2-S</u>
Station	<u>308+65</u>
Offset	<u>14.0ft Lt CL WB</u>
Ground Surface Elev.	<u>415.2</u>

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	--------------------------------	----------------------------------

Surface Water Elev.	<u>405.5</u>	ft
Stream Bed Elev.	<u> </u>	ft
Groundwater Elev.:		
▽ First Encounter	<u>380.7</u>	ft
▽ Upon Completion	<u> </u>	ft
▼ After Hrs.	<u> </u>	ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

V. Stiff Grey and mottled Brown,
Moist CLAY (*continued*)

2	2.3	35
3	S	

Medium Grey, V. Moist CLAY
(continued)

1	0.8	24
2	B	

Stiff Grey and mottled Brown,
Moist CLAY

1		
2	16	48

Hard Grey, Dry Weathered CLAY SHALE	350.20
-------------------------------------	--------

18		
----	--	--

Hard Grey, Dry CLAY SHALE

Stiff Brown, Moist SILTY CLAY to CLAY

1	1.6	42
1	B	

Bottom of hole @ 65.3 feet

Ground Surface Elevation
referenced to BM at NW corner of
SN 100-0018; Elev. 416.6

Hammer Efficiency = 75% (To convert "N" values to "N60", multiply by 1.25)

Medium Grey, V. Moist CLAY

WOH		
WOH	0.6	28
WOH	B	

-75-

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

Appendix E

Settlement Analysis





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ===== East Abutment / Boring 1-S (0106)

TYPE OF SURCHARGE ===== 1 (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) == 27 FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT ===== 120 PCF

NEW EMBANKMENT FILL HEIGHT ===== 27 FT

PROPOSED WIDTH AT TOP ===== 90 FT

PROPOSED WIDTH AT BOTTOM ===== 198 FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT ===== 120 PCF

EXISTING EMBANKMENT HEIGHT ===== 27 FT


EXISTING WIDTH AT TOP ===== 42 FT

EXISTING WIDTH AT BASE ===== 150 FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
1.5	120	2.50	21	3.269	0.000	0.567	0.099	0.100	0.00
1.5	120	2.50	21	3.327	0.000	0.567	0.099	0.100	0.00
2.5	120	0.20	34	3.403	0.001	0.918	0.216	0.700	0.00
2.5	120	0.40	30	3.497	0.003	0.810	0.180	0.436	0.00
2.5	120	0.40	33	3.588	0.007	0.891	0.207	0.436	0.00
2.5	120	2.10	27	3.678	0.014	0.729	0.153	0.106	0.00
2.5	120	1.50	35	3.765	0.023	0.945	0.225	0.142	0.00
2.5	120	1.80	31	3.850	0.034	0.837	0.189	0.121	0.00
2.5	120	1.80	31	3.933	0.047	0.837	0.189	0.121	0.00
2.5	120	0.80	28	4.016	0.060	0.756	0.162	0.242	0.00
2.5	120	0.80	28	4.097	0.075	0.756	0.162	0.242	0.01

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.02 IN.

EMBANKMENT AND SOIL PROFILE





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ===== West Abutment / Boring 2-S (0106)

TYPE OF SURCHARGE ===== 1 (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) == 27 FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT ===== 120 PCF

NEW EMBANKMENT FILL HEIGHT ===== 27 FT

PROPOSED WIDTH AT TOP ===== 90 FT

PROPOSED WIDTH AT BOTTOM ===== 198 FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT ===== 120 PCF

EXISTING EMBANKMENT HEIGHT ===== 27 FT


EXISTING WIDTH AT TOP ===== 42 FT

EXISTING WIDTH AT BASE ===== 150 FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
3.5	120	0.70	32	3.307	0.000	0.864	0.198	0.271	0.00
2.5	120	0.70	29	3.422	0.001	0.783	0.171	0.271	0.00
2.5	120	0.70	28	3.515	0.004	0.756	0.162	0.271	0.00
2.5	120	0.80	26	3.607	0.009	0.702	0.144	0.242	0.00
2.5	120	0.80	27	3.695	0.016	0.729	0.153	0.242	0.00
2.5	120	1.10	27	3.782	0.025	0.729	0.153	0.184	0.00
2.5	120	1.10	27	3.867	0.036	0.729	0.153	0.184	0.00
2.5	120	1.20	27	3.950	0.049	0.729	0.153	0.171	0.00
2.5	120	1.20	27	4.032	0.063	0.729	0.153	0.171	0.00
2.5	120	1.40	37	4.114	0.078	0.999	0.243	0.150	0.00
2.5	120	1.40	37	4.195	0.093	0.999	0.243	0.150	0.01

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.02 IN.

EMBANKMENT AND SOIL PROFILE





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ====**East Abutment / Boring 1-S (0107)**

TYPE OF SURCHARGE =====**1** (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) ==**27** FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT =====**120** PCF

NEW EMBANKMENT FILL HEIGHT =====**27** FT

PROPOSED WIDTH AT TOP =====**90** FT

PROPOSED WIDTH AT BOTTOM =====**198** FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT =====**120** PCF

EXISTING EMBANKMENT HEIGHT =====**27** FT


EXISTING WIDTH AT TOP =====**42** FT

EXISTING WIDTH AT BASE =====**150** FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
1.2	120	1.50	24	3.263	0.000	0.648	0.126	0.142	0.00
2.5	120	1.70	21	3.334	0.000	0.567	0.099	0.127	0.00
2.5	120	1.10	25	3.429	0.001	0.675	0.135	0.184	0.00
2.5	120	1.00	24	3.523	0.004	0.648	0.126	0.200	0.00
2.5	120	0.10	30	3.614	0.009	0.810	0.180	0.850	0.00
2.5	120	2.90	24	3.702	0.016	0.648	0.126	0.100	0.00
2.5	120	2.90	24	3.789	0.026	0.648	0.126	0.100	0.00
2.5	120	1.80	29	3.873	0.037	0.783	0.171	0.121	0.00
2.5	120	1.80	29	3.956	0.050	0.783	0.171	0.121	0.00
2.5	120	1.00	43	4.039	0.064	1.161	0.297	0.200	0.01
2.0	120	1.00	43	4.112	0.077	1.161	0.297	0.200	0.01

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.02 IN.

EMBANKMENT AND SOIL PROFILE





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ===== West Abutment / Boring 2-S (0107)

TYPE OF SURCHARGE ===== 1 (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) == 27 FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT ===== 120 PCF

NEW EMBANKMENT FILL HEIGHT ===== 27 FT

PROPOSED WIDTH AT TOP ===== 90 FT

PROPOSED WIDTH AT BOTTOM ===== 198 FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT ===== 120 PCF

EXISTING EMBANKMENT HEIGHT ===== 27 FT


EXISTING WIDTH AT TOP ===== 42 FT

EXISTING WIDTH AT BASE ===== 150 FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
1.7	120	2.50	19	3.273	0.000	0.513	0.081	0.100	0.00
2.5	120	1.20	21	3.353	0.000	0.567	0.099	0.171	0.00
2.5	120	0.60	29	3.448	0.002	0.783	0.171	0.309	0.00
2.5	120	0.30	35	3.541	0.005	0.945	0.225	0.550	0.00
2.5	120	0.40	29	3.632	0.010	0.783	0.171	0.436	0.00
2.5	120	1.00	26	3.720	0.018	0.702	0.144	0.200	0.00
2.5	120	2.30	35	3.806	0.028	0.945	0.225	0.100	0.00
2.5	120	2.30	35	3.890	0.040	0.945	0.225	0.100	0.00
3.0	120	1.60	48	3.981	0.054	1.296	0.342	0.134	0.00
2.5	120	1.60	48	4.071	0.070	1.296	0.342	0.134	0.00
2.5	120	1.60	42	4.153	0.085	1.134	0.288	0.134	0.00

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.02 IN.

EMBANKMENT AND SOIL PROFILE



Appendix F


Slope Stability Analysis





Soil Parameters for Slope Stability Analysis

SN 100-0106 - East Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c' (ksf)	θ (deg.)	c' (ksf)	θ (deg.)
1	Crushed Aggregate	406.8	125	0	40	0	40
2	Rock Fill	389.3	125	0	40	0	40
3	Stiff Silty Clay Loam	387.8	125	2.5	0	0.1	28
4	Soft Silty Clay	380.3	120	0.4	0	0.1	26
5	Stiff Moist Clay	370.3	125	1.8	0	0.1	28
6	Medium Moist Clay	364.8	125	0.8	0	0.1	28
7	Stiff Moist Clay	360.3	125	1.6	0	0.1	28
8	Stiff Moist Clay	352.3	125	2.6	0	0.1	28
9	Sandstone	-	150	0	45	0	45










Soil Parameters for Slope Stability Analysis

SN 100-0106 - West Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c' (ksf)	θ (deg.)	c' (ksf)	θ (deg.)
1	Crushed Aggregate	405.4	125	0	40	0	40
2	Rock Fill	388.9	125	0	40	0	40
3	Medium Moist Clay/ Silty Clay	375.4	120	0.7	0	0.1	26
4	Stiff Moist Clay	360.4	125	1.2	0	0.1	28
5	Soft to Medium Moist Clay/Silty Clay	350.4	120	0.4	0	0.1	26
6	Stiff Moist Sandy Clay	348.4	125	1.8	0	0.1	28
7	Sandstone	-	150	0	45	0	45










Soil Parameters for Slope Stability Analysis

SN 100-0107 - East Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c' (ksf)	θ (deg.)	c' (ksf)	θ (deg.)
1	Stiff Moist Clay	398.2	125	2.4	0	0.1	28
2	Stiff Moist Clay	385.7	125	1.6	0	0.1	28
3	Stiff Moist Silt Loam	383.2	125	1.7	0	0.1	28
4	Stiff Moist Silty Clay Loam	378.2	125	1.0	0	0.1	28
5	Soft Silty Clay Loam	375.7	120	0.1	0	0.1	26
6	Stiff Moist Clay	370.7	125	2.9	0	0.1	28
7	Stiff Moist Clay	365.2	125	1.6	0	0.1	28
8	Medium Moist Clay	360.7	125	1.0	0	0.1	28
9	Soft/Medium Moist Clay	350.7	120	0.3	0	0.1	26
10	Sandstone	-	150	0	45	0	45










Soil Parameters for Slope Stability Analysis

SN 100-0107 - West Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c' (ksf)	θ (deg.)	c' (ksf)	θ (deg.)
1	Stiff Moist Clay	390.2	125	1.5	0	0.1	26
2	Stiff Moist Clay	388.2	125	2.5	0	0.1	28
3	Stiff Moist Clay	385.7	125	1.2	0	0.1	28
4	Soft/Medium Moist Clay	378.2	120	0.4	0	0.1	26
5	Medium Silty Clay Loam	375.7	125	1.0	0	0.1	28
6	Stiff Moist Clay	370.7	125	2.3	0	0.1	28
7	Stiff Moist Clay	360.7	125	1.6	0	0.1	28
8	Medium Moist Clay	360.7	125	0.7	0	0.1	28
9	Sandstone	-	150	0	45	0	45







Appendix G

Seismic Site Class Determination





SEISMIC SITE CLASS DETERMINATION

PROJECT TITLE=====IL 13 over Crab Orchard Lake (SN 100-0106 and 100-0107)

Substructure 1

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0018-1-S
Top of Boring Elev. 414.8 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 6 (Blows/ft.) Soil Site Class E
N_{ch} (bar): 22 (Blows/ft.) Soil Site Class D <----Controls
s_u (bar): 1.62 (ksf) Soil Site Class D

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.8	1.00 0	B
	410.3	3.50 22	
	406.8	3.50 22	B
	402.8	4.00 5	
3.2	398.8	4.00 5	
7.2	394.8	4.00 5	
11.2	390.8	4.00 5	B
14.2	387.8	3.00 4 2.50	B
16.7	385.3	2.50 1 0.20	B
21.7	380.3	5.00 1 0.40	B
24.2	377.8	2.50 5 2.10	B
27.2	374.8	3.00 4 1.50	
31.7	370.3	4.50 5 1.80	B
37.2	364.8	5.50 3 0.80	B
41.7	360.3	4.50 4 1.60	B
46.7	355.3	5.00 8 2.90	
49.7	352.3	3.00 10 2.30	B
100.0	302.0	50.30 100 10.00	R

Substructure 2

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0018-2-S
Top of Boring Elev. 414.9 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 5 (Blows/ft.) Soil Site Class E
N_{ch} (bar): 19 (Blows/ft.) Soil Site Class D <----Controls
s_u (bar): 1.41 (ksf) Soil Site Class D

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.9	1.00 0	B
	409.7	4.25 22	
	405.4	4.25 22	B
0.6	401.4	4.00 5	
4.6	397.4	4.00 5	
8.6	393.4	4.00 5	
13.1	388.9	4.50 5	B
16.6	385.4	3.50 1 0.70	B
19.1	382.9	2.50 1 0.70	B
21.6	380.4	2.50 2 0.70	B
24.1	377.9	2.50 4 0.80	B
26.6	375.4	2.50 2 0.80	B
31.6	370.4	5.00 2 1.10	
36.6	365.4	5.00 7 1.20	
41.6	360.4	5.00 4 1.40	B
46.6	355.4	5.00 1 0.60	B
51.6	350.4	5.00 0 0.40	B
53.6	348.4	2.00 13 1.80	B
100.0	302.0	46.40 100 10.00	R

Substructure 3

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0066-1-S
Top of Boring Elev. 415.2 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 6 (Blows/ft.) Soil Site Class E
N_{ch} (bar): NA (Blows/ft.) NA
s_u (bar): 1.18 (ksf) Soil Site Class D <----Controls

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.7	1.50 0	B
	411.2	2.50 4 2.50	
	408.7	2.50 7 2.30	
	406.2	2.50 7 2.50	
	403.7	2.50 8 2.50	
0.8	401.2	2.50 7 2.00	
3.8	398.2	3.00 8 2.70	B
6.3	395.7	2.50 8 1.70	
8.8	393.2	2.50 7 1.60	
11.3	390.7	2.50 7 1.90	
13.8	388.2	2.50 6 1.30	
16.3	385.7	2.50 5 1.50	B
18.8	383.2	2.50 5 1.70	B
21.3	380.7	2.50 3 1.10	B
23.8	378.2	2.50 4 1.00	B
26.3	375.7	2.50 1 0.10	B
31.3	370.7	5.00 7 2.90	B
36.8	365.2	5.50 5 1.80	B
41.3	360.7	4.50 3 1.00	B
46.3	355.7	5.00 2 0.30	B
51.3	350.7	5.00 1 0.60	B
100.0	302.0	48.70 100 10.00	R

Substructure 4

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0066-2-S
Top of Boring Elev. 415.2 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 6 (Blows/ft.) Soil Site Class E
N_{ch} (bar): NA (Blows/ft.) NA
s_u (bar): 1.51 (ksf) Soil Site Class D <----Controls

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.7	1.50 0	B
	410.7	3.00 3 1.40	B
	408.2	2.50 5 2.30	B
	405.7	2.50 3 1.60	
	403.2	2.50 5 1.70	
1.3	400.7	2.50 5 1.30	
3.8	398.2	2.50 5 1.50	
6.3	395.7	2.50 5 1.50	
8.8	393.2	2.50 5 1.90	
11.8	390.2	3.00 6 1.90	B
13.8	388.2	2.00 8 2.50	B
16.3	385.7	2.50 5 1.20	B
18.8	383.2	2.50 2 0.60	B
21.3	380.7	2.50 0 0.30	B
23.8	378.2	2.50 1 0.40	B
26.3	375.7	2.50 2 1.00	B
31.3	370.7	5.00 5 2.30	B
36.8	365.2	5.50 4 1.60	B
41.3	360.7	4.50 2 1.60	B
46.3	355.7	5.00 0 0.60	
50.8	351.2	4.50 3 0.80	B
100.0	302.0	49.20 100 10.00	R

Global Site Class Definition: Substructures 1 through 4

N (bar): 6 (Blows/ft.) Soil Site Class E
N_{ch} (bar): 56 (Blows/ft.) Soil Site Class C
s_u (bar): 1.43 (ksf) Soil Site Class D <----Controls

Appendix H

Liquefaction Analysis





LIQUEFACTION ANALYSIS

REFERENCE BORING NUMBER ===== 0107 E. Abut.
ELEVATION OF BORING GROUND SURFACE ===== 415.20 FT.
DEPTH TO GROUNDWATER - DURING DRILLING ===== 11.00 FT. (Below Boring Ground Surface)
DEPTH TO GROUNDWATER - DURING EARTHQUAKE ===== 11.50 FT. (Below Finished Grade Cut or Fill Surface)
PEAK HORIZ. GROUND SURFACE ACCELERATION COEFFICIENT (As) ===== 0.422
EARTHQUAKE MOMENT MAGNITUDE ===== 7.6
FINISHED GRADE FILL OR CUT FROM BORING SURFACE ===== 0.50 FT. (Fill Height)
HAMMER EFFICIENCY===== 73 %
BOREHOLE DIAMETER===== 8 IN.
SAMPLING METHOD===== Sampler w/out Liners

EQ MAGNITUDE SCALING FACTOR

(MSF) = 0.982

AVG. SHEAR WAVE VELOCITY (top 40')

$V_{s,40'}$ = 364 FT./SEC.

PGA CALCULATOR

Earthquake Moment Magnitude = 7.58
Source-To-Site Distance, R (km) = 111.51
Ground Motion Prediction Equations = NMSZ
PGA = 0.143

ELEV. OF SAMPLE (FT.)	BORING DATA							CONDITIONS DURING DRILLING					CONDITIONS DURING EARTHQUAKE				CORR. RESIST. CRR 7.5 CRR	SOIL MASS PART. FACTOR (r _s)	EQ INDUCED CSR	FACTOR OF SAFETY * CRR/CSR
	BORING SAMPLE DEPTH (FT.)	SPT N VALUE (BLOWS)	UNCONF. COMPR. STR., Q _u (TSF.)	% FINES < #200 (%)	PLAST. INDEX PI	LIQUID LIMIT LL	MOIST. CONTENT w _c (%)	EFFECTIVE UNIT WT. (KCF.)	VERT. STRESS (KSF.)	CORR. SPT N VALUE (N ₁) ₆₀	EQUIV. CLN. SAND SPT N VALUE (N ₁) _{60cs}	CRR RESIST. MAG 7.5 CRR 7.5	EFFECTIVE UNIT WT. (KCF.)	VERT. STRESS (KSF.)	TOTAL VERT. STRESS (KSF.)	OVER- BURDEN CORR. FACT. (Ks)				
413.7	1.5	1						0.095	0.143	1.962	1.962	0.053	0.095	0.203	0.203	1.500	0.078	0.968	0.266	N.L. (1)
410.2	5	4	2.5					0.133	0.608	6.832	6.832	0.086	0.133	0.668	0.668	1.277	0.108	0.906	0.249	N.L. (1)
407.7	7.5	7	2.3					0.132	0.938	10.893	10.893	0.121	0.132	0.998	0.998	1.196	0.142	0.857	0.235	N.L. (1)
405.2	10	7	2.5					0.133	1.271	10.736	10.736	0.120	0.133	1.331	1.331	1.116	0.131	0.806	0.221	N.L. (1)
402.7	12.5	8	2.5		12	30	20	0.070	1.446	12.378	12.378	0.135	0.070	1.506	1.599	1.088	0.144	0.754	0.220	N.L. (2)
400.2	15	7	2		12	30	21	0.067	1.613	10.795	10.795	0.120	0.067	1.673	1.923	1.058	0.125	0.704	0.222	N.L. (2)
398.2	17	8	2.7		12	30	18	0.071	1.755	12.196	12.196	0.133	0.071	1.815	2.189	1.039	0.136	0.666	0.220	N.L. (2)
395.2	20	8	1.7		12	30	19	0.065	1.950	11.943	11.943	0.131	0.065	2.010	2.572	1.013	0.130	0.613	0.215	N.L. (2)
392.7	22.5	7	1.6		12	30	19	0.065	2.113	10.219	10.219	0.115	0.065	2.173	2.890	0.994	0.112	0.574	0.210	N.L. (2)
390.2	25	7	1.9		12	30	19	0.067	2.280	9.958	9.958	0.113	0.067	2.340	3.214	0.977	0.108	0.541	0.204	N.L. (2)
387.7	27.5	6	1.3		12	30	19	0.062	2.435	8.326	8.326	0.099	0.062	2.495	3.525	0.965	0.093	0.512	0.198	N.L. (2)
385.7	29.5	5	1.5		12	30	24	0.064	2.563	6.793	6.793	0.086	0.064	2.623	3.777	0.956	0.081	0.493	0.195	N.L. (2)
383.2	32	5	1.7		9	28	21	0.065	2.726	6.612	6.612	0.085	0.065	2.786	4.096	0.944	0.078	0.472	0.191	N.L. (2)
380.7	34.5	3	1.1		11	31	25	0.060	2.876	3.872	3.872	0.064	0.060	2.936	4.402	0.937	0.059	0.456	0.188	N.L. (2)
378.2	37	4	1		12	30	24	0.059	3.023	5.042	5.042	0.072	0.059	3.083	4.705	0.928	0.066	0.443	0.185	N.L. (2)
375.7	39.5	1	0.1		12	30	30	0.035	3.111	1.245	1.245	0.050	0.035	3.171	4.949	0.923	0.045	0.432	0.185	N.L. (2)
370.7	44.5	7	2.9		12	30	24	0.072	3.471	8.239	8.239	0.098	0.072	3.531	5.621	0.894	0.086	0.417	0.182	N.L. (2)
365.7	49.5	5	1.8		12	30	29	0.066	3.801	5.606	5.606	0.077	0.066	3.861	6.263	0.885	0.067	0.408	0.182	N.L. (2)
360.7	54.5	3	1		12	30	43	0.059	4.096	3.226	3.226	0.060	0.059	4.156	6.870	0.874	0.051	0.403	0.183	N.L. (2)
355.7	59.5	2	0.3		12	30	24	0.046	4.326	2.083	2.083	0.053	0.046	4.386	7.412	0.865	0.045	0.399	0.185	N.L. (2)

* FACTOR OF SAFETY DESCRIPTIONS

N.L. (1) = NOT LIQUEFIABLE, ABOVE EQ GROUND WATER ELEVATION

N.L. (2) = NOT LIQUEFIABLE, $PI \geq 12$ OR $w_c/LL \leq 0.85$

N.L. (3) = NOT LIQUEFIABLE, $(N_1)_{60} > 25$

(C) = CONTRACTIVE SOIL TYPES

(D) = DILATIVE SOIL TYPES

Appendix I

Integral Abutment Feasibility Analysis



GENERAL DATA

STRUCTURE NUMBER=====100-0106
STRUCTURE TYPE =====MULTI-SPAN
STRUCTURE SKEW=====0 DEGREES
SUPER. DATA IN REFERENCE TO SUB. DATA =====ABUT 1

TOTAL STRUCTURE LENGTH=====140.00 FT
NUMBER OF SPANS =====3
END SPAN LENGTH =====42.00 FT
ADJACENT INTERIOR SPAN LENGTH =====56.00 FT

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (END OR MAIN SPAN)			
BEAM TYPE =====	WIDE FLANGE		
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (ADJACENT SPAN)			
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

ABUTMENT #1 DATA			
ABUTMENT NAME =====	East		
ABUTMENT REFERENCE BORING =====	B-1		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	12		
PILE SPACING PERP. TO CL =====	6	FT	

ABUTMENT #2 DATA			
ABUTMENT NAME =====	West		
ABUTMENT REFERENCE BORING =====	B-2		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	12		
PILE SPACING PERP. TO CL =====	6	FT	

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #1				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUIV. FOR N VALUE (TSF)
406.80	1.20		84	4.0
404.30	2.50		30	3.3
401.80	2.50		9	2.3
399.30	2.50		7	2.2
398.00	1.30		7	2.2

10.00 FT = TOTAL DEPTH ENTERED

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #2				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUIV. FOR N VALUE (TSF)
405.40	2.60		84	4.0
402.90	2.50		30	3.3
400.40	2.50		9	2.3
398.00	2.40		7	2.2

10.00 FT = TOTAL DEPTH ENTERED

WEIGHTED AVERAGE Qu FOR ABUTMENT #1===== 2.70 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #1
= 1/(1.45-[0.3*2.7])===== 1.56


WEIGHTED AVERAGE Qu FOR ABUTMENT #2===== 2.96 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #2
= 1/(1.45-[0.3*2.96])===== 1.78

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #1 = [1.56*12*0+1.78*12*140]/[1.56*12+1.78*12]===== 74.57 FT

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #2 = [1.78*12*0+1.56*12*140]/[1.78*12+1.56*12]===== 65.43 FT

ABUT 1 (East) - EXPANSION LENGTH LIMIT CHART - 0 DEG. SKEW



--- = Estimated expansion length for the indicated abutment. Piles with an expansion length greater than this are suitable for consideration.
(Note: The same size pile should be used at both abutments.)

GENERAL DATA

STRUCTURE NUMBER=====100-0106 - Widening Embankment
STRUCTURE TYPE =====MULTI-SPAN
STRUCTURE SKEW=====0 DEGREES
SUPER. DATA IN REFERENCE TO SUB. DATA =====ABUT 1

TOTAL STRUCTURE LENGTH=====140.00 FT
NUMBER OF SPANS =====3
END SPAN LENGTH =====42.00 FT
ADJACENT INTERIOR SPAN LENGTH =====56.00 FT

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (END OR MAIN SPAN)			
BEAM TYPE =====	WIDE FLANGE		
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (ADJACENT SPAN)			
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

ABUTMENT #1 DATA			
ABUTMENT NAME =====	East		
ABUTMENT REFERENCE BORING =====	B-1		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	12		
PILE SPACING PERP. TO CL =====	6	FT	

ABUTMENT #2 DATA			
ABUTMENT NAME =====	West		
ABUTMENT REFERENCE BORING =====	B-2		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	12		
PILE SPACING PERP. TO CL =====	6	FT	

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #1				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUITV. FOR N VALUE (TSF)
405.50	2.50	1.0		
403.00	2.50	1.0		
400.50	2.50	1.0		
398.00	2.50	1.0		

10.00 FT = TOTAL DEPTH ENTERED

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #2				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUITV. FOR N VALUE (TSF)
405.50	2.50	1.0		
403.00	2.50	1.0		
400.50	2.50	1.0		
398.00	2.50	1.00		

10.00 FT = TOTAL DEPTH ENTERED

WEIGHTED AVERAGE Qu FOR ABUTMENT #1===== 1.00 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #1
= 1/(1.45-[0.3*1])===== 0.87


WEIGHTED AVERAGE Qu FOR ABUTMENT #2===== 1.00 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #2
= 1/(1.45-[0.3*1])===== 0.87

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #1 = [0.87*12*0+0.87*12*140]/[0.87*12+0.87*12]===== 70.00 FT

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #2 = [0.87*12*0+0.87*12*140]/[0.87*12+0.87*12]===== 70.00 FT

ABUT 1 (East) - EXPANSION LENGTH LIMIT CHART - 0 DEG. SKEW



----- = Estimated expansion length for the indicated abutment. Piles with an expansion length greater than this are suitable for consideration.
(Note: The same size pile should be used at both abutments.)

By inspection, 0107 widening embankment condition OK

GENERAL DATA

STRUCTURE NUMBER=====100-0107
STRUCTURE TYPE =====MULTI-SPAN
STRUCTURE SKEW=====0 DEGREES
SUPER. DATA IN REFERENCE TO SUB. DATA =====ABUT 1

TOTAL STRUCTURE LENGTH=====140.00 FT
NUMBER OF SPANS =====3
END SPAN LENGTH =====42.00 FT
ADJACENT INTERIOR SPAN LENGTH =====56.00 FT

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (END OR MAIN SPAN)			
BEAM TYPE =====	WIDE FLANGE		
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.33	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (ADJACENT SPAN)			
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.33	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

ABUTMENT #1 DATA			
ABUTMENT NAME =====	East		
ABUTMENT REFERENCE BORING =====	B-1		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	10		
PILE SPACING PERP. TO CL =====	6.33	FT	

ABUTMENT #2 DATA			
ABUTMENT NAME =====	West		
ABUTMENT REFERENCE BORING =====	B-2		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	10		
PILE SPACING PERP. TO CL =====	6.33	FT	

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #1				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUIV. FOR N VALUE (TSF)
407.70	0.30	2.3		
405.20	2.50	2.5		
402.70	2.50	2.5		
400.20	2.50	2.0		
398.20	2.00	2.7		
398.00	0.20	1.70		

10.00 FT = TOTAL DEPTH ENTERED

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #2				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUIV. FOR N VALUE (TSF)
405.70	2.30	1.6		
403.20	2.50	1.7		
400.70	2.50	1.3		
398.20	2.50	1.50		
398.00	0.20	1.50		

10.00 FT = TOTAL DEPTH ENTERED

WEIGHTED AVERAGE Qu FOR ABUTMENT #1===== 2.39 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #1
= 1/(1.45-[0.3*2.39])===== 1.37


WEIGHTED AVERAGE Qu FOR ABUTMENT #2===== 1.52 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #2
= 1/(1.45-[0.3*1.52])===== 1.01

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #1 = [1.37*10*0+1.01*10*140]/[1.37*10+1.01*10]===== 59.41 FT

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #2 = [1.01*10*0+1.37*10*140]/[1.01*10+1.37*10]===== 80.59 FT

ABUT 1 (East) - EXPANSION LENGTH LIMIT CHART - 0 DEG. SKEW



----- = Estimated expansion length for the indicated abutment. Piles with an expansion length greater than this are suitable for consideration.
(Note: The same size pile should be used at both abutments.)

Appendix J

Driven Pile Analysis





IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0106 - W. Abut.
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====410.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, LIQUEF., DD) =====None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1500 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====66.67 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====179.99 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====67.50 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter=====4.700 FT. Unplugged Pile Perimeter=====6.975 FT.
Plugged Pile End Bearing Area=====1.379 SQFT. Unplugged Pile End Bearing Area=====0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	66 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.50	2.50		22	Sandy Gravel	6.0		50.2	9.0		13.7	14	0	0	8	5
403.00	2.50		30	Sandy Gravel	9.4	44.2	35.3	14.0	4.8	25.1	25	0	0	14	7
400.50	2.50		9	Sandy Gravel	2.5	19.9	38.5	3.7	2.1	28.8	29	0	0	16	10
398.00	2.50		7	Sandy Gravel	1.9	20.6	26.7	2.9	2.2	30.2	27	0	0	15	12
395.50	2.50		2	Sandy Gravel	0.5	6.9	41.0	0.8	0.7	32.5	33	0	0	18	15
393.00	2.50		6	Sandy Gravel	1.6	20.6	42.7	2.4	2.2	34.9	35	0	0	19	17
391.00	2.00		6	Sandy Gravel	1.3	20.6	26.8	2.0	2.2	35.1	27	0	0	15	19
388.90	2.10		1	Sandy Gravel	0.2	3.4	37.1	0.3	0.4	36.5	36	0	0	20	21
385.40	3.50	0.70			8.7	13.5	45.8	12.9	1.5	49.3	46	0	0	25	25
382.90	2.50	0.70			6.2	13.5	52.0	9.2	1.5	58.5	52	0	0	29	27
380.40	2.50	0.70			6.2	13.5	60.1	9.2	1.5	67.9	60	0	0	33	30
377.90	2.50	0.80			6.9	15.5	67.0	10.3	1.7	78.2	67	0	0	37	32
375.40	2.50	0.80			6.9	15.5	79.8	10.3	1.7	89.1	80	0	0	44	35
370.40	5.00	1.10			18.0	21.3	99.7	26.7	2.3	116.1	100	0	0	55	40
365.40	5.00	1.20			19.3	23.2	122.8	28.6	2.5	145.0	123	0	0	68	45
360.40	5.00	1.40			21.6	27.1	128.9	32.0	2.9	175.4	129	0	0	71	50
355.40	5.00	0.60			10.8	11.6	135.9	16.0	1.2	191.0	136	0	0	75	55
350.40	5.00	0.40			7.5	7.7	170.4	11.1	0.8	205.0	170	0	0	94	60
348.40	2.00	1.80			10.2	34.8	145.8	15.2	3.7	216.4	146	0	0	80	62
347.40	1.00			Sandstone	0.0	0.0	424.9	0.0	0.0	246.5	246	0	0	136	62.6
346.40	1.00			Sandstone	97.6	279.1	522.5	144.8	30.1	391.3	391	0	0	215	63.6
345.40	1.00			Sandstone	97.6	279.1	620.1	144.8	30.1	536.1	536	0	0	295	64.6
344.40	1.00			Sandstone	97.6	279.1	717.7	144.8	30.1	680.9	684	0	0	374	65.6
343.40	1.00			Sandstone	97.6	279.1	815.3	144.8	30.1	825.7	815	0	0	448	66.6
342.40	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0106 - E. Abut.

REFERENCE BORING =====1-S

LRFD or ASD or SEISMIC =====LRFD

PILE CUTOFF ELEV. =====410.00 ft

GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft

GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None

BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft

TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1500 kips

TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====66.67 ft

NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1

Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 179.99 KIPS

Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 67.50 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.

Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	61 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.50	2.50		30	Sandy Gravel	9.4		22.7	14.0		15.4	15	0	0	8	5
403.00	2.50		9	Sandy Gravel	2.5	13.3	27.4	3.7	1.4	19.3	19	0	0	11	7
400.50	2.50		7	Sandy Gravel	1.9	15.5	19.7	2.9	1.7	21.1	20	0	0	11	10
398.00	2.50		2	Sandy Gravel	0.5	5.9	35.0	0.8	0.6	23.5	24	0	0	13	12
395.50	2.50		6	Sandy Gravel	1.6	20.6	36.6	2.4	2.2	26.0	26	0	0	14	15
393.00	2.50		6	Sandy Gravel	1.6	20.6	21.1	2.4	2.2	26.6	21	0	0	12	17
390.80	2.20		1	Sandy Gravel	0.2	3.4	21.8	0.4	0.4	27.0	22	0	0	12	19
389.30	1.50	0.20			1.2	3.9	67.4	1.7	0.4	33.5	33	0	0	18	21
387.80	1.50	2.50			9.5	48.3	32.4	14.1	5.2	42.8	32	0	0	18	22
385.30	2.50	0.20			1.9	3.9	38.2	2.9	0.4	46.1	38	0	0	21	25
380.30	5.00	0.40			7.5	7.7	78.5	11.1	0.8	60.7	61	0	0	33	30
377.80	2.50	2.10			14.1	40.6	81.0	20.9	4.4	80.4	80	0	0	44	32
374.80	3.00	1.50			13.6	29.0	100.4	20.1	3.1	101.1	100	0	0	55	35
370.30	4.50	1.80			23.0	34.8	104.1	34.1	3.7	133.2	104	0	0	57	40
364.80	5.50	0.80			15.3	15.5	134.8	22.7	1.7	157.5	135	0	0	74	45
360.30	4.50	1.60			21.3	30.9	181.2	31.6	3.3	191.7	181	0	0	100	50
354.80	5.50	2.90			38.6	56.0	208.2	57.3	6.0	247.8	208	0	0	115	55
352.30	2.50	2.30			15.0	44.4	178.7	22.2	4.8	265.2	179	0	0	98	58
351.30	1.00			Sandstone	0.0	0.0	457.8	0.0	0.0	295.3	295	0	0	162	58.7
350.30	1.00			Sandstone	97.6	279.1	555.4	144.8	30.1	440.1	440	0	0	242	59.7
349.30	1.00			Sandstone	97.6	279.1	653.0	144.8	30.1	584.9	585	0	0	322	60.7
349.17	0.13			Sandstone	12.7	279.1	665.7	18.8	30.1	603.7	604	0	0	332	60.8
348.17	1.00			Sandstone	97.6	279.1	763.3	144.8	30.1	748.6	749	0	0	412	61.8
347.17	1.00			Sandstone	97.6	279.1	860.8	144.8	30.1	893.4	864	0	0	473	62.8
346.17	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0107 - W. Abut.
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====410.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1400 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====63.08 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====177.55 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====66.58 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter=====4.700 FT. Unplugged Pile Perimeter=====6.975 FT.
Plugged Pile End Bearing Area=====1.379 SQFT. Unplugged Pile End Bearing Area=====0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	63 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.20	2.80	1.60			13.2		46.1	19.6		23.2	23	0	0	13	5
402.70	2.50	1.70			12.3	32.9	50.7	18.3	3.5	40.6	41	0	0	22	7
400.20	2.50	1.30			10.2	25.1	64.7	15.2	2.7	56.2	56	0	0	31	10
397.70	2.50	1.50			11.3	29.0	76.0	16.8	3.1	73.0	73	0	0	40	12
395.20	2.50	1.50			11.3	29.0	95.1	16.8	3.1	90.6	91	0	0	50	15
392.70	2.50	1.90			13.2	36.7	108.3	19.6	4.0	110.2	108	0	0	60	17
390.20	2.50	1.90			13.2	36.7	133.1	19.6	4.0	131.1	131	0	0	72	20
388.20	2.00	2.50			12.7	48.3	120.7	18.8	5.2	147.2	121	0	0	66	22
385.70	2.50	1.20			9.6	23.2	118.7	14.3	2.5	160.2	119	0	0	65	24
383.20	2.50	0.60			5.4	11.6	118.3	8.0	1.2	167.6	118	0	0	65	27
380.70	2.50	0.30			2.8	5.8	123.1	4.2	0.6	172.0	123	0	0	68	29
378.20	2.50	0.40			3.7	7.7	138.4	5.5	0.8	178.8	138	0	0	76	32
375.70	2.50	1.00			8.3	19.3	171.9	12.4	2.1	193.9	172	0	0	95	34
370.70	5.00	2.30			29.9	44.4	188.3	44.4	4.8	236.9	188	0	0	104	39
365.70	5.00	1.60			23.6	30.9	211.9	35.1	3.3	271.9	212	0	0	117	44
360.70	5.00	1.60			23.6	30.9	216.2	35.1	3.3	304.9	216	0	0	119	49
355.70	5.00	0.60			10.8	11.6	230.9	16.0	1.2	321.4	231	0	0	127	54
351.20	4.50	0.80			12.5	15.5	399.7	18.5	1.7	356.7	357	0	0	196	59
350.20	1.00			Shale	58.5	171.8	458.2	86.9	18.5	443.6	444	0	0	244	59.8
349.20	1.00			Shale	58.5	171.8	516.8	86.9	18.5	530.5	517	0	0	284	60.8
348.20	1.00			Shale	58.5	171.8	575.3	86.9	18.5	617.4	575	0	0	316	61.8
347.20	1.00			Shale	58.5	171.8	633.9	86.9	18.5	704.3	634	0	0	349	62.8
346.20	1.00			Shale	58.5	171.8	692.4	86.9	18.5	791.2	692	0	0	381	63.8
345.20	1.00			Shale	58.5	171.8	751.0	86.9	18.5	878.1	751	0	0	413	64.8
344.20	1.00			Shale		171.8			18.5						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0107 - E. Abut.

REFERENCE BORING =====1-S

LRFD or ASD or SEISMIC =====LRFD

PILE CUTOFF ELEV. =====410.00 ft

GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft

GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None

BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft

TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1400 kips

TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====63.08 ft

NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1

Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 177.55 KIPS

Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 66.58 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.

Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	62 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.20	2.80	2.50			17.7		66.0	26.3		31.5	32	0	0	17	5
402.70	2.50	2.50			15.8	48.3	72.2	23.5	5.2	54.0	54	0	0	30	7
400.20	2.50	2.00			13.7	38.6	99.4	20.3	4.2	75.7	76	0	0	42	10
398.20	2.00	2.70			13.3	52.2	93.4	19.8	5.6	93.4	93	0	0	51	12
395.20	3.00	1.70			14.8	32.9	106.3	21.9	3.5	115.1	106	0	0	58	15
392.70	2.50	1.60			11.8	30.9	123.9	17.5	3.3	133.3	124	0	0	68	17
390.20	2.50	1.90			13.2	36.7	125.5	19.6	4.0	151.7	126	0	0	69	20
387.70	2.50	1.30			10.2	25.1	139.6	15.2	2.7	167.3	140	0	0	77	22
385.70	2.00	1.50			9.0	29.0	152.5	13.4	3.1	181.1	153	0	0	84	24
383.20	2.50	1.70			12.3	32.9	153.2	18.3	3.5	198.1	153	0	0	84	27
380.70	2.50	1.10			9.0	21.3	160.3	13.4	2.3	211.3	160	0	0	88	29
378.20	2.50	1.00			8.3	19.3	151.2	12.4	2.1	221.8	151	0	0	83	32
375.70	2.50	0.10			1.0	1.9	206.3	1.5	0.2	229.1	206	0	0	113	34
370.70	5.00	2.90			35.1	56.0	220.2	52.1	6.0	278.9	220	0	0	121	39
365.70	5.00	1.80			25.6	34.8	230.3	37.9	3.7	315.1	230	0	0	127	44
360.70	5.00	1.00			16.7	19.3	233.4	24.8	2.1	338.4	233	0	0	128	49
355.70	5.00	0.30			5.7	5.8	244.9	8.4	0.6	347.5	245	0	0	135	54
350.70	5.00	0.60			10.8	11.6	415.9	16.0	1.2	380.8	381	0	0	209	59
349.70	1.00			Shale	58.5	171.8	474.4	86.9	18.5	467.7	468	0	0	257	60.3
348.70	1.00			Shale	58.5	171.8	533.0	86.9	18.5	554.6	533	0	0	293	61.3
347.70	1.00			Shale	58.5	171.8	591.5	86.9	18.5	641.5	592	0	0	325	62.3
346.70	1.00			Shale	58.5	171.8	650.1	86.9	18.5	728.4	650	0	0	358	63.3
345.70	1.00			Shale	58.5	171.8	708.6	86.9	18.5	815.2	709	0	0	390	64.3
344.70	1.00			Shale	58.5	171.8	767.2	86.9	18.5	902.1	767	0	0	422	65.3
343.70	1.00			Shale		171.8			18.5						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0106 - Pier 1
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 391.40 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====385.30 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====2900 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====66.67 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 347.98 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 130.49 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	507 KIPS	272 KIPS	63 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.
Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
386.40	5.00	0.70			12.4		25.9	18.4		19.8	20	7	0	4	23
383.90	2.50	0.70			6.2	13.5	32.1	9.2	1.5	29.0	29	7	0	9	25
381.40	2.50	0.70			6.2	13.5	40.2	9.2	1.5	38.4	38	7	0	14	28
378.90	2.50	0.80			6.9	15.5	47.1	10.3	1.7	48.7	47	7	0	19	30
376.40	2.50	0.80			6.9	15.5	59.9	10.3	1.7	59.6	60	7	0	26	33
371.40	5.00	1.10			18.0	21.3	79.8	26.7	2.3	86.5	80	7	0	37	38
366.40	5.00	1.20			19.3	23.2	102.9	28.6	2.5	115.5	103	7	0	50	43
361.40	5.00	1.40			21.6	27.1	109.0	32.0	2.9	145.9	109	7	0	53	48
356.40	5.00	0.60			10.8	11.6	116.0	16.0	1.2	161.5	116	7	0	57	53
351.40	5.00	0.40			7.5	7.7	150.5	11.1	0.8	175.4	150	7	0	76	58
349.40	2.00	1.80			10.2	34.8	125.9	15.2	3.7	186.9	126	7	0	62	60
348.40	1.00			Sandstone	0.0	0.0	405.0	0.0	0.0	216.9	217	7	0	113	60.6
347.40	1.00			Sandstone	97.6	279.1	502.6	144.8	30.1	361.8	362	7	0	192	61.6
346.40	1.00			Sandstone	97.6	279.1	600.2	144.8	30.1	506.6	507	7	0	272	62.6
345.40	1.00			Sandstone	97.6	279.1	697.8	144.8	30.1	651.4	651	7	0	351	63.6
344.40	1.00			Sandstone	97.6	279.1	795.4	144.8	30.1	796.2	795	7	0	431	64.6
343.40	1.00			Sandstone	97.6	279.1	893.0	144.8	30.1	941.0	893	7	0	484	65.6
342.40	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0106 - Pier 2
REFERENCE BORING =====1-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 391.40 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====385.30 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft
TOTAL FACTORED SUBSTRUCTURE LOAD =====2900 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====66.67 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 347.98 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 130.49 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	576 KIPS	303 KIPS	60 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.
Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
387.80	3.60	2.50			22.8		26.7	33.8		34.2	27	13	0	2	21
385.30	2.50	0.20			1.9	3.9	32.4	2.9	0.4	37.5	32	14	0	4	24
380.30	5.00	0.40			7.5	7.7	72.8	11.1	0.8	52.1	52	14	0	15	29
377.80	2.50	2.10			14.1	40.6	75.3	20.9	4.4	71.8	72	14	0	26	31
374.80	3.00	1.50			13.6	29.0	94.6	20.1	3.1	92.6	93	14	0	37	34
370.30	4.50	1.80			23.0	34.8	98.3	34.1	3.7	124.6	98	14	0	40	39
364.80	5.50	0.80			15.3	15.5	129.0	22.7	1.7	148.9	129	14	0	57	44
360.30	4.50	1.60			21.3	30.9	175.4	31.6	3.3	183.2	175	14	0	83	49
354.80	5.50	2.90			38.6	56.0	202.4	57.3	6.0	239.2	202	14	0	98	54
352.30	2.50	2.30			15.0	44.4	172.9	22.2	4.8	256.7	173	14	0	82	57
351.30	1.00			Sandstone	0.0	0.0	452.1	0.0	0.0	286.7	287	14	0	144	57.7
350.30	1.00			Sandstone	97.6	279.1	549.7	144.8	30.1	431.6	432	14	0	224	58.7
349.30	1.00			Sandstone	97.6	279.1	647.2	144.8	30.1	576.4	576	14	0	303	59.7
348.30	1.00			Sandstone	97.6	279.1	744.8	144.8	30.1	721.2	724	14	0	383	60.7
347.30	1.00			Sandstone	97.6	279.1	842.4	144.8	30.1	866.0	842	14	0	450	61.7
346.30	1.00			Sandstone	97.6	279.1	940.0	144.8	30.1	1010.8	940	14	0	503	62.7
345.30	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0107 - Pier 1
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 391.80 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====385.30 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====2700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====63.08 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====342.42 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====128.41 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	559 KIPS	290 KIPS	62 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter=====4.700 FT. Unplugged Pile Perimeter=====6.975 FT.
Plugged Pile End Bearing Area=====1.379 SQFT. Unplugged Pile End Bearing Area=====0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
388.20	3.60	2.50			22.8		46.0	33.8		36.3	36	13	0	7	21
385.70	2.50	1.20			9.6	23.2	44.0	14.3	2.5	49.4	44	18	0	6	23
383.20	2.50	0.60			5.4	11.6	43.6	8.0	1.2	56.7	44	18	0	6	26
380.70	2.50	0.30			2.8	5.8	48.4	4.2	0.6	61.2	48	18	0	9	28
378.20	2.50	0.40			3.7	7.7	63.7	5.5	0.8	68.0	64	18	0	17	31
375.70	2.50	1.00			8.3	19.3	97.2	12.4	2.1	83.1	83	18	0	28	33
370.70	5.00	2.30			29.9	44.4	113.6	44.4	4.8	126.0	114	18	0	45	38
365.70	5.00	1.60			23.6	30.9	137.2	35.1	3.3	161.1	137	18	0	58	43
360.70	5.00	1.60			23.6	30.9	141.5	35.1	3.3	194.1	142	18	0	60	48
355.70	5.00	0.60			10.8	11.6	156.2	16.0	1.2	210.5	156	18	0	68	53
351.20	4.50	0.80			12.5	15.5	325.0	18.5	1.7	245.9	246	18	0	117	58
350.20	1.00			Shale	58.5	171.8	383.5	86.9	18.5	332.8	333	18	0	165	58.8
349.20	1.00			Shale	58.5	171.8	442.1	86.9	18.5	419.7	420	18	0	213	59.8
348.20	1.00			Shale	58.5	171.8	500.6	86.9	18.5	506.6	501	18	0	258	60.8
347.20	1.00			Shale	58.5	171.8	559.2	86.9	18.5	593.4	559	18	0	290	61.8
346.20	1.00			Shale	58.5	171.8	617.7	86.9	18.5	680.3	648	48	0	322	62.8
345.20	1.00			Shale	58.5	171.8	676.3	86.9	18.5	767.2	676	48	0	354	63.8
344.20	1.00			Shale		171.8			18.5						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0107 - Pier 2
REFERENCE BORING =====1-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 391.80 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====385.30 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft
TOTAL FACTORED SUBSTRUCTURE LOAD =====2700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====63.08 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 342.42 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 128.41 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	556 KIPS	292 KIPS	62 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.
Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
387.70	4.10	1.30			16.8		45.7	24.9		28.0	28	9	0	6	21
385.70	2.00	1.50			9.0	29.0	58.7	13.4	3.1	41.8	42	14	0	9	23
383.20	2.50	1.70			12.3	32.9	59.4	18.3	3.5	58.8	59	14	0	18	26
380.70	2.50	1.10			9.0	21.3	66.4	13.4	2.3	72.0	66	14	0	22	28
378.20	2.50	1.00			8.3	19.3	57.4	12.4	2.1	82.5	57	14	0	17	31
375.70	2.50	0.10			1.0	1.9	112.5	1.5	0.2	89.8	90	14	0	35	33
370.70	5.00	2.90			35.1	56.0	126.3	52.1	6.0	139.6	126	14	0	55	38
365.70	5.00	1.80			25.6	34.8	136.4	37.9	3.7	175.8	136	14	0	61	43
360.70	5.00	1.00			16.7	19.3	139.6	24.8	2.1	199.2	140	14	0	63	48
355.70	5.00	0.30			5.7	5.8	151.1	8.4	0.6	208.2	151	14	0	69	53
350.70	5.00	0.60			10.8	11.6	322.0	16.0	1.2	241.5	242	14	0	119	58
349.70	1.00			Shale	58.5	171.8	380.6	86.9	18.5	328.4	328	14	0	166	59.3
348.70	1.00			Shale	58.5	171.8	439.1	86.9	18.5	415.3	415	14	0	214	60.3
347.70	1.00			Shale	58.5	171.8	497.7	86.9	18.5	502.2	498	14	0	260	61.3
346.70	1.00			Shale	58.5	171.8	556.2	86.9	18.5	589.1	556	14	0	292	62.3
345.70	1.00			Shale	58.5	171.8	614.8	86.9	18.5	676.0	645	14	0	324	63.3
344.70	1.00			Shale	58.5	171.8	673.3	86.9	18.5	762.9	673	14	0	356	64.3
343.70	1.00			Shale		171.8			18.5						