

STRUCTURE GEOTECHNICAL REPORT

BRIDGE REPLACEMENT FAP 331 (IL 13) OVER CRAB ORCHARD LAKE

Section 1-4(B-1)
Williamson County, Illinois
Job No. C-99-045-13
Contract No. 78373
PTB 200-038
Existing Structure No. 100-0020 (EB)/100-0067 (WB)
Proposed Structure No. 100-0108 (EB)/100-0109 (WB)

Prepared For:
IDOT District 9
2801 W. Murphysboro Rd.
Carbondale, IL 62903
T: 618-549-2171



Prepared By:
Civil Design, Inc.
Tyler Ziegler, P.E., S.E.
307 E. Washington Ave.
Effingham, IL 62401
tziegler@civildesigninc.com T: 217-340-0349



Handwritten signature of Tyler J. Ziegler 2-5-2024
Exp. 11-30-2025

February 2024

Table of Contents

1.0 Project Description and Scope	1
1.1 Introduction	1
1.2 Existing Structure Information	1
1.3 Proposed Structure Information.....	2
2.0 Field Exploration	2
2.1 Subsurface Exploration and Testing	2
2.2 Subsurface Conditions.....	2
3.0 Geotechnical Evaluations and Recommendations	4
3.1 Settlement	4
3.2 Slope Stability.....	4
3.3 Seismic Considerations	5
3.4 Scour	6
3.5 Mining Activity	6
3.6 Liquefaction	7
3.7 Lateral Load Analysis	7
4.0 Foundation Recommendations	9
4.1 Abutments	9
4.2 Piers.....	11
5.0 Construction Considerations	13
5.1 Construction Activities	13
5.2 Temporary Shoring	13
5.3 Foundation Construction	13
5.4 Excavation	13
6.0 Limitations	14

Appendices

- A) Location Map
- B) Type, Size, and Location Plan (TS&L)
- C) Subsurface Data Profile Plot
- D) Soil Boring and Rock Core Logs
- E) Settlement Analysis
- F) Slope Stability Analysis
- G) Seismic Site Class Determination
- H) Liquefaction Analysis
- I) Integral Abutment Feasibility Analysis
- J) Driven Pile Analysis



1.0 Project Description and Scope

1.1 Introduction

The geotechnical investigation summarized herein was performed for the proposed dual bridges at IL 13 over Crab Orchard Lake in Williamson County, Illinois. See Appendix A for Location Map. The purpose of this report is to provide geotechnical design and construction recommendations to aid in the structure planning, final design plans and specification preparation.

1.2 Existing Structure Information

SN 100-0067 - Originally built in 1939, the west bound structure is a three span continuous wide flange bridge. The 0 degree skew structure is 123'-6" from back to back abutment with approximate span lengths of 38'-3", 47'-0" and 38'-3". The abutments are pile bent abutments on H-piles driven to refusal. The pier foundations consist of a single row of precast concrete piles.

The structure was later reconstructed in 1989 including a new superstructure, abutment caps and pier caps. The original piling was incorporated into the reconstruction of the substructure caps. The current, reconstructed superstructure consists of 7 composite steel beam lines of W24x55's for spans one and three and W24x62's for span two. Beams are spaced on 6'-4" centers. The reinforced concrete deck thickness is 7 1/2" and is on a normal crown. The clear width between face to face of parapets is 40'-0" and the overall out to out width of the bridge is 43'-2". At the piers, two new H-piles were driven and incorporated into the caps.

SN 100-0066 has a sufficiency rating of 88.4 with a deck rating of 8, very good condition, superstructure rating of 5, fair condition with minor section loss, and a substructure rating of 5, fair condition with minor section loss.

SN 100-0020 - Originally built in 1964, the eastbound structure is a three span continuous wide flange bridge. The 0 degree skew structure is 123'-0" from back to back abutment with approximate span lengths of 35'-9", 46'-11" and 35'-9". The superstructure consists of 7 steel beam lines of 27WF94 on 6'-4" centers with a 7" reinforced concrete deck on normal crown. The clear width between face to face of parapets is 40'-0" and the overall out to out width of the bridge is 42'-0". The abutments are pile bent abutments on H-piles driven to refusal with the front row battered and the back row vertical. The wingwalls consist of 12" walls bearing on a single H-pile. The piers are pile bents on a single row of 7 individually encased H-piles driven to refusal.

Two rehabilitations have been complete since the original construction. In 1997, repairs included abutment joint replacement, new elastomeric bearings and new diaphragms. In 1999, repair included partial and full depth patching of the deck in the driving lanes only, extending and eliminating drains, and installation of a concrete overlay. The overlay work consisted of 1/2" scarification with a 2 1/4" microsilica concrete overlay for a total deck thickness of 8 3/4".

SN 100-0020 has a sufficiency rating of 63.0 with a deck rating of 5, fair condition with minor section loss, superstructure rating of 4, poor condition with advanced deterioration, and a substructure rating of 6, satisfactory condition with minor deterioration.



1.3 Proposed Structure Information

Proposed SN 100-0108 to replace SN 100-0020 and proposed SN 100-0109 to replace SN 100-0067. The proposed replacement structures are 3 span bridges with continuous, composite steel W27 beams with an 8" reinforced concrete deck on a 0 degree skew. Proposed back to back abutment lengths are 128'-6" with span lengths of 38'-0" – 52'-6" – 38'-0". SN 100-0108 consists of 13 beams with typical spacing at 5'-10" centers and 3'-1" overhangs for an overall width of 76'-2" out to out. SN 100-0109 consists of 10 beams with typical spacing at 6'-2" centers and 2'-4" overhangs for an overall width of 60'-2" out to out. The SN 100-0108 roadway cross sections consist of a 6'-0" shoulder, 45'-6" roadway, 10'-0" shoulder, and a 11'-0" multi use trail. The SN 100-0109 roadway cross sections consist of a 17'-4" shoulder/ramp, 34'-0" roadway, and a 6'-0" shoulder. Staged construction will be utilized to maintain traffic. For further proposed structure information, see Appendix B for Type, Size, and Location Plan (TS&L).

2.0 Field Exploration

2.1 Subsurface Exploration and Testing

The subsurface investigation consisted of four borings drilled by the Illinois Department of Transportation in June and August of 2014. Borings were taken near the west and east abutment locations at each structure. Soil boring exploration was performed by drilling methods using a hollow stem auger and split spoon. Rock coring performed with conventional rotary drilling with water. See Appendix C for Subsurface Data Profile Plot and Appendix D for Soil Boring and Rock Core Logs.

Table 2.1 - Boring Log Summary

Location	Boring No.	Station	Offset	Ground Surface Elevation	Top of Rock Elevation
SN 100-0108 (E. Abut.)	1-S	336+71	15' RT - CL EB	414.9	355.9
SN 100-0108 (W. Abut.)	2-S	335+27	15' RT - CL EB	414.9	347.9
SN 100-0109 (E. Abut.)	1-S	336+82	13' LT - CL WB	415.3	348.8
SN 100-0109 (W. Abut.)	2-S	335+21	13' LT - CL WB	415.2	352.2

In addition to the borings discussed above, the existing borings of SN 100-0020 from 1964 are included in Appendix D to provide the designer with further soils information. In particular, the recent drillings do not include borings at the piers. The existing borings indicate the top of rock elevations of 348.2 and 348.7 at the existing west and east piers, respectively.

2.2 Subsurface Conditions

The groundwater conditions at each soil boring varies. See Table 2.2 below. Temperature, seasonal variations, and recent rainfall conditions may influence the levels of groundwater table. Without extended periods of observation, the measurement of groundwater conditions may not give a true indication of typical groundwater levels. Volume of water depends on the permeability of the soils.



Table 2.2 – Groundwater Conditions Summary

Location	Boring No.	First Encounter	Upon Completion	After 24 Hours
SN 100-0108 (E. Abut.)	1-S	403.8	-----	-----
SN 100-0108 (W. Abut.)	2-S	403.9	-----	-----
SN 100-0109 (E. Abut.)	1-S	383.3	-----	-----
SN 100-0109 (W. Abut.)	2-S	385.7	-----	-----

SN 100-0108 - Built 25 years after the adjacent westbound structure, crushed aggregate (CA-6) and rock fill embankment layers are encountered below the groundline and appear to have been used to build up the surrounding elevation to construct this bridge. The crushed aggregate extends down 8 and 7.5 feet in borings 1-S and 2-S, respectively, and has SPT (N) values ranging from 24 to 84. The rock fill extends down 24.5 feet in borings 1-S and 2-S. Riprap and crusher run make up the rock fill with primarily boulder sized with some gravel and sand recovered in the sample tube. Rock fill SPT (N) values range from 1 to 30.

Below the rockfill down to a depth of 34 feet, the boring show soft to stiff, grey, mottled grey, and brown, moist silty clay to silty clay loam with SPT (N) values ranging from WOH to 6 blows per foot, Q_u values of 0.3 to 1.9 tsf, and moisture contents ranging between 21% and 30%. From 34 feet to down to rock, both borings show soft to stiff, grey to mottled brown moist clays with SPT (N) values ranging from WOH to 10 blows per foot, Q_u values of 0.4 to 1.9 tsf, and moisture contents ranging between 23% and 48%.

At a depth of 59.1 feet, boring 1-S encounters a very dense grey, dry sandstone layer with SPT (N) of 100/0.5". Boring 2-S encounters a dense grey, dry sandstone with clay shale lenses at a depth of 70 feet with SPT (N) of 100/1".

SN 100-0109 – Both borings, 1-S and 2-S, encountered medium to very stiff brown and grey moist clay to silty clay from the ground surface elevation to an approximate depth of 25 feet and 22 feet respectively. The moist clay has SPT (N) values ranging from WOH to 7 blows per foot with Q_u values of 0.6 to 2.3 tsf and moisture contents ranging between 19% and 23%.

Beneath the top moist clay layers, boring 1-S shows a potentially liquefiable layer at depths of 25 to 27 feet. This layer consists of stiff, moist to very moist silty loam to silty clay loam with average soil contents of 10% sand, 71% silt, and 19% clay. Average liquid limit is 32 and plasticity index is 10, both values being estimated based on visual ID and historical database. SPT (N) value is 4 blows per foot with a Q_u value of 1.2 tsf and moisture content of 21%. Boring 2-S shows a potentially liquefiable layer at depths of 22 to 27 feet. This layer consists of medium stiff to stiff grey moist to very moist silty loam to silty clay loam with average soil contents of 10% sand, 71% silt, and 19% clay. Average liquid limit is 32 and plasticity index is 10, both values being estimated based on visual ID and historical database. SPT (N) values range from 1 to 2 blows per foot with Q_u values of 0.8 to 1.1 tsf and a moisture content of 23%.

From 27 to 37 feet, both borings show soft to stiff grey and mottled brown moist silty clay loam with SPT (N) values ranging from WOH to 4 blows per foot, Q_u values of 0.3 to 1.2 tsf, and moisture



contents ranging between 21% and 30%. From 37 feet down to rock, both borings show soft to stiff, grey to mottled brown moist clays with SPT (N) values ranging from WOH to 2 blows per foot, Q_u values of 0.3 to 1.9 tsf, and moisture contents ranging between 20% and 49%.

At a depth of 66.5 feet, boring 1-S encounters a very dense grey, dry sandstone layer with SPT (N) of 100/1". Rock core logs at 1-S show the top 5 feet of rock with an RQD of 63% and uniaxial compressive strength (UCS) of 350 tsf. The next 5 feet have an RQD of 60% and UCS of 250 tsf. Boring 2-S encounters a very dense grey, dry sandstone at a depth of 63 feet with SPT (N) of 100/1".

3.0 Geotechnical Evaluations and Recommendations

3.1 Settlement

Existing Embankment - Based on the provided preliminary plan and profile, the anticipated difference between the existing and proposed elevations at the abutments is minimal. Thus, settlement of the existing embankment is not anticipated due to minimal changes in loading and existing soil conditions. By inspection, the proposed structure should result in less than 0.4 inches of settlement. Per IDOT Geotechnical Manual Section 6.9.2, driven pile capacity need not account for downdrag if total settlement of soil around the piling is less than 0.4 inches.

Regarding settlement of approach slabs, one end of the slab is supported by the pile supported abutment. The other end of the slab is supported by the existing embankment subgrades. Provided proper compaction according to IDOT Standard Specifications is performed during construction, settlement of the approach slab is not a concern.

Proposed Widening Embankment – Due to the widening of the bridges, proposed embankment outside of the limits of the existing embankment is necessary. Potential settlement due to the proposed widened embankment was investigated using the IDOT Cohesive Soil Settlement Estimate spreadsheet. This simplified procedure estimates the primary settlement anticipated. The results from the settlement analysis shows settlement of less than 0.1". See Appendix E. In addition, secondary settlement is considered negligible with no organic layers are present.

3.2 Slope Stability

Slope stability analyses of the end slopes at both abutments of each structure were performed due to the high seismic region, unique high water conditions and proposed embankment required for widening. Engineering soil properties taken from the subsurface exploration descriptions were input and slope stability was evaluated using the software program StablPro. The Bishop's method analysis was used to search for the critical circular failure surface to calculate the factor of safety for the slope.

A critical factor of safety was calculated for three modeled conditions: short term static, long term static, and seismic. Short term conditions capture full cohesive values, while long term conditions assume drained soil properties. A live load surcharge of 250 psf was considered at both abutments. For seismic analysis, a horizontal acceleration coefficient of 0.422g was calculated according to guidance in the FHWA-NHI-11-032, LFRD Seismic Analysis and Design of Transportation Geotechnical Features and Structural Foundations.

See Table 3.1 below for slope stability factors of safety at each abutment. Each abutment location achieved the minimum factor of safety of 1.5 for static conditions and 1.0 for seismic conditions. See Appendix F for soil parameters and individual output of the analyses presented in the table.



Table 3.1 - Summary of Slope Stability Calculated Factors of Safety

Structure No.	Location	Short Term Static	Long Term Static	Seismic
100-0108	East Abut.	1.65	2.12	1.02
100-0108	West Abut.	1.50	2.06	1.01
100-0109	East Abut.	1.66	1.76	1.03
100-0109	West Abut.	1.67	1.76	1.02

As validation of the results, no known issues or concerns are present or have been present at the existing embankment slopes which have been in place for over 55 plus years. In addition, the existing piles supporting the abutments and piers will remain in place and increase the nominal slope stability FOS by intersecting the circular failure planes.

3.3 Seismic Considerations

LRFD Seismic Soil Site Class Definition was determined based on the methodology described in IDOT AGMU 9.1 and the IDOT BBS 149 form for Seismic Site Class Determination. See Appendix G for determination.

Further seismic parameters were determined using the figures and tables provided in AASHTO LRFD Bridge Design Specifications, Article 3.10 for Earthquake Effects, EQ. These parameters are based on a 1000 Year Return Period with a Probability of Exceedance of 7% in 75 years. See table below for a summary of seismic parameters.

Table 3.2 - Summary of Seismic Parameters

Parameter	Value
Seismic Soil Site Class	D
Spectral Acceleration Coefficient at period of 0.2 sec., S_s	0.682g
Spectral Acceleration Coefficient at period of 1.0 sec., S_1	0.171g
Site Factor, Short Period, F_a	1.24
Site Factor, Long Period, F_v	2.10
Design Spectral Acceleration at 0.2 sec. (SDS)	0.864g



Design Spectral Acceleration at 1.0 sec. (SD1)	0.359g
Seismic Performance Zone	SPZ 3

The Spectral Acceleration Coefficient at T=1.0 sec. (SD1) and Seismic Performance Zone were confirmed using Bridge Manual Planning Section 2.3.10.3.

Abutment foundations shall be designed for the full elastic base shear (R=1.0) and the solid wall encased pile bent piers shall be designed with an R of 2.0 for the longitudinal and transverse directions per BM 3.15.4.3.

3.4 Scour

Design scour elevations for the proposed structures were provided by Crawford, Murphy & Tilly. See table below. Stone Riprap, Class A4 is proposed to protect the bridge embankment side slopes from each abutment down to the toe of the lake bed.

Table 3.3 – Design Scour Elevation Table

Event/Limit State	Design Scour Elevations (ft.)				Item 113
	W. Abut.	Pier 1	Pier 2	E. Abut.	
Q100	Note 1	386.4	386.4	Note 1	5
Q200	Note 1	386.3	386.3	Note 1	
Design	Note 1	386.4	386.4	Note 1	
Check	Note 1	386.3	386.3	Note 1	

Note 1: Bottom of Abutment Cap Elevation

Scour loss shall be accounted for in the pier pile capacity design calculations. The design event shall be considered for the Strength Limit State and the check event shall be considered for the Extreme Event II Limit State. Though by inspection of the minimal difference between design and check scour elevations, the design event controls over the check event due to larger factored loads and smaller factored geotechnical resistance required for the Strength Limit State.

3.5 Mining Activity

Reviewing the Illinois State Geological Survey (ISGS) “Directory of Coal Mines in Illinois” for Williamson County, no mining activity is present at the bridge location. The nearest underground mine proximity region is located near Cambria, 2 miles northeast of the project location.



3.6 Liquefaction

The subsurface exploration indicated a potential liquefiable soil layer in the SN 100-0109 east abutment soil boring (1-S) between elevations 390.3 to 388.3 as well as the west abutment soil boring (2-S) between elevations 393.2 to 388.2 respectively. By inspection, no liquefiable layers are present at the other subject boring locations.

A liquefaction analysis was performed using the IDOT Liquefaction Analysis spreadsheet. The results from the liquefaction analysis show no liquefaction concern within the first 60 ft of the soil profile for either boring; thus, liquefaction was not considered for the pile capacity tables below. See Appendix H for Liquefaction Analysis.

3.7 Lateral Load Analysis

The tables below provide soil parameters to structural engineer for lateral or displacement analysis of the foundations. The values were estimated based on the descriptions given in the soil boring logs. Short term conditions are recommended for lateral load analysis. Full cohesion was assumed with a friction angle of 0 degrees for cohesive soils. No specific analyses were performed on the soil to determine the estimated parameters.

Table 3.4 –Soil Parameters for Lateral Load Analysis at SN 100-0108 Pier 1 (2-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Medium Silty Clay to Silty Clay Loam	387.9	125	0.6	0	300	0.007
Soft Silty Clay to Silty Clay Loam	386.4	120	0.4	0	100	0.01
Stiff Clay to Silty Clay	382.9	125	1.1	0	300	0.007
Soft Silty Clay	380.4	120	0.3	0	100	0.01
Medium to Stiff Silty Clay to Clay	377.9	125	1.0	0	300	0.007
Soft Silty Clay to Clay	375.4	120	0.4	0	100	0.01
Stiff Clay	365.4	125	1.3	0	300	0.007
Soft Clay	360.4	120	0.4	0	100	0.01
Medium Clay	355.4	125	0.7	0	300	0.007
Soft to Medium Clay	350.4	120	0.5	0	100	0.01
Stiff Clay to Clay Shale	347.9	130	1.5	0	500	0.005
Sandstone	-	150	0	45	-	0.001

Table 3.5 –Soil Parameters for Lateral Load Analysis at SN 100-0108 Pier 2 (1-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Soft to Medium Silty Clay to Silty Clay Loam	385.9	120	0.3	0	100	0.01
Stiff Silty Clay to Clay	383.4	125	1.9	0	300	0.007
Medium Clay Loam to Silty Clay Loam	380.9	125	0.8	0	300	0.007
Stiff Clay	369.9	125	1.9	0	300	0.007
Stiff Clay	355.9	125	1.2	0	300	0.007
Sandstone	-	150	0	45	-	0.001

Table 3.6 –Soil Parameters for Lateral Load Analysis at SN 100-0109 Pier 1 (2-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Stiff Silt Loam to Silty Clay Loam	390.2	125	1.1	0	300	0.007
Medium Silt Loam to Silty Clay Loam	388.2	125	0.8	0	300	0.007
Medium to Soft Silty Clay Loam	385.7	120	0.5	0	100	0.01
Medium to Soft Silty Clay Loam	383.2	125	1.0	0	300	0.007
Soft Clay to Silty Clay	380.7	120	0.3	0	100	0.01
Medium to Stiff Silty Clay to Silty Clay Loam	378.2	125	1.0	0	300	0.007
Soft Clay to Silty Clay	375.7	120	0.3	0	100	0.01
Medium Silty Clay	370.7	125	0.8	0	300	0.007
Stiff Clay	365.7	125	1.5	0	300	0.007
Medium to Stiff Clay	355.7	125	0.8	0	300	0.007
Medium Clay	352.7	125	0.6	0	300	0.007
Sandstone	-	150	0	45	-	0.001

Table 3.7 –Soil Parameters for Lateral Load Analysis at SN 100-0109 Pier 2 (1-S)

Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		K (pci)	ϵ_{50}
			c' (ksf)	θ (deg.)		
Stiff Silty Loam to Silty Clay Loam	388.3	125	1.2	0	300	0.007
Soft to Med. Stiff Silty Clay Loam	385.8	120	0.5	0	100	0.01
Stiff Silty Clay Loam	383.3	125	1.2	0	300	0.007
Soft Clay	378.3	120	0.3	0	100	0.01
Stiff Clay	365.3	125	1.6	0	300	0.007
Medium to Soft Clay	350.8	120	0.5	0	100	0.01
Stiff Clay to Sandy Clay	348.8	125	1.6	0	300	0.007
Sandstone	-	150	0	45	-	0.001

4.0 Foundation Recommendations

4.1 Abutments

Preliminary superstructure loads for the proposed structure configuration discussed above were provided by Civil Design, Inc. See tables below for total factored loads at each substructure. These loads include the approach slab and abutment self-weight.

Table 4.1 – SN 100-0108 Abut. Load

Location	Total Factored Reaction (k)
W. Abut.	1,700
E. Abut.	1,700

Table 4.2 – SN 100-0109 Abut. Load

Location	Total Factored Reaction (k)
W. Abut.	1,300
E. Abut.	1,300

Integral abutments are preferred to eliminate joints in the bridge decks, decreasing maintenance costs and increasing service life. See results of preliminary Integral Abutment Feasibility Analysis in Appendix I. The designer shall verify integral abutment feasibility analysis with final configuration. In addition, see IDOT ABD Memo 19.8 for further integral abutment design guidance.

Foundation type for integral abutments shall be pile supported with a pile placed under each girder. Due to the presence of sandstone at the subject site and H-piles being most effective in point bearing applications, H-piles are recommended over metal shell piles.

The tables below summarize the nominal required bearing (R_N), factored resistance available (R_F), estimated pile length and estimated pile tip elevation for the strength limit state. R_N indicates the resistance of the pile during driving, which assists the Contractor from causing damage to the pile. R_F represents the net long term axial geotechnical resistance available to support the factored structure

loads. The estimated pile lengths include a 2 foot embedment into the abutment. Analyses have been performed using the IDOT Static Method of Estimating Pile Length. See Appendix J.

The factored resistance available values shown in the tables are intended to provide the designer with a range of feasible options for the anticipated vertical loading. Pile tip elevations are shown at the maximum nominal required bearing of the pile. Piles shall be evaluated for lateral resistance in final design.

Table 4.3 – H-Pile Capacity at SN 100-0108 West Abutment (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	66	343.7
HP 12x53	418	230	66	343.7
HP 14x73	578	317	67	342.7

Table 4.4 – H-Pile Capacity at SN 100-0108 East Abutment (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	56	353.7
HP 12x53	418	230	56	353.7
HP 14x73	578	317	57	352.7

Table 4.5 – H-Pile Capacity at SN 100-0109 West Abutment (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	60	348.1
HP 12x53	418	230	60	348.1
HP 14x73	578	317	61	349.1

Table 4.6 – H-Pile Capacity at SN 100-0109 East Abutment (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 10x42	335	184	63	348.1
HP 12x53	418	230	63	348.1
HP 14x73	578	317	63	348.1

The capacities provided above for SN 100-0108 neglect the resistance from the top 10 ft below the cap. Due to no blow counts provided by the boring logs for the crushed aggregate and rockfill layers, precoring holes extending 10 ft below the caps and backfilling with bentonite is recommended at SN 100-0108.

One test pile is recommended at each abutment location. Due to the presence of the rockfill riprap layer and hard sandstone, pile shoes are recommended.

4.2 Piers

Preliminary superstructure loads for the proposed structure configuration discussed above were provided by Civil Design, Inc. See tables below for total factored loads at each substructure.

Table 4.7 – SN 100-0108 Pier Load

Location	Total Factored Reaction (k)
Pier 1	3,200
Pier 2	3,200

Table 4.8 – SN 100-0109 Pier Load

Location	Total Factored Reaction (k)
Pier 1	2,600
Pier 2	2,600

A pile-supported bent matches the existing substructure foundations. In addition, driven piles are recommended at the abutments so pile driving equipment will already be mobilized. Driven piles appear to be the most efficient pier foundation type. Similar to the abutments, H-piles are recommended over metal shell piles due to the presence of sandstone.

The tables below summarize the nominal required bearing (R_N), factored resistance available (R_F), estimated pile length and estimated pile tip elevation. R_N indicates the resistance of the pile during driving, which assists the Contractor from causing damage to the pile. R_F represents the net long term axial geotechnical resistance available to support the factored structure loads. The estimated pile lengths include a 1 foot embedment into the pier cap. Analysis has been performed using the IDOT Static Method of Estimating Pile Length. See Appendix J.

The factored resistance available values shown in the tables are intended to provide the designer with a range of feasible options for the anticipated vertical loading. Piles shall be evaluated for lateral resistance in final design.

Table 4.9 – H-Pile Capacity at SN 100-0108 Pier 1 (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	224	65	344.0
HP 12x74	589	312	68	341.0
HP 14x73	578	310	66	343.0

Table 4.10 – H-Pile Capacity at SN 100-0108 Pier 2 (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	226	55	354.0
HP 12x74	589	320	56	353.0
HP 14x73	578	312	56	353.0

Table 4.11 – H-Pile Capacity at SN 100-0109 Pier 1 (2-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	221	60	349.0
HP 12x74	589	314	61	348.0
HP 14x73	578	306	61	348.0

Table 4.12 – H-Pile Capacity at SN 100-0109 Pier 2 (1-S) – Strength Limit State

Pile Size	Max. Nominal Required Bearing, R_N (kips)	Max. Factored Resistance Available, R_F (kips)	Estimated Pile Length (ft.)	Estimated Pile Tip Elevation (ft.)
HP 12x53	418	220	62	347.0
HP 12x74	589	313	63	346.0
HP 14x73	578	305	63	346.0

One test pile is recommended at each pier location. Pile shoes are recommended when driving into hard sandstone.

5.0 Construction Considerations

5.1 Construction Activities

All construction activities shall be performed in accordance with the current IDOT Standard Specifications for Road and Bridge Construction and any pertinent Special Provisions or Policies.

The bridge cone embankment necessary for widening the existing roadway shall satisfy the requirements of Section 205 of the Standard Specifications.

5.2 Temporary Shoring

Temporary shoring will be required at the abutments during staged construction. From the preliminary TS&L, the distance from the proposed profile grade to the bottom of proposed abutment is approximately 8 feet, which represents the maximum soil retention anticipated. Investigating the subsurface conditions below the excavation line, the use of IDOT temporary sheet piling design charts appears feasible at the abutments for SN 100-0109. The use of a temporary soil retention system is advised at SN 100-0108 due to drivability concerns with the encountered crushed aggregate and rockfill. In addition, Type 2 Cofferdams will be required at both piers during staged construction due to more than 6 feet of water anticipated above the bottom of the pier. Seal coat is recommended at each cofferdam.

5.3 Foundation Construction

Conventional pile driving equipment and methodologies shall be assumed.

5.4 Excavation

Excavation shall be performed in accordance with IDOT Standard Specifications Section 202. Substructure construction shall occur after removal of the existing structure is complete.

A Joint Utility Locating Information for Excavators (J.U.L.I.E.) locate shall be performed prior to commencing construction activities to determine underground utilities within the project limits. On



SN 100-0067, fiber optics utility runs through the existing abutment backwalls and spans the entire length of the bridge on hangers. In addition, IDOT shall be contacted to locate private utilities.

At foundation and structural fill locations, the exposed subgrade shall be proofrolled to aid in locating any unstable and unsuitable materials. Unstable and unsuitable materials shall be removed and replaced with compacted structural fill.

6.0 Limitations


The analysis and discussion provided herein are for the exclusive use of IDOT District 9. They are based upon the subsurface data obtained at boring locations within the bridge area and are specific to the project described, our understanding of the project as described herein, and geotechnical engineering practice consistent with the standard of care.



Appendix A

Location Map





Location Map

IL 13 over Crab Orchard Lake
 Williamson County, Illinois
 Existing Structure No. 100-0020 (EB)/100-0067 (WB)
 Proposed Structure No. 100-0108 (EB)/100-0109 (WB)

Appendix B

Type, Size, and Location Plan (TS&L)




Bench Mark: Sq. cut in N.W. corner W. wall of S.N. 100-0020.



Existing Structure: S.N. 100-0020 was originally constructed in 1964 under F.A. Rte. 14, Section 5-3B-4. The structure is a three span (35'-9", 46'-11", 35'-9") continuous wide flange bridge with seven beam lines on pile bent abutments. The structure is 123'-0" from bk. to bk. abutments on a zero degree skew. The clear width is 40'-0" between face to face of parapets and the overall out to out width of the bridge is 42'-0". The superstructure consists of seven beam lines of 27WF94 on 6'-4" centers. The original reinforced concrete deck thickness was 7", but was later scarified 1/2" (1999) and a 2 1/4" Microsilica concrete overlay was installed for a total thickness of +/- 8 3/4". The bridge deck is on a normal crown. The abutments are pile bent abutments on H-piles driven to refusal. The wingwalls consist of 12" walls bearing on a single H-pile. The piers are pile bents on seven individually encased piles driven to refusal.

Traffic to be maintained utilizing stage construction.

No salvage.



*Drive piles at abutments in precored holes that extend 10' below the bottom of abutment caps and fill holes with Bentonite after pile driving.



HIGHWAY CLASSIFICATION

F.A.P. Rte. 331 - IL Rte. 13 E.B.
Functional Class: Other Principal Arterial
ADT: 16,000 (2011); 23,560 (2037)
ADTT: 600 (2011); 760 (2037)
DHV: 2,355
Design Speed: 65 m.p.h.
Posted Speed: 55 m.p.h.
One-Way Traffic
Directional Dist.: 100

LOADING HL-93

Allow 50#/sq. ft. for future wearing surface.

DESIGN SPECIFICATIONS

2020 AASHTO LRFD Bridge Design Specifications, 9th Edition.


DESIGN STRESSES

FIELD UNITS

f'c = 3,500 psi (Substructure)
f'c = 4,000 psi (Superstructure)
fy = 60,000 psi (Reinforcement)
fy = 50,000 psi (M270 Grade 50)
All new structural steel to be galvanized.


SEISMIC DATA

Seismic Performance Zone (SPZ) = 3
Design Spectral Acceleration at 1.0 sec. (SD1) = 0.359g
Design Spectral Acceleration at 0.2 sec. (SDS) = 0.864g
Soil Site Class = D



PROFILE GRADE

Along Centerline of Eastbound Lanes



LOCATION SKETCH

GENERAL PLAN AND ELEVATION

IL 13 E.B. OVER CRAB ORCHARD LAKE

F.A.P. RT. 331 - SEC. 1-4(B-3)

WILLIAMSON COUNTY

STATION 336+00.00

STRUCTURE NO. 100-0108



CIVIL DESIGN, INC.
WBE | DBE
EFFINGHAM, IL
LICENSE #184.003222

USER NAME =

DESIGNED - K. STREICHER

REVISED -

CHECKED - R TIWARI

REVISED -

PLOT SCALE =

DRAWN - K. STREICHER

REVISED -

PLOT DATE =

CHECKED - R TIWARI

REVISED -

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

SHEET 1 OF 2 SHEETS

F.A.P. RTE. 331

SECTION


COUNTY WILLIAMSON

TOTAL SHEETS


SHEET NO.

CONTRACT NO. 78373

MODEL: Default
FILE NAME: P:\5XXXXX\50X-51XX\5000 - IDOT PTB 200-038 D9 IL 13 Crab Orchard Bridges\24-Structures\CAD\MS\TSL\100-0108 - R1.dgn
2/4/2024 12:33:27 PM



CROSS SECTION
(Looking East)
* Prior to grinding




PIER SKETCH

WATERWAY INFORMATION

Drainage Area = 3.2 Sq. mi. Low Grade Elev. 414.6 @ Sta. 333+50									
Flood	Freq. Yr.	Q C.F.S.	Opening Ft ²		Nat. H.W.E.	Head - Ft.		Headwater El.	
			Exist.	Prop.		Exist.	Prop.	Exist.	Prop.
Ten-Year	10	731	968	1,075	407.5	0.0	0.0	407.5	407.5
Design	50	1,164	1,065	1,182	408.5	0.0	0.0	408.5	408.5
Base	100	1,356	1,106	1,227	408.9	0.0	0.0	408.9	408.9
Scour Check	200	1,541	1,147	1,271	409.3	0.0	0.0	409.3	409.3
Max. Calc.	500	1,853	1,221	1,351	410.0	0.0	0.0	410.0	410.0

DESIGN SCOUR ELEVATION TABLE

Event / Limit State	Design Scour Elevations (ft.)				
	W. Abut.	Pier 1	Pier 2	E. Abut.	Item 113
Q100	408.1	386.4	386.4	408.1	5
Q200	408.1	386.3	386.3	408.1	
Design	408.1	386.4	386.4	408.1	
Check	408.1	386.3	386.3	408.1	



SECTION THRU INTEGRAL ABUTMENT
(Horiz. dim. @ Rt. L's)

DETAILS

IL 13 W.B. OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SEC. 1-4(B-4)
WILLIAMSON COUNTY
STATION 336+00.00
STRUCTURE NO. 100-0109

MODEL: Default
FILE NAME: P:\5XXXXX\50XX-51XX\5000 - IDOT PTB 200-038 D9 IL 13 Crab Orchard Bridges\24-Structures\CAD\STSL\100-0109 - R1.dgn
1/8/2024 4:07:49 PM

Appendix C



Subsurface Data Profile Plot



Boring 2-S
STA 335+27
OFFSET 15 FT RT CL EBL
EL 414.9 FT
8/5/2014

PR ϕ PROFILE

Boring 1-S
STA 336+71
OFFSET 15 FT RT CL EBL
EL 414.9 FT
8/6/2014



LEGEND

EL = Elevation (FT)
D = Depth Below Existing Ground Surface (FT)
N = SPT N-VALUE (AASHTO T206)
Qu = Unconfined Compressive Strength in tons per sq. ft. (tsf)
Failure Mode (B=bulge, S=shear, P=penetrometer)
W% = Moisture Content Percentage

▽ = Groundwater Level First Encountered
Soil profile is for illustrative purposes only. Actual conditions will vary.

SUBSURFACE DATA PROFILE
ILL 13 EB OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SECTION 1-4(B-1)
WILLIAMSON COUNTY
STATION 309+50.00
SN 100-0108

Boring 2-S
STA 335+21
OFFSET 13 FT LT CL WBL
EL 415.2 FT
6/16/2014

PR CL PROFILE

Boring 1-S
STA 336+82
OFFSET 13 FT LT CL EBL
EL 415.3 FT
6/16/2014

	D	N	Qu	W%
Asphalt & crushed aggregate	413.7			
Very stiff, moist, brown and grey, Clay to Silty Clay A7-6	5	3	2.3 B	19
	5	5	2.1 B	20
Stiff, moist, brown and grey, Clay A7-6	10	4	1.4 B	22
	4	4	1.9 B	21
	15	4	1.6 B	22
	4	4	1.5 B	21
	20	4	1.9 B	23
	4	4	1.5 B	22
Stiff, moist to very moist, grey, Silt Loam to Silty Clay Loam A-4	25	4	1.1 S	23
Medium, moist to very moist, grey, Silt Loam to Silty Clay Loam A-4	388.2	3	0.8 B	23
Medium to soft, very moist, grey, Silty Clay Loam A-6	385.7	1	0.5 B	25
Medium to stiff, moist to very moist grey mottled brown, Silty Clay Loam A-6	383.2	6	1.0 S	23
	380.7	35	1	0.3 B
Soft, very moist, brown and grey, Clay to Silty Clay A7-6	378.2	5	1.0 B	26
Medium to stiff, moist to very moist brown and grey, Silty Clay to Silty Clay Loam A-6	375.7	40	1	0.3 B
	3	3	0.8 B	27
Soft, very moist, brown and grey, Clay to Silty Clay A7-6	370.7	45	-	-
Medium, very moist, grey mottled brown, Silty Clay A-6		4	1.5 B	27
Stiff, moist, grey mottled brown, Clay A7-6	365.7	50	-	-
Medium to stiff, moist to very moist grey, Clay A7-6 with organics and some Sand		3	1.0 B	29
	55	-	-	-
	1	1	0.8 B	35
Medium, very moist, gret, Clay A7-6 with broken Sandstone and Coal	355.7	60	-	-
	352.2	4	0.6 B	25
Very dense, dry, grey, Sandstone	352.1	65	100/1"	-
End of Boring				
	70	-	-	-
	75	-	-	-
	80	-	-	-
	85	-	-	-
	90	-	-	-

EL	D	N	Qu	W%
Asphalt and crushed aggregate	413.8			
Very stiff, moist brown Silty Clay A-6	410.8	5	7	2.3 B
Very stiff, moist, brown and grey, Clay to silty Clay A7-6	408.3	6	2.1 B	19
Medium, moist to very moist, brow Clay to Silty Clay A7-6	405.8	10	1	0.6 B
Stiff, moist, brown and grey, Clay to Silty Clay A7-6		6	1.9 B	22
	15	6	1.6 B	20
	5	5	1.9 B	21
	20	5	1.4 B	22
Stiff, moist to very moist, grey and brown, Clay A7-6	395.8	5	1.2 B	20
	390.3	25	4	1.5 B
Stiff, moist to very moist, grey, Silt Loam to Silty Clay Loam A-4	388.3	8	1.2 S	21
Medium to soft, very moist, grey and brown, Silty Clay Loam A-6	385.8	2	0.5 B	26
Stiff, moist, grey mottled brown, Silty Clay Loam A-6	383.3	6	1.2 B	23
Soft, very moist to wet, grey and brown, Clay A7-6	378.3	35	1	0.3 B
Stiff, moist to very moist, grey and brown, Clay A7-6		1	0.3 B	29
	40	4	1.6 B	27
	4	4	1.9 B	28
	45	3	1.6 S	49
Medium to soft, very moist, grey, Clay A7-6	365.3	50	1	0.5 B
	55	1	0.6 B	31
	60	1	0.5 B	24
	65	4	1.6 b	20
Stiff, moist, grey, Clay to Sandy Clay A7-6	350.8	70	100/1"	-
Sandstone	348.8			
Very Dense, dry, grey, Sandstone	348.3			
Very dense, dry, grey, Sandstone with some clay layers	343.8			
	338.7			
End of Boring				
	75			
	80			
	85			
	90			

LEGEND

EL = Elevation (FT)
D = Depth Below Existing Ground Surface (FT)
N = SPT N-VALUE (AASHTO T206)
Qu = Unconfined Compressive Strength in tons per sq. ft. (tsf)
Failure Mode (B=bulge, S=shear, P=penetrometer)
W% = Moisture Content Percentage

▽ = Groundwater Level First Encountered

Soil profile is for illustrative purposes only. Actual conditions will vary.

SUBSURFACE DATA PROFILE
ILL 13 WB OVER CRAB ORCHARD LAKE
F.A.P. RT. 331 - SECTION 1-4(B-1)
WILLIAMSON COUNTY
STATION 309+50.00
SN 100-0109

FILE NAME =	USER NAME = \$USER\$	DESIGNED - TAW	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	SHEET 1 OF 1 SHEETS	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
\$FILELS		DRAWN - TAW	REVISED -			57		WILLIAMSON	1	1
	PLOT SCALE = \$SCALE\$	CHECKED - TJZ	REVISED -							
\$MODEL\$NAMES	PLOT DATE = \$DATE\$	DATE - 10/25/22	REVISED -					ILLINOIS	FED. AID PROJECT	

Appendix D

Soil Boring and Rock Core Logs



Page 1 of 2

Date 8/6/14

COUNTY Williamson **DRILLING METHOD** Hollow Stem Auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lbs

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS. from 137 (Rev. 8-99)



ROUTE IL 13 EB (FAP 331) **DESCRIPTION** IL 13 EB over Crab Orchard Lake **LOGGED BY** L. Estel

SECTION 5-3B-4 **LOCATION** 1.6 mi E. of Jackson Co. (near E. Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM

COUNTY Williamson **DRILLING METHOD** Hollow Stem Auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lbs

STRUCT. NO.	100-0020
Station	336+00

BORING NO.	<u>1-S</u>
Station	<u>336+71</u>
Offset	<u>15.0ft Rt of EB CL</u>
Ground Surface Elev.	<u>414.9</u>

DEPTH (ft)	BLOWS	UCS (tsf)	MOIST (%)
---------------	-------	--------------	--------------

Surface Water Elev.	405.2	ft
Stream Bed Elev.		ft
Groundwater Elev.:		
▽ First Encounter	403.8	ft
▽ Upon Completion		ft
▼ After Hrs.		ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Stiff Grey and mottled Brown,
Moist CLAY (continued)

	2	1.9	39
—	3	B	

--	--

Bottom of hole at 59.1 feet

Ground Surface Elevation
referenced to BM at NW corner
SN 100-0020; Elev. 416.70

Hammer Efficiency: 75%
To convert "N" values to "N60",
multiply by 1.25

Note: Augers kicked out of plumb preventing use of the core barrel. Sandstone too hard to auger without overtightening drill rods, therefore unable to confirm solid formation of sandstone.

Drilled by: R. Moberly

Stiff Grey and mottled Brown,
Moist CLAY with broken
SANDSTONE GRAVEL

-55	1		
	3	1.2	23
	5	B	

-75			

V. Dense Grey, Dry SANDSTONE

100/0.5"

--	--	--	--

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

Page 1 of 2Date 8/5/14

COUNTY Williamson **DRILLING METHOD** Hollow Stem Auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lbs

D E P T H	B L O W S	U C S Qu	M O I S T T
(ft)		(tsf)	(%)

[illegible]

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS. from 137 (Rev. 8-99)



SOIL BORING LOG

ROUTE IL 13 EB (FAP 331)	DESCRIPTION	IL 13 EB over Crab Orchard Lake	LOGGED BY	L. Estel
---------------------------------	--------------------	---------------------------------	------------------	----------

SECTION	5-3B-4	LOCATION	1.6 mi E. of Jackson Co. (near W. Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM
----------------	--------	-----------------	--

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lbs
---------------	------------	------------------------	---	--------------------	------------------

STRUCT. NO. 100-0020
Station 336+00

BORING NO.	<u>2-S</u>
Station	<u>335+27</u>
Offset	<u>15.0ft Rt of EB CL</u>
Ground Surface Elev.	<u>414.9</u>

DEPTH (ft)	BLOW S	UCS Qu (tsf)	MOIST (%)
---------------	-----------	--------------------	--------------

Surface Water Elev.	<u>405.2</u>	ft
Stream Bed Elev.	<u> </u>	ft
Groundwater Elev.:		
▽ First Encounter	<u>403.9</u>	ft
▽ Upon Completion	<u> </u>	ft
▼ After Hrs.	<u> </u>	ft

D E P T H (ft)	B L O W S	U C S Qu (tsf)	M O I S T (%)
-----------------------------------	-----------------------	--------------------------------	----------------------------------

Stiff Grey and mottled Brown,
Moist CLAY (continued)

	2	1.9	26
—	4	B	

CLAY (continued)

	WOH	0.5	25
—	WOH	B	

	365.40
Soft Grey, V. Moist CLAY	

-50	WOH		
-----	-----	--	--

Hard Grey, Dry CLAY SHALE	345.30
Borehole continued with rock coring.	

70	100/1"		
----	--------	--	--

M. Sfiif Grey, V. Moist CLAY

-55	WOH		
	WOH	0.7	33
	WOH	B	

Hammer Efficiency: 75%
To convert "N" values to "N60",
multiply by 1.25

-75			

Drilled by: R. Moberly

Ground Surface Elevation
referenced to BM at NW corner
SN 100-0020; Elev. 416.70

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



ROCK CORE LOG

ROUTE IL 13 EB (FAP 331) DESCRIPTION IL 13 EB over Crab Orchard Lake LOGGED BY L. Estel

SECTION 5-3B-4 LOCATION 1.6 mi E. of Jackson Co. (near W. Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM

COUNTY Williamson CORING METHOD Conventional rotary with water

STRUCT. NO. 100-0020 CORING BARREL TYPE & SIZE NV3 5FT NWJ
Station 336+00

BORING NO. 2-S
Station 335+27
Offset 15.0ft Rt of EB CL
Ground Surface Elev. 414.9 ft

Core Diameter 1.78 in
Top of Rock Elev. 347.90 ft
Begin Core Elev. 345.30 ft

DEPTH (ft)	CORE (#)	RECOVER (%)	R.Q.D. (%)	CORE TIME (min/ft)	STRENGTH (tsf)
345.30 -70	1	89	17		
340.30 -75	2	100	72		
335.30 -80					
-85					

V. Dense Grey, Dry SANDSTONE with CLAY seams

V. Dense Grey, Dry SANDSTONE

Bottom of hole @ 79.6 ft

Ground Surface Elevation referenced to BM at NW corner SN 100-0020; Elev. 416.70

Drilled by: R. Moberly

Color pictures of the cores Yes, attached

Cores will be stored for examination until 5 Years after Construction

The "Strength" column represents the uniaxial compressive strength of the core sample (ASTM D-2938)

RQD is the ratio of the total length of sound core specimens >4" to total length of core run

BBS, form 138 (Rev. 8-99)

Illinois Department of Transportation
District Nine Materials
Unconfined Compressive Strength

FAP 331 (IL 13)
Structure 100-0020 (Boring 2-S)
Williamson County



Boring #	Specimen#	Depth	Unconfined Compression
2-S	1	76'5"	5,306 psi
2-S	2	77'3"	3,739 psi
2-S	3	77'9"	4,041 psi
2-S	4	78'10"	4,391 psi

1963 Borings for SN 100-0020

STATE OF ILLINOIS
DEPARTMENT OF PUBLIC WORKS & BUILDINGS
DIVISION OF HIGHWAYS

ROUTE NO	SECTION	COUNTY	TOTAL SHEETS	SHEET NO
F A 14	53B-4	WILLIAMSON	18	13
FED ROAD DIST NO 1		LEND 6	FED AID PROJECT	

SHEET NO. 8
8 SHEETS

COUNTY WILLAMETTE		Elevation	N	Ch / L.T.	W (%)	Surface Water El.	ADS. Q.	Elevation	N	Ch / L.T.	W (%)
Boring No. 1						Groundwater El. at Completion	—				
Station 335+38						After — Hours	—				
Offset: 7 ft. E.											
Ground Surface	391.2	0				See previous column			9	1.3B	23
Stiff moist gray silt loam A-4(9)							366.2	-23		1.0B	35
	387.7	3	2.0P	23		Medium moist gray clay A7-6(13-10)	364.7				
Stiff moist gray mottled brown to brown silty clay loam A-4(8) to A-6(9)						Medium moist gray clay A-6(11-12)				6	0.4B
	-5										
		12	3.0P	23			361.7	-30		6	0.5B
						Stiff wet gray clay A7-6(14-15)					
		9	1.0B	34							
	382.2										
Medium moist brown mottled gray and black silty clay A-6(10-11)		-10					358.2	-8	1.0B	35	
		4	0.5B	26		Medium wet gray clay loam A-4(6)					
		4	0.5B	27		Soft very moist gray clay A7-6(13-14)	356.2	-33		6	0.4B
	377.2					Soft very moist gray silty clay A-6(9-10)	354.7	-2			
Stiff moist gray mottled brown and black clay A7-6(15)-15											
		7	2.0B	27						7	0.6B
							352.2				
Stiff to stiff moist to very moist gray to gray mottled brown clay A-6(12)						Hard moist gray mottled brown clay loam A-4(8)		-40		32	4.0P
		8	0.4B	34							
	374.7										
		-20				Soft to medium dry gray clay shale.	348.7	-56			
			1.4B	25							
							346.0	-45			

COUNTY. Williamson		Elevation	N	Co / P.M.	W
Boring No. 1					
Station. 335+38					
Offset. 7 fts. N.E.					
See previous sheet		+0	32	4.0P.2	
Soft to medium dry gray clay shale		348.7	56		
					Corro RIS Recovery
		346.0 +.1			
Medium gray medium grained sandstone with thin shale seams		344.1			
Bottom of hole = 45.7 feet					
Washing procedure was used in drilling entire hole.		-50			
Location: N.W. Cor. NE1, NE2, Sec 17 T9S, R1E, 3rd P.M.					

[illegible]

COUNTY Williamson		Elevation	X	Qr./ft.	%	Surface Water El. Groundwater El. at Completion After — Hours	605.0 	Elevation	X	Qr./ft.	%
Boring No. A											
Station 37A+2											
Offset 7 ft., Rt.											
Ground Surface	390.9	0				see previous column		9	1.8 B	A	
Medium vet gr. Silt Loam A-4(8)								-25	10	1.1 B	A
	386.9		2	1.0 P	31						
Silty to medium moist gr. mot. br. Silty Clay Loam, A-4(8)	-5		9	1.1 B	21		362.9	7	0.8 R		
						Medium moist gr. clay, A-6(12-13)		-30	A	.51 B	R
	381.9		8	0.9 B	24						
Medium moist gr. mot. br. Silty clay A-6(9-10)	-10		7	0.4 B	28			5	0.6 R		
Very stiff moist gr. mot. br. and bk. clay, A-7-6(17*)								-35	6	0.6 R	
			13	1.8 B	34						
	-15		9	1.8 B	38						
							371.2	5	0.7 R		
	372.9		8	1.5 S	43	Soft gr. Sandy Shale		-40	100	Blown sand	
Stiff moist gr. mot. br. and bk. to dark gr. clay, A-7-6(15*)	-20		8	1.1 S	38		350.0	8		Dredged mud	
						Medium gr. fine grained sandstone with thin laminations of black clay shale		-45			

COUNTY: Williamson			Surface Water El. <u>405.0</u>			Elevation		
Boring No. <u>3</u>	Station <u>336+23</u>	Offset <u>2 ft. L.</u>	Elevation	N	Ch./A.L.	Groundwater El. at Completion	N	Ch./A.L.
			After <u>2</u> Hours					
Ground Surface	393.0	0				see previous column	370.2	8 1.4B 3
Soft wet brown to gray silty clay A-6(9-10)								-25
						Stiff moist brown to gray to dark gray clay A7-6(15)		9 1.2B 4
								8 1.0B 3
367.7	-5	3	No Recovery					-30
Stiff moist gray mottled brown silty clay loam A-6(8-9)								7 No Recovery
385.2		5'	2.0P	-				
Medium to stiff moist gray mottled brown silty clay A-6(9-10)								-35
	-10	11	0.8B	22			360.2	8 1.0B 3
380.2		7	1.1B	23		Medium gray mottled brown clay A7-6(12-13)		5 0.7B 3
								-35
	-15	9	2.0B	22			355.2	11 0.9B 3
Very stiff gray mottled brown and black clay A7-6(17+)						Medium moist gray clay A7-6(15)		
								-40
		12	2.0B	22			352.7	7 0.8B 2
						Medium moist gray silty clay A-6(12)		
	-20	12	1.0B	41				15 1.0B 2
							348.7	-45
						see next sheet		

COUNTY Williamson		Elevation	N	Co./A.I.	
Boring No. 3					
Station. 336-21					
Offset. 9 Fts. L&L					
		10			
<u>See previous sheet</u>	352.7		7	0.8B	2"
Medium moist gray silty clay A-6(12)					
			15	1.0B	2"
	348.7				
<u>Soft gray clay shale</u>	43	100			
	347.7				
<u>Medium gray fine grained sandstone</u>	347.5	100		Blown 2"	
<u>Bottom of hole = 45.5 feet</u>					
		-80			
<u>Washing procedure was used in drilling entire hole.</u>					

COUNTY	Williamson	Elevation	N	Qr./A.L.
Boring No.	4			
Station	225-62			
Offset	7 Ft., Rt.			
		40		
see previous sheet	350.0			
Medium gr. fine grained sandstone with thin laminations of black sandy shale				↑ Dredged 80% Recover
	365.5	65		
Bottom of hole = 454.5 feet				
Washing procedure used in drilling the entire hole.				

N-Standard Penetration Test-
Blows per foot to drive 2"
O.D. Split Spoon Sampler 12" with
140# hammer falling 30".

Qu - Unconfined Compressive Strength - t/sf
w - Water Content - percent of oven dry weight - %

Type failure:
B—Bulge Failure
S—Shear Failure
E—Estimated Value
D—Discarded Value

DESIGNED	Emory J. Strickland
CHECKED	R. C. Williams
DRAWN	E. S.
CHECKED	T. O. D.


FEB 18 1964

EXAMINED W.C. Baumann
ENGINEER OF BRIDGE AND TRAFFIC STRUCTURES

PASSED E. J. Shurtz
SUPERVISOR OF DESIGN

APPROVED E. J. Shurtz

BORINGS
F.A.R.T. 14 SEC. 5-3B-4
WILLIAMSON CO.
STA. 336+00





SOIL BORING LOG

ROUTE# FAP 331 (IL 13 WB) **DESCRIPTION** IL 13 WB Over Crab Orchard Lake **LOGGED BY** L. Estel

SECTION (5B-1)DR-1 **LOCATION** 1.6 mi. E. of Jackson Co. (near E. Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM

COUNTY Williamson **DRILLING METHOD** Hollow Stem Auger (8" O.D., 3.25" I.D.) **HAMMER TYPE** Auto SPT 140 lbs

STRUCT. NO.	100-0067
Station	336+00

BORING NO.	<u>1-S</u>
Station	<u>336+82</u>
Offset	<u>13.0ft Lt of WB CL</u>
Ground Surface Elev.	<u>415.3</u>

DEPTH (ft)	BLOWS	UCS (tsf)	MOIST (%)
---------------	-------	--------------	--------------

Surface Water Elev.	405.2	ft
Stream Bed Elev.		ft
Groundwater Elev.:		
▽ First Encounter	383.3	ft
▽ Upon Completion		ft
▼ After Hrs.		ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

HMA Pavement over crushed Aggregate				Stiff Brown and Grey, Moist to V. Moist CLAY to SILTY CLAY (continued)		2 3	1.2 B	20
413.80								
V. Stiff Brown, Moist SILTY CLAY						1		
	1					2	1.5	23
	3	2.3	19			2	B	
	4	B						
410.80								
V. Stiff Brown and Grey, Moist CLAY to SILTY CLAY					390.30	1		
	-5	1				4	1.2	21
		2	2.1	19		4	S	
		4	B					
408.30								
M. Stiff Brown, Moist to V. Moist CLAY to SILTY CLAY		WOH			388.30	WOH		
		1	0.6	23		WOH	0.5	26
		WOH	B			2	B	
405.80								
Stiff Brown and Grey, Moist CLAY to SILTY CLAY					385.80	1		
	-10	1				3	1.2	23
		2	1.9	22		3	B	
		4	B					
		1			383.30	WOH		
		3	1.6	20		1	0.3	28
		3	B			WOH	B	
	-15	1				WOH		
		2	1.9	21		1	0.3	29
		3	B			WOH	B	
		1			378.30	1		
		2	1.4	22		2	1.6	27
		3	B			2	B	
395.80								
	-20	1				1		

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation

Division of Highways District 9

SOIL BORING LOG

Page 2 of 2

Date 6/16/14

ROUTE	FAP 331 (IL 13 WB)	DESCRIPTION	IL 13 WB Over Crab Orchard Lake	LOGGED BY	L. Estel
--------------	---------------------------	--------------------	---------------------------------	------------------	----------

SECTION (5B-1)DR-1 **LOCATION** 1.6 mi. E. of Jackson Co. (near E. Abut.), **SEC. 17, TWP. 9S, RNG. 1E, PM**

COUNTY	Williamson	DRILLING METHOD	Hollow Stem Auger (8" O.D., 3.25" I.D.)	HAMMER TYPE	Auto SPT 140 lbs
---------------	------------	------------------------	---	--------------------	------------------

STRUCT. NO.	100-0067
Station	336+00

BORING NO.	<u>1-S</u>
Station	<u>336+82</u>
Offset	<u>13.0ft Lt of WB CL</u>
Ground Surface Elev.	<u>415.3</u>

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Surface Water Elev.	<u>405.2</u>	ft
Stream Bed Elev.	<u> </u>	ft
Groundwater Elev.:		
▼ First Encounter	<u>383.3</u>	ft
▼ Upon Completion	<u> </u>	ft
▼ After Hrs.	<u> </u>	ft

D E P T H	B L O W S	U C S Qu	M O I S T
(ft)		(tsf)	(%)

Stiff Grey and Brown, Moist to V.
Moist CLAY (continued)

	2	1.9	28
	2	B	

CLAY (continued)

1	0.5	24
WOH	B	

-45	WOH		
	1	1.6	49
	2	S	

Stiff Grey, Moist CLAY to SANDY CLAY

-65	1		
	2	1.6	20
	2	B	

-50	1		
-----	---	--	--

Soft to M. Stiff Grey, V. Moist
CLAY

WOH	0.5	32
1	B	

Ground surface elevation
referenced to benchmark at NW
corner of SN 100-0020; Elev.
416.70

-70			
-----	--	--	--

-55	WOH		
	1	0.6	31
	WOH	B	

Hammer efficiency: 75%
To convert "N" values to "N60",
multiply by 1.25

Drilled by: R. Moberly

-75			

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated) Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation

Division of Highways
District 9

ROCK CORE LOG

Page 1 of 1

Date 6/16/14

ROUTE FAP 331 (IL 13 WB) DESCRIPTION IL 13 WB Over Crab Orchard Lake LOGGED BY L. Estel

SECTION (5B-1)DR-1 LOCATION 1.6 mi. E. of Jackson Co. (near E. Abut.), SEC. 17, TWP. 9S, RNG. 1E, PM

COUNTY Williamson CORING METHOD Conventional rotary with water

STRUCT. NO. 100-0067 CORING BARREL TYPE & SIZE NV3 5FT NWJ

Station 336+00

BORING NO. 1-S

Station 336+82

Offset 13.0ft Lt of WB CL

Ground Surface Elev. 415.3 ft

Core Diameter 1.78 in

Top of Rock Elev. 348.80 ft

Begin Core Elev. 348.70 ft

DEPTH (ft)	CORE (#)	RECOVERY (%)	R.Q.D. (%)	CORE TIME (min/ft)	STRENGTH (tsf)
	1	88	63		299.1
					355.7
					-70
	2	100	60		301.7
					291.2
					-75
					240.1
					338.70
					-80
					-85

V. Dense Grey, Dry SANDSTONE

V. Dense Grey, Dry SANDSTONE with some CLAY layers

Bottom of hole @ 76.6 ft

Ground Surface Elevation referenced to BM at NW corner of SN 100-0020; Elev.
416.7

Drilled by: R. Moberly

Color pictures of the cores Yes, attached

Cores will be stored for examination until 5 Years after Construction

The "Strength" column represents the uniaxial compressive strength of the core sample (ASTM D-2938)

RQD is the ratio of the total length of sound core specimens >4" to total length of core run

BBS, form 138 (Rev. 8-99)

ROCK CORE 100-0067 IL 13 WB OVER CRAB ORCHARD LAKE.GPJ D6TEMPLT.GDT 5/11/21

Illinois Department of Transportation
District Nine Materials
Unconfined Compressive Strength

FAP 331 (IL 13)
Structure 100-0067 (Boring 1-S)
Williamson County



<u>Boring #</u>	<u>Specimen#</u>	<u>Depth</u>	<u>Unconfined Compression</u>
1-S	1	67' 4"	4,154 psi
1-S	2	69' 0"	4,940 psi
1-S	3	72' 2"	4,190 psi
1-S	4	73' 6"	4,045 psi
1-S	5	75' 10"	3,335 psi



SOIL BORING LOG

ROUTE AP 331 (IL 13 WB) DESCRIPTION IL 13 WB Over Crab Orchard Lake LOGGED BY L. Estel

SECTION (5B-1)DR-1 LOCATION 1.6 mi. E. of Jackson Co. (near W. Abut.), SEC. 17, TWP. 9S, RNG. 1E,

COUNTY Williamson DRILLING METHOD Hollow Stem Auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140 PMs

STRUCT. NO. 100-0067
Station 336+00

BORING NO. 2-S
Station 335+21
Offset 13.0ft Lt of WB CL
Ground Surface Elev. 415.2 ft

DEPTH H (ft)	B L O W S (tsf)	U C S Qu (tsf)	M O I S T (%)	Surface Water Elev. <u>405.2</u> ft Stream Bed Elev. _____ ft Groundwater Elev.: ▽ First Encounter <u>385.7</u> ft ▽ Upon Completion _____ ft ▽ After _____ Hrs. _____ ft	DEPTH H (ft)	B L O W S (tsf)	U C S Qu (tsf)	M O I S T (%)
				Stiff Brown and Grey, Moist CLAY (continued)		2	1.5	22
						2	B	
413.70								
	1			Stiff Grey, Moist to V. Moist SILTY LOAM to SILTY CLAY LOAM		1		
	1	2.3	19			2	1.1	23
	2	B				2	S	
				90% Fines<#200, LL 32, PI 10 (Estimated based on visual ID and historical database)				
	1					1		
	2	2.1	20	M. Stiff Grey, Moist to V. Moist SILTY LOAM to SILTY CLAY LOAM		1	0.8	23
	3	B				2	B	
408.20								
	1			90% Fines<#200, LL 32, PI 10 (Estimated based on visual ID and historical database)		WOH		
	2	1.4	22			1	0.5	25
	2	B		Soft to M. Stiff Grey, V. Moist SILTY CLAY LOAM		WOH	B	
	1			91% Fines<#200, LL 37, PI 14 ▽ (Estimated based on visual ID and historical database)		1		
-10	2	1.9	21			3	1.0	23
	2	B		M. Stiff Grey and mottled Brown, Moist to V. Moist SILTY CLAY LOAM		3	S	
	1			91% Fines<#200, LL 37, PI 14 (Estimated based on visual ID and historical database)		WOH		
	2	1.6	22			1	0.3	30
	2	B				WOH	B	
				Soft Brown and Grey, V. Moist CLAY to SILTY CLAY				
	1							
-15	2	1.5	21	95% Fines<#200, LL 44, PI 24 (Estimated based on visual ID and historical database)		1		
	2	B				2	1.0	26
						3	B	
	1			M. Stiff Brown and Grey, Moist to V. Moist SILTY CLAY to SILTY CLAY LOAM		WOH		
	2	1.9	23			1	0.3	29
	2	B		94% Fines<#200, LL 39, PI 18 (Estimated based on visual ID and historical database)		WOH	B	
				Soft Grey and mottled Brown, V. Moist CLAY				
-20	1					WOH		

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated)
Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



Illinois Department of Transportation
Division of Highways
District 9

SOIL BORING LOG

Page 2 of 2

Date 6/16/14

ROUTE AP 331 (IL 13 WB) DESCRIPTION IL 13 WB Over Crab Orchard Lake LOGGED BY L. Estel

SECTION (5B-1)DR-1 LOCATION 1.6 mi. E. of Jackson Co. (near W. Abut.), SEC. 17, TWP. 9S, RNG. 1E,

COUNTY Williamson DRILLING METHOD Hollow Stem Auger (8" O.D., 3.25" I.D.) HAMMER TYPE Auto SPT 140PMs

STRUCT. NO. 100-0067
Station 336+00

BORING NO. 2-S
Station 335+21
Offset 13.0ft Lt of WB CL
Ground Surface Elev. 415.2 ft

DEPTH (ft)	BLOW S	UCS Qu (tsf)	MOIST T (%)
---------------	-----------	--------------------	-------------------

Surface Water Elev. 405.2 ft
Stream Bed Elev. ft

Groundwater Elev.:
▽ First Encounter 385.7 ft
▽ Upon Completion ft
▽ After Hrs. ft

DEPTH (ft)	BLOW S	UCS Qu (tsf)	MOIST T (%)
---------------	-----------	--------------------	-------------------

91% Fines<#200, LL 50, PI 29
(Estimated based on visual ID and historical database)
M. Stiff Grey and mottled Brown,
V. Moist SILTY CLAY

1	0.8	27
2	B	

M. Stiff Grey, V. Moist CLAY with broken SANDSTONE and COAL
(continued)

2	0.6	25
2	B	

96% Fines<#200, LL 44, PI 23
(Estimated based on visual ID and historical database) (continued)

1		
2		

V. Dense Grey, Dry SANDSTONE

100/1"		
--------	--	--

Stiff Grey and mottled Brown,
Moist CLAY

1		
2	1.5	27
2	B	

Bottom of hole @ 63.1 ft

1		
2		

M. Stiff Grey, Moist to V. Moist
CLAY with ORGANICS and some
SAND

1		
1	1.0	29
2	B	

Ground Surface Elevation
referenced to BM at NW corner of
SN 100-0020; Elev. 416.7

1		
1		

Hammer Efficiency 75%
To convert "N" values to "N60",
multiply by 1.25

Drilled by: R. Moberly

1		
1		

WOH
1
WOH

1	0.8	35
WOH	B	

1		
1		

355.70
-60

1		
---	--	--

352.20

1		
---	--	--

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated)
Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

Appendix E

Settlement Analysis





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ===== East Abutment / Boring 1-S (0108)

TYPE OF SURCHARGE ===== 1 (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) == 27 FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT ===== 120 PCF

NEW EMBANKMENT FILL HEIGHT ===== 27 FT

PROPOSED WIDTH AT TOP ===== 90 FT

PROPOSED WIDTH AT BOTTOM ===== 198 FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT ===== 120 PCF

EXISTING EMBANKMENT HEIGHT ===== 27 FT


EXISTING WIDTH AT TOP ===== 42 FT

EXISTING WIDTH AT BASE ===== 150 FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
3.1	120	0.50	28	3.300	0.000	0.756	0.162	0.361	0.00
2.5	120	0.30	28	3.407	0.001	0.756	0.162	0.550	0.00
2.5	120	1.90	23	3.500	0.003	0.621	0.117	0.116	0.00
2.5	120	0.80	21	3.592	0.008	0.567	0.099	0.242	0.00
2.5	120	1.90	26	3.681	0.014	0.702	0.144	0.116	0.00
2.5	120	1.90	41	3.768	0.024	1.107	0.279	0.116	0.00
2.5	120	1.90	39	3.853	0.035	1.053	0.261	0.116	0.00
2.5	120	1.90	39	3.937	0.047	1.053	0.261	0.116	0.00
2.5	120	1.20	48	4.019	0.061	1.296	0.342	0.171	0.00
2.5	120	1.20	48	4.101	0.075	1.296	0.342	0.171	0.01
2.5	120	1.10	25	4.182	0.090	0.675	0.135	0.184	0.00

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.02 IN.

EMBANKMENT AND SOIL PROFILE





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ===== West Abutment / Boring 2-S (0108)

TYPE OF SURCHARGE ===== 1 (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) == 27 FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT ===== 120 PCF

NEW EMBANKMENT FILL HEIGHT ===== 27 FT

PROPOSED WIDTH AT TOP ===== 90 FT

PROPOSED WIDTH AT BOTTOM ===== 198 FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT ===== 120 PCF

EXISTING EMBANKMENT HEIGHT ===== 27 FT


EXISTING WIDTH AT TOP ===== 42 FT

EXISTING WIDTH AT BASE ===== 150 FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
3.6	120	0.60	26	3.309	0.000	0.702	0.144	0.309	0.00
2.0	120	0.40	28	3.416	0.001	0.756	0.162	0.436	0.00
1.5	120	1.10	26	3.482	0.003	0.702	0.144	0.184	0.00
3.5	120	0.30	30	3.574	0.007	0.810	0.180	0.550	0.00
2.5	120	1.00	26	3.681	0.014	0.702	0.144	0.200	0.00
2.5	120	0.40	27	3.768	0.024	0.729	0.153	0.436	0.00
2.5	120	1.90	26	3.853	0.035	0.702	0.144	0.116	0.00
2.5	120	1.90	26	3.937	0.047	0.702	0.144	0.116	0.00
2.5	120	1.30	28	4.019	0.061	0.756	0.162	0.160	0.00
2.5	120	1.30	28	4.101	0.075	0.756	0.162	0.160	0.00
2.5	120	0.40	31	4.182	0.090	0.837	0.189	0.436	0.01

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.03 IN.

EMBANKMENT AND SOIL PROFILE





COHESIVE SOIL SETTLEMENT ESTIMATE

LOCATION AND BORING USED ===== East Abutment / Boring 1-S (0109)

TYPE OF SURCHARGE ===== 1 (1=2:1 bridge cone, 2=continuous embank., 3=rectangular surch.)

DEPTH TO WATER TABLE (below top of existing embankment) == 27 FT

NEW EMBANKMENT:

NEW EMBANKMENT FILL UNIT WEIGHT ===== 120 PCF

NEW EMBANKMENT FILL HEIGHT ===== 27 FT

PROPOSED WIDTH AT TOP ===== 90 FT

PROPOSED WIDTH AT BOTTOM ===== 198 FT (which is a 2.0:1 slope)

ASSUMPTIONS:

Soil Deposit is Normally Consolidated

Cohesive Layers are Saturated

Soils have a Low Sensitivity

Liquid Limit (LL)=Moist. Content (MC%)

Initial Void Ratio (Eo)=2.7*(MC%)/100

Comp. Index (Cc)=0.009*(LL-10)

Neglecting Granular & Secondary Settlement

EXISTING EMBANKMENT (IF ANY):

EXISTING EMBANKMENT UNIT WEIGHT ===== 120 PCF

EXISTING EMBANKMENT HEIGHT ===== 27 FT


EXISTING WIDTH AT TOP ===== 42 FT

EXISTING WIDTH AT BASE ===== 150 FT (which is a 2.0:1 slope)

LAYER THICK (FT)	TOTAL UNIT WT. (PCF)	UNCONF. COMP. STRENGTH (Qu) (TSF)	MOIST. CONTENT (%)	EXISTING PRESSURE (KSF)	PRESSURE INCREASE (KSF)	INITIAL VOID RATIO	COMPRESSION INDEX (Cc)	Qu CORRECTION FACTOR	LAYER SETTLEMENT (IN.)
2.7	120	1.50	23	3.292	0.000	0.621	0.117	0.142	0.00
2.0	120	1.20	21	3.382	0.001	0.567	0.099	0.171	0.00
2.5	120	0.50	26	3.467	0.002	0.702	0.144	0.361	0.00
2.5	120	1.20	23	3.559	0.006	0.621	0.117	0.171	0.00
2.5	120	0.30	28	3.649	0.012	0.756	0.162	0.550	0.00
2.5	120	0.30	29	3.737	0.020	0.783	0.171	0.550	0.00
2.5	120	1.60	27	3.823	0.030	0.729	0.153	0.134	0.00
2.5	120	1.90	28	3.907	0.042	0.756	0.162	0.116	0.00
2.5	120	1.90	28	3.989	0.056	0.756	0.162	0.116	0.00
2.5	120	1.60	49	4.071	0.070	1.323	0.351	0.134	0.00
2.5	120	1.60	49	4.153	0.085	1.323	0.351	0.134	0.01

TOTAL SETTLEMENT UNDER CENTER OF BRIDGE CONE = 0.02 IN.

EMBANKMENT AND SOIL PROFILE



Appendix F


Slope Stability Analysis





Soil Parameters for Slope Stability Analysis

SN 100-0108 - East Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c'	θ	c'	θ
				(ksf)	(deg.)	(ksf)	(deg.)
1	Crushed Aggregate	407.4	125	0	40	0	40
2	Rock Fill	390.4	125	0	40	0	40
3	M. Silty Clay/Clay Loam	387.9	125	0.6	0	0.1	28
4	Soft Silty Clay/Clay Loam	386.4	120	0.4	0	0.1	26
5	Stiff Clay/Silty Clay	382.9	125	1.1	0	0.1	28
6	Soft Silty Clay	380.4	120	0.3	0	0.1	26
7	M. Stiff Silty Clay	377.9	125	1	0	0.1	28
8	Soft Silty Clay	375.4	120	0.4	0	0.1	26
9	Stiff Clay	365.4	125	1.3	0	0.1	28
10	Soft Clay	360.4	120	0.4	0	0.1	26
11	Medium Clay	355.4	125	0.7	0	0.1	28
12	Soft Clay	350.4	120	0.5	0	0.1	26
13	Stiff Clay/Clay Shale	347.9	130	1.5	0	0.1	28
14	Sandstone	-	150	0	45	0	45










Soil Parameters for Slope Stability Analysis

SN 100-0108 - West Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c'	θ	c'	θ
				(ksf)	(deg.)	(ksf)	(deg.)
1	Crushed Aggregate	406.9	125	0	40	0	40
2	Rock Fill	390.4	125	0	40	0	40
3	Soft Silty Clay/Clay Loam	385.9	125	0.3	0	0.1	28
4	Stiff Silty Clay/Clay	383.4	120	1.9	0	0.1	26
5	M. Stiff Moist Clay Loam	380.9	125	0.8	0	0.1	28
6	Stiff Moist Clay	378.4	125	1.9	0	0.1	28
7	Stiff Moist Clay	360.4	125	1.1	0	0.1	28
8	Stiff Moist Clay w/ Gravel	355.9	125	1.2	0	0.1	28
9	Sandstone	-	150	0	45	0	45










Soil Parameters for Slope Stability Analysis

SN 100-0109 - East Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c'	θ	c'	θ
				(ksf)	(deg.)	(ksf)	(deg.)
1	Crushed Aggregate	413.8	125	0	40	0	40
2	V. Stiff Silty Clay	410.8	125	2.3	0	0.1	28
3	V. Stiff Clay/Silty Clay	408.3	125	2.1	0	0.1	28
4	M. Clay/Silty Clay	405.8	125	0.6	0	0.1	28
5	Stiff Clay/Silty Clay	395.8	125	1.4	0	0.1	28
6	Stiff Clay/Silty Clay	390.3	125	1.2	0	0.1	28
7	Stiff Silty Loam	388.3	125	1.2	0	0.1	28
8	Soft Silty Clay Loam	385.8	120	0.5	0	0.1	26
9	Stiff Silty Clay Loam	383.3	125	1.2	0	0.1	28
10	Soft Clay	378.3	120	0.3	0	0.1	26
11	Stiff Clay	365.3	125	1.6	0	0.1	28
12	M./ Soft Clay	350.8	120	0.5	0	0.1	26
13	Stiff Sandy Clay	348.8	125	1.6	0	0.1	28
14	Sandstone	-	150	0	45	0	45









Soil Parameters for Slope Stability Analysis


SN 100-0109 - West Abutment

Layer #	Soil Description	Elev. at Bottom of Layer	γ (pcf)	Short Term		Long Term	
				c' (ksf)	θ (deg.)	c' (ksf)	θ (deg.)
1	Crushed Aggregate	413.7	125	0	40	0	40
2	V. Stiff Clay/Silty Clay	408.2	125	2.1	0	0.1	28
3	Stiff Clay	393.2	125	1.4	0	0.1	28
4	Stiff Silt Loam/Silty Clay	390.2	125	1.1	0	0.1	28
5	M. Silty Loam/Silty Clay	388.2	125	0.8	0	0.1	28
6	M./Soft Silty Clay Loam	385.7	125	0.5	0	0.1	28
7	M./Soft Silty Clay Loam	383.2	125	1	0	0.1	28
8	Soft Clay/Silty Clay	380.7	120	0.3	0	0.1	26
9	M. Silty Clay/Silty Loam	378.2	125	1	0	0.1	28
10	Soft Clay/Silty Clay	375.7	120	0.3	0	0.1	26
11	Medium Silty Clay	370.7	125	0.8	0	0.1	28
12	Stiff Clay	365.7	125	1.5	0	0.1	28
13	Medium/Stiff Clay	355.7	125	0.8	0	0.1	28
14	Medium Clay	352.7	125	0.6	0	0.1	28
15	Sandstone	-	150	0	45	0	45

SN 100-0109 West Abutment Short Term Strength







Appendix G

Seismic Site Class Determination





SEISMIC SITE CLASS DETERMINATION

PROJECT TITLE=====IL 13 over Crab Orchard Lake (SN 100-0108 and 100-0109)

Substructure 1

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0020-1-S
Top of Boring Elev. 414.9 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 11 (Blows/ft.) Soil Site Class E
N_{ch} (bar): 23 (Blows/ft.) Soil Site Class D <----Controls
s_u (bar): 2.04 (ksf) Soil Site Class C

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.9	1.00 0	B
	410.4	3.50 22	
	406.9	3.50 22	B
	402.9	4.00 5	
3.1	398.9	4.00 5	
7.1	394.9	4.00 5	
11.6	390.4	4.50 5	B
14.1	387.9	2.50 0 0.50	
16.1	385.9	2.00 0 0.30	B
18.6	383.4	2.50 5 1.90	B
21.1	380.9	2.50 5 0.80	B
23.6	378.4	2.50 6 1.90	B
28.6	373.4	5.00 6 1.90	
33.6	368.4	5.00 5 1.90	
38.6	363.4	5.00 3 1.20	
41.6	360.4	3.00 3 1.10	B
46.1	355.9	4.50 8 1.20	B
100.0	302.0	53.90 100 10.00	R

Substructure 2

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0020-2-S
Top of Boring Elev. 414.9 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 10 (Blows/ft.) Soil Site Class E
N_{ch} (bar): 21 (Blows/ft.) Soil Site Class D <----Controls
s_u (bar): 1.18 (ksf) Soil Site Class D

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.9	1.00 0	B
	410.4	3.50 22	
	407.4	3.00 22	B
	403.4	4.00 5	
2.6	399.4	4.00 5	
7.1	394.9	4.50 5	
11.6	390.4	4.50 5	B
14.1	387.9	2.50 1 0.60	B
15.6	386.4	1.50 2 0.40	B
19.1	382.9	3.50 8 1.10	B
21.6	380.4	2.50 0 0.30	B
24.1	377.9	2.50 2 1.00	B
26.6	375.4	2.50 0 0.40	B
31.6	370.4	5.00 6 1.90	
36.6	365.4	5.00 1 1.30	B
41.6	360.4	5.00 0 0.40	B
46.6	355.4	5.00 0 0.70	B
51.6	350.4	5.00 0 0.50	B
54.1	347.9	2.50 16 1.50	B
100.0	302.0	45.90 100 10.00	R

Substructure 3

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0067-1-S
Top of Boring Elev. 415.3 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 4 (Blows/ft.) Soil Site Class E
N_{ch} (bar): NA (Blows/ft.) NA
s_u (bar): 1.27 (ksf) Soil Site Class D <----Controls

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.8	1.50 0	B
	410.8	3.00 7 2.30	B
	408.3	2.50 6 2.10	B
	405.8	2.50 1 0.60	B
	403.3	2.50 6 1.90	
1.2	400.8	2.50 6 1.60	
3.7	398.3	2.50 5 1.90	
6.2	395.8	2.50 5 1.40	B
8.7	393.3	2.50 5 1.20	
11.7	390.3	3.00 4 1.50	B
13.7	388.3	2.00 8 1.20	B
16.2	385.8	2.50 2 0.50	B
18.7	383.3	2.50 6 1.20	B
21.2	380.8	2.50 1 0.30	
23.7	378.3	2.50 1 0.30	B
26.7	375.3	3.00 4 1.60	
31.7	370.3	5.00 4 1.90	
36.7	365.3	5.00 3 1.60	B
41.7	360.3	5.00 1 0.50	
46.7	355.3	5.00 1 0.60	
51.2	350.8	4.50 1 0.50	B
53.2	348.8	2.00 4 1.50	B
100.0	302.0	46.80 100 10.00	R

Substructure 4

Base of Substruct. Elev. (or ground surf for bents) 408 ft.
Pile or Shaft Dia. 12 inches
Boring Number 0067-2-S
Top of Boring Elev. 415.2 ft.
Approximate Fixity Elev. 402 ft.

Individual Site Class Definition:

N (bar): 5 (Blows/ft.) Soil Site Class E
N_{ch} (bar): NA (Blows/ft.) NA
s_u (bar): 1.32 (ksf) Soil Site Class D <----Controls

Seismic Soil Column	Bot. Of Sample	Sample	Layer Description
Depth	Elevation	Thick. N Qu Boundary	
(ft)		(ft.) (tsf)	
	413.7	1.50 0	B
	410.7	3.00 3 2.30	
	408.2	2.50 5 2.10	B
	405.7	2.50 4 1.40	
	403.2	2.50 4 1.90	
1.3	400.7	2.50 4 1.60	
3.8	398.2	2.50 4 1.50	
6.3	395.7	2.50 4 1.90	
8.8	393.2	2.50 4 1.50	B
11.8	390.2	3.00 4 1.10	B
13.8	388.2	2.00 3 0.80	B
16.3	385.7	2.50 1 0.50	B
18.8	383.2	2.50 6 1.00	B
21.3	380.7	2.50 1 0.30	B
23.8	378.2	2.50 5 1.00	B
26.3	375.7	2.50 1 0.30	B
31.3	370.7	5.00 3 0.80	B
36.3	365.7	5.00 4 1.50	B
41.3	360.7	5.00 3 1.00	
46.3	355.7	5.00 1 0.80	B
49.3	352.7	3.00 4 0.60	B
100.0	302.0	50.70 100 10.00	R

Global Site Class Definition: Substructures 1 through 4

N (bar): 8 (Blows/ft.) Soil Site Class E
N_{ch} (bar): 57 (Blows/ft.) Soil Site Class C
s_u (bar): 1.44 (ksf) Soil Site Class D <----Controls

Appendix H

Liquefaction Analysis





LIQUEFACTION ANALYSIS

REFERENCE BORING NUMBER ===== 0109 E. Abut.
ELEVATION OF BORING GROUND SURFACE ===== 415.30 FT.
DEPTH TO GROUNDWATER - DURING DRILLING ===== 10.00 FT. (Below Boring Ground Surface)
DEPTH TO GROUNDWATER - DURING EARTHQUAKE ===== 10.50 FT. (Below Finished Grade Cut or Fill Surface)
PEAK HORIZ. GROUND SURFACE ACCELERATION COEFFICIENT (As) ===== 0.422
EARTHQUAKE MOMENT MAGNITUDE ===== 7.6
FINISHED GRADE FILL OR CUT FROM BORING SURFACE ===== 0.50 FT. (Fill Height)
HAMMER EFFICIENCY===== 73 %
BOREHOLE DIAMETER===== 8 IN.
SAMPLING METHOD===== Sampler w/out Liners

EQ MAGNITUDE SCALING FACTOR

(MSF) = 0.982

AVG. SHEAR WAVE VELOCITY (top 40')

$V_{s,40'}$ = 300 FT./SEC.

PGA CALCULATOR

Earthquake Moment Magnitude = 7.58
Source-To-Site Distance, R (km) = 111.51
Ground Motion Prediction Equations = NMSZ
PGA = 0.143

BORING DATA								CONDITIONS DURING DRILLING					CONDITIONS DURING EARTHQUAKE								
ELEV. OF SAMPLE	BORING SAMPLE DEPTH	SPT N VALUE	UNCONF. COMPR. STR., Q_u (TSF.)	% FINES < #200 (%)	PLAST. INDEX PI	LIQUID LIMIT LL	MOIST. CONTENT w_c (%)	EFFECTIVE UNIT WT. (KCF.)	VERT. STRESS (KSF.)	CORR. SPT N VALUE (N_1) ₆₀	EQUIV. CLN. SAND SPT N VALUE (N_1) _{60cs}	CRR RESIST. MAG 7.5 CRR _{7.5}	EFFECTIVE UNIT WT. (KCF.)	VERT. STRESS (KSF.)	TOTAL STRESS (KSF.)	OVER- BURDEN CORR. FACT. (Ks)	CORR. RESIST. CRR _{7.5} CRR	SOIL MASS PART. FACTOR (r_d)	EQ INDUCED CSR	FACTOR OF SAFETY * CRR/CSR	
413.8	1.5	1						0.095	0.143	1.962	1.962	0.053	0.095	0.203	0.203	1.500		0.078	0.953	0.261	N.L. (1)
410.8	4.5	7	2.3					0.132	0.539	12.292	12.292	0.134	0.132	0.599	0.599	1.365		0.179	0.878	0.241	N.L. (1)
408.3	7	6	2.1					0.130	0.864	9.480	9.480	0.109	0.130	0.924	0.924	1.209		0.129	0.815	0.223	N.L. (1)
405.8	9.5	1	0.6					0.116	1.154	1.561	1.561	0.051	0.116	1.214	1.214	1.118		0.056	0.752	0.206	N.L. (1)
402.8	12.5	6	1.9		12	30	22	0.067	1.355	9.500	9.500	0.109	0.067	1.415	1.571	1.097		0.117	0.682	0.208	N.L. (2)
400.3	15	6	1.6		12	30	20	0.065	1.517	9.472	9.472	0.108	0.065	1.577	1.889	1.070		0.114	0.628	0.206	N.L. (2)
397.8	17.5	5	1.9		12	30	21	0.067	1.685	7.785	7.785	0.094	0.067	1.745	2.213	1.043		0.096	0.581	0.202	N.L. (2)
395.8	19.5	5	1.4		12	30	22	0.063	1.811	7.678	7.678	0.093	0.063	1.871	2.463	1.028		0.094	0.547	0.198	N.L. (2)
392.8	22.5	5	1.2		12	30	20	0.061	1.994	7.491	7.491	0.092	0.061	2.054	2.834	1.007		0.091	0.504	0.191	N.L. (2)
390.3	25	4	1.5		12	30	23	0.064	2.154	5.843	5.843	0.078	0.064	2.214	3.150	0.991		0.076	0.475	0.185	N.L. (2)
388.3	27	8	1.2	90	10	32	21	0.061	2.276	11.455	18.746	0.200	0.061	2.336	3.396	0.973		0.191	0.455	0.182	N.L. (2)
385.8	29.5	2	0.5	91	14	37	26	0.051	2.403	2.805	8.366	0.099	0.051	2.463	3.680	0.967		0.094	0.435	0.178	N.L. (2)
383.3	32	6	1.2	91	14	37	23	0.061	2.556	8.199	14.839	0.158	0.061	2.616	3.988	0.947		0.147	0.419	0.175	N.L. (2)
380.8	34.5	1	0.3	92	29	50	28	0.046	2.671	1.341	6.610	0.085	0.046	2.731	4.259	0.948		0.079	0.406	0.174	N.L. (2)
378.3	37	1	0.3	92	29	50	29	0.046	2.786	1.317	6.580	0.084	0.046	2.846	4.530	0.940		0.078	0.396	0.173	N.L. (2)
375.3	40	4	1.6		12	30	27	0.065	2.981	5.100	5.100	0.073	0.065	3.041	4.913	0.930		0.066	0.386	0.171	N.L. (2)
370.3	45	4	1.9		12	30	28	0.067	3.316	4.835	4.835	0.071	0.067	3.376	5.560	0.911		0.063	0.375	0.170	N.L. (2)
365.3	50	3	1.6		12	30	49	0.065	3.641	3.452	3.452	0.061	0.065	3.701	6.197	0.895		0.054	0.369	0.169	N.L. (2)
360.3	55	1	0.5		12	30	32	0.051	3.896	1.109	1.109	0.050	0.051	3.956	6.764	0.883		0.043	0.365	0.171	N.L. (2)
355.3	60	1	0.6		12	30	31	0.053	4.161	1.067	1.067	0.049	0.053	4.221	7.341	0.871		0.042	0.363	0.173	N.L. (2)

* FACTOR OF SAFETY DESCRIPTIONS

N.L. (1) = NOT LIQUEFIABLE, ABOVE EQ GROUND WATER ELEVATION

N.L. (2) = NOT LIQUEFIABLE, $PI \geq 12$ OR $w_c/LL \leq 0.85$

N.L. (3) = NOT LIQUEFIABLE, $(N_1)_{60} > 25$

(C) = CONTRACTIVE SOIL TYPES

(D) = DILATIVE SOIL TYPES



LIQUEFACTION ANALYSIS

REFERENCE BORING NUMBER ===== 0109 W. Abut.
ELEVATION OF BORING GROUND SURFACE ===== 415.20 FT.
DEPTH TO GROUNDWATER - DURING DRILLING ===== 10.00 FT. (Below Boring Ground Surface)
DEPTH TO GROUNDWATER - DURING EARTHQUAKE ===== 10.50 FT. (Below Finished Grade Cut or Fill Surface)
PEAK HORIZ. GROUND SURFACE ACCELERATION COEFFICIENT (As) ===== 0.422
EARTHQUAKE MOMENT MAGNITUDE ===== 7.6
FINISHED GRADE FILL OR CUT FROM BORING SURFACE ===== 0.50 FT. (Fill Height)
HAMMER EFFICIENCY===== 73 %
BOREHOLE DIAMETER===== 8 IN.
SAMPLING METHOD===== Sampler w/out Liners

EQ MAGNITUDE SCALING FACTOR

(MSF) = 0.982

AVG. SHEAR WAVE VELOCITY (top 40')

$V_{s,40'}$ = 282 FT./SEC.

PGA CALCULATOR

Earthquake Moment Magnitude = 7.58
Source-To-Site Distance, R (km) = 111.51
Ground Motion Prediction Equations = NMSZ
PGA = 0.143

ELEV. OF SAMPLE (FT.)	BORING DATA							CONDITIONS DURING DRILLING					CONDITIONS DURING EARTHQUAKE							
	BORING SAMPLE DEPTH (FT.)	SPT N VALUE (BLOWS)	UNCONF. COMPR. STR., Q_u (TSF.)	% FINES < #200 (%)	PLAST. INDEX PI	LIQUID LIMIT LL	MOIST. CONTENT w_c (%)	EFFECTIVE UNIT WT. (KCF.)	VERT. STRESS (KSF.)	CORR. SPT N VALUE (N_1) ₆₀	EQUIV. CLN. SAND SPT N VALUE (N_1) _{60cs}	CRR RESIST. MAG 7.5 CRR _{7.5}	EFFECTIVE UNIT WT. (KCF.)	VERT. STRESS (KSF.)	TOTAL STRESS (KSF.)	OVER- BURDEN CORR. FACT. (Ks)	CORR. RESIST. CRR _{7.5} CRR	SOIL MASS PART. FACTOR (r_d)	EQ INDUCED CSR	FACTOR OF SAFETY * CRR/CSR
413.7	1.5	1						0.095	0.143	1.962	1.962	0.053	0.095	0.203	0.203	1.500	0.078	0.948	0.260	N.L. (1)
410.7	4.5	3	2.3					0.132	0.539	5.240	5.240	0.074	0.132	0.599	0.599	1.291	0.094	0.867	0.238	N.L. (1)
408.2	7	5	2.1					0.130	0.864	7.900	7.900	0.095	0.130	0.924	0.924	1.199	0.112	0.800	0.219	N.L. (1)
405.7	9.5	4	1.4					0.125	1.176	6.208	6.208	0.081	0.125	1.236	1.236	1.119	0.089	0.735	0.202	N.L. (1)
402.7	12.5	4	1.9		12	30	21	0.067	1.377	6.297	6.297	0.082	0.067	1.437	1.593	1.084	0.087	0.663	0.201	N.L. (2)
400.2	15	4	1.6		12	30	22	0.065	1.540	6.280	6.280	0.082	0.065	1.600	1.912	1.060	0.085	0.609	0.200	N.L. (2)
397.7	17.5	4	1.5		12	30	21	0.064	1.700	6.206	6.206	0.081	0.064	1.760	2.228	1.039	0.083	0.562	0.195	N.L. (2)
395.2	20	4	1.9		12	30	23	0.067	1.867	6.084	6.084	0.080	0.067	1.927	2.551	1.020	0.080	0.521	0.189	N.L. (2)
393.2	22	4	1.5		12	30	22	0.064	1.995	5.977	5.977	0.080	0.064	2.055	2.804	1.006	0.079	0.494	0.185	N.L. (2)
390.2	25	4	1.1	90	10	32	23	0.060	2.175	5.817	11.980	0.131	0.060	2.235	3.171	0.987	0.127	0.459	0.179	N.L. (2)
388.2	27	3	0.8	90	10	32	23	0.057	2.289	4.284	10.140	0.114	0.057	2.349	3.410	0.976	0.110	0.441	0.175	N.L. (2)
385.7	29.5	1	0.5	91	14	37	25	0.051	2.417	1.399	6.679	0.085	0.051	2.477	3.693	0.968	0.081	0.421	0.172	N.L. (2)
383.2	32	6	1	91	14	37	23	0.059	2.564	8.186	14.823	0.158	0.059	2.624	3.997	0.946	0.147	0.406	0.170	N.L. (2)
380.7	34.5	1	0.3	95	24	44	30	0.046	2.679	1.339	6.607	0.084	0.046	2.739	4.268	0.948	0.079	0.394	0.168	N.L. (2)
378.2	37	5	1	94	18	39	26	0.059	2.827	6.533	12.840	0.139	0.059	2.887	4.571	0.926	0.126	0.384	0.167	N.L. (2)
375.7	39.5	1	0.3		12	30	29	0.046	2.942	1.283	1.283	0.050	0.046	3.002	4.842	0.933	0.046	0.377	0.167	N.L. (2)
370.7	44.5	3	0.8		12	30	27	0.057	3.227	3.680	3.680	0.063	0.057	3.287	5.439	0.916	0.056	0.366	0.166	N.L. (2)
365.7	49.5	4	1.5		12	30	27	0.064	3.547	4.672	4.672	0.070	0.064	3.607	6.071	0.899	0.061	0.360	0.166	N.L. (2)
360.7	54.5	3	1		12	30	29	0.059	3.842	3.354	3.354	0.061	0.059	3.902	6.678	0.885	0.053	0.356	0.167	N.L. (2)
355.7	59.5	1	0.8		12	30	35	0.057	4.127	1.072	1.072	0.049	0.057	4.187	7.275	0.873	0.042	0.354	0.169	N.L. (2)

* FACTOR OF SAFETY DESCRIPTIONS

N.L. (1) = NOT LIQUEFIABLE, ABOVE EQ GROUND WATER ELEVATION

N.L. (2) = NOT LIQUEFIABLE, $PI \geq 12$ OR $w_c/LL \leq 0.85$

N.L. (3) = NOT LIQUEFIABLE, $(N_1)_{60} > 25$

(C) = CONTRACTIVE SOIL TYPES

(D) = DILATIVE SOIL TYPES

Appendix I

Integral Abutment Feasibility Analysis



GENERAL DATA

STRUCTURE NUMBER=====100-0108
STRUCTURE TYPE =====MULTI-SPAN
STRUCTURE SKEW=====0 DEGREES
SUPER. DATA IN REFERENCE TO SUB. DATA =====ABUT 1

TOTAL STRUCTURE LENGTH=====128.50 FT
NUMBER OF SPANS =====3
END SPAN LENGTH =====38.00 FT
ADJACENT INTERIOR SPAN LENGTH =====52.50 FT

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (END OR MAIN SPAN)			
BEAM TYPE =====	WIDE FLANGE		
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (ADJACENT SPAN)			
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

ABUTMENT #1 DATA			
ABUTMENT NAME =====	East		
ABUTMENT REFERENCE BORING =====	B-1		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	13		
PILE SPACING PERP. TO CL =====	6	FT	

ABUTMENT #2 DATA			
ABUTMENT NAME =====	West		
ABUTMENT REFERENCE BORING =====	B-2		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	13		
PILE SPACING PERP. TO CL =====	6	FT	

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #1				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUIV. FOR N VALUE (TSF)
406.90	1.10		84	4.0
404.40	2.50		30	3.3
401.90	2.50		9	2.3
399.40	2.50		7	2.2
398.00	1.40		7	2.2

10.00 FT = TOTAL DEPTH ENTERED

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #2				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUIV. FOR N VALUE (TSF)
407.40	0.60		84	4.0
404.90	2.50		30	3.3
402.40	2.50		9	2.3
399.90	2.50		7	2.2
398.00	1.90		7	2.2

10.00 FT = TOTAL DEPTH ENTERED

WEIGHTED AVERAGE Qu FOR ABUTMENT #1===== 2.68 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #1
= 1/(1.45-[0.3*2.68])===== 1.55


WEIGHTED AVERAGE Qu FOR ABUTMENT #2===== 2.59 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #2
= 1/(1.45-[0.3*2.59])===== 1.49

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #1 = [1.55*13*0+1.49*13*128.5]/[1.55*13+1.49*13]===== 62.89 FT

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #2 = [1.49*13*0+1.55*13*128.5]/[1.49*13+1.55*13]===== 65.61 FT

ABUT 1 (East) - EXPANSION LENGTH LIMIT CHART - 0 DEG. SKEW



--- = Estimated expansion length for the indicated abutment. Piles with an expansion length greater than this are suitable for consideration.
(Note: The same size pile should be used at both abutments.)

GENERAL DATA

STRUCTURE NUMBER=====100-0108 - Widening Embankment
STRUCTURE TYPE =====MULTI-SPAN
STRUCTURE SKEW=====0 DEGREES
SUPER. DATA IN REFERENCE TO SUB. DATA =====ABUT 1

TOTAL STRUCTURE LENGTH=====128.50 FT
NUMBER OF SPANS =====3
END SPAN LENGTH =====38.00 FT
ADJACENT INTERIOR SPAN LENGTH =====52.50 FT

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (END OR MAIN SPAN)			
BEAM TYPE =====	WIDE FLANGE		
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (ADJACENT SPAN)			
WIDE FLANGE =====	W27X102		
BEAM SPACING PERP. TO CL =====	6.00	FT	
SLAB THICKNESS =====	8.00	IN	
SLAB F'C =====	4.00	KSI	

ABUTMENT #1 DATA			
ABUTMENT NAME =====	East		
ABUTMENT REFERENCE BORING =====	B-1		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	13		
PILE SPACING PERP. TO CL =====	6	FT	

ABUTMENT #2 DATA			
ABUTMENT NAME =====	West		
ABUTMENT REFERENCE BORING =====	B-2		
BOTTOM OF ABUTMENT ELEVATION =====	408	FT	
ESTIMATED NUMBER OF PILES AT ABUT. =====	13		
PILE SPACING PERP. TO CL =====	6	FT	

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #1				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUITV. FOR N VALUE (TSF)
405.50	2.50	1.0		
403.00	2.50	1.0		
400.50	2.50	1.0		
398.00	2.50	1.0		

10.00 FT = TOTAL DEPTH ENTERED

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #2				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUITV. FOR N VALUE (TSF)
405.50	2.50	1.0		
403.00	2.50	1.0		
400.50	2.50	1.0		
398.00	2.50	1.00		

10.00 FT = TOTAL DEPTH ENTERED

WEIGHTED AVERAGE Qu FOR ABUTMENT #1===== 1.00 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #1
= 1/(1.45-[0.3*1])===== 0.87


WEIGHTED AVERAGE Qu FOR ABUTMENT #2===== 1.00 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #2
= 1/(1.45-[0.3*1])===== 0.87

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #1 = [0.87*13*0+0.87*13*128.5]/[0.87*13+0.87*13]===== 64.25 FT

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #2 = [0.87*13*0+0.87*13*128.5]/[0.87*13+0.87*13]===== 64.25 FT

ABUT 1 (East) - EXPANSION LENGTH LIMIT CHART - 0 DEG. SKEW



----- = Estimated expansion length for the indicated abutment. Piles with an expansion length greater than this are suitable for consideration.
(Note: The same size pile should be used at both abutments.)

By inspection, 0109 widening embankment condition OK

GENERAL DATA

STRUCTURE NUMBER=====100-0109
STRUCTURE TYPE =====MULTI-SPAN
STRUCTURE SKEW=====0 DEGREES
SUPER. DATA IN REFERENCE TO SUB. DATA =====ABUT 1

TOTAL STRUCTURE LENGTH=====128.50 FT
NUMBER OF SPANS =====3
END SPAN LENGTH =====38.00 FT
ADJACENT INTERIOR SPAN LENGTH =====52.50 FT

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (END OR MAIN SPAN)		
BEAM TYPE =====	WIDE FLANGE	
WIDE FLANGE =====	W27X102	
BEAM SPACING PERP. TO CL =====	6.17	FT
SLAB THICKNESS =====	8.00	IN
SLAB F'C =====	4.00	KSI

SUPERSTRUCTURE POSITIVE MOMENT REGION DATA (ADJACENT SPAN)		
WIDE FLANGE =====	W27X102	
BEAM SPACING PERP. TO CL =====	6.17	FT
SLAB THICKNESS =====	8.00	IN
SLAB F'C =====	4.00	KSI

ABUTMENT #1 DATA		
ABUTMENT NAME =====	East	
ABUTMENT REFERENCE BORING =====	B-1	
BOTTOM OF ABUTMENT ELEVATION =====	408	FT
ESTIMATED NUMBER OF PILES AT ABUT. =====	10	
PILE SPACING PERP. TO CL =====	6.17	FT

ABUTMENT #2 DATA		
ABUTMENT NAME =====	West	
ABUTMENT REFERENCE BORING =====	B-2	
BOTTOM OF ABUTMENT ELEVATION =====	408	FT
ESTIMATED NUMBER OF PILES AT ABUT. =====	10	
PILE SPACING PERP. TO CL =====	6.17	FT

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #1				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUITV. FOR N VALUE (TSF)
405.80	2.20	0.6		
402.80	3.00	1.9		
400.30	2.50	1.6		
398.00	2.30	1.9		

10.00 FT = TOTAL DEPTH ENTERED

SOIL DATA FOR 10 FT BENEATH BOTTOM OF ABUTMENT #2				
BOT. OF LAYER ELEV. (FT)	LAYER THICKNESS (FT)	UNCONFINED COMPRESSIVE STRENGTH (TSF)	N S.P.T. VALUE (BLOWS/12 IN.)	Qu EQUITV. FOR N VALUE (TSF)
405.20	2.80	1.4		
402.70	2.50	1.9		
400.20	2.50	1.6		
398.00	2.20	1.50		

10.00 FT = TOTAL DEPTH ENTERED

WEIGHTED AVERAGE Qu FOR ABUTMENT #1===== 1.54 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #1
= 1/(1.45-[0.3*1.54])===== 1.01


WEIGHTED AVERAGE Qu FOR ABUTMENT #2===== 1.60 TSF

PILE STIFFNESS MODIFIER FOR ABUTMENT #2
= 1/(1.45-[0.3*1.6])===== 1.03

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #1 = [1.01*10*0+1.03*10*128.5]/[1.01*10+1.03*10]===== 64.82 FT

DISTANCE TO CENTROID OF STIFFNESS FROM ABUTMENT #2 = [1.03*10*0+1.01*10*128.5]/[1.03*10+1.01*10]===== 63.68 FT

ABUT 1 (East) - EXPANSION LENGTH LIMIT CHART - 0 DEG. SKEW



----- = Estimated expansion length for the indicated abutment. Piles with an expansion length greater than this are suitable for consideration.
(Note: The same size pile should be used at both abutments.)

Appendix J

Driven Pile Analysis





IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0108 - W. Abut.
REFERENCE BORING =====2-SLRFD or ASD or SEISMIC ===== LRFD
PILE CUTOFF ELEV. ===== 410.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) ===== None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD ===== ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) ===== ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	67 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD ===== 1700 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)===== 76.17 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE ===== 1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 178.55 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 66.96 KIPS

PILE TYPE AND SIZE ===== Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.
Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.50	2.50		0	Sandy Gravel	0.0	0.0	0.0	0.0	0.0	0.0	0	0	0	0	5
403.00	2.50		0	Sandy Gravel	0.0	0.0	0.0	0.0	0.0	0.0	0	0	0	0	7
400.50	2.50		0	Sandy Gravel	0.0	0.0	0.0	0.0	0.0	0.0	0	0	0	0	10
398.00	2.50		0	Sandy Gravel	0.0	0.0	20.6	0.0	0.0	2.2	2	0	0	1	12
395.50	2.50		6	Sandy Gravel	1.6	20.6	22.3	2.4	2.2	4.7	5	0	0	3	15
393.00	2.50		6	Sandy Gravel	1.6	20.6	6.7	2.4	2.2	5.3	5	0	0	3	17
390.40	2.60		1	Sandy Gravel	0.3	3.4	15.2	0.4	0.4	6.6	7	0	0	4	20
387.90	2.50	0.60			5.4	11.6	16.7	8.0	1.2	14.2	14	0	0	8	22
386.40	1.50	0.40			2.2	7.7	32.5	3.3	0.8	18.9	19	0	0	10	24
382.90	3.50	1.10			12.6	21.3	29.6	18.7	2.3	36.0	30	0	0	16	27
380.40	2.50	0.30			2.8	5.8	46.0	4.2	0.6	41.7	42	0	0	23	30
377.90	2.50	1.00			8.3	19.3	42.7	12.4	2.1	52.8	43	0	0	24	32
375.40	2.50	0.40			3.7	7.7	75.5	5.5	0.8	61.5	61	0	0	34	35
370.40	5.00	1.90			26.5	36.7	90.3	39.3	4.0	99.5	90	0	0	50	40
365.40	5.00	1.30			20.4	25.1	93.4	30.3	2.7	128.0	93	0	0	51	45
360.40	5.00	0.40			7.5	7.7	106.6	11.1	0.8	139.6	107	0	0	59	50
355.40	5.00	0.70			12.4	13.5	115.1	18.4	1.5	157.6	115	0	0	63	55
350.40	5.00	0.50			9.2	9.7	143.6	13.6	1.0	173.3	144	0	0	79	60
347.90	2.50	1.50			11.3	29.0	297.7	16.8	3.1	205.4	205	0	0	113	62
346.90	1.00			Shale	58.5	171.8	356.3	86.9	18.5	292.3	292	0	0	161	63.1
345.90	1.00			Shale	58.5	171.8	414.8	86.9	18.5	379.2	379	0	0	209	64.1
344.90	1.00			Shale	58.5	171.8	473.4	86.9	18.5	466.1	466	0	0	256	65.1
343.90	1.00			Shale	58.5	171.8	531.9	86.9	18.5	553.0	532	0	0	293	66.1
342.90	1.00			Shale	58.5	171.8	590.5	86.9	18.5	639.9	590	0	0	325	67.4
341.90	1.00			Shale	58.5	171.8	649.0	86.9	18.5	726.8	649	0	0	357	68.4
340.90	1.00			Shale		171.8			18.5						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0108 - E. Abut.

REFERENCE BORING =====1-S

LRFD or ASD or SEISMIC =====LRFD

PILE CUTOFF ELEV. =====410.00 ft

GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft

GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None

BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft

TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1700 kips

TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====76.17 ft

NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1

Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 178.55 KIPS

Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 66.96 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.

Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	57 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.50	2.50		0	Sandy Gravel	0.0	0.0	0.0	0.0	0.0	0.0	0	0	0	0	5
403.00	2.50		0	Sandy Gravel	0.0	0.0	0.0	0.0	0.0	0.0	0	0	0	0	7
400.50	2.50		0	Sandy Gravel	0.0	0.0	0.0	0.0	0.0	0.0	0	0	0	0	10
398.00	2.50		0	Sandy Gravel	0.0	0.0	20.6	0.0	0.0	2.2	2	0	0	1	12
395.50	2.50		6	Sandy Gravel	1.6	20.6	22.3	2.4	2.2	4.7	5	0	0	3	15
393.00	2.50		6	Sandy Gravel	1.6	20.6	6.7	2.4	2.2	5.3	5	0	0	3	17
390.40	2.60		1	Sandy Gravel	0.3	3.4	13.2	0.4	0.4	6.4	6	0	0	3	20
387.90	2.50	0.50			4.6	9.7	14.0	6.8	1.0	12.7	13	0	0	7	22
385.90	2.00	0.30			2.3	5.8	47.2	3.4	0.6	19.4	19	0	0	11	24
383.40	2.50	1.90			13.2	36.7	39.1	19.6	4.0	36.8	37	0	0	20	27
380.90	2.50	0.80			6.9	15.5	67.3	10.3	1.7	49.4	49	0	0	27	29
378.40	2.50	1.90			13.2	36.7	80.6	19.6	4.0	69.0	69	0	0	38	32
374.90	3.50	1.90			18.5	36.7	99.1	27.5	4.0	96.5	97	0	0	53	35
369.90	5.00	1.90			26.5	36.7	112.0	39.3	4.0	134.4	112	0	0	62	40
364.90	5.00	1.20			19.3	23.2	129.4	28.6	2.5	162.7	129	0	0	71	45
360.40	4.50	1.10			16.2	21.3	147.5	24.1	2.3	187.0	148	0	0	81	50
355.90	4.50	1.20			17.3	23.2	420.8	25.7	2.5	240.3	240	0	0	132	54
354.90	1.00			Sandstone	97.6	279.1	518.4	144.8	30.1	385.1	385	0	0	212	55.1
353.90	1.00			Sandstone	97.6	279.1	615.9	144.8	30.1	529.9	530	0	0	291	56.1
352.90	1.00			Sandstone	97.6	279.1	713.5	144.8	30.1	674.7	675	0	0	371	57.1
351.90	1.00			Sandstone	97.6	279.1	811.1	144.8	30.1	819.6	811	0	0	446	58.1
350.90	1.00			Sandstone	97.6	279.1	908.7	144.8	30.1	964.4	909	0	0	509	59.1
349.90	1.00			Sandstone	97.6	279.1	1006.3	144.8	30.1	1109.2	1006	0	0	553	60.1
348.90	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0109 - W. Abut.
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====410.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	61 FT.

TOTAL FACTORED SUBSTRUCTURE LOAD =====1300 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====60.17 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====172.84 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====64.82 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter=====4.700 FT. Unplugged Pile Perimeter=====6.975 FT.
Plugged Pile End Bearing Area=====1.379 SQFT. Unplugged Pile End Bearing Area=====0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.20	2.80	1.40			12.1		48.8	17.9		21.9	22	0	0	12	5
402.70	2.50	1.90			13.2	36.7	56.2	19.6	4.0	40.9	41	0	0	22	7
400.20	2.50	1.60			11.8	30.9	66.1	17.5	3.3	58.2	58	0	0	32	10
397.70	2.50	1.50			11.3	29.0	85.1	16.8	3.1	75.8	76	0	0	42	12
395.20	2.50	1.90			13.2	36.7	90.6	19.6	4.0	94.6	91	0	0	50	15
392.70	2.50	1.50			11.3	29.0	94.2	16.8	3.1	110.6	94	0	0	52	17
390.20	2.50	1.10			9.0	21.3	97.4	13.4	2.3	123.3	97	0	0	54	20
387.70	2.50	0.80			6.9	15.5	98.6	10.3	1.7	133.0	99	0	0	54	22
385.20	2.50	0.50			4.6	9.7	112.8	6.8	1.0	140.8	113	0	0	62	25
382.70	2.50	1.00			8.3	19.3	107.6	12.4	2.1	151.8	108	0	0	59	27
380.20	2.50	0.30			2.8	5.8	124.0	4.2	0.6	157.4	124	0	0	68	30
377.70	2.50	1.00			8.3	19.3	118.8	12.4	2.1	168.4	119	0	0	65	32
375.20	2.50	0.30			2.8	5.8	131.3	4.2	0.6	173.6	131	0	0	72	35
370.20	5.00	0.80			13.9	15.5	158.7	20.6	1.7	195.7	159	0	0	87	40
365.20	5.00	1.50			22.6	29.0	171.7	33.5	3.1	228.2	172	0	0	94	45
360.20	5.00	1.00			16.7	19.3	184.5	24.8	2.1	252.5	185	0	0	101	50
355.70	4.50	0.80			12.5	15.5	193.1	18.5	1.7	270.7	193	0	0	106	54
352.20	3.50	0.60			7.6	11.6	189.1	11.2	1.2	280.6	189	0	0	104	58
351.20	1.00			Sandstone	0.0	0.0	468.2	0.0	0.0	310.7	311	0	0	171	58.8
350.20	1.00			Sandstone	97.6	279.1	565.8	144.8	30.1	455.5	456	0	0	251	59.8
349.20	1.00			Sandstone	97.6	279.1	663.4	144.8	30.1	600.3	600	0	0	330	60.8
348.20	1.00			Sandstone	97.6	279.1	761.0	144.8	30.1	745.2	745	0	0	440	61.8
347.20	1.00			Sandstone	97.6	279.1	858.6	144.8	30.1	890.0	859	0	0	472	62.8
346.20	1.00			Sandstone	97.6	279.1	956.1	144.8	30.1	1034.8	956	0	0	526	63.8
345.20	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0109 - E. Abut.

REFERENCE BORING =====1-S

LRFD or ASD or SEISMIC =====LRFD

PILE CUTOFF ELEV. =====410.00 ft

GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 408.00 ft

GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====None

BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====ft

TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====1300 kips

TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====60.17 ft

NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1

Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 172.84 KIPS

Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 64.82 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.

Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	318 KIPS	63 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
405.80	2.20	0.60			4.8		41.5	7.1		11.0	11	0	0	6	4
402.80	3.00	1.90			15.9	36.7	51.6	23.6	4.0	34.0	34	0	0	19	7
400.30	2.50	1.60			11.8	30.9	69.2	17.5	3.3	52.1	52	0	0	29	10
397.80	2.50	1.90			13.2	36.7	72.7	19.6	4.0	70.7	71	0	0	39	12
395.80	2.00	1.40			8.6	27.1	77.5	12.8	2.9	83.1	77	0	0	43	14
392.80	3.00	1.20			11.6	23.2	94.8	17.1	2.5	100.9	95	0	0	52	17
390.30	2.50	1.50			11.3	29.0	100.4	16.8	3.1	117.0	100	0	0	55	20
388.30	2.00	1.20			7.7	23.2	94.5	11.4	2.5	127.0	95	0	0	52	22
385.80	2.50	0.50			4.6	9.7	112.6	6.8	1.0	135.2	113	0	0	62	24
383.30	2.50	1.20			9.6	23.2	104.9	14.3	2.5	147.7	105	0	0	58	27
380.80	2.50	0.30			2.8	5.8	107.7	4.2	0.6	151.9	108	0	0	59	29
378.30	2.50	0.30			2.8	5.8	135.7	4.2	0.6	158.8	136	0	0	75	32
375.30	3.00	1.60			14.2	30.9	155.7	21.0	3.3	180.5	156	0	0	86	35
370.30	5.00	1.90			26.5	36.7	176.3	39.3	4.0	219.1	176	0	0	97	40
365.30	5.00	1.60			23.6	30.9	178.7	35.1	3.3	251.9	179	0	0	98	45
360.30	5.00	0.50			9.2	9.7	189.8	13.6	1.0	265.7	190	0	0	104	50
355.30	5.00	0.60			10.8	11.6	198.7	16.0	1.2	281.5	199	0	0	109	55
350.80	4.50	0.50			8.2	9.7	228.2	12.2	1.0	296.1	228	0	0	125	59
348.80	2.00	1.60			9.4	30.9	485.8	14.0	3.3	336.8	337	0	0	185	61
347.80	1.00			Sandstone	97.6	279.1	583.4	144.8	30.1	481.6	482	0	0	265	62.2
346.80	1.00			Sandstone	97.6	279.1	681.0	144.8	30.1	626.5	626	0	0	345	63.2
345.80	1.00			Sandstone	97.6	279.1	778.6	144.8	30.1	771.3	771	0	0	424	64.2
344.80	1.00			Sandstone	97.6	279.1	876.1	144.8	30.1	916.1	876	0	0	482	65.2
343.80	1.00			Sandstone	97.6	279.1	973.7	144.8	30.1	1060.9	974	0	0	536	66.2
342.80	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0108 - Pier 1
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 393.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====386.40 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====3200 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====76.17 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 336.09 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 126.03 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	534 KIPS	286 KIPS	65 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.
Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
387.90	5.10	0.60			11.0		18.7	16.3		17.2	17	6	0	3	21
386.40	1.50	0.40			2.2	7.7	34.5	3.3	0.8	22.0	22	7	0	5	23
382.90	3.50	1.10			12.6	21.3	31.7	18.7	2.3	39.0	32	7	0	10	26
380.40	2.50	0.30			2.8	5.8	48.0	4.2	0.6	44.7	45	7	0	17	29
377.90	2.50	1.00			8.3	19.3	44.8	12.4	2.1	55.8	45	7	0	17	31
375.40	2.50	0.40			3.7	7.7	77.5	5.5	0.8	64.5	64	7	0	28	34
370.40	5.00	1.90			26.5	36.7	92.4	39.3	4.0	102.5	92	7	0	44	39
365.40	5.00	1.30			20.4	25.1	95.4	30.3	2.7	131.0	95	7	0	45	44
360.40	5.00	0.40			7.5	7.7	108.7	11.1	0.8	142.7	109	7	0	52	49
355.40	5.00	0.70			12.4	13.5	117.2	18.4	1.5	160.6	117	7	0	57	54
350.40	5.00	0.50			9.2	9.7	145.7	13.6	1.0	176.3	146	7	0	73	59
347.90	2.50	1.50			11.3	29.0	299.8	16.8	3.1	208.4	208	7	0	107	61
346.90	1.00			Shale	58.5	171.8	358.3	86.9	18.5	295.3	295	7	0	155	62.1
345.90	1.00			Shale	58.5	171.8	416.9	86.9	18.5	382.2	382	7	0	203	63.1
344.90	1.00			Shale	58.5	171.8	475.4	86.9	18.5	469.1	469	7	0	251	64.1
343.90	1.00			Shale	58.5	171.8	534.0	86.9	18.5	556.0	534	7	0	286	65.1
342.90	1.00			Shale	58.5	171.8	592.5	86.9	18.5	642.9	592	7	0	349	66.1
341.90	1.00			Shale	58.5	171.8	651.0	86.9	18.5	729.8	651	7	0	351	67.1
340.90	1.00			Shale		171.8			18.5						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0108 - Pier 2
REFERENCE BORING =====1-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 393.00 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====386.40 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft
TOTAL FACTORED SUBSTRUCTURE LOAD =====3200 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====76.17 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts ===== 336.09 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts ===== 126.03 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	578 KIPS	313 KIPS	56 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter===== 4.700 FT. Unplugged Pile Perimeter===== 6.975 FT.
Plugged Pile End Bearing Area===== 1.379 SQFT. Unplugged Pile End Bearing Area===== 0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
387.90	5.10	0.50			9.3		15.1	13.9		14.5	14	5	0	3	21
385.90	2.00	0.30			2.3	5.8	48.3	3.4	0.6	21.2	21	5	0	7	23
383.40	2.50	1.90			13.2	36.7	40.3	19.6	4.0	38.6	39	5	0	16	26
380.90	2.50	0.80			6.9	15.5	68.5	10.3	1.7	51.1	51	5	0	23	28
378.40	2.50	1.90			13.2	36.7	81.8	19.6	4.0	70.8	71	5	0	34	31
374.90	3.50	1.90			18.5	36.7	100.3	27.5	4.0	98.3	98	5	0	49	34
369.90	5.00	1.90			26.5	36.7	113.2	39.3	4.0	136.1	113	5	0	57	39
364.90	5.00	1.20			19.3	23.2	130.6	28.6	2.5	164.5	131	5	0	67	44
360.40	4.50	1.10			16.2	21.3	148.7	24.1	2.3	188.8	149	5	0	77	49
355.90	4.50	1.20			17.3	23.2	422.0	25.7	2.5	242.1	242	5	0	128	53
354.90	1.00			Sandstone	97.6	279.1	519.5	144.8	30.1	386.9	387	5	0	208	54.1
353.90	1.00			Sandstone	97.6	279.1	617.1	144.8	30.1	531.7	532	5	0	287	55.1
352.90	1.00			Sandstone	97.6	279.1	714.7	144.8	30.1	676.5	677	5	0	367	56.4
351.90	1.00			Sandstone	97.6	279.1	812.3	144.8	30.1	821.3	812	5	0	442	57.4
350.90	1.00			Sandstone	97.6	279.1	909.9	144.8	30.1	966.1	910	5	0	495	58.4
349.90	1.00			Sandstone	97.6	279.1	1007.5	144.8	30.1	1110.9	1007	5	0	549	59.4
348.90	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0109 - Pier 1
REFERENCE BORING =====2-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 393.70 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====386.40 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft

TOTAL FACTORED SUBSTRUCTURE LOAD =====2600 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====60.17 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====345.69 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====129.63 KIPS

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter=====4.700 FT. Unplugged Pile Perimeter=====6.975 FT.
Plugged Pile End Bearing Area=====1.379 SQFT. Unplugged Pile End Bearing Area=====0.149 SQFT.

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	499 KIPS	263 KIPS	60 FT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
392.70	1.00	1.50			4.5		25.8	6.7		9.0	9	2	0	2	16
390.20	2.50	1.10			9.0	21.3	29.0	13.4	2.3	21.7	22	7	0	5	19
387.70	2.50	0.80			6.9	15.5	30.1	10.3	1.7	31.4	30	11	0	5	21
385.20	2.50	0.50			4.6	9.7	44.4	6.8	1.0	39.3	39	11	0	10	24
382.70	2.50	1.00			8.3	19.3	39.2	12.4	2.1	50.2	39	11	0	10	26
380.20	2.50	0.30			2.8	5.8	55.6	4.2	0.6	55.9	56	11	0	19	29
377.70	2.50	1.00			8.3	19.3	50.4	12.4	2.1	66.8	50	11	0	16	31
375.20	2.50	0.30			2.8	5.8	62.9	4.2	0.6	72.1	63	11	0	23	34
370.20	5.00	0.80			13.9	15.5	90.3	20.6	1.7	94.1	90	11	0	38	39
365.20	5.00	1.50			22.6	29.0	103.2	33.5	3.1	126.6	103	11	0	46	44
360.20	5.00	1.00			16.7	19.3	116.1	24.8	2.1	151.0	116	11	0	53	49
355.70	4.50	0.80			12.5	15.5	124.7	18.5	1.7	169.1	125	11	0	57	53
352.20	3.50	0.60			7.6	11.6	120.7	11.2	1.2	179.1	121	11	0	55	57
351.20	1.00			Sandstone	0.0	0.0	399.8	0.0	0.0	209.1	209	11	0	104	57.8
350.20	1.00			Sandstone	97.6	279.1	497.4	144.8	30.1	354.0	354	11	0	183	58.8
349.20	1.00			Sandstone	97.6	279.1	595.0	144.8	30.1	498.8	499	11	0	263	59.8
348.20	1.00			Sandstone	97.6	279.1	692.5	144.8	30.1	643.6	644	11	0	343	60.8
347.20	1.00			Sandstone	97.6	279.1	790.1	144.8	30.1	788.4	788	11	0	422	61.8
346.20	1.00			Sandstone	97.6	279.1	887.7	144.8	30.1	933.2	888	11	0	477	62.8
345.20	1.00			Sandstone		279.1			30.1						



IDOT STATIC METHOD OF ESTIMATING PILE LENGTH

SUBSTRUCTURE=====100-0109 - Pier 2
REFERENCE BORING =====1-S
LRFD or ASD or SEISMIC =====LRFD
PILE CUTOFF ELEV. =====409.00 ft
GROUND SURFACE ELEV. AGAINST PILE DURING DRIVING = 393.70 ft
GEOTECHNICAL LOSS TYPE (None, Scour, Liquef., DD) =====Scour
BOTTOM ELEV. OF SCOUR, LIQUEF., or DD =====386.40 ft
TOP ELEV. OF LIQUEF. (so layers above apply DD) =====ft
TOTAL FACTORED SUBSTRUCTURE LOAD =====2600 kips
TOTAL LENGTH OF SUBSTRUCTURE (along skew)=====60.17 ft
NUMBER OF ROWS OF PILES PER SUBSTRUCTURE =====1
Approx. Factored Loading Applied per pile at 8 ft. Cts =====345.69 KIPS
Approx. Factored Loading Applied per pile at 3 ft. Cts =====129.63 KIPS

MAX. REQUIRED BEARING & RESISTANCE for Selected Pile, Soil Profile, & Losses

Maximum Nominal Req'd Bearing of <u>Pile</u>	Maximum Nominal Req'd Bearing of <u>Boring</u>	Maximum Factored Resistance Available in <u>Boring</u>	Maximum Pile Driveable Length in <u>Boring</u>
578 KIPS	534 KIPS	281 KIPS	62 FT.

PILE TYPE AND SIZE =====Steel HP 14 X 73

Plugged Pile Perimeter=====4.700 FT. Unplugged Pile Perimeter=====6.975 FT.
Plugged Pile End Bearing Area=====1.379 SQFT. Unplugged Pile End Bearing Area=====0.149 SQFT.

BOT. OF LAYER ELEV. (FT.)	LAYER THICK. (FT.)	UNCONF. COMPR. STRENGTH (TSF.)	S.P.T. N VALUE (BLOWS)	GRANULAR OR ROCK LAYER DESCRIPTION	NOMINAL PLUGGED			NOMINAL UNPLUG'D			NOMINAL REQ'D BEARING (KIPS)	FACTORED GEOTECH. LOSS FROM SCOUR or DD (KIPS)	FACTORED GEOTECH. LOSS LOAD FROM DD (KIPS)	FACTORED RESISTANCE AVAILABLE (KIPS)	ESTIMATED PILE LENGTH (FT.)
					SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)	SIDE RESIST. (KIPS)	END BRG. RESIST. (KIPS)	TOTAL RESIST. (KIPS)					
392.80	0.90	1.20			3.5		32.5	5.1		8.3	8	2	0	3	16
390.30	2.50	1.50			11.3	29.0	38.0	16.8	3.1	24.4	24	8	0	5	19
388.30	2.00	1.20			7.7	23.2	32.1	11.4	2.5	34.4	32	12	0	5	21
385.80	2.50	0.50			4.6	9.7	50.2	6.8	1.0	42.6	43	12	0	11	23
383.30	2.50	1.20			9.6	23.2	42.5	14.3	2.5	55.1	42	12	0	11	26
380.80	2.50	0.30			2.8	5.8	45.3	4.2	0.6	59.3	45	12	0	13	28
378.30	2.50	0.30			2.8	5.8	73.3	4.2	0.6	66.2	66	12	0	24	31
375.30	3.00	1.60			14.2	30.9	93.3	21.0	3.3	87.9	88	12	0	36	34
370.30	5.00	1.90			26.5	36.7	113.9	39.3	4.0	126.5	114	12	0	50	39
365.30	5.00	1.60			23.6	30.9	116.3	35.1	3.3	159.3	116	12	0	52	44
360.30	5.00	0.50			9.2	9.7	127.4	13.6	1.0	173.1	127	12	0	58	49
355.30	5.00	0.60			10.8	11.6	136.3	16.0	1.2	188.9	136	12	0	63	54
350.80	4.50	0.50			8.2	9.7	165.8	12.2	1.0	203.5	166	12	0	79	58
348.80	2.00	1.60			9.4	30.9	423.4	14.0	3.3	244.2	244	12	0	122	60
347.80	1.00			Sandstone	97.6	279.1	521.0	144.8	30.1	389.0	389	12	0	202	61.2
346.80	1.00			Sandstone	97.6	279.1	618.6	144.8	30.1	533.9	534	12	0	281	62.2
345.80	1.00			Sandstone	97.6	279.1	716.2	144.8	30.1	678.7	679	42	0	364	63.2
344.80	1.00			Sandstone	97.6	279.1	813.8	144.8	30.1	823.5	844	42	0	435	64.2
343.80	1.00			Sandstone	97.6	279.1	911.3	144.8	30.1	968.3	944	42	0	489	65.2
342.80	1.00			Sandstone		279.1			30.1						