

**BEAM 7**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+51.09	-24.00	658.86	658.86
@ EXP. JT.	116+53.18	-24.00	658.87	658.87
@ BRG. S. ABUT.	116+54.09	-24.00	658.88	658.88
A	116+64.09	-24.00	658.96	659.05
B	116+74.09	-24.00	659.03	659.20
C	116+84.09	-24.00	659.07	659.32
D	116+94.09	-24.00	659.10	659.40
E	117+04.09	-24.00	659.12	659.45
F	117+14.09	-24.00	659.12	659.46
G	117+24.09	-24.00	659.10	659.43
H	117+34.09	-24.00	659.07	659.37
I	117+44.09	-24.00	659.02	659.28
J	117+54.09	-24.00	658.96	659.16
K	117+64.09	-24.00	658.88	659.02
L	117+74.09	-24.00	658.78	658.87
M	117+84.09	-24.00	658.67	658.71
@ BRG. PIER	117+98.09	-24.00	658.48	658.48
N	118+08.09	-24.00	658.33	658.32
O	118+18.09	-24.00	658.17	658.16
P	118+28.09	-24.00	657.98	658.00
Q	118+38.09	-24.00	657.78	657.83
R	118+48.09	-24.00	657.57	657.64
S	118+58.09	-24.00	657.34	657.44
T	118+68.09	-24.00	657.09	657.22
U	118+78.09	-24.00	656.83	656.96
V	118+88.09	-24.00	656.55	656.67
W	118+98.09	-24.00	656.25	656.36
X	119+08.09	-24.00	655.94	656.01
@ BRG. N. ABUT.	119+22.09	-24.00	655.48	655.48
@ EXP. JT.	119+23.01	-24.00	655.45	655.45
BK. N. ABUT.	119+25.09	-24.00	655.38	655.38

**STAGE CONSTRUCTION LINE 2**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+51.25	-21.00	658.92	658.92
@ EXP. JT.	116+53.33	-21.00	658.94	658.94
@ BRG. S. ABUT.	116+54.25	-21.00	658.94	658.94
A	116+64.25	-21.00	659.02	659.11
B	116+74.25	-21.00	659.09	659.26
C	116+84.25	-21.00	659.13	659.38
D	116+94.25	-21.00	659.16	659.46
E	117+04.25	-21.00	659.18	659.51
F	117+14.25	-21.00	659.18	659.52
G	117+24.25	-21.00	659.16	659.49
H	117+34.25	-21.00	659.13	659.43
I	117+44.25	-21.00	659.08	659.34
J	117+54.25	-21.00	659.02	659.22
K	117+64.25	-21.00	658.94	659.08
L	117+74.25	-21.00	658.84	658.92
M	117+84.25	-21.00	658.73	658.77
@ BRG. PIER	117+98.25	-21.00	658.54	658.54
N	118+08.25	-21.00	658.39	658.38
O	118+18.25	-21.00	658.22	658.22
P	118+28.25	-21.00	658.04	658.06
Q	118+38.25	-21.00	657.84	657.88
R	118+48.25	-21.00	657.62	657.70
S	118+58.25	-21.00	657.39	657.50
T	118+68.25	-21.00	657.15	657.27
U	118+78.25	-21.00	656.88	657.02
V	118+88.25	-21.00	656.60	656.73
W	118+98.25	-21.00	656.31	656.41
X	119+08.25	-21.00	656.00	656.06
@ BRG. N. ABUT.	119+22.25	-21.00	655.53	655.53
@ EXP. JT.	119+23.17	-21.00	655.50	655.50
BK. N. ABUT.	119+25.25	-21.00	655.43	655.43

**BEAM 8**

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+51.46	-17.00	659.00	659.00
@ EXP. JT.	116+53.54	-17.00	659.02	659.02
@ BRG. S. ABUT.	116+54.46	-17.00	659.03	659.03
A	116+64.46	-17.00	659.10	659.20
B	116+74.46	-17.00	659.17	659.34
C	116+84.46	-17.00	659.21	659.46
D	116+94.46	-17.00	659.25	659.54
E	117+04.46	-17.00	659.26	659.59
F	117+14.46	-17.00	659.26	659.60
G	117+24.46	-17.00	659.24	659.57
H	117+34.46	-17.00	659.21	659.51
I	117+44.46	-17.00	659.16	659.41
J	117+54.46	-17.00	659.09	659.29
K	117+64.46	-17.00	659.01	659.15
L	117+74.46	-17.00	658.92	659.00
M	117+84.46	-17.00	658.80	658.84
@ BRG. PIER	117+98.46	-17.00	658.62	658.62
N	118+08.46	-17.00	658.47	658.46
O	118+18.46	-17.00	658.30	658.30
P	118+28.46	-17.00	658.12	658.13
Q	118+38.46	-17.00	657.92	657.96
R	118+48.46	-17.00	657.70	657.78
S	118+58.46	-17.00	657.47	657.57
T	118+68.46	-17.00	657.22	657.35
U	118+78.46	-17.00	656.96	657.09
V	118+88.46	-17.00	656.68	656.80
W	118+98.46	-17.00	656.38	656.48
X	119+08.46	-17.00	656.07	656.14
@ BRG. N. ABUT.	119+22.46	-17.00	655.61	655.61
@ EXP. JT.	119+23.38	-17.00	655.57	655.57
BK. N. ABUT.	119+25.46	-17.00	655.50	655.50