

STAGE CONSTRUCTION LINE 1

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+53.45	21.00	658.94	658.94
@ EXP. JT.	116+55.53	21.00	658.95	658.95
@ BRG. S. ABUT.	116+56.45	21.00	658.96	658.96
A	116+66.45	21.00	659.04	659.13
B	116+76.45	21.00	659.10	659.27
C	116+86.45	21.00	659.14	659.39
D	116+96.45	21.00	659.17	659.47
E	117+06.45	21.00	659.18	659.51
F	117+16.45	21.00	659.18	659.52
G	117+26.45	21.00	659.16	659.49
H	117+36.45	21.00	659.12	659.42
I	117+46.45	21.00	659.07	659.32
J	117+56.45	21.00	659.00	659.20
K	117+66.45	21.00	658.92	659.06
L	117+76.45	21.00	658.82	658.90
M	117+86.45	21.00	658.70	658.74
@ BRG. PIER	118+00.45	21.00	658.51	658.51
N	118+10.45	21.00	658.35	658.35
O	118+20.45	21.00	658.18	658.18
P	118+30.45	21.00	658.00	658.01
Q	118+40.45	21.00	657.79	657.84
R	118+50.45	21.00	657.58	657.65
S	118+60.45	21.00	657.34	657.45
T	118+70.45	21.00	657.09	657.22
U	118+80.45	21.00	656.82	656.96
V	118+90.45	21.00	656.54	656.67
W	119+00.45	21.00	656.24	656.34
X	119+10.45	21.00	655.93	655.99
@ BRG. N. ABUT.	119+24.45	21.00	655.46	655.46
@ EXP. JT.	119+25.37	21.00	655.43	655.43
BK. N. ABUT.	119+27.45	21.00	655.35	655.35

BEAM 14

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+53.61	24.00	658.88	658.88
@ EXP. JT.	116+55.69	24.00	658.90	658.90
@ BRG. S. ABUT.	116+56.61	24.00	658.90	658.90
A	116+66.61	24.00	658.98	659.07
B	116+76.61	24.00	659.04	659.21
C	116+86.61	24.00	659.08	659.33
D	116+96.61	24.00	659.11	659.41
E	117+06.61	24.00	659.12	659.45
F	117+16.61	24.00	659.12	659.46
G	117+26.61	24.00	659.10	659.43
H	117+36.61	24.00	659.06	659.36
I	117+46.61	24.00	659.01	659.26
J	117+56.61	24.00	658.94	659.14
K	117+66.61	24.00	658.85	658.99
L	117+76.61	24.00	658.75	658.84
M	117+86.61	24.00	658.64	658.68
@ BRG. PIER	118+00.61	24.00	658.45	658.45
N	118+10.61	24.00	658.29	658.28
O	118+20.61	24.00	658.12	658.12
P	118+30.61	24.00	657.93	657.95
Q	118+40.61	24.00	657.73	657.78
R	118+50.61	24.00	657.51	657.59
S	118+60.61	24.00	657.28	657.38
T	118+70.61	24.00	657.03	657.15
U	118+80.61	24.00	656.76	656.89
V	118+90.61	24.00	656.47	656.60
W	119+00.61	24.00	656.18	656.28
X	119+10.61	24.00	655.86	655.93
@ BRG. N. ABUT.	119+24.61	24.00	655.39	655.39
@ EXP. JT.	119+25.52	24.00	655.36	655.36
BK. N. ABUT.	119+27.61	24.00	655.29	655.29

BEAM 15

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+53.97	31.00	658.74	658.74
@ EXP. JT.	116+56.06	31.00	658.76	658.76
@ BRG. S. ABUT.	116+56.97	31.00	658.77	658.77
A	116+66.97	31.00	658.84	658.93
B	116+76.97	31.00	658.90	659.08
C	116+86.97	31.00	658.94	659.19
D	116+96.97	31.00	658.97	659.27
E	117+06.97	31.00	658.98	659.31
F	117+16.97	31.00	658.98	659.32
G	117+26.97	31.00	658.96	659.29
H	117+36.97	31.00	658.92	659.22
I	117+46.97	31.00	658.87	659.12
J	117+56.97	31.00	658.80	658.99
K	117+66.97	31.00	658.71	658.85
L	117+76.97	31.00	658.61	658.70
M	117+86.97	31.00	658.49	658.53
@ BRG. PIER	118+00.97	31.00	658.30	658.30
N	118+10.97	31.00	658.15	658.14
O	118+20.97	31.00	657.97	657.97
P	118+30.97	31.00	657.79	657.80
Q	118+40.97	31.00	657.58	657.63
R	118+50.97	31.00	657.36	657.44
S	118+60.97	31.00	657.13	657.23
T	118+70.97	31.00	656.88	657.00
U	118+80.97	31.00	656.61	656.74
V	118+90.97	31.00	656.32	656.45
W	119+00.97	31.00	656.02	656.13
X	119+10.97	31.00	655.71	655.77
@ BRG. N. ABUT.	119+24.97	31.00	655.24	655.24
@ EXP. JT.	119+25.89	31.00	655.21	655.21
BK. N. ABUT.	119+27.97	31.00	655.13	655.13

G:\IDOT\21850_006_CumberlandAve\Drawings\CADD Sheets\016014-sh-t-tsl-DkElevTbl.6.dgn