

BEAM 16

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+54.34	38.00	658.60	658.60
@ EXP. JT.	116+56.42	38.00	658.62	658.62
@ BRG. S. ABUT.	116+57.34	38.00	658.63	658.63
A	116+67.34	38.00	658.70	658.80
B	116+77.34	38.00	658.76	658.94
C	116+87.34	38.00	658.80	659.05
D	116+97.34	38.00	658.83	659.13
E	117+07.34	38.00	658.84	659.17
F	117+17.34	38.00	658.84	659.18
G	117+27.34	38.00	658.81	659.14
H	117+37.34	38.00	658.78	659.08
I	117+47.34	38.00	658.72	658.98
J	117+57.34	38.00	658.65	658.85
K	117+67.34	38.00	658.57	658.71
L	117+77.34	38.00	658.47	658.55
M	117+87.34	38.00	658.35	658.39
@ BRG. PIER	118+01.34	38.00	658.16	658.16
N	118+11.34	38.00	658.00	657.99
O	118+21.34	38.00	657.83	657.82
P	118+31.34	38.00	657.64	657.66
Q	118+41.34	38.00	657.44	657.48
R	118+51.34	38.00	657.21	657.29
S	118+61.34	38.00	656.98	657.08
T	118+71.34	38.00	656.73	656.85
U	118+81.34	38.00	656.46	656.59
V	118+91.34	38.00	656.17	656.30
W	119+01.34	38.00	655.87	655.98
X	119+11.34	38.00	655.56	655.62
@ BRG. N. ABUT.	119+25.34	38.00	655.09	655.09
@ EXP. JT.	119+26.26	38.00	655.05	655.05
BK. N. ABUT.	119+28.34	38.00	654.98	654.98

BEAM 17

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+54.71	45.00	658.47	658.47
@ EXP. JT.	116+56.79	45.00	658.49	658.49
@ BRG. S. ABUT.	116+57.71	45.00	658.49	658.49
A	116+67.71	45.00	658.57	658.66
B	116+77.71	45.00	658.62	658.80
C	116+87.71	45.00	658.67	658.91
D	116+97.71	45.00	658.69	658.99
E	117+07.71	45.00	658.70	659.03
F	117+17.71	45.00	658.70	659.04
G	117+27.71	45.00	658.67	659.00
H	117+37.71	45.00	658.63	658.94
I	117+47.71	45.00	658.58	658.83
J	117+57.71	45.00	658.51	658.71
K	117+67.71	45.00	658.42	658.56
L	117+77.71	45.00	658.32	658.41
M	117+87.71	45.00	658.20	658.24
@ BRG. PIER	118+01.71	45.00	658.01	658.01
N	118+11.71	45.00	657.85	657.85
O	118+21.71	45.00	657.68	657.68
P	118+31.71	45.00	657.49	657.51
Q	118+41.71	45.00	657.29	657.33
R	118+51.71	45.00	657.07	657.14
S	118+61.71	45.00	656.83	656.94
T	118+71.71	45.00	656.58	656.70
U	118+81.71	45.00	656.31	656.44
V	118+91.71	45.00	656.02	656.15
W	119+01.71	45.00	655.72	655.82
X	119+11.71	45.00	655.40	655.47
@ BRG. N. ABUT.	119+25.71	45.00	654.93	654.93
@ EXP. JT.	119+26.63	45.00	654.90	654.90
BK. N. ABUT.	119+28.71	45.00	654.83	654.83

BEAM 18

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+55.08	52.00	658.33	658.33
@ EXP. JT.	116+57.16	52.00	658.35	658.35
@ BRG. S. ABUT.	116+58.08	52.00	658.36	658.36
A	116+68.08	52.00	658.43	658.52
B	116+78.08	52.00	658.49	658.66
C	116+88.08	52.00	658.53	658.77
D	116+98.08	52.00	658.55	658.85
E	117+08.08	52.00	658.56	658.89
F	117+18.08	52.00	658.56	658.90
G	117+28.08	52.00	658.53	658.86
H	117+38.08	52.00	658.49	658.79
I	117+48.08	52.00	658.44	658.69
J	117+58.08	52.00	658.37	658.57
K	117+68.08	52.00	658.28	658.42
L	117+78.08	52.00	658.18	658.26
M	117+88.08	52.00	658.06	658.10
@ BRG. PIER	118+02.08	52.00	657.87	657.87
N	118+12.08	52.00	657.71	657.70
O	118+22.08	52.00	657.53	657.53
P	118+32.08	52.00	657.34	657.36
Q	118+42.08	52.00	657.14	657.18
R	118+52.08	52.00	656.92	656.99
S	118+62.08	52.00	656.68	656.79
T	118+72.08	52.00	656.43	656.55
U	118+82.08	52.00	656.16	656.29
V	118+92.08	52.00	655.87	656.00
W	119+02.08	52.00	655.57	655.67
X	119+12.08	52.00	655.25	655.32
@ BRG. N. ABUT.	119+26.08	52.00	654.78	654.78
@ EXP. JT.	119+26.99	52.00	654.75	654.75
BK. N. ABUT.	119+29.08	52.00	654.68	654.68

G:\IDOT\21850_006_CumberlandAve\Drawings\CADD Sheets\016014-sh-t-tsl-DkElevTbl.7.dgn