

BEAM 19

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+55.44	59.00	658.19	658.19
@ EXP. JT.	116+57.53	59.00	658.21	658.21
@ BRG. S. ABUT.	116+58.44	59.00	658.22	658.22
A	116+68.44	59.00	658.29	658.38
B	116+78.44	59.00	658.35	658.52
C	116+88.44	59.00	658.39	658.64
D	116+98.44	59.00	658.41	658.71
E	117+08.44	59.00	658.42	658.75
F	117+18.44	59.00	658.41	658.76
G	117+28.44	59.00	658.39	658.72
H	117+38.44	59.00	658.35	658.65
I	117+48.44	59.00	658.30	658.55
J	117+58.44	59.00	658.22	658.42
K	117+68.44	59.00	658.14	658.28
L	117+78.44	59.00	658.03	658.12
M	117+88.44	59.00	657.91	657.95
@ BRG. PIER	118+02.44	59.00	657.72	657.72
N	118+12.44	59.00	657.56	657.55
O	118+22.44	59.00	657.39	657.38
P	118+32.44	59.00	657.20	657.21
Q	118+42.44	59.00	656.99	657.04
R	118+52.44	59.00	656.77	656.85
S	118+62.44	59.00	656.53	656.64
T	118+72.44	59.00	656.28	656.40
U	118+82.44	59.00	656.01	656.14
V	118+92.44	59.00	655.72	655.85
W	119+02.44	59.00	655.42	655.52
X	119+12.44	59.00	655.10	655.17
@ BRG. N. ABUT.	119+26.44	59.00	654.63	654.63
@ EXP. JT.	119+27.36	59.00	654.60	654.60
BK. N. ABUT.	119+29.44	59.00	654.52	654.52

BEAM 20

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
BK. S. ABUT.	116+55.81	66.00	658.06	658.06
@ EXP. JT.	116+57.89	66.00	658.07	658.07
@ BRG. S. ABUT.	116+58.81	66.00	658.08	658.08
A	116+68.81	66.00	658.15	658.25
B	116+78.81	66.00	658.21	658.39
C	116+88.81	66.00	658.25	658.50
D	116+98.81	66.00	658.27	658.57
E	117+08.81	66.00	658.28	658.61
F	117+18.81	66.00	658.27	658.61
G	117+28.81	66.00	658.25	658.58
H	117+38.81	66.00	658.21	658.51
I	117+48.81	66.00	658.15	658.41
J	117+58.81	66.00	658.08	658.28
K	117+68.81	66.00	657.99	658.13
L	117+78.81	66.00	657.89	657.98
M	117+88.81	66.00	657.77	657.81
@ BRG. PIER	118+02.81	66.00	657.57	657.57
N	118+12.81	66.00	657.42	657.41
O	118+22.81	66.00	657.24	657.24
P	118+32.81	66.00	657.05	657.07
Q	118+42.81	66.00	656.84	656.89
R	118+52.81	66.00	656.62	656.70
S	118+62.81	66.00	656.38	656.49
T	118+72.81	66.00	656.13	656.25
U	118+82.81	66.00	655.86	655.99
V	118+92.81	66.00	655.57	655.70
W	119+02.81	66.00	655.27	655.37
X	119+12.81	66.00	654.95	655.01
@ BRG. N. ABUT.	119+26.81	66.00	654.48	654.48
@ EXP. JT.	119+27.73	66.00	654.44	654.44
BK. N. ABUT.	119+29.81	66.00	654.37	654.37

G:\IDOT\21850_006_CumberlandAve\Drawings\CADD Sheets\016014-sh-t-tsl-DkElevTbl.8.dgn