

LANDSCAPING LEGEND

-  SEEDING CLASS 2A
-  TOPSOIL, 6" WEED CONTROL
-  SEEDING CLASS 4
-  TOPSOIL, 6" WEED CONTROL
-  SEEDING CLASS 4B (MOD)
-  TOPSOIL, 6" WEED CONTROL
-  SODDING, SALT TOLERANT
-  TOPSOIL, 24" (MEDIAN ONLY) WEED CONTROL
-  TOPSOIL 6" (EXCEPT MEDIAN) WEED CONTROL
-  EROSION CONTROL BLANKET

SELECTIVE MOWING STAKE WITH WETLAND OR PRAIRIE PLANT SIGN

**US Route 45
LaGrange Rd**


STA 276+57, RT
STA 302+95, LT
D3-2 (72" X 30")
2-WOOD POST (4" X 4")

THERMOPLASTIC PAVEMENT MARKING - LINE 4" (WHITE) 10' DASH, 30' SKIP (TYPICAL)
RAISED REFLECTIVE PAVEMENT MARKERS (TYPICAL) SEE NOTES.

THERMOPLASTIC PAVEMENT MARKING - LINE 6" (WHITE)
RAISED REFLECTIVE PAVEMENT MARKERS (TYPICAL) SEE NOTES

THERMOPLASTIC PAVEMENT MARKING - LETTERS & SYMBOLS (WHITE) TYPICAL SEE DISTRICT 1 STD TC-13 FOR DETAILS

PAVEMENT MARKING LIMITS
STA 303+94.00
MATCH EXISTING



PAVEMENT MARKING LIMITS
STA 272+96.00
MATCH EXISTING

LEFT LANE
MUST
TURN LEFT

STA 274+20, CT
R3-7 (30" X 30")
METAL POST TYPE B

THERMOPLASTIC PAVEMENT MARKING - LINE 6" (DOTTED WHITE)
3' DASH, 9' SKIP (TYP)

THERMOPLASTIC PAVEMENT MARKING - LINE 6" (WHITE)
POLYUREA PAVEMENT MARKING TYPE I
LINE 24" (WHITE) STOP BAR (TYPICAL)



STA 275+85, LT
STA 275+85, RT
STA 301+66, LT
STA 302+77, RT
R8-3 (24" X 24")
METAL POST TYPE B

LANDSCAPING NOTES:

1. PLAN VIEW BREAKS BETWEEN SEEDING TYPES ARE APPROXIMATE. SEE PROPOSED CROSS SECTIONS FOR DETAILS.
2. MULCH METHOD 2 SHALL BE USED AT ALL SEEDING LOCATIONS NOT PROTECTED BY EROSION CONTROL BLANKET. HATCHING HAS BEEN OMITTED FOR CLARITY.
3. WEED CONTROL, NON-SELECTIVE AND NON-RESIDUAL SHOULD BE USED AT ALL SEEDING CLASS 4 AREAS ADJACENT TO WETLAND AND FOREST PRESERVE.
4. WEED CONTROL, BROADLEAF, SHOULD BE USED IN TURF AREAS INCLUDING ALL SEEDING 2A AND SODDING.
5. WEED CONTROL, TEASEL SHOULD BE USED ALONG RIGHT-OF-WAY WHERE PRESENT.

PAVEMENT MARKING NOTES:

1. FOR PCC PAVEMENT:
POLYUREA PAVEMENT MARKING TYPE I SHALL BE USED FOR FINAL PAVEMENT MARKINGS OF THE SIZE AND COLOR SPECIFIED.
2. FOR HOT-MIX ASPHALT PAVEMENT:
THERMOPLASTIC PAVEMENT MARKING SHALL BE USED FOR FINAL PAVEMENT MARKINGS OF THE SIZE AND COLOR SPECIFIED.
3. FOR RAISED REFLECTIVE PAVEMENT MARKERS PLACEMENT,
SPACING AND COLOR SEE DISTRICT 1 STANDARD TC-11.

LEGEND

- ONE-WAY CRYSTAL MARKER
- ONE-WAY AMBER MARKER
- TWO-WAY AMBER MARKER



**US Route 45
LaGrange Rd**

STA 325+60, RT
STA 330+38, LT
D3-2 (72" X 30")
2-WOOD POST (4" X 4")



STA 331+29, LT
R3-5R (30" X 36")
METAL POST TYPE B

PAVEMENT MARKING LIMITS
STA 322+75.00
MATCH EXISTING



STA 324+72, LT
STA 324+92, RT
R1-1 (36" X 36")
METAL POST TYPE B

THERMOPLASTIC PAVEMENT MARKING - LINE 6" (WHITE)
POLYUREA PAVEMENT MARKING TYPE I
- LINE 24" (WHITE) STOP BAR (TYP)

THERMOPLASTIC PAVEMENT MARKING - LINE 6" (WHITE)

THERMOPLASTIC PAVEMENT MARKING - LETTERS & SYMBOLS (WHITE) TYPICAL SEE DISTRICT 1 STD TC-13 FOR DETAILS

PAVEMENT MARKING LIMITS
STA 331+35.00
MATCH EXISTING



STA 330+78, RT
R8-3 (24" X 24")
METAL POST TYPE B



STA 326+06, LT
W14-3 (48" X 48" X 36")
2-METAL POST TYPE B

100 S. WACKER DR.
SUITE 600
CHICAGO, IL 60606
TEL (312) 939-1000
FAX (312) 939-4998



FILE NAME = D160M61-SHT-LNDSCP-PMK05.dgn	USER NAME = Anthony.Plutz	DESIGNED - BFH	REVISED -
		DRAWN - BFH	REVISED -
		CHECKED - MJT	REVISED -
		DATE - 03/13/2013	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

LANDSCAPING, PAVEMENT MARKING AND SIGNING PLAN
153RD STREET AND 149TH STREET

SCALE: 1"=50' SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
330	103R-4	COOK	877	301
LA-05		CONTRACT NO. 60M61		
ILLINOIS FED. AID PROJECT				