



NOTES:

- 1. Actual quantities of repairs shall be approved by the Engineer.
- Existing vertical reinforcement extending into the removal area shall be cleaned, straightened, and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
- 3. Cost of removal of existing bearings shall be included in the cost of Jacking and Cribbing.

LEGEND

Concrete Removal

Structural Repair of Concrete (Depth equal to or less than 5 inches)

— Epoxy Crack Injection

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Concrete Removal	Cu. Yd.	19.8
Structural Repair of Concrete (Depth equal to or less than 5 inches)	Sq. Ft.	126
Epoxy Crack Injection	Foot	3
Jacking and Cribbing	Each	8
		•

BOWMAN, BARRETT & ASSOCIATES INC. CONSULTING ENGINEERS
Chicago, Illinois
312.228.0100
www.bbandainc.com

USER NAME = DESIGNED - TL REVISED CHECKED - BAK REVISED PLOT SCALE = DRAWN MTR REVISED PLOT DATE = 11/08/2012 CHECKED - TL REVISED

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 6 REMOVAL AND REPAIR DETAILS STRUCTURE NO. 016-2437 SHEET NO. S-53 OF S-83 SHEETS

SECTION COUNTY 94 2012-060-BR COOK 285 216 CONTRACT NO. 60V61