GENERAL NOTES

INDEX OF SHEETS

SHT_NO	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS, STANDARDS, GENERAL NOTES
3-4	SUMMARY OF QUANTITIES
5-6	TYPICAL SECTIONS
7 - 8	SCHEDULES OF QUANTITIES
9	TIE POINTS/PAVEMENT MARKINGS
10	GEOPAK ELEMENTS IDENTIFICATION SHEET
11	PROPOSED REMOVAL AND CONSTRUCTION SHEET
12	RIGHT OF WAY SHEET
1 3	GEOMETRICS SHEET
14	SIDEWALK ELEVATIONS
15	TRUCK ROUTE DETOUR
16	CURB DETAIL SHEETS
17	SIGN DETAIL SHEETS
18-26	CROSS-SECTIONS

STANDARDS

000001-06	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
353001-04	PCC BASE COURSE WITH HMA BINDER AND SURFACE COURSES
424001-07	PERPENDICULAR CURB RAMPS FOR SIDEWALKS
424011-01	CORNER PARALLEL CURB RAMPS FOR SIDEWALKS
606001-05	CONCRETE CURB TYPE B AND COMBINATION CONCRETE
	CURB AND GUTTER
701701-08	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701801-05	LANE CLOSURE MULTILANE 1W OR 2W CROSSWALK OR
	SIDEWALK CLOSURE

701901-02

USER NAME * russellof

FILE NAME *

١.	FAC	TQR:	SUSEE) FOR	ES.	TIMATI	٧G	PLAN	OUAN	TITIE	S ARE	A5	FOLLOWS	AND	SHALL
	NOT	₽€	USED	FOR	THE	BASIS	OF	FINA	ער סח	ANTIT	[ES:				

ALL HOT MIX ASPHALT	2.016 TONS/CU YD
ALL AGGREGATE	2.05 TONS/CU YO
BITUMINOUS MATERIALS:	
ON PAVEMENT	0.09 GAL/SO YD
INTERMEDIATE LIFTS	
(FOG COATS)	0.04 GAL/SO YD
ON AGGREGATE SURFACE	0.32 GAL/SQ YD
AGGREGATE (PRIME COAT)	0.0015 TONS/SO YD

- 2. PROTECTIVE COAT SHALL BE APPLIED TO CONCRETE CURB AND GUTTER 420. 18 OF THE STANDARD SPECIFICATIONS.
- 3. AT ALL LOCATIONS WHERE THE PROPOSED BITUMINOUS OR CONCRETE PAVEMENT JOINS AN EXISTING BITUMINOUS OR CONCRETE PAVEMENT. A FULL DEPTH SAWED JOINT SHALL BE CONSTRUCTED. THE COST OF THIS JOINT WILL BE INCLUDED IN THE COST OF THE TYPE OF PAVEMENT BEING CONSTRUCTED.
- 4. PRIOR TO PLACEMENT OF THE FINAL PAYEMENT MARKINGS THE RESIDENT ENGINEER SHOULD CONTACT THE BUREAU OF OPERATIONS AND ARRANGE FOR INSPECTION AND APPROVAL OF THE PAYEMENT MARKING LAYOUT.
- 5. FORMS FOR COMBINATION CONCRETE CURB AND GUTTER SHALL BE METAL ONLY. EXCEPT THAT WOOD FORMS MAY BE USED ON SHORT RADIUS CURVES.
- 6. SIDEWALK REMOVAL ADJACENT TO EXISTING BUILDINGS SHALL BE DONE BY HAND. SPECIAL CARE SHALL BE TAKEN NOT TO DISTURB EXISTING BRICK OR EXISTING CURB. THE CONTRACTOR WILL BE RESPONSIBLE FOR DAMAGES TO THE EXISTING BRICK OR CURB.
- 7. COMMITMENTS: NO LANE CLOSURE DURING THRESHERMANS FESTIVAL FROM AUGUST 14TH TO AUGUST 18TH

Location(s):	Hot-Mix Asphalt Surface Course
Mîxture Use(s):	Polymerized Hot-Mix Asphalt Surface Course, Mix D. N105
AC/PG:	SBS PG76-22
RAP % (Mgx):	SEE SPECIAL PROVISIONS
Design Air Voids:	4.0 %, 105 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-9.5 mm or IL12.5 mm
Friction Aggregate:	D Surface

Location(s):	Hot-Mix Asphalt Binder Course
Mixture Use(s):	Polymerized Hot-Mix Asphalt Leveling Binder, N90, IL-9,5 Fine-Graded
AC/PG:	SBS PG76-22
RAP % (Mgx):	SEE SPECIAL PROVISIONS
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-9.5 FG
Friction Aggregate:	None

Examined By: Examined By: Examined By Examined By

Examined By:

Prepared By:

Examined By:

Approved By:

REVISED -INDEX OF SHEETS STATE OF ILLINOIS REVISED 42

SCALE:

DRAWN ci\p*.work\p+idot\=ussellof\d\$318837\783\$4-shto-cvr.soq.index.dgn PLOT SCALE . 120,0000 1/ 10. CHECKED -REVISED PLOT DATE = 1/23/2013 DATE -REVISED

DESIGNED -

DEPARTMENT OF TRANSPORTATION

STANDARDS, GENERAL NOTES OF SHEETS STA. SHEET TO STA.

COUNTY TOTAL SHEET NO.
PERRY 26 2 SECTION CONTRACT NO. 78324 ILLINOIS FED. AID PROJECT