

Prepared By: Joe Zlaniewicz
DISTRICT STUDIES & PLANS ENGINEER

Examined By: James Linn Eng
DISTRICT LAND ACQUISITION ENGINEER

Examined By: Connie Nuber
DISTRICT PROGRAM DEVELOPMENT ENGINEER

Examined By: Will Nels
DISTRICT OPERATIONS ENGINEER

Examined By: Doug Halferich
DISTRICT CONSTRUCTION ENGINEER

Examined By: Bruce Whitehead
DISTRICT MATERIALS ENGINEER

Examined By: KR
DISTRICT PROJECT IMPLEMENTATION ENGINEER

Approved By: Omer Osman Jr
DEPUTY DIRECTOR OF HIGHWAYS, REGION 5 ENGINEER

AUGUST 17, 2012
DATE

MIXTURES REQUIREMENTS

Location(s):	Hot-Mix Asphalt Surface Course
Mixture Use(s):	Hot-Mix Asphalt Surface Course, Mix D, N90
AC/PG:	PG64-22
RAP % (Max):	SEE SPECIAL PROVISIONS
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-9.5 mm or IL12.5 mm
Friction Aggregate:	D Surface

Location(s):	Hot-Mix Asphalt Binder Course
Mixture Use(s):	Hot-Mix Asphalt Leveling Binder, N90, IL-9.5 Fine-Graded
AC/PG:	PG64-22
RAP % (Max):	SEE SPECIAL PROVISIONS
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-9.5 FG
Friction Aggregate:	None

Location(s):	Hot-Mix Asphalt Incidental Surface Course
Mixture Use(s):	Hot-Mix Asphalt Surface Course, Mix C, N70
AC/PG:	PG64-22
RAP % (Max):	SEE SPECIAL PROVISIONS
Design Air Voids:	4.0 %, 70 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-9.5 mm or IL12.5 mm
Friction Aggregate:	C Surface

Location(s):	Hot-Mix Asphalt Shoulders
Mixture Use(s):	Hot-Mix Asphalt Shoulders, N30
AC/PG:	PG58-22
RAP % (Max):	SEE SPECIAL PROVISIONS
Design Air Voids:	2.0 %, 30 Gyration Design
Mixture Composition: (Gradation Mixture)	HMA Shoulder
Friction Aggregate:	None