

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
355	10-00196-03-RS	LIVINGSTON	5	5

PROJECT NO. RS-0355(121)

SCHEDULE OF RESURFACING QUANTITIES

Unit weight Constant = 112.0 lbs./s.y./inch

LOCATION (QUANTITY)	LENGTH	AREA (SQ YD)	HMA SURF REMOVAL VAR DEPTH (SQ YD)	HMA SURF REMOVAL DECK (SQ YD)	SHORT- TERM PAVT MARKING (FOOT)	WORK ZONE PAVT MK REM (SQ FT)	PAINT PVT MARKING LINE, 4" (FOOT)	BIT MATLS PR CT * (GALLON)	BIT MATLS PR CT MC-30 (GALLON)	AGG PR CT (TON)	AREA REFL CR CONT (SQ YD)	WATERPRF MEMBRANE SYSTEM (SQ YD)	LEVEL BINDER IL-9.5 N50 (TON)	BIT CONC SURF CSE "C" N50 (TON)	INCIDENTAL BIT SURF (TON)	AGG WEDGE SHOULDERS TYPE B (TON)
+33. to 1+83. (TAPER)	150	367	257	-	30	5	38	18	-	-	122	-	7	31	-	13
1+83. to 88+53.	8670	21193	-	-	1734	289	2168	1,060	-	42	21193	-	1,187	1,780	-	1097
88+53. to 90+28. (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
90+28. to 90+52. (053-3034)	24	59	59	-	4	1	6	3	-	-	59	-	3	5	-	-
90+52. to 92+27. (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
92+27. to 106+11.	1384	3383	-	-	276	46	346	169	-	7	3383	-	189	284	-	175
106+11. to 107+00. Sta Eq.	89	218	-	-	-	-	-	-	-	-	-	-	-	-	-	-
107+00. to 217+84.81	11085	27096	-	-	2216	369	2771	1,355	-	54	27096	-	1,517	2,276	-	1403
217+84.81 to 217+85.45 Sta Eq.	0.64	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-
217+85.45 to 291+13.5	7328	17913	-	-	1466	244	1832	896	-	36	17913	-	1,003	1,505	-	927
291+13.5 to 292+88.5 (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
292+88.5 to 293+33.5 (053-3033)	45	110	-	-	-	-	-	-	-	-	-	-	-	-	-	-
293+33.5 to 295+08.5 (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
295+08.5 to 372+65.	7757	18960	-	-	1552	259	1939	948	-	38	18960	-	1,062	1,593	-	982
372+65. to 373+00. Sta Eq.	35	86	-	-	-	-	-	-	-	-	-	-	-	-	-	-
373+00. to 432+51.5	5952	14548	-	-	1190	198	1488	727	-	29	14548	-	815	1,222	-	753
432+51.5 to 434+26.5 (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
434+26.5 to 434+69.5 (053-3032)	43	105	105	-	8	1	11	5	-	-	105	-	6	9	-	5
434+69.5 to 436+44.5 (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
436+44.5 to 496+76.72	6032	14745	-	-	1206	201	1508	737	-	29	14745	-	826	1,239	-	763
496+76.72 to 498+51.72 (TAPER)	175	428	244	-	36	6	44	21	-	-	122	-	7	36	-	13
498+51.72 to 499+92.38 (053-3447)	140.7	469	141	469	28	5	35	23	-	-	-	469	26	39	-	-
499+92.38 to 500+28. End	36	87	175	-	8	1	9	4	-	-	-	-	-	7	-	-
Sta. Eqs. And 053-3033 Omission	-169.64	-415	-	-	-	-	-	-	-	-	-	-	-	-	-	-
TOTAL JOB LENGTH OR MAINLINE QUANTITY	49825.36	121795	2447	469	9970	1661	12456	6092	-	235	118978	469	6690	10242	-	6209
MISCELLANEOUS																
PRIVATE & COMMERCIAL ENTRANCES (29)	-	-	-	-	-	-	-	-	245.0	-	-	-	33	52	182.0	-
SIDEROAD INTERSECTIONS (16)	-	-	-	-	-	-	-	144.0	-	-	-	-	64	64	240.0	-
M.B.T.O.'s (16)	-	-	-	-	-	-	-	-	-	-	-	-	14	22	-	-
TOTALS OF MAINLINE & MISC.	49,825	121,795	2,447	469	9,970	1,661	12,456	6,236	245	235	118,978	469	6,801	10,380	422	6,209

CLASS "D" PATCH, TYPE IV, 6 INCH IS LOCATED AT STATION 481+71 OVER A CULVERT REPLACEMENT DONE BY OTHERS. APPROX. DIMENSIONS = 22' X 45'.

* BITUMINOUS MATERIALS (PRIME COAT) SHALL BE IN ACCORDANCE WITH THE TABLE SHOWN IN ARTICLE 406.02 OF THE STANDARD SPECIFICATIONS.

Z:\COW\ROAD Projects\00198RS3-Flanagan-Long\PT\Planning\Est\Cost-Resurf\Sched-Flan\Long\Plat\SchedResurfChys