

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P.	05-00130-00-BR	WILL	41	35
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT-	

SHEET NO. 23
OF 23 SHEETS

CONTRACT NO. 83889

AGI Job No. 04-225		BORING LOG NO. SB-12		Sheet 1 of 2																																																																																																		
CLIENT URS		PROJECT Proposed Route 59 Pedestrian Bridge																																																																																																				
STATION: 116+50		OFFSET (ft): CL		LOCATION IL Route 59 at ComEd Easement																																																																																																		
COUNTY: Will		<table border="1"> <thead> <tr> <th rowspan="2">DEPTH (FT.)</th> <th colspan="3">SAMPLES</th> <th colspan="4">TESTS</th> </tr> <tr> <th>SPT-N BLOWS / FT.</th> <th>NUMBER</th> <th>TYPE</th> <th>% RECOVERY</th> <th>MOISTURE, %</th> <th>DRY DENSITY PCF</th> <th>Qu tsf Failure Type</th> <th>HN: Units ppm</th> <th>Estim. Coefficient of Permeability k_v (cm/sec)</th> </tr> </thead> <tbody> <tr> <td>0-38.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>38.5-41.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>41.0-45.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>45.0-50.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>50.0-55.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>55.0-60.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>60.0-65.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>65.0-65.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				DEPTH (FT.)	SAMPLES			TESTS				SPT-N BLOWS / FT.	NUMBER	TYPE	% RECOVERY	MOISTURE, %	DRY DENSITY PCF	Qu tsf Failure Type	HN: Units ppm	Estim. Coefficient of Permeability k _v (cm/sec)	0-38.5										38.5-41.0										41.0-45.0										45.0-50.0										50.0-55.0										55.0-60.0										60.0-65.0										65.0-65.5									
DEPTH (FT.)	SAMPLES						TESTS																																																																																															
	SPT-N BLOWS / FT.	NUMBER	TYPE	% RECOVERY	MOISTURE, %	DRY DENSITY PCF	Qu tsf Failure Type	HN: Units ppm	Estim. Coefficient of Permeability k _v (cm/sec)																																																																																													
0-38.5																																																																																																						
38.5-41.0																																																																																																						
41.0-45.0																																																																																																						
45.0-50.0																																																																																																						
50.0-55.0																																																																																																						
55.0-60.0																																																																																																						
60.0-65.0																																																																																																						
65.0-65.5																																																																																																						
Client Job No.: S.N. 099-6002		CITY & STATE: Naperville, Illinois																																																																																																				
SURFACE ELEVATION Datum: USGS 687.0		GRAPHIC LOG																																																																																																				
Drilling Without Sampling																																																																																																						
Continued on Next Page																																																																																																						
WATER LEVEL OBSERVATIONS		Applied GeoScience, Inc.		STARTED 4-24-06 FINISHED 4-24-06																																																																																																		
WL	▽ 38 WD	2385 Hammond Drive, Suite 6 Schaumburg, Illinois 60173 Tel: (847) 303-0300 Fax: (847) 303-0900		DRILL CO. Stryker	DRILL RIG D-60																																																																																																	
WL	▽			DRILLER Fred	ASST DRILLER GE																																																																																																	
WL	▽			ENGGEOL ND	APPROVED AMM																																																																																																	

AGI Job No. 04-225		BORING LOG NO. SB-12		Sheet 2 of 2																																																																																																		
CLIENT URS		PROJECT Proposed Route 59 Pedestrian Bridge																																																																																																				
STATION: 116+50		OFFSET (ft): CL		LOCATION IL Route 59 at ComEd Easement																																																																																																		
COUNTY: Will		<table border="1"> <thead> <tr> <th rowspan="2">DEPTH (FT.)</th> <th colspan="3">SAMPLES</th> <th colspan="4">TESTS</th> </tr> <tr> <th>SPT-N BLOWS / FT.</th> <th>NUMBER</th> <th>TYPE</th> <th>% RECOVERY</th> <th>MOISTURE, %</th> <th>DRY DENSITY PCF</th> <th>Qu tsf Failure Type</th> <th>HN: Units ppm</th> <th>Estim. Coefficient of Permeability k_v (cm/sec)</th> </tr> </thead> <tbody> <tr> <td>35-38.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>38.5-41.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>41.0-45.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>45.0-50.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>50.0-55.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>55.0-60.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>60.0-65.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>65.0-65.5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				DEPTH (FT.)	SAMPLES			TESTS				SPT-N BLOWS / FT.	NUMBER	TYPE	% RECOVERY	MOISTURE, %	DRY DENSITY PCF	Qu tsf Failure Type	HN: Units ppm	Estim. Coefficient of Permeability k _v (cm/sec)	35-38.5										38.5-41.0										41.0-45.0										45.0-50.0										50.0-55.0										55.0-60.0										60.0-65.0										65.0-65.5									
DEPTH (FT.)	SAMPLES						TESTS																																																																																															
	SPT-N BLOWS / FT.	NUMBER	TYPE	% RECOVERY	MOISTURE, %	DRY DENSITY PCF	Qu tsf Failure Type	HN: Units ppm	Estim. Coefficient of Permeability k _v (cm/sec)																																																																																													
35-38.5																																																																																																						
38.5-41.0																																																																																																						
41.0-45.0																																																																																																						
45.0-50.0																																																																																																						
50.0-55.0																																																																																																						
55.0-60.0																																																																																																						
60.0-65.0																																																																																																						
65.0-65.5																																																																																																						
Client Job No.: S.N. 099-6002		CITY & STATE: Naperville, Illinois																																																																																																				
(continued)		GRAPHIC LOG																																																																																																				
<p>38.5 SILTY CLAY, some sand & gravel, gray, hard, (CL) 648.5</p> <p>41.0 SAND & GRAVEL, with limestone, gray, wet, med. dense to dense, (SW-GP) 646.0</p> <p>65.0 LIMESTONE with sand, gray, Auger and spoon refusal at 65.5 feet. 622.0 621.5</p> <p>End Of Boring</p>																																																																																																						
WATER LEVEL OBSERVATIONS		Applied GeoScience, Inc.		STARTED 4-24-06 FINISHED 4-24-06																																																																																																		
WL	▽ 38 WD	2385 Hammond Drive, Suite 6 Schaumburg, Illinois 60173 Tel: (847) 303-0300 Fax: (847) 303-0900		DRILL CO. Stryker	DRILL RIG D-60																																																																																																	
WL	▽			DRILLER Fred	ASST DRILLER GE																																																																																																	
WL	▽			ENGGEOL ND	APPROVED AMM																																																																																																	

c:\naperville_25365506_pedbridge\bridge\pre-final\plans\drawings\23_soil_boring_12.dwg 12/8/2006 1:37:41 PM

DESIGNED MDS
CHECKED JPB
DRAWN MDS
CHECKED JPB

URS
100 South Wacker Drive,
Suite 500
Chicago, IL 60606
(312) 939-1000

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
SOIL BORING 12

ROUTE 59 PEDESTRIAN BRIDGE
CITY OF NAPERVILLE, WILL COUNTY

F.A.P. RTE. SECTION: 05-00130-00-BR
STATION 113+02.46 STRUCTURE NO. 099-6002
SCALE: N.T.S. DATE: 12/8/2006