

CONST. JT. - SOUTH EDGE OF WESTBOUND CLOSURE POUR

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10864.62	-38.84	808.38	808.38
⊕ Brg. N. Abut.	10870.24	-37.83	808.41	808.41
A	10880.08	-36.07	808.46	808.55
B	10889.92	-34.32	808.50	808.68
C	10899.77	-32.56	808.54	808.80
D	10909.61	-30.80	808.56	808.90
E	10919.46	-29.04	808.58	808.98
F	10929.30	-27.28	808.60	809.04
G	10939.14	-25.52	808.61	809.08
H	10948.99	-23.76	808.61	809.10
I	10958.83	-22.00	808.60	809.09
J	10968.68	-20.24	808.59	809.06
K	10978.52	-18.48	808.58	809.00
L	10988.36	-16.72	808.55	808.93
M	10998.21	-14.96	808.52	808.83
N	11008.05	-13.20	808.48	808.72
O	11017.90	-11.44	808.44	808.59
P	11027.74	-9.68	808.39	808.45
⊕ Brg. S. Abut.	11034.10	-8.54	808.36	808.36
Bk. S. Abut.	11039.71	-7.54	808.32	808.32

GIRDER 10

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10861.25	-36.90	808.40	808.40
⊕ Brg. N. Abut.	10866.86	-35.90	808.43	808.43
A	10876.71	-34.14	808.48	808.57
B	10886.55	-32.38	808.53	808.70
C	10896.39	-30.62	808.56	808.82
D	10906.24	-28.86	808.59	808.93
E	10916.08	-27.10	808.62	809.01
F	10925.93	-25.34	808.63	809.08
G	10935.77	-23.58	808.64	809.12
H	10945.61	-21.82	808.65	809.14
I	10955.46	-20.06	808.64	809.13
J	10965.30	-18.30	808.64	809.10
K	10975.15	-16.54	808.62	809.05
L	10984.99	-14.78	808.60	808.97
M	10994.83	-13.02	808.57	808.88
N	11004.68	-11.26	808.54	808.77
O	11014.52	-9.50	808.49	808.64
P	11024.37	-7.74	808.45	808.50
⊕ Brg. S. Abut.	11030.73	-6.61	808.41	808.41
Bk. S. Abut.	11036.34	-5.60	808.38	808.38

GIRDER 11

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10849.78	-30.32	808.46	808.46
⊕ Brg. N. Abut.	10855.40	-29.31	808.50	808.50
A	10865.24	-27.55	808.55	808.64
B	10875.08	-25.79	808.60	808.78
C	10884.93	-24.03	808.65	808.91
D	10894.77	-22.27	808.69	809.02
E	10904.62	-20.51	808.72	809.11
F	10914.46	-18.76	808.74	809.18
G	10924.30	-17.00	808.76	809.23
H	10934.15	-15.24	808.77	809.26
I	10943.99	-13.48	808.78	809.26
J	10953.83	-11.72	808.78	809.24
K	10963.68	-9.96	808.77	809.20
L	10973.52	-8.20	808.75	809.13
M	10983.37	-6.44	808.73	809.04
N	10993.21	-4.68	808.71	808.94
O	11003.05	-2.92	808.67	808.82
P	11012.90	-1.16	808.63	808.69
⊕ Brg. S. Abut.	11019.26	-0.02	808.60	808.60
Bk. S. Abut.	11024.87	0.98	808.54	808.54

GIRDER 12

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10838.32	-23.73	808.51	808.51
⊕ Brg. N. Abut.	10843.93	-22.73	808.55	808.55
A	10853.77	-20.97	808.62	808.71
B	10863.62	-19.21	808.67	808.85
C	10873.46	-17.45	808.73	808.99
D	10883.30	-15.69	808.77	809.11
E	10893.15	-13.93	808.81	809.21
F	10902.99	-12.17	808.84	809.29
G	10912.84	-10.41	808.87	809.34
H	10922.68	-8.65	808.89	809.38
I	10932.52	-6.89	808.90	809.39
J	10942.37	-5.13	808.91	809.37
K	10952.21	-3.37	808.91	809.33
L	10962.06	-1.61	808.90	809.27
M	10971.90	0.15	808.88	809.19
N	10981.74	1.91	808.81	809.04
O	10991.59	3.67	808.73	808.88
P	11001.43	5.43	808.64	808.70
⊕ Brg. S. Abut.	11007.79	6.56	808.59	808.59
Bk. S. Abut.	11013.40	7.57	808.53	808.53

GIRDER 13

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10826.85	-17.15	808.56	808.56
⊕ Brg. N. Abut.	10832.46	-16.14	808.60	808.60
A	10842.30	-14.38	808.67	808.76
B	10852.15	-12.62	808.74	808.91
C	10861.99	-10.86	808.80	809.06
D	10871.84	-9.10	808.85	809.18
E	10881.68	-7.34	808.89	809.29
F	10891.52	-5.59	808.93	809.38
G	10901.37	-3.83	808.97	809.44
H	10911.21	-2.07	808.99	809.48
I	10921.06	-0.31	809.01	809.50
J	10930.90	1.45	808.98	809.45
K	10940.74	3.21	808.94	809.37
L	10950.59	4.97	808.89	809.26
M	10960.43	6.73	808.83	809.14
N	10970.28	8.49	808.76	808.99
O	10980.12	10.25	808.69	808.84
P	10989.96	12.01	808.61	808.67
⊕ Brg. S. Abut.	10996.32	13.15	808.56	808.56
Bk. S. Abut.	11001.94	14.15	808.51	808.51

⊕ LONGITUDINAL JOINT

Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. N. Abut.	10824.15	-15.60	808.56	808.56
⊕ Brg. N. Abut.	10829.76	-14.59	808.61	808.61
A	10839.61	-12.83	808.68	808.77
B	10849.45	-11.07	808.75	808.93
C	10859.29	-9.31	808.81	809.07
D	10869.14	-7.55	808.86	809.20
E	10878.98	-5.80	808.91	809.31
F	10888.83	-4.04	808.95	809.40
G	10898.67	-2.28	808.99	809.46
H	10908.51	-0.52	809.02	809.51
I	10918.36	1.24	809.00	809.49
J	10928.20	3.00	808.96	809.43
K	10938.05	4.76	808.92	809.35
L	10947.89	6.52	808.87	809.25
M	10957.73	8.28	808.81	809.12
N	10967.58	10.04	808.75	808.98
O	10977.42	11.80	808.68	808.83
P	10987.27	13.56	808.61	808.66
⊕ Brg. S. Abut.	10993.63	14.70	808.55	808.55
Bk. S. Abut.	10999.24	15.70	808.50	808.50