



SOIL BORING LOG

Page 1 of 1
Date 5/18/11

ROUTE I-39 DESCRIPTION I-39 South Bound, MP 68.48, Station 540+00 LOGGED BY Larry Myers
SECTION D3 OVD Message SG-2012 LOCATION SE 1/4, SEC. 13, TWP. 35N, RNG. 1E
COUNTY LaSalle DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME Automatic

Table with columns for Depth (ft), Blow Count (blows/6"), and Soil Description. Includes data for Surface Water Elev., Stream Bed Elev., Groundwater Elev., and various soil types like Augered Shoulder Stone, Silty Clay Loam, etc.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
BBS, form 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 1
Date 5/18/11

ROUTE I-39 DESCRIPTION I-39 South Bound, MP 68.48, Station 540+00 LOGGED BY Larry Myers
SECTION D3 OVD Message SG-2012 LOCATION SE 1/4, SEC. 13, TWP. 35N, RNG. 1E
COUNTY LaSalle DRILLING METHOD Hollow Stem Auger HAMMER TYPE CME Automatic

Table with columns for Depth (ft), Blow Count (blows/6"), and Soil Description. Includes data for Surface Water Elev., Stream Bed Elev., Groundwater Elev., and various soil types like Augered Brown Silty Clay Loam, Hard Gray Silty Clay Loam, etc.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
BBS, form 137 (Rev. 8-99)

SOIL BORING LOG
I-39 SB, MP 68.48, STATION 540+00