

MAINLINE							
LOCATIONS MILE MARKERS	LENGTH	HMA SURF		MIX FOR JTS	BIT MAT	POLY HMA SURF	COMMENTS
		REM	VAR DEPTH	CRKS & FLANG	PRIME COAT	CSE "D", N90	
		SQ YD		TON	GALLON	TON	
SOUTHBOUND DRIVING LANE							
197.5 - 201.5	20656	29836		9.0	3879	5430	SN 053-0128 OMISSION
203.4 - 204.7	6864	9915		3.0	1289	1804	
NORTHBOUND DRIVING LANE							
195 - 196.7	8976	12965		3.9	1685	2360	
198.8 - 200.8	10560	15253		4.6	1983	2776	
TOTALS	47056	67970		20	8836	12370	

PAVEMENT MARKING									
LOCATIONS MILE MARKERS	LENGTH	URETHANE		GROOVE FOR	GROOVE FOR	RAISED REFL	RAISED REFL	SHORT TERM	WORK ZONE
		LINE 4"	LINE 8"	REC PAVT MARK 5"	REC PAVT MARK 9"	PAVT MARK	PAVT MARK REM	PAVT MARK	PAVT MARK REM
		FOOT	FOOT	FOOT	FOOT	EACH	EACH	FOOT	SQ FT
SOUTHBOUND DRIVING LANE									
197.5 - 201.5	18804	18804	877	18804	877	9	9	826	272.6
203.4-204.7	6864	6864		6864				275	90.8
NORTHBOUND DRIVING LANE									
195 - 196.7	8334	8334	417	8334	417	9	9	359	118.5
198.8 - 200.8	9878	9878	457	9878	457	12	12	422	139.3
TOTALS	43880	43880	1751	43880	1751	30	30	1882	621

CLASS A PATCHING							
LOCATION MILE MARKERS	NO. OF PATCHES	SOUTHBOUND DRIVING LANE					
		LENGTH	WIDTH	TY II	TY IV	PATCH	SAW
		FOOT	FOOT	SQ YD	SQ YD	SQ YD	FOOT
197.5 - 201.5							
TYPE II	12	6	12	96.0		96.0	744
TYPE IV	4	19	12		101.2	101.2	352
203.4 - 204.7							
TYPE II	3	6	12	24.0		24.0	186
TYPE IV	1	19	12		25.3	25.3	88
TOTALS				120	127	247	1370

CLASS A PATCHING							
LOCATION MILE MARKERS	NO. OF PATCHES	NORTHBOUND DRIVING LANE					
		LENGTH	WIDTH	TY II	TY IV	PATCH	SAW
		FOOT	FOOT	SQ YD	SQ YD	SQ YD	FOOT
195 - 196.7							
TYPE II	5	6	12	40.0		40.0	310
TYPE IV	1	19	12		25.3	25.3	88
198.8 - 200.8							
TYPE II	5	6	12	40.0		40.0	310
TYPE IV	1	19	12		25.3	25.3	88
TOTALS				80	51	131	796

SHOULDER REPAIR			
LOCATIONS MILE MARKERS	HMA SURF VAR DEPTH	BIT MAT PRIME COAT	HMA SHLDS
	SQ YD	GALLON	TON
VARIOUS LOCATIONS			
195 - 205	700	56	127
TOTALS	700	56	127