



STRUCTURE SCHEDULE											
STR NO.	STATION	OFFSET	RT/LT	TYPE	F&G	RIM EL.	INV. N	INV. S	INV. E	INV. W	REMARKS
38	STA. 28+01.61	13.00	RT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	642.55				639.42	
37	STA. 28+37.56	13.00	LT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	642.17	638.80		638.90		
36	STA. 29+80.69	14.23	LT	MANHOLES, TYPE A, 4'-DIAMETER, TYPE 1 FRAME, OPEN LID	FG TY 1 CL	640.98	634.36	637.41		634.26	
39	STA. 29+78.29	29.48	LT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	640.50		634.48	634.58		
40	STA. 29+50.52	47.69	LT	INLET, TYPE A	TY 8	640.10	635.00				
42	STA. 60+62.41	17.49	LT	INLETS, TYPE G-1	DIAGONAL	638.50				635.80	Control Point Given for B-6.12 Curb & Gutter
41	STA. 30+29.99	28.27	RT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	639.39				635.65	
35	STA. 30+48.73	13.00	LT	INLETS MANHOLE, TYPE G-1, 5'-DIAMETER	DIAGONAL	640.38	633.62				
34	STA. 31+68.19	13.00	LT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	639.62	632.37	632.17	636.78		
43	STA. 31+68.19	13.00	RT	INLETS, TYPE G-1	DIAGONAL	639.62				636.90	
33	STA. 32+15.96	13.00	LT	INLETS MANHOLE, TYPE G-1, 5'-DIAMETER	DIAGONAL	639.28	634.88	631.94		631.36	
47	STA. 32+71.52	13.00	RT	INLETS, TYPE G-1	DIAGONAL	639.12				636.30	
44	STA. 32+77.73	13.00	LT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	639.44	635.27	635.17		636.17	
45	STA. 33+48.32	13.00	LT	INLETS MANHOLE, TYPE G-1, 4'-DIAMETER	DIAGONAL	639.44	636.10(EX)	636.00		636.98	
46	STA. 33+48.31	26.38	LT	INLET, TYPE A	TY 6	639.50				637.10	
48	STA. 33+16.05	24.35	RT	INLET, TYPE A	TY 6	638.44				636.23	
49	STA. 33+15.04	20.1	RT	MANHOLE ADJUST WITH NEW TIF CL	FG TY 1 CL	639.3					EX. RIM = 637.78
50	STA. 33+76.11	19.86	RT	MANHOLE ADJUST WITH NEW TIF CL	FG TY 1 CL	640.16					EX. RIM = 639.53

PIPE SCHEDULE									
PIPE NO.	U/S - D/S	LENGTH (FT)	SIZE (IN)	CLASS/TYPE	U/S INV	D/S INV	SLOPE	TRENCH BACKFILL (CU YD.)	REMARKS
38	38-37	42	12	SS CL A 1	639.42	638.90	1.00%	5.5	
37	37-36	140	12	SS CL A 1	638.80	637.41	1.00%	25.2	
36	36-35	64	15	SS CL A 2	634.36	633.72	1.00%	58.6	
39	39-36	12	15	SS CL A 2	634.58	634.46	1.00%	8.9	
40	40-39	32	12	SS CL A 2	635.00	634.68	1.00%	15.2	
42	42-41	31	12	SS CL A 1	635.8	635.65	0.50%	4.7	
41	41-35	43	12	SS CL A 1	635.65	635.44	0.50%	12.0	
35	35-34	115	15	SS CL A 2	633.62	632.47	1.00%	101.4	
34	34-33	44	15	SS CL A 2	632.37	631.94	1.00%	41.4	
43	43-34	25	12	SS CL A 1	636.9	636.78	0.50%	3.3	
47	47-44	26	12	SS CL A 1	636.3	636.17	0.50%	3.4	
44	44-33	58	12	SS CL A 2	635.17	634.88	0.50%	14.9	
45	45-44	67	12	SS CL A 1	636.00	635.27	1.09%	13	
46	46-45	9	12	SS CL A 1	637.10	636.98	1.50%	1.2	
48	48-49	2	12	SS CL A 1	636.23	636.18	2.50%	0.3	
38A	38A-37	5	6	PIPE DRAIN	639.10	639.00	2.00%	0.5	CAP U.S. END

