



HEXAGON NUT
 AMER. NAT'L. STD. HEAVY HEX. FLAT NUT
 (ANSI B 18.2.2 - 1972)

FLAT WASHER
 AMER. NAT'L. STD. TYPE "B"
 SERIES "W"
 (ANSI B 18.22.1 - 1945, R1975)

LOCK WASHER
 AMER. NAT'L. STD. HELICAL SPRING LOCK WASHER, REGULAR
 (ANSI B 18.21.1 - 1972)

MATERIAL:

ASTM A-36 MODIFIED STEEL, 55 000 LBS. MINIMUM YIELD.
HARDWARE TO BE FURNISHED & ATTACHED IN PLACE ON ROD FOR SHIPPING:
 2 HEX. NUTS, HEAVY, GALV., 1".
 2 WASHERS, STEEL, ROUND, GALV., TYPE "B", SERIES "W", 1".
 1 WASHER, LOCK, STEEL, GALV., HELICAL SPRING, REGULAR, 1".
 BOLT & NUTS SHALL HAVE AN AMERICAN STANDARD CLASS 2 DR 3 FIT.
 (NUT IS TAPPED OVERSIZE BY 1/32")

1" x 60"
STEEL ANCHOR BOLT
 COMMODITY CODE 37-8180-0220

REVISED	CITY OF CHICAGO DEPT. OF STREETS AND SANITATION BUREAU OF ELECTRICAL ENGINEERING	
A 9-4-1983	DRAWN EUGENE GEPUIS	CHECKED A. MILLER
B	DESIGN ENGINEER	DATE
C		
D		
E		
Y		
B	SIZE 17" x 28"	SCALE 1/8"

830
 UNIT: SEPT. 3, 1983

A ZINC COATING, 0.0021 INCH IN THICKNESS
 SHALL BE APPLIED OVER THIS LENGTH AND
 COVERED WITH HEAVY NO-D-10, OR EQUAL,
 RUST INHIBITING COMPOUND

REVISIONS	
NAME	DATE

\tech\nt\p\0465\p\0465\elec\14\cvt\9\cvt\contract 902\dec05\2004\2004.dwg
 02/02/2005 09:02:37 AM