

TYPE I ELASTOMERIC EXP. BRG. PIER 1

³₄'' ¢ Threaded Stud with flat washer & hex nut. (4-Reqd.) 258" x 1'-4" x 2'-2" Bonded - Layers of 3₄" Elastomer (55 Durometer) -3 -3₁₆" Steel Plates

> Note: Shim plates shall not be placed under Bearing Assembly.


BEARING ASSEMBLY

NOTES

See sheet 16 of 29 for Anchor Bolt installation. $^{7}_{8}$ " ϕ holes in bottom flange for - $^{3}_{4}$ " ϕ studs will be drilled in the field for existing girders. Cost included with Jacking and Cribbing.

Anchor bolts at fixed bearings may be built into the masonry at proposed girders.

The Structural Steel bearing plates of the elastomeric bearing assembly shall conform to the requirements of AASHTO M270, Grade 50.




* Field weld at existing girders. Cost included with Jacking and Cribbing.

 $B \blacktriangleleft$

ROUTE NO.	SECTION	cou	NTY	TOTAL SHEETS	SHEET NO.	SHEET NO. 15
F.A.P. RTE. 774	107BY	EFFINGHAM		273	241	29 SHEETS
FED. ROAD D	IST. NO. 7	ILLINOIS	FED. AID	PROJECT-		


CONTRACT NO. 94827



ELEVATION AT PIER 2

SECTION B-B


FIXED BEARING PIER 2



PINTLE

Cost of existing bearing removal and disposal is included with Jacking and Cribbing, Total number to be removed = 24

EXISTING BEARING REMOVAL DETAIL



SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates. Weight included with Structural Steel.

JACKING AND CRIBBING PROCEDURE

- 1. The Contractor shall submit for approval by the Engineer, plans for jacking and cribbing prior to commencing any work at the bearings. See Special Provision for Jacking and Cribbing. Dead Load = 7 k per girder at each abutment and 23 k per girder at each pier. Use 10 ton min jack capacity at abutments and 25 ton min jack capacity at the piers.
- 2. Jacking and Cribbing shall be done after the existing concrete deck is removed.
- 3. The existing structural steel shall be raised according to the Special Provision for Jacking and Cribbing and to a height sufficient to form, pour and cure the concrete bearing seats, remove the existing bearings and install the new bearings.
- 4. Once the new bearings are in place the existing steel can be lowered into place and connected to the bearings.
- 5. After the existing and proposed girders are sitting on and connected to the new bearings and the proposed diaphragms are in place, forming for the new deck pour can begin.

BILL OF MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly Type I	Each	10
Jacking and Cribbing	L. Sum	1

SHEET TITLE	
BEARING DETAILS	
PROJECT IL RTE. 32/33 OVER LITTLE WABASH RIVER F.A.P. RTE. 774 SECTION 107BY EFFINGHAM COUNTY STATION 1011+50.17 STRUCTURE NO. 025-0078	PROJECT NO. O2017 SCALE DATE DRAWN BY TFG/CFC CHECKED BY GJB/MCB
COOMBE—BLOXDORF P.C. Engineers /Land Surveyors Springfield, Illinois Design Firm License No. 184-002703	15 0F 29 SHTS