

SCHEDULE OF QUANTITIES

78300200 - RAISED REFLECTIVE PAVEMENT MARKERS REMOVAL

78300200 - RAISED REFLECTIVE PAVEMENT MARKERS REMOVAL (CONT.)

4" SKIP-DASH (WHITE) WITH SINGLE RRPMS (FAP 693)

4" SOLID (WHITE) WITH SINGLE RRPMS (FAP 693)

LOCATION	RAMP OR DIRECTION	STATION	TO	STATION	LENGTH (FT.)	# OF LINES	ONE-WAY CRYSTAL (EACH)	TWO-WAY AMBER (EACH)	ONE-WAY AMBER (EACH)	LOCATION FAP 693 (IL 9)	RAMP OR DIRECTION	STATION	TO	STATION	LENGTH (FT.)	# OF LINES	ONE-WAY CRYSTAL (EACH)	TWO-WAY AMBER (EACH)	ONE-WAY AMBER (EACH)
											E.B.	906+48	-	907+58	110.0	1.0	3	-	-
FAP 693 (IL 9)	E.B. & W.B.	889+23	-	907+58	3670.0	2.0	46	-	-	FAP 693 (IL 9)	W.B.	909+22	-	910+77	155.0	1.0	4	-	-
FAP 693 (IL 9)	E.B. & W.B.	909+22	-	916+58	2208.0	3.0	28	-	-	FAP 693 (IL 9)	W.B.	153+77	-	154+98	121.0	1.0	2	-	-
FAP 693 (IL 9)	E.B.	152+86	-	163+12	1026.0	1.0	26	-	-	FAP 693 (IL 9)	E.B.	155+44	-	157+95	251.0	1.0	7	-	-
FAP 693 (IL 9)	W.B.	153+00	-	157+06	406.0	1.0	10	-	-	FAP 693 (IL 9)	E.B.	156+76	-	157+75	99.0	1.0	3	-	-
FAP 693 (IL 9)	E.B.	155+79	-	157+87	208.0	1.0	6	-	-	FAP 693 (IL 9)	E.B.	157+87	-	158+87	100.0	1.0	3	-	-
FAP 693 (IL 9)	W.B.	159+21	-	163+12	391.0	1.0	10	-	-	FAP 693 (IL 9)	E.B.	158+97	-	163+12	415.0	1.0	2	-	-
FAP 693 (IL 9)	NW RAMP	10+62	-	16+24	562.0	1.0	16	-	-	FAP 693 (IL 9)	NW RAMP	10+62	-	11+16.5	54.5	1.0	2	-	-
FAP 693 (IL 9)	NW RAMP	11+16.5	-	16+85	568.5	1.0	16	-	-	FAP 693 (IL 9)	W.B.	164+39	-	168+90	451.0	1.0	12	-	-
FAP 693 (IL 9)	SE RAMP	10+78	-	16+58	580.0	1.0	16	-	-	FAP 693 (IL 9)	W.B.	168+56	-	169+89	133.0	1.0	5	-	-
FAP 693 (IL 9)	SE RAMP	10+88	-	16+58	570.0	1.0	16	-	-	FAP 693 (IL 9)	W.B.	168+97	-	170+79	182.0	1.0	5	-	-
FAP 693 (IL 9)	W.B.	164+39	-	172+67	828.0	1.0	22	-	-	FAP 693 (IL 9)	E.B.	171+59	-	172+67	108.0	1.0	3	-	-
FAP 693 (IL 9)	E.B.	164+24	-	168+04	380.0	1.0	10	-	-	TOTAL =							51	-	-

4" DOUBLE SOLID (YELLOW) WITH SINGLE RRPMS (FAP 693)

LOCATION	RAMP OR DIRECTION	STATION	TO	STATION	LENGTH (FT.)	# OF LINES	ONE-WAY CRYSTAL (EACH)	TWO-WAY AMBER (EACH)	ONE-WAY AMBER (EACH)	LOCATION FAP 693 (IL 9)	RAMP OR DIRECTION	STATION	TO	STATION	LENGTH (FT.)	# OF LINES	ONE-WAY CRYSTAL (EACH)	TWO-WAY AMBER (EACH)	ONE-WAY AMBER (EACH)
FAP 693 (IL 9)	E.B.	169+35	-	172+67	332.0	1.0	10	-	-	FAP 693 (IL 9)	W.B.	912+54	-	915+00	404.0	1.0	-	-	7
FAP 693 (IL 9)	W.B.	169+89	-	171+48	159.0	1.0	4	-	-	FAP 693 (IL 9)	E.B. & W.B.	915+00	-	916+58	168.0	1.0	-	4	-
						TOTAL =	236	-	-								-	4	7

4" SOLID/SKIP-DASH (YELLOW) WITH SINGLE RRPMS (FAP 693)

LOCATION	RAMP OR DIRECTION	STATION	TO	STATION	LENGTH (FT.)	# OF LINES	ONE-WAY CRYSTAL (EACH)	TWO-WAY AMBER (EACH)	ONE-WAY AMBER (EACH)										
FAP 693 (IL 9)	E.B. & W.B.	889+23	-	905+84	3322.0	2.0	-	84	-	FAP 693 (IL 9) TOTAL =									
FAP 693 (IL 9)	W.B.	905+84	-	907+58	174.0	1.0	-	5	-										
						TOTAL =	-	89	-										

4" SKIP-DASH (WHITE) WITH DOUBLE RRPMS (FAP 704)

LOCATION	RAMP OR DIRECTION	STATION	TO	STATION	LENGTH (FT.)	# OF LINES	ONE-WAY CRYSTAL (EACH)	TWO-WAY AMBER (EACH)	ONE-WAY AMBER (EACH)
FAP 704 (I-55 BUS)	N.B. & S.B.	230+65	-	279+25	4860.0	4.0	486	-	-
FAP 704 (I-55 BUS)	S.B.	232+89	-	236+19	330.0	1.0	10	-	-
FAP 704 (I-55 BUS)	N.B.	238+87	-	241+26	239.0	1.0	6	-	-
FAP 704 (I-55 BUS)	N.B.	242+81	-	246+46	365.0	1.0	10	-	-
FAP 704 (I-55 BUS)	S.B.	247+78	-	251+48	370.0	1.0	10	-	-
FAP 704 (I-55 BUS)	S.B.	253+02	-	256+48	346.0	1.0	10	-	-
						TOTAL =	532	-	-

* 693 & 704
** (129)I-2, (1,2)I, & (FAP 10)I