INDEX OF SHEETS

DESCRIPTION	SHE	ET	NO.
COVER	1		
INDEX OF SHEETS, LIST OF STANDARDS, GENERAL NOTES & COMMITMENTS	2		
SUMMARY OF QUANTITIES	3	to	4
TYPICAL CROSS-SECTIONS	5		
SCHEDULES OF QUANTITIES	6		
ALIGNMENT, TIES, AND BENCHMARKS	7		
DISTRICT 5 DETAIL NO. 40800050A - FIELD ENTRANCES (NONCOMMERCIAL RURAL)	8	to	9
DISTRICT 5 DETAIL NO. 40800050C - PRIVATE COMMERCIAL ENTRANCES (NONCOMMERCIAL AND COMMERCIAL RURAL)	10	to	11
DISTRICT 5 DETAIL NO. 7800AAAA - PAVEMENT MARKING AND MARKERS (RURAL & URBAN APPLICATIONS)	12	to	15

LIST OF STANDARDS

STANDARD NO.	DESCRIPTION
000001-08	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001006	DECIMAL OF AN INCH AND OF A FOOT
701006-05	OFF-ROAD OPERATIONS, 2L, 2W, 15' (4.5 M) TO 24" (600 MM) FROM PAVEMENT
701011-04	OFF-ROAD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701306-04	LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS \geq 45
701311-03	LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY
701901-08	TRAFFIC CONTROL DEVICES
780001-05	TYPICAL PAVEMENT MARKINGS
781001-04	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

GENERAL NOTES

G.N.-100A

ELECTRONIC FILES AND/OR ELECTRONIC SURVEY INFORMATION INCLUDING CADD FILES WILL NOT BE AVAILABLE TO THE CONTRACTOR.

G.N.-105.09A

ALL ELEVATIONS SHOWN IN THE PLANS ARE BASED ON NORTH AMERICAN VERTICAL DATUM OF 1988. (NAVD 88)

G.N. -406H

MIXTURE REQUIREMENTS

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

LOCATION(S):	BOWMAN AVE	l
MIXTURE USE(S):	MAINLINE SURFACE	, & IŅĆIĎĒNTĀL) ↔
AC/PG:	PG 64-22	
DESIGN AIR VOIDS	4.0% @ NDES=50	
MIXTURE COMP (GRADATION)	IL-9.5	
FRICTION AGGREGATE	MIX C	
MIXTURE WEIGHT	112	
QUALITY MANAGEMENT PROGRAM	QC/QA	
SUBLOT SIZE	N.A.	
MATERIAL TRANSFER DEVICE (REQUIRED ?)	NO	

G.N.- 703A

SHORT TERM PAVEMENT MARKING SHALL BE APPLIED TO THE PAVEMENT AFTER ANY OF THE FOLLOWING: COLD MILLING AND/OR PLACING BITUMINOUS MATERIALS (TACK COAT), LEVELING BINDER (MACHINE METHOD), BINDER AND SURFACE COURSES. SHORT TERM PAVEMENT MARKING PLACED ON THE SURFACE SHALL COINCIDE WITH THE FINAL PAVEMENT STRIPING. SHORT TERM PAVEMENT MARKING PLACED PRIOR TO THE SURFACE SHALL COINCIDE WITH THE EXISTING PAVEMENT MARKINGS. USE 4 FEET PER 40 FEET (OR 10% PER STATION).

G.N.- 781

THE FINAL PAVEMENT MARKINGS SHALL BE IN PLACE PRIOR TO PLACING THE RAISED REFLECTIVE PAVEMENT MARKERS.

COMMITMENTS

THERE ARE NO COMMITMENTS FOR THIS CONTRACT

USER NAME = meglisk	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 40.0000 ' / in.	CHECKED -	REVISED -
PLOT DATE = 01/25/22	DATE -	REVISED -

INDEX OF SHEETS, LIST OF STANDARDS,				
GENERAL NOTES & COMMITMENTS				
CHEET NO 1 OF 1 CHEETE STA	TO CTA			

F.A.S. SECTION		COUNTY	TOTAL SHEETS	SHE	
500	500 116 RS		VERMILION	15	2
			CONTRACT	NO. 7)F62
ILLINOIS FED A		ID PROJECT			