

TEMPORARY RAMPS

LOCATION STATION	DESCRIPTION	WIDTH (FT)	AREA (SQ YD)
SIDE ROADS			
Sta 936+91.00 LT	13 TH ST	41.0	23.0
Sta 937+12.00 RT	13 TH ST	30.0	17.0
Sta 941+28.00 LT	12 TH ST	39.0	22.0
Sta 941+28.00 RT	12 TH ST	39.0	22.0
Sta 945+49.00 LT	11 TH ST	37.0	21.0
Sta 945+49.00 RT	11 TH ST	39.0	22.0
Sta 949+55.00 LT	10 TH ST	40.0	22.0
Sta 949+55.00 RT	10 TH ST	37.0	21.0
Sta 954+91.00 LT	9 TH ST	39.0	22.0
Sta 954+91.00 RT	9 TH ST	37.0	21.0
Sta 959+72.00 LT	8 TH ST	39.0	22.0
Sta 959+72.00 RT	8 TH ST	38.0	21.0
Sta 963+03.00 LT	7 TH ST	37.5	21.0
Sta 963+03.00 RT	7 TH ST	37.5	21.0
Sta 965+74.00 LT	6 TH ST	39.0	22.0
Sta 965+74.00 RT	6 TH ST	36.5	20.5
Sta 969+66.00 LT	5 TH ST	38.0	21.0
Sta 969+66.00 RT	5 TH ST	39.0	22.0
Sta 975+12.00 LT	4 TH ST	42.0	23.5
Sta 975+12.00 RT	4 TH ST	38.5	21.5
Sta 1001+74.00 LT	COUNTY RD	41.0	23.0
Sta 1001+74.00 RT	COUNTY RD	41.0	23.0
IL 104			
STA. 935+65.00 TO STA. 935+71.50	BUTT JOINT	6.5	4.0
STA. 987+51.25 TO STA. 987+86.25	BUTT JOINT	45.0	25.0
STA. 989+93.75 TO STA. 990+28.25	BUTT JOINT	45.0	25.0
		TOTAL	528.5

AGGREGATE SHOULDERS TYPE B

LOCATION STATION TO STATION		LENGTH (FT)	WIDTH (FT)	(TONS)
IL (104)				
STA. 935+65.00 TO STA. 937+02.10	LEFT & RIGHT	137.10	3.00	16.0
STA. 982+05.00 TO STA. 987+86.25	LEFT & RIGHT	581.25	2.00	44.0
BRIDGE OMISSION STA 987+86.25 TO STA 989+93.75				
STA. 989+93.75 TO STA. 996+50.00	LEFT & RIGHT	656.25	2.00	50.0
STA. 996+50.00 TO STA. 997+00.00	LEFT & RIGHT	50.00	3.00	6.0
STATION EQUATION 997+00.00 BK = 996+73.13 AH				
STA. 996+73.13 TO STA. 1095+05.45	LEFT & RIGHT	9832.32	3.00	1120.0
TOTAL				1236.0

COMBINATION CONCRETE CURB & GUTTER SCHEDULE

LOCATION			COMB. CONC. CURB & GUTTER REMOVAL (FT)	COMB. CONC. CURB & GUTTER TYPE B-6.24 (FT)	SUB-BASE GRANULAR MAT. TYPE A, 6" (SQ YD)
STATION	TO	STATION			
FAP 753 (IL 104)					
STA. 937+29.52 RT	TO	STA. 940+94.45 RT	364	364	145
STA. 949+06.82 LT	TO	STA. 949+43.48 LT	43	43	17
STA. 949+69.19 LT	TO	STA. 949+99.89 LT	42	42	17
TOTAL			449	449	179

DRIVEWAY SCHEDULE

LOCATION	CONCRETE DRIVEWAY REMOVAL (SQ. YD)	PORTLAND CEMENT CONCRETE DRIVEWAY, 6 INCH (SQ. YD)	PORTLAND CEMENT CONCRETE DRIVEWAY, 8 INCH (SQ. YD)
CE STA. 938+00.00 RT.	36.50		41
PE STA. 938+35.00 RT.	12.00	13.50	
PE STA. 938+73.00 RT.	-	14.00	
PE STA. 939+29.00 RT.	7.00	13.00	
PE STA. 940+67.00 RT.	13.5	16.50	
TOTAL	69.00	57.00	41

MANHOLES TO BE ADJUSTED

LOCATION	OFFSET	QUANTITY
STA. 969+84.0	LT	1
STA. 975+15.0	LT	1
TOTAL		2

WATER VALVES TO BE ADJUSTED

LOCATION	OFFSET	QUANTITY
STA. 969+88.0	LT	1
TOTAL		1

SANGAMON COUNTY