

GENERAL NOTES

Plan dimensions and details relative to the existing structure have been taken from existing plans and are subject to nominal construction variations. It shall be the Contractors responsibility to verify such dimensions and details in the field and make necessary approved adjustments prior to the construction or ordering of material. Such variations shall not be cause for additional compensation or a change in the scope of the work. The Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Areas of deck repairs shown are estimated. The Engineer shall show actual locations of deck repairs on as-built plans. Five percent of the total bridge deck area was assumed to be Deck Slab Repair (Partial).

Price per lined foot for Silicone Joint Sealer, 1 3/4 " shall include the removal of the existing joint seal.

The following mixture requirements are applicable for the project:

- Mixture Use: Surface Course, 1 1/2"
- Application: Hot-Mix Asphalt Surface Course, Mix "D", N90
- PG Grade: PG 64-22
- Design Air Voids: 4.0% @ Ndesign = 90
- Mixture Composition: IL-9.5
- Friction Aggregate: Mixture D

The existing hot-mix asphalt wearing surface is not known to contain asbestos.

TOTAL BILL OF MATERIALS

SN 051-0022 (EB)

ITEM DESCRIPTION	UNIT	QUANTITY
Hot-Mix Asphalt Surface Removal (Deck)	Sq. Yd.	457
Hot-Mix Asphalt Surface Course, Mix "D", N90	Ton	39
Deck Slab Repair (Partial)	Sq. Yd.	23
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	1
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	14
Waterproofing Membrane System	Sq. Yd.	457
Silicone Joint Sealer, 1 3/4 "	Foot	98

TOTAL BILL OF MATERIALS

SN 051-0023 (WB)

ITEM DESCRIPTION	UNIT	QUANTITY
Hot-Mix Asphalt Surface Removal (Deck)	Sq. Yd.	457
Hot-Mix Asphalt Surface Course, Mix "D", N90	Ton	39
Deck Slab Repair (Partial)	Sq. Yd.	23
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	16
Waterproofing Membrane System	Sq. Yd.	457
Silicone Joint Sealer, 1 3/4 "	Foot	98