

COMMITMENTS

The property owners Mr. & Mrs. Larry Plate shall be notified thirty (30) days prior to construction. They may be contacted at (309) 653-2366. Any field tile intercepted or disturbed during construction shall be replaced or repaired.

The property owners Mr. John Bruketta and Mr. Joseph Brketta shall be notified thirty (30) days prior to construction. They may be contacted at (309) 758-5118. Any field tile intercepted or disturbed during construction shall be replaced or repaired.

The Superintendent of Schools Mr. John Marshall, shall be notified thirty (30) days prior to construction on the school property at (309) 758-5130.

JOB SPECIFIC NOTES

BOX CULVERT EXTENSIONS

All dewatering for the construction and repairs of the culvert are the responsibility of the contractor.

STATUS OF UTILITIES

STATUS OF UTILITIES					
AmerenCIPS					
Route	Offset	Location	Type of Utility	Type of Conflict	Disposition
US 136	46' Lt.	483+50 to 484+50	4" Gas Line	Ditch Grading	Relocate
Mid Century Telephone Cooperative, Inc.					
Route	Offset	Location	Type of Utility	Type of Conflict	Disposition
US 136	38' Rt.	478+50 to 180+50	Buried Fiber Optic	Ditch Grading	Relocate
US 136	34' Rt.	487+30 to 490+40	Buried Fiber Optic	Ditch Grading/Structure	Relocate
US 136	38' Lt.	483+50 to 484+50	Buried Fiber Optic	Ditch Grading	Relocate
US 136	38' Lt.	486+50 to 488+50	Buried Fiber Optic	Ditch Grading	Relocate
US 136	38' Lt.	490+20 to 490+40	Buried Fiber Optic	Ditch Grading/Structure	Relocate
US 136	38' to 32' Lt.	490+75 to 490+85	Buried Fiber Optic	Ditch Grading	Relocate
US 136	38' Rt.	491+60 to 28+25	Buried Fiber Optic	Ditch Grading	Relocate
US 136	30' Lt.	492+80 to 498+80	Buried Fiber Optic	Ditch Grading	Relocate
US 136	37' Lt.	499+80 to 29+00	Buried Fiber Optic	Ditch Grading	Relocate
US 136	34' Rt.	28+70 to 29+00	Buried Fiber Optic	Ditch Grading/Structure	Caution
US 136	34' Rt.	31+40 to 34+50	Buried Fiber Optic	Ditch Grading	Relocate
US 136	31' Lt.	32+60 to 38+60	Buried Fiber Optic	Ditch Grading	Relocate
US 136	26' Rt.	35+35 to 35+60	Buried Fiber Optic	Ditch Grading	Relocate
US 136	28' Rt.	38+35 to 38+60	Buried Fiber Optic	Ditch Grading	Relocate

BITUMINOUS MIXTURE REQUIREMENTS

PAY CODE	40603335	X4067107	35501308	40800050		
			44201815		48203020	48203020
Mixture Use(s):	Surface Course (including CH 2)	Leveling Binder (including CH 2)	Base Cse, 6" (Entrances) & CID Patches	Incidental Bit. Surface (Top 2" on entrances in 3R section) (3' wedge on entrances in 3P section)	HMA Shoulders (lower lifts)	HMA Shoulders (surface lifts)
AC/PG:	PG 64-22	SBS or SBR 70-22	PG 64-22	PG 64-22	PG 64-22	PG 64-22
RAP% (Max): **	15%	0%	25%	15%	30%	30%
Design Air Voids:	4.0% @ N=50	3.0% @ N=50	4.0% @ N=50	4.0% @ N=50	4.0% @ N=30	3.0% @ N=30
Mixture Composition: (Gradation Mixture)	IL 9.5 or IL12.5	IL 4.75	IL 19.0	IL 9.5 or IL12.5	IL 19.0L	IL 9.5L
Friction Aggregate:	Mixture D (Dolomite only)	N.A.	N.A.	Mixture C	N.A.	Mix C

** If RAP option is selected, the asphalt cement grade may need to be adjusted, this will be determined by the Materials Engineer.

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**COMMITMENTS/JOB SPECIFIC NOTES
STATUS OF UTILITES/BITUMINOUS**

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
315	109RS-4.110RS-2	FULTON		3
CONTRACT NO. 68330				
ILLINOIS FED. AID PROJECT				

FILE NAME =	USER NAME = ghidnaam
propplianshts.dgn	

DESIGNED -	REVISED -
DRAWN -	REVISED -
CHECKED -	REVISED -
DATE -	REVISED -

SCALE:	SHEET NO.	OF	SHEETS	STA.	TO	STA.
--------	-----------	----	--------	------	----	------