

PAVEMENT MARKING SCHEDULE FOR NORMAL MAINLINE

| TYPICAL PVT MRK LEGEND = | | | 7 | 2 | 1 | | | | | |
|--------------------------|--------------------------|----------------|---------------------|--------------------------|-----------------------------------|---------------------|--------------------------|-----------------------------------|-----------------------------------|-------------------------|
| | | | 78000200 | 70300220 | 78000200 | 78000200 | 70300220 | 78100100 | 78100100 | 70300100 |
| TYPICAL # | LENGTH OF TYPICAL (FOOT) | SETS OF DASHES | 4" THERMO SKIP-DASH | TEMPORARY PVT MK LINE 4" | 4" THERMO BOTH SIDES OF TURN LANE | 4" THERMO SKIP DASH | TEMPORARY PVT MK LINE 4" | RAISED REFLECTIVE PAVEMENT MARKER | RAISED REFLECTIVE PAVEMENT MARKER | SHORT TERM PVT MARKINGS |
| | | | WHITE (FOOT) | WHITE (FOOT) | YELLOW (FOOT) | YELLOW (FOOT) | YELLOW (FOOT) | AMBER (EACH) | CLEAR (EACH) | (FOOT) |
| 1 | 164.0 | 4 | 164.0 | 164.0 | 328.0 | 82.0 | 328.0 | 8 | 8 | 65.6 |
| 2 | 190.0 | 4 | 190.0 | 190.0 | 380.0 | 95.0 | 380.0 | 10 | 10 | 76 |
| 3 | 1261.0 | 4 | 1261.0 | 1261.0 | 2522.0 | 630.5 | 2522.0 | 63 | 63 | 504.4 |
| 4 | 1373.0 | 5 | 1716.3 | 1716.3 | 2746.0 | 686.5 | 2746.0 | 69 | 86 | 686.5 |
| 5 | 600.0 | 4 | 600.0 | 600.0 | 1200.0 | 300.0 | 1200.0 | 30 | 30 | 240 |
| 6 | 1138.0 | 4 | 1138.0 | 1138.0 | 0.0 | 0.0 | 0.0 | 0 | 57 | 455.2 |
| 7 | 918.0 | 4 | 918.0 | 918.0 | 1836.0 | 459.0 | 1836.0 | 46 | 46 | 367.2 |
| 8 | 832.0 | 4 | 832.0 | 832.0 | 0.0 | 0.0 | 0.0 | 0 | 42 | 332.8 |
| 9 | 613.0 | 4 | 613.0 | 613.0 | 0.0 | 0.0 | 0.0 | 0 | 31 | 245.2 |
| 10 | 337.0 | 1 | 84.3 | 84.3 | 0.0 | 0.0 | 0.0 | 0 | 4 | 33.7 |
| 10 | 100.0 | 2 | 50.0 | 50.0 | 0.0 | 0.0 | 0.0 | 0 | 3 | 20 |
| 10 | 237.0 | 2 | 118.5 | 118.5 | 0.0 | 0.0 | 0.0 | 0 | 6 | 47.4 |
| 11 | 224.0 | 2 | 112.0 | 112.0 | 0.0 | 0.0 | 0.0 | 0 | 6 | 44.8 |
| 12 | 110.0 | 2 | 55.0 | 55.0 | 0.0 | 0.0 | 0.0 | 0 | 3 | 22 |
| 13 | 357.0 | 1 | 89.3 | 89.3 | 0.0 | 0.0 | 0.0 | 0 | 4 | 35.7 |
| 14 | 4913.0 | 1 | 1228.3 | 1228.3 | 0.0 | 0.0 | 0.0 | 0 | 61 | 491.3 |
| 24 | 919.0 | 1 | 229.8 | 229.8 | 0.0 | 0.0 | 0.0 | 0 | 11 | 91.9 |
| 25 | 1234.0 | 2 | 617.0 | 617.0 | 0.0 | 0.0 | 0.0 | 0 | 31 | 246.8 |
| 26 | 897.0 | 1 | 224.3 | 224.3 | 0.0 | 0.0 | 0.0 | 0 | 11 | 89.7 |
| 27 | 284.0 | 1 | 71.0 | 71.0 | 0.0 | 0.0 | 0.0 | 0 | 4 | 28.4 |
| TOTAL= | | | 10311.5 | 10311.5 | 9012.0 | 2253.0 | 9012.0 | 225 | 516 | 4124.6 |
| USE= | | | 10312.0 | 10312.0 | 9012.0 | 2253.0 | 9012.0 | 225 | 516 | 4125.0 |

PAVEMENT MARKING SCHEDULE FOR BLOOMINGTON MAINLINE

| TYPICAL PVT MRK LEGEND = | | | | | | | 7 | | | |
|--------------------------|--------------------------|----------------|---------------------|--------------------------|-----------------------------------|-------------------------|----------|----------|----------|----------|
| | | | | | | | 78000200 | 70300220 | 78100100 | 70300100 |
| TYPICAL # | LENGTH OF TYPICAL (FOOT) | SETS OF DASHES | 4" THERMO SKIP-DASH | TEMPORARY PVT MK LINE 4" | RAISED REFLECTIVE PAVEMENT MARKER | SHORT TERM PVT MARKINGS | | | | |
| | | | WHITE (FOOT) | WHITE (FOOT) | CLEAR (EACH) | (FOOT) | | | | |
| 15 | 4245.0 | 3 | 3183.8 | 3183.8 | 159 | 1273.5 | | | | |
| 16 | 1229.0 | 3 | 921.8 | 921.8 | 46 | 368.7 | | | | |
| 17 | 1710.0 | 3 | 1282.5 | 1282.5 | 64 | 513 | | | | |
| 18 | 149.0 | 2 | 74.5 | 74.5 | 4 | 29.8 | | | | |
| 19 | 615.0 | 1 | 153.8 | 153.8 | 8 | 61.5 | | | | |
| 20 | 80.0 | 3 | 60.0 | 60.0 | 3 | 24 | | | | |
| 21 | 1471.0 | 3 | 1103.3 | 1103.3 | 55 | 441.3 | | | | |
| 22 | 1707.0 | 3 | 1280.3 | 1280.3 | 64 | 512.1 | | | | |
| 23 | 1241.0 | 3 | 930.8 | 930.8 | 47 | 372.3 | | | | |
| 28 | 3298.0 | 1 | 824.5 | 824.5 | 41 | 329.8 | | | | |
| 29 | 1680.0 | 3 | 1260.0 | 1260.0 | 63 | 504 | | | | |
| 30 | 1570.0 | 3 | 1177.5 | 1177.5 | 59 | 471 | | | | |
| 30 | 184.0 | 2 | 92.0 | 92.0 | 5 | 36.8 | | | | |
| 31 | 3899.0 | 1 | 974.8 | 974.8 | 49 | 389.9 | | | | |
| TOTAL= | | | 13319.3 | 13319.3 | 666 | 5327.7 | | | | |
| USE= | | | 13319.0 | 13319.0 | 666 | 5328.0 | | | | |