

ENTRANCE IMPROVEMENT SCHEDULE FOR RURAL / URBAN														
LOCATION	TYPE OF ENTRANCE	MATERIAL TYPE	WIDTH (EDGE OF PAVEMENT)	WIDTH (ENTRANCE WIDTH)	RT OFFSET	LT OFFSET	LENGTH (FROM EDGE OF PVT/ BIT SHLD TO LIMITS OF IMPROVEMENT)	PR BIT. CONC. AVERAGE THICKNESS	HMA SURF REM. - BUTT JOINT	P. C. C. SURF. REM. - BUTT JOINT	BIT MATLS (P. C.)	AGG (P. C.)	INCIDENTAL BIT. SURF.	AGG SURF CSE - TY B
(LT / RT) (STA) ((FE / PE / CE / MB) (RURAL / URBAN)	(EX / PR)	FOOT		FOOT	FOOT	FOOT	INCH	SQ. YD.	SQ. YD.	TON	TON	TON	TON
LT STA 762+00	T. R.	BIT	36	20			25	1.5	---	---	0.03	0.11	6.53	0.93
RT STA 762+67	P. E.	BIT	16	16			8	1.5	---	---	0.01	0.02	1.19	0.53
LT STA 1290+10	C. E.	BIT	130	130			10	1.5	144.44	---	0.05	0.21	12.13	0.00
RT STA 1295+12	P. E.	BIT	42	30			8	1.5	32.00	---	0.01	0.05	2.69	0.00
LT STA 1296+15	T. R.	BIT	30	20			10	1.5	---	---	0.01	0.04	2.33	0.83
LT STA 1298+58	P. E.	CONC	26	10			8	1.5	---	16.00	0.01	0.02	1.34	0.00
LT STA 1299+60	P. E.	BIT	80	40			8	1.5	---	---	0.02	0.09	5.23	1.99
LT STA 1301+00	P. E.	BIT	26	20			8	1.5	20.44	---	0.01	0.03	1.72	0.00
RT STA 1301+75	P. E.	CONC	42	28			8	1.5	---	31.11	0.01	0.04	2.61	0.00
LT STA 1302+07	P. E.	BIT	68	30			8	1.5	---	---	0.02	0.07	4.33	1.63
RT STA 1302+79	P. E.	BIT	42	30			8	1.5	---	---	0.01	0.05	2.69	1.20
LT STA 1302+94	P. E.	BIT	22	10			8	1.5	---	---	0.01	0.02	1.19	0.53
LT STA 1303+25	P. E.	CONC	38	10			8	1.5	---	21.33	0.01	0.03	1.79	0.00
LT STA 1303+60	P. E.	BIT	26	12			8	1.5	---	---	0.01	0.02	1.42	0.63
RT STA 1303+60	P. E.	BIT	22	10			8	1.5	---	---	0.01	0.02	1.19	0.53
LT STA 1304+24	P. E.	BIT	96	20			8	1.5	---	---	0.03	0.11	6.42	1.93
RT STA 1304+33	P. E.	BIT	24	16			8	1.5	---	---	0.01	0.03	1.49	0.66
LT STA 1305+57	P. E.	BIT	59	20			8	1.5	---	---	0.02	0.06	3.66	1.31
RT STA 1305+57	P. E.	BIT	20	16			8	1.5	16.00	---	0.01	0.02	1.34	0.00
LT STA 29+15	T. R.	BIT	32	30			25	1.5	86.11	---	0.03	0.12	7.23	0.00
RT STA 29+16	T. R.	BIT	32	30			25	1.5	86.11	---	0.03	0.12	7.23	0.00
TOTAL									758.7	68.4	1.1	4.1	239.1	55.2