

## FLUSH PAVED MEDIAN: TWO-WAY LEFT TURN LANE WITH ONE-WAY LEFT TURN LANE AT SIGNALIZED INTERSECTION

## TYPICAL PAVEMENT MARKING LEGEND

(Note: This is a District Standard Legend. Some elements may not apply to specific project.)

- 4(100) Solid (Yellow)
- 2 4(100) Solid (White)
- 3) 2-6(150) Crosswalk **c** 6'-6" (2m)min C.-C. (White) 2-8(200) Crosswalk @ 6'-6" (2m)min C.-C. (White) (When traffic signals are present.)
- 6(150) Skip-Dash (White)

(See Special Note 1)

(See Special Note 1)

- 8(200) Solid (White)
- 12(300) Diagonal (White) (Item 6) is shown on Std. 780001)
- 24(600) Stop Bar (White)

(See Std. 780001 and Special Notes 2 & 3)

- 4(100) Skip-Dash (Yellow)
- (10) 12(300) Diagonal (Yellow) (See Table A)
- 4(100) Double Solid (Yellow)

See Table A 11(280) C.-C.

## SPECIAL NOTES

- 1. Skip-Dash markings will be centered between both ends of city blocks and shall be placed in alignment transversly across the pavement.
- 2. The following shall apply to arrows located in one-way left turn lanes:
  - A. A minimum of two (2) arrows is required.
  - B. The maximum spacing between arrows is 80' (24 m).
  - C. Arrows shall be evenly spaced if three (3) or more are required.
- 3. The following shall apply to arrow pairs located in two-way left turn lanes:
- A. A minimum of two (2) arrow pairs is required.
- B. The maximum spacing between arrow pairs is 200' (61 m).
- C. Arrow pairs shall be evenly spaced if three (3) or more are required.
- D. The spacing between Bi Directional Left Turn Arrows is 33' (10 m).

## GENERAL NOTES

- 1. Refer to State Standard 780001 for additional Pavement Markings including letters & arrows.
- 2. See Plans for Pavement Markings adjacent to curbed islands and medians, and through lane reductions.

O1-O1-97 RENUM. F-8.03, NEW REVISION BOX T.P.   10-16-06 REVISED TO 2007 SPEC.  O2-O7-97 ADD BI DIRECTIONAL DIMENSION IO-97 CORRECT BI DIRECTIONAL DIMENSION O8-02 ADD CROSSWALK DMNS. WITH T.S.  O8-02 ADD CROSSWALK DMNS. WITH T.S.  O8-04 ADD CROSSWALK DMNS. WITH T.S.  O8-05 REVISION BOX TYPICAL PAVEMENT MARKINGS  STATE OF ILLINOIS TYPICAL PAVEMENT MARKINGS  OE-ONTRACT NO. 68743  NOT TO SCALE  ONT TO SCALE  ONTRACT NO. 68743												1
O2-07-97 ADD BY DIRECTIONAL DIMENSION  10-97 CORRECT BI DIRECTIONAL DIMENSION  SHT, 1 OF 2  TYPICAL PAVEMENT MARKINGS  656 (B)RS-3 <sub>1</sub> (L)RS-4  TAZEWELL 34 33  DEPARTMENT OF TRANSPORTATION  SHT, 1 OF 2  CONTRACT NO. 68743	01-01-97	RENUM. F-8.03, NEW REVISION BOX	T.P.	10-16-06 REVISED TO 2007 SPEC.				F.A.P.	SECTION	COUNTY	TOTAL S	HEET
10-97 CORRECT BI DIRECTIONAL DIMENSION J.A. DEPARTMENT OF TRANSPORTATION SHT, 1 OF 2 CONTRACT NO. 68743	02-07-97	ADD BI DIRECTIONAL DIMENSION	J.A.		STATE OF ILLINOIS		TYPICAL PAVEMENT MARKINGS	KIE.				NO.
O8-02 ADD CROSSWALK DMNS, WITH T.S. M.A. CADD STD. 780001-D4 FED. ROAD DIST, NO. ILLINOIS/FED. AID PROJECT	10-97	CORRECT BI DIRECTIONAL DIMENSION	J.A.		DEPARTMENT OF TRANSPORTATION		SHT 1 OF 2	636	אינאני-כאנטי		34	743
	08-02	ADD CROSSWALK DMNS. WITH T.S.	M.A.			NOT TO SCALE		FED. ROAD	DIST. NO. ILLINOIS FED. A		NO. 60	/43