

SCHEDULE OF PARTIAL DEPTH PATCHES

STATION	DIRECTION	LANE	LENGTH (ft)	WIDTH (ft)	PARTIAL DEPTH REMOVAL	PARTIAL DEPTH PATCHING
					X4401705 (sq_yd)	X4421000 (Ton)
109+15	NB	DL	6	6	4.0	0.7
127+40	NB	DL	6	12	8.0	1.3
196+73	NB	DL	6	6	4.0	0.7
199+33	NB	DL	6	6	4.0	0.7
240+67	NB	PL	6	6	4.0	0.7
240+09	NB	DL	6	6	4.0	0.7
234+11	NB	DL	4	12	5.3	0.9
232+53	NB	PL	4	12	5.3	0.9
223+02	SB	AUX LN	4	8	3.6	0.6
222+69	SB	AUX LN	4	10	4.4	0.7
222+46	SB	AUX LN	4	12	5.3	0.9
220+40	SB	TURN LN	4	12	5.3	0.9
219+87	SB	MBL RD	100	4	44.4	7.5
204+60	SB	DL	6	12	8.0	1.3
203+06	SB	DL	4	12	5.3	0.9
203+06	SB	PL	4	12	5.3	0.9
201+40	SB	DL	4	12	5.3	0.9
197+62	SB	DL	6	6	4.0	0.7
186+18	SB	DL	4	12	5.3	0.9
186+18	SB	PL	4	12	5.3	0.9
173+46	SB	DL	6	6	4.0	0.7
172+02	SB	DL	6	6	4.0	0.7
153+12	SB	DL	6	12	8.0	1.3
151+90	SB	DL	6	12	8.0	1.3
151+50	SB	DL	6	12	8.0	1.3
150+65	SB	DL	4	12	5.3	0.9
150+65	SB	PL	4	12	5.3	0.9
150+25	SB	DL	6	6	4.0	0.7
148+32	SB	DL	4	12	5.3	0.9
146+40	SB	DL	4	12	5.3	0.9
144+30	SB	DL	4	12	5.3	0.9
128+88	SB	DL	4	12	5.3	0.9
121+04	SB	DL	4	12	5.3	0.9
85+07	SB	DL	4	12	5.3	0.9
81+00	SB	DL	4	6	2.7	0.4
79+78	SB	DL	4	6	2.7	0.4
78+61	SB	DL	4	6	2.7	0.4
75+38	SB	DL	4	6	2.7	0.4
72+57	SB	DL	4	6	2.7	0.4
70+20	SB	DL	4	6	2.7	0.4
69+80	SB	DL	4	6	2.7	0.4
69+40	SB	DL	4	12	5.3	0.9
69+15	SB	DL	6	6	4.0	0.7
68+76	SB	DL	4	6	2.7	0.4
68+41	SB	DL	4	12	5.3	0.9
67+58	SB	DL	4	6	2.7	0.4
59+86	SB	DL	4	6	2.7	0.4
56+29	SB	DL	4	6	2.7	0.4
50+50	SB	DL	4	12	5.3	0.9
50+50	SB	PL	4	12	5.3	0.9
50+11	SB	DL	4	12	5.3	0.9
48+93	SB	DL	4	4	1.8	0.3
TOTAL =					280.9	47.2
USE =					281.0	47.0

SCHEDULE OF CLASS D PATCHES

STATION	DIRECTION	LANE	LENGTH (ft)	WIDTH (ft)	DEPTH 11 (in)	PATCH AREA	
						44201773 TYPE I (sq_yd)	44201777 TYPE II (sq_yd)
190+22	NB	SHLD	4	10	10.75	4.4	0.0
234+33	NB	DL	4	12	10.75	0.0	5.3
234+33	NB	PL	4	12	10.75	0.0	5.3
256+00	NB		4	12	10.75	0.0	5.3
256+00	SB		4	12	10.75	0.0	5.3
239+04	SB	PL	4	12	10.75	0.0	5.3
239+04	SB	DL	4	12	10.75	0.0	5.3
234+33	SB	DL	4	12	10.75	0.0	5.3
234+33	SB	PL	4	12	10.75	0.0	5.3
234+33	SB	TURN LN	4	12	10.75	0.0	5.3
TOTAL =						4.4	48.0
USE =						5.0	48.0