

HOT-MIX ASPHALT

STATION	TO	STATION	LENGTH (FT)	WIDTH (FT)	AREA (SQ YD)	SURFACE THICKNESS (IN)	POLYMER LEVEL BINDER THICKNESS (IN)	40600100 BIT MATL PRIME (GAL)	40600300 AGG PR COAT (TON)	40603570 POLY HMA SC MIX "E" N90 (TON)	40600845 POLYMER LB (MM) (TON)	
3026+00.00		3041+70.00	1570.0	VAR	10030.79	1.5	0.75	1003.08	20.06	842.59	421.29	
BRIDGE OMISSION												
3043+70.00		3052+85.00	915.0	54.0	5392.50	1.5	0.75	539.25	10.79	452.97	226.49	
BRIDGE OMISSION												
3056+36.00		3061+50.00	514.0	54.0	2941.22	1.5	0.75	294.12	5.88	247.06	123.53	
CONCRETE SECTION OMISSION												
<u>E 16TH ST AUX LN</u>												
RT	3029+03.00	3030+68.40	165.4	VAR	148.55	1.5	0.75	14.86	0.30	12.48	6.24	
<u>W 16TH ST AUX LN</u>												
LT	3027+82.60	3029+61.10	178.5	VAR	294.50	1.5	0.75	29.45	0.59	24.74	12.37	
<u>14TH ST ACCEL LN & RAMP</u>												
LT	3033+19.80	3036+91.80	372.0	VAR	477.62	1.5	0.75	47.76	0.96	40.12	20.06	
<u>14TH ST DECEL LN & RAMP</u>												
RT	3033+64.60	3038+60.00	495.4	VAR	661.46	1.5	0.75	66.15	1.32	55.56	27.78	
<u>14TH ST DECEL LN & RAMP</u>												
LT	3039+12.10	3041+70.00	257.9	VAR	473.25	1.5	0.75	47.33	0.95	39.75	19.88	
<u>14TH ST ACCEL LN & RAMP</u>												
RT	3040+63.00	3041+70.00	107.0	VAR	271.51	1.5	0.75	27.15	0.54	22.81	11.40	
<u>I-74 ACCEL LN & RAMP</u>												
LT	3043+70.00	3046+97.60	327.6	VAR	652.62	1.5	0.75	65.26	1.31	54.82	27.41	
<u>I-74 DECEL LN & RAMP</u>												
RT	3043+70.00	3048+96.50	526.5	VAR	908.54	1.5	0.75	90.85	1.82	76.32	38.16	
<u>I-74 DECEL LN & RAMP</u>												
LT	3048+41.80	3052+85.00	443.2	VAR	541.47	1.5	0.75	54.15	1.08	45.48	22.74	
<u>I-74 ACCEL LN & RAMP</u>												
RT	3051+62.00	3052+85.00	123.0	VAR	260.24	1.5	0.75	26.02	0.52	21.86	10.93	
<u>I-74 ACCEL LN & RAMP</u>												
LT	3056+36.00	3057+67.20	131.2	VAR	297.91	1.5	0.75	29.79	0.60	25.02	12.51	
<u>I-74 DECEL LN & RAMP</u>												
RT	3056+36.00	3060+61.40	425.4	VAR	598.99	1.5	0.75	59.90	1.20	50.32	25.16	
<u>I-74 DECEL LN & RAMP</u>												
LT	3059+39.10	3061+50.00	210.9	VAR	128.88	1.5	0.75	12.89	0.26	10.83	5.41	
	21+04.30	27+60.00	655.7	VAR	4700.35	1.5	0.75	470.04	9.40	394.83	197.41	
	27+60.00	53+26.56	2566.5	55	15684.17	1.5	0.75	1568.42	31.37	1317.47	658.74	
					44464.57			4446.46	88.93	3735.02	1867.51	
								<u>USE =</u>	4447.0	89.0	3735.0	1868.0