

TRENCHLESS PIPE, INSTALLATION, 18"

STATION	OFFSET	FOOT
CLEAR LAKE AVE 29+60.00	RT	26
TOTAL		26

TRENCHLESS PIPE, INSTALLATION, 24"

STATION	OFFSET	FOOT
CLEAR LAKE AVE 31+50.00	RT	43
TOTAL		43

TRENCHLESS PIPE, INSTALLATION, 48"

STATION	OFFSET	FOOT
CLEAR LAKE AVE 29+95.00	LT&RT	131
TOTAL		131

CONCRETE COLLAR, SPECIAL

STATION	OFFSET	CU YD
CLEAR LAKE AVE 30+15.00	109' RT	0.60
TOTAL		0.60

BRICK WALL REMOVAL

STATION TO	STATION	OFFSET	FOOT
NORTH FRONTAGE RD 1+40.00	1+40.00	RT	8
1+40.00	1+56.00	RT	16
TOTAL			24

STORM SEWER (WATER MAIN REQUIREMENTS) 36"

STATION TO	STATION	OFFSET	FOOT
CLEAR LAKE AVE 21+00.00	22+80.00	LT	180
22+80.00	23+35.00	LT	55
23+35.00	25+58.00	LT	223
25+58.00	26+75.00	LT	117
26+75.00	26+84.38	LT	17
TOTAL			592

STORM SEWER (WATER MAIN REQUIREMENTS) 24"

STATION	OFFSET	FOOT
CLEAR LAKE AVE 31+50.00	RT	17
SOUTH FRONTAGE RD 15+93.10	41.75' LT	103
TOTAL		120

RETAINING WALL REMOVAL

STATION TO	STATION	OFFSET	CU YD
RE-ALIGNED HILL ST 1+27.00	2+06.00	RT	26
TOTAL			26

STORM SEWER TO BE FILLED

STATION TO	STATION	OFFSET	CU YD
CLEAR LAKE AVE 130+87.50	131+03.51	LT	1
20+05.39	20+15.69	LT	5
20+15.69	20+47.40	LT	5
20+41.38	20+47.40	LT	1
20+47.40	20+95.00	LT	6
30+30.71	3'x3' box 35+01.77	RT	47 6
TOTAL			71

CONCRETE ISLAND (SPECIAL)

STATION TO	STATION	OFFSET	SQ FT
ISLANDS CLEAR LAKE/DIRKSEN NW QUADRANT	-	-	350
NE QUADRANT	-	-	510
SE QUADRANT	-	-	1317
SW QUADRANT	-	-	278
ISLAND K-MART/WALGREENS	-	-	261
TOTAL			2,716

PARKING LOT PAVEMENT REMOVAL

STATION TO	STATION	OFFSET	SQ YD
CLEAR LAKE AVE 127+35.00	127+48.00	LT	22
127+48.00	128+65.00	LT	190
131+00.00	132+00.00	LT	362
20+54.94	21+16.01	RT	35
26+82.00	27+07.00	LT	63
RE-ALIGNED HILL 0+90.00	1+48.00	LT	148
0+90.00	2+70.00	RT	87
HARDEE'S ENTRANCE 0+88.00	1+30.00	RT	48
WENDY'S LOT 1+62.00	1+88.00	RT	35
K-MART/WALGREEN'S 101+00.00	102+07.00	-	1787
SOUTH FRONTAGE RD 11+00.00	13+50.00	-	1257
13+50.00	15+00.00	-	1048
15+00.00	16+53.00	-	281
DIRKSEN PKWY 166+36.00	167+94.00	LT	209
168+00.00	169+44.00	RT	224
169+80.00	170+40.00	RT	86
TOTAL			5,882

SEE SHEET 161 FOR PARKING LOT PAVEMENT REMOVAL AT ENTRANCES

REMOVE INLET BOX

STATION	OFFSET	EACH
CLEAR LAKE AVE 123+23.18	34.83' LT	1
TOTAL		1

CORRUGATED MEDIAN REMOVAL

STATION TO	STATION	OFFSET	SQ FT
CLEAR LAKE AVE 20+14.00	20+35.00	LT	88
22+58.00	23+30.00	RT	358
24+44.00	24+80.00	LT	409
24+85.00	25+70.00	RT	827
28+52.00	29+35.00	LT	612
29+60.00	30+53.00	RT	710
34+78.00	35+75.00	LT	596
TOTAL			3,600

STORM SEWER (WATERMAIN REQUIREMENT) 18"

STATION TO	STATION	OFFSET	FOOT
CLEAR LAKE AVE 29+52.18	29+60.00	RT	35
TOTAL			35

STORM SEWER (WATERMAIN REQUIREMENT) 48"

STATION TO	STATION	OFFSET	FOOT
CLEAR LAKE AVE 29+95.00	-	RT	15
TOTAL			15

REVISIONS	
NAME	DATE

SCHEDULE OF QUANTITIES