

ENTRANCE IMPROVEMENT SCHEDULE FOR RURAL / URBAN "PPP" PROJECTS

LOCATION	TYPE OF ENTRANCE	EX MATERIAL TYPE	WIDTH 1	WIDTH 2	WIDTH 3	WIDTH 4	LENGTH (FROM EDGE OF PVT/HMA SHLD TO LIMITS OF HMA APRON)	LENGTH (FROM EDGE OF PVT/HMA SHLD TO LIMITS OF IMPROVEMENT)	PR HMA CONC. THICKNESS	HMA SURF. REMOVAL - BUTT JOINT	PREP OF BASE	AGG. BASE REPAIR	AGGREGATE SURFACE COURSE TY - B	BIT (P. C.)	AGG (P. C.)	INCIDENTAL HMA SURF.
(LT / RT) (STA) (+)	(FE / PE / CE / MB) (RURAL / URBAN)	(EARTH / AGG. / HMA / P. C. C.)	FOOT	FOOT	FOOT	FOOT	FOOT	FOOT	INCH	SQ. YD.	SQ. YD.	TON	TON	TON	TON	TON
RT STA 60+11	GROVE ST	HMA	0.0	CADD	CADD	0.0	10.0	0	2.00	164.6	0.0	0.0	0.0	0.06	0.3	18.4
LT STA 133+91	TR 266	HMA	0.0	CADD	CADD	0.0	10.0	0	2.00	137.0	0.0	0.0	0.0	0.05	0.3	15.3
RT STA 133+91	TR 266	HMA	0.0	CADD	CADD	0.0	10.0	0	2.00	96.6	0.0	0.0	0.0	0.04	0.2	10.8
RT STA 147+45	PE	AGG	14.0	30.0	65.2	14.0	5.0	7.0	2.25	30.3	0.0	0.0	1.6	0.01	0.0	3.8
RT STA 153+66	MB	HMA	0.0	26.0	53.5	0.0	5.0	0.0	2.25	22.1	0.0	0.0	0.0	0.01	0.0	2.8
LT STA 153+76	PE	HMA	24.0	50.0	0.0	0.0	5.0	0.0	2.25	13.9	0.0	0.0	0.0	0.01	0.0	1.8
LT STA 154+64	PE	AGG	24.0	38.0	48.0	0.0	5.0	7.0	2.25	23.9	0.0	0.0	2.2	0.01	0.0	3.0
RT STA 159+85	PE	CONC	16.0	45.8	62.1	0.0	5.0	0.0	2.25	30.0	0.0	0.0	0.0	0.01	0.0	3.8
RT STA 167+54	MB	HMA	0.0	21.0	48.5	0.0	5.0	0.0	2.25	19.3	0.0	0.0	0.0	0.01	0.0	2.4
LT STA 167+54	CE	AGG	32.0	44.0	58.0	0.0	7.0	5.0	2.25	39.7	0.0	0.0	2.0	0.02	0.0	5.0
LT STA 174+77	CE	AGG	30.0	42.0	56.0	0.0	7.0	5.0	2.25	38.1	0.0	0.0	1.9	0.01	0.0	4.8
RT STA 180+58	MB	AGG	0.0	20.0	64.0	0.0	5.0	0.0	2.25	0.0	23.3	4.0	0.0	0.00	0.0	7.8
LT STA 180+78	CE	HMA	35.0	47.0	61.0	0.0	7.0	0.0	2.25	42.0	0.0	0.0	0.0	0.02	0.0	5.3
LT STA 197+35	PE	AGG	19.0	35.0	45	0.0	5.0	7.0	2.25	22.2	0.0	0.0	1.9	0.01	0.0	2.8
RT STA 197+40	MB	HMA	0.0	26.0	53.5	0.0	5.0	0.0	2.25	22.1	0.0	0.0	0.0	0.01	0.0	2.8
LT STA 200+50	PE	AGG	25.0	40.0	50.0	0.0	5.0	7.0	2.25	25.0	0.0	0.0	2.3	0.01	0.0	3.2
RT STA 204+88	PE	AGG	16.0	31.8	41.6	0.0	5.0	7.0	2.25	20.4	0.0	0.0	1.7	0.01	0.0	2.6
LT STA 796+34	PE	AGG	24.0	38.0	52.0	0.0	7.0	7.0	2.00	35.0	0.0	0.0	2.1	0.01	0.0	3.9
RT STA 796+00	MB	HMA	0.0	20.0	53.0	0.0	7.0	0.0	2.00	28.4	0.0	0.0	0.0	0.01	0.0	3.2
LT STA 791+74	CE	AGG	33.0	43.0	61.0	0.0	9.0	5.0	2.00	52.0	0.0	0.0	1.8	0.02	0.0	5.8
RT STA 773+48	TR 222	AGG	34.0	46.6	89.2	14.0	6.0	7.0	2.25	49.9	0.0	0.0	2.9	0.02	0.0	6.3
LT STA 767+33	PE	AGG	19.0	33.0	45.0	0.0	6.0	7.0	2.25	26.0	0.0	0.0	1.9	0.01	0.0	3.3
RT STA 767+21	MB	HMA	0.0	23.0	56.0	0.0	6.0	0.0	2.25	26.3	0.0	0.0	0.0	0.01	0.0	3.3
IL 106 STA 12+66	TR 289	HMA	0.0	CADD	CADD	0.0	6.0	7.0	2.25	84.8	0.0	0.0	0.0	0.03	0.2	10.7
TOKEN QUANTITY TO BE USED AT THE DISCRETION OF THE ENGINEER										0.0	100.0	15.0	0.0	0.00	0.0	0.0
TOTAL =										1049.6	123	19	22	0.4	1.0	133

* SEE PREVIOUS SHEET FOR DETAIL OF DIMENSION LOCATIONS