

44000155		HMA SURFACE REMOVAL 1 1/2" (OUTSIDE SHOULDER)						(SQ YD)
LOCATION	DIRECTION	STATION	TO	STATION	LENGTH (FOOT)	AVG. WIDTH (FOOT)	AREA (SQ YD)	REMARKS
ML	EB	23+77.22	TO	26+14.72	237.5	8	211.1	OUTSIDE SHOULDER
EB IL 29 EXIT RAMP TO SB I-55		26+14.72	TO	28+72.85	252.3	8	224.2	RAMP OUTSIDE SHOULDER
EB IL 29 EXIT RAMP TO SB I-55		27+34.33	TO	28+75.84	VARIES		142.8	INSIDE GORE SHOULDER
ML	EB	28+75.84	TO	38+26.92	951.1	10	1,056.8	
SB I-55 EXIT RAMP TO EB IL 29		38+26.98	TO	39+04.92	VARIES		46.9	INSIDE GORE SHOULDER
SB I-55 EXIT RAMP TO EB IL 29								
EB IL 29 EXIT RAMP TO NB I-55		38+31.	TO	44+52.14	622.1	8	553.0	RAMP OUTSIDE SHOULDER
EB IL 29 EXIT RAMP TO NB I-55		43+69.83	TO	44+58.16	VARIES		87.0	INSIDE GORE SHOULDER
ML	EB	44+58.16	TO	50+54.96	596.8	10	663.1	
NB I-55 EXIT RAMP TO EB IL 29		50+54.96	TO	51+94.95	VARIES		71.3	INSIDE GORE SHOULDER
NB I-55 EXIT RAMP TO EB IL 29		50+58.31	TO	59+66.63	908.9	8	807.9	RAMP OUTSIDE SHOULDER
ML	EB	60+59.37	TO	66+50.58	591.2	10	656.9	OUTSIDE SHOULDER
STATION EQUATION 66+50.58 BK = 49+55.50 AH								
ML	EB	49+55.5	TO	58+53.41	897.9	10	997.7	OUTSIDE SHOULDER
BRIDGE OMISSION 58+53.41 TO 61+75.41								
ML	EB	61+75.41	TO	86+66.61	2491.2	10	2,768.0	OUTSIDE SHOULDER
ML	EB	86+66.61	TO	87+48.51	81.9	7	63.7	
ML	EB	87+48.51	TO	91+13.43	364.92	4	162.2	
ML	EB	91+13.43	TO	94+00.00	286.57	10	318.4	
STATION EQUATION 113+89.34 BK = 114+08.37 AH								
BRIDGE OMISSION 154+93.37 TO 159+20.65								
ML	EB	204+50.	TO	209+59.65	509.7	10	566.3	OUTSIDE SHOULDER
STATION EQUATION 209+59.65 BK = 209+44.28 AH								
ML	EB	209+44.28	TO	229+93.4	2,049.1	10	2,276.8	OUTSIDE SHOULDER
TOTAL							11,674.0	

44000155		HMA SURFACE REMOVAL 1 1/2" (INSIDE SHOULDER)						(SQ YD)
LOCATION	DIRECTION	STATION	TO	STATION	LENGTH (FOOT)	AVG. WIDTH (FOOT)	AREA (SQ YD)	REMARKS
ML	EB	27+68.69	TO	60+05.55	3,236.9	4	1,438.6	INSIDE SHOULDER
ML	EB	61+09.11	TO	66+50.58	541.5	4	240.7	INSIDE SHOULDER
STATION EQUATION 66+50.58 BK = 49+55.50 AH								
ML	EB	49+55.5	TO	58+53.41	897.9	4	399.1	INSIDE SHOULDER
BRIDGE OMISSION 58+53.41 TO 61+75.41								
ML	EB	61+75.41	TO	62+30.2	54.8	4	24.4	INSIDE SHOULDER
ML	EB	62+84.83	TO	77+66.87	1,482.0	4	658.7	INSIDE SHOULDER
ML	EB	78+94.92	TO	92+05.93	1,311.0	4	582.7	INSIDE SHOULDER
ML	EB	93+11.87	TO	94+00.	88.1	4	39.2	INSIDE SHOULDER
STATION EQUATION 113+89.34 BK = 114+08.37 AH								
BRIDGE OMISSION 154+93.37 TO 159+20.65								
ML	EB	204+50.	TO	209+59.65	509.7	4	226.5	INSIDE SHOULDER
STATION EQUATION 209+59.65 BK = 209+44.28 AH								
ML	EB	210+31.71	TO	219+28.66	897.0	4	398.6	INSIDE SHOULDER
ML	EB	220+59.55	TO	225+99.07	539.5	4	239.8	INSIDE SHOULDER
TOTAL							4,248.1	

ML = MAINLINE  
EB = EASTBOUND  
WB = WESTBOUND

44000155		HMA SURFACE REMOVAL 1 1/2" (OUTSIDE SHOULDER)						(SQ YD)
LOCATION	DIRECTION	STATION	TO	STATION	LENGTH (FOOT)	AVG. WIDTH (FOOT)	AREA (SQ YD)	REMARKS
SB I-55 EXIT RAMP TO WB IL 29		23+77.21	TO	31+12.56	749.6	8	666.3	RAMP OUTSIDE SHOULDER
SB I-55 EXIT RAMP TO WB IL 29		29+75.29	TO	31+18.04	VARIES		110.8	INSIDE GORE SHOULDER
ML	WB	31+18.04	TO	35+74.4	456.4	10	507.1	OUTSIDE SHOULDER
WB IL 29 EXIT RAMP TO SB I-55		35+74.4	TO	36+59.15	VARIES		91.5	INSIDE GORE SHOULDER
WB IL 29 EXIT RAMP TO SB I-55								
NB I-55 EXIT RAMP TO WB IL 29		35+82.08	TO	41+92.45	624.1	8	554.7	RAMP OUTSIDE SHOULDER
NB I-55 EXIT RAMP TO WB IL 29		41+18.61	TO	41+96.67	VARIES		42.4	INSIDE GORE SHOULDER
ML	WB	41+96.67	TO	49+29.71	733.0	10	814.5	
WB IL 29 EXIT RAMP TO NB I-55		49+29.71	TO	50+88.6	VARIES		156.7	INSIDE GORE SHOULDER
WB IL 29 EXIT RAMP TO NB I-55		49+33.	TO	52+28.44	297.2	8	264.1	RAMP OUTSIDE SHOULDER
ML	WB	52+28.44	TO	60+01.03	772.6	10	858.4	OUTSIDE SHOULDER
ML	WB	61+36.47	TO	64+33.21	296.7	4	131.9	OUTSIDE SHOULDER
ML	WB	64+33.21	TO	66+50.58	217.4	7	169.1	SHOULDER VARIES 4' TO 10'
STATION EQUATION 66+50.58 BK = 49+55.50 AH								
ML	WB	49+55.5	TO	50+60.	104.5	10	116.1	OUTSIDE SHOULDER
BRIDGE OMISSION 58+50.9 TO 61+75.96								
ML	WB	76+50.	TO	77+20.57	70.6	10	78.4	OUTSIDE SHOULDER
ML	WB	79+15.57	TO	81+39.89	224.3	4	99.7	OUTSIDE SHOULDER
ML	WB	81+39.89	TO	84+14.16	274.3	7	213.3	SHOULDER VARIES 4' TO 10'
ML	WB	84+14.16	TO	113+89.34	2,975.2	10	3,305.8	OUTSIDE SHOULDER
STATION EQUATION 113+89.34 BK = 114+08.37 AH								
ML	WB	114+08.37	TO	154+58.79	4,050.4	10	4,500.5	OUTSIDE SHOULDER
ML	WB	154+58.79	TO	154+95.25	36.5	7	28.4	OUTSIDE SHOULDER
BRIDGE OMISSION 154+95.25 TO 159+21.23								
ML	WB	159+21.25	TO	160+42.14	120.9	6.5	87.3	SHOULDER VARIES 3' TO 10'
ML	WB	160+42.14	TO	209+30.48	4,888.3	10	5,431.5	OUTSIDE SHOULDER
STATION EQUATION 209+59.65 BK = 209+44.28 AH								
ML	WB	210+64.13	TO	214+46.65	382.5	4	170.0	OUTSIDE SHOULDER
ML	WB	214+46.65	TO	215+57.24	110.6	7	86.0	SHOULDER VARIES 4' TO 10'
ML	WB	215+57.24	TO	219+57.37	400.1	10	444.6	OUTSIDE SHOULDER
ML	WB	220+76.61	TO	224+54.14	377.5	4	167.8	OUTSIDE SHOULDER
ML	WB	224+54.14	TO	225+88.07	133.9	7	104.2	SHOULDER VARIES 4' TO 10'
ML	WB	225+88.07	TO	229+27.25	339.2	10	376.9	OUTSIDE SHOULDER
TOTAL							19,577.9	

44000155		HMA SURFACE REMOVAL 1 1/2" (INSIDE SHOULDER)						(SQ YD)
LOCATION	DIRECTION	STATION	TO	STATION	LENGTH (FOOT)	AVG. WIDTH (FOOT)	AREA (SQ YD)	REMARKS
ML	WB	27+65.89	TO	60+03.48	3,237.6	4	1,438.9	INSIDE SHOULDER
ML	WB	61+11.79	TO	64+40.42	328.6	2	73.0	INSIDE SHOULDER
ML	WB	64+40.42	TO	64+72.65	32.2	3	10.7	INSIDE SHOULDER
ML	WB	64+72.65	TO	66+50.58	177.9	4	79.1	INSIDE SHOULDER
STATION EQUATION 66+50.58 BK = 49+55.50 AH								
ML	WB	49+55.5	TO	50+60.	104.5	4	46.4	INSIDE SHOULDER
BRIDGE OMISSION 58+50.9 TO 61+75.96								
ML	WB	76+50.	TO	77+72.84	122.8	4	54.6	INSIDE SHOULDER
ML	WB	78+90.21	TO	81+28.12	237.9	2	52.9	INSIDE SHOULDER
ML	WB	81+28.12	TO	81+79.97	51.9	3	17.3	INSIDE SHOULDER
ML	WB	81+79.97	TO	91+98.97	1,019.0	4	452.9	INSIDE SHOULDER
ML	WB	92+93.38	TO	103+16.5	1,023.1	4	454.7	INSIDE SHOULDER
ML	WB	103+16.5	TO	113+89.34	1,034.9	4	460.0	INSIDE SHOULDER
STATION EQUATION 113+89.34 BK = 114+08.37 AH								
ML	WB	114+08.97	TO	124+24.36	1,015.4	4	451.3	INSIDE SHOULDER
ML	WB	124+75.27	TO	128+00.47	325.2	2	72.3	INSIDE SHOULDER
ML	WB	128+00.47	TO	128+38.81	38.3	3	12.8	INSIDE SHOULDER
ML	WB	128+38.81	TO	149+05.06	2,066.3	4	918.3	INSIDE SHOULDER
ML	WB	149+43.69	TO	154+96.25	552.6	4	245.6	INSIDE SHOULDER
BRIDGE OMISSION 154+95.25 TO 159+21.23								
ML	WB	159+21.25	TO	169+13.07	991.8	4	440.8	INSIDE SHOULDER
ML	WB	169+67.69	TO	195+92.52	2,624.8	4	1,166.6	INSIDE SHOULDER
ML	WB	196+29.37	TO	209+41.62	1,312.3	4	583.2	INSIDE SHOULDER
STATION EQUATION 209+59.65 BK = 209+44.28 AH								
ML	WB	210+35.98	TO	219+26.3	890.3	4	395.7	INSIDE SHOULDER
ML	WB	220+62.13	TO	225+99.61	537.5	4	238.9	INSIDE SHOULDER
TOTAL							7,666.0	